



FortiOS - Log Reference

Version 6.2.15

FORTINET DOCUMENT LIBRARY

<https://docs.fortinet.com>

FORTINET VIDEO GUIDE

<https://video.fortinet.com>

FORTINET BLOG

<https://blog.fortinet.com>

CUSTOMER SERVICE & SUPPORT

<https://support.fortinet.com>

FORTINET TRAINING & CERTIFICATION PROGRAM

<https://www.fortinet.com/training-certification>

FORTINET TRAINING INSTITUTE

<https://training.fortinet.com>

FORTIGUARD CENTER

<https://www.fortiguard.com>

END USER LICENSE AGREEMENT

<https://www.fortinet.com/doc/legal/EULA.pdf>

FEEDBACK

Email: techdoc@fortinet.com



June 08, 2023

FortiOS 6.2.15 Log Reference

01-6215-538745-20230608

TABLE OF CONTENTS

Change Log	29
Introduction	30
Before you begin	30
What's new	31
FortiOS 6.2.15	31
FortiOS 6.2.14	31
FortiOS 6.2.13	31
FortiOS 6.2.12	31
FortiOS 6.2.11	31
FortiOS 6.2.10	31
FortiOS 6.2.9	31
FortiOS 6.2.8	31
FortiOS 6.2.7	32
FortiOS 6.2.6	32
FortiOS 6.2.5	32
FortiOS 6.2.4	32
FortiOS 6.2.3	32
FortiOS 6.2.2	32
FortiOS 6.2.1	32
FortiOS 6.2.0	33
Log Types and Subtypes	34
Type	34
Subtype	34
List of log types and subtypes	34
UTM log subtypes	35
FortiOS priority levels	37
Log field format	37
Log Schema Structure	38
Log message fields	38
Log ID numbers	41
Log ID definitions	42
FortiGuard Web Filter Categories	45
CEF Support	48
FortiOS to CEF log field mapping guidelines	48
CEF priority levels	48
Examples of CEF support	49
Traffic log support for CEF	49
Event log support for CEF	51
Antivirus log support for CEF	52
Webfilter log support for CEF	53
IPS log support for CEF	54
Email Spamfilter log support for CEF	54
Anomaly log support for CEF	55

VoIP log support for CEF	55
DLP log support for CEF	56
Application log support for CEF	57
WAF log support for CEF	57
DNS log support for CEF	57
SSH log support for CEF	58
UTM Extended Logging	59
Enabling extended logging	59
Extended logging option in UTM profiles	59
Syslog server mode	60
Example of an extended log	60
Log Messages	61
Anomaly	61
18432 - LOGID_ATTCK_ANOMALY_TCP_UDP	61
18433 - LOGID_ATTCK_ANOMALY_ICMP	62
18434 - LOGID_ATTCK_ANOMALY_OTHERS	64
App	66
28672 - LOGID_APP_CTRL_IM_BASIC	66
28673 - LOGID_APP_CTRL_IM_BASIC_WITH_STATUS	67
28674 - LOGID_APP_CTRL_IM_BASIC_WITH_COUNT	69
28675 - LOGID_APP_CTRL_IM_FILE	70
28676 - LOGID_APP_CTRL_IM_CHAT	72
28677 - LOGID_APP_CTRL_IM_CHAT_BLOCK	73
28678 - LOGID_APP_CTRL_IM_BLOCK	75
28704 - LOGID_APP_CTRL_IPS_PASS	76
28705 - LOGID_APP_CTRL_IPS_BLOCK	78
28706 - LOGID_APP_CTRL_IPS_RESET	81
28720 - LOGID_APP_CTRL_SSH_PASS	83
28721 - LOGID_APP_CTRL_SSH_BLOCK	84
28736 - LOGID_APP_CTRL_PORT_ENF	86
28737 - LOGID_APP_CTRL_PROTO_ENF	88
AV	90
8192 - MSGID_INFECT_WARNING	90
8193 - MSGID_INFECT_NOTIF	93
8194 - MSGID_INFECT_MIME_WARNING	95
8195 - MSGID_INFECT_MIME_NOTIF	97
8200 - MSGID_MIME_FILETYPE_EXE_WARNING	100
8201 - MSGID_MIME_FILETYPE_EXE_NOTIF	102
8202 - MSGID_AVQUERY_WARNING	104
8203 - MSGID_AVQUERY_NOTIF	106
8204 - MSGID_MIME_AVQUERY_WARNING	108
8205 - MSGID_MIME_AVQUERY_NOTIF	111
8212 - MSGID_MALWARE_LIST_WARNING	113
8213 - MSGID_MALWARE_LIST_NOTIF	115
8214 - MSGID_MIME_MALWARE_LIST_WARNING	118
8215 - MSGID_MIME_MALWARE_LIST_NOTIF	120
8448 - MSGID_BLOCK_WARNING	122
8450 - MSGID_BLOCK_MIME_WARNING	124

8451 - MSGID_BLOCK_MIME_NOTIF	126
8452 - MSGID_BLOCK_COMMAND	128
8457 - MSGID_MMS_CHECKSUM	130
8458 - MSGID_MMS_CHECKSUM_NOTIF	132
8704 - MSGID_OVERSIZE_WARNING	134
8705 - MSGID_OVERSIZE_NOTIF	136
8706 - MSGID_OVERSIZE_MIME_WARNING	137
8707 - MSGID_OVERSIZE_MIME_NOTIF	139
8708 - MSGID_OVERSIZE_STREAM_UNCOMP_WARNING	141
8709 - MSGID_OVERSIZE_STREAM_UNCOMP_NOTIF	143
8720 - MSGID_SWITCH_PROTO_WARNING	145
8721 - MSGID_SWITCH_PROTO_NOTIF	146
8960 - MSGID_SCAN_UNCOMPSIZELIMIT_WARNING	148
8961 - MSGID_SCAN_UNCOMPSIZELIMIT_NOTIF	150
8962 - MSGID_SCAN_ARCHIVE_ENCRYPTED_WARNING	153
8963 - MSGID_SCAN_ARCHIVE_ENCRYPTED_NOTIF	155
8964 - MSGID_SCAN_ARCHIVE_CORRUPTED_WARNING	157
8965 - MSGID_SCAN_ARCHIVE_CORRUPTED_NOTIF	160
8966 - MSGID_SCAN_ARCHIVE_MULTIPART_WARNING	162
8967 - MSGID_SCAN_ARCHIVE_MULTIPART_NOTIF	164
8968 - MSGID_SCAN_ARCHIVE_NESTED_WARNING	167
8969 - MSGID_SCAN_ARCHIVE_NESTED_NOTIF	169
8970 - MSGID_SCAN_ARCHIVE_OVERSIZE_WARNING	171
8971 - MSGID_SCAN_ARCHIVE_OVERSIZE_NOTIF	174
8972 - MSGID_SCAN_ARCHIVE_UNHANDLED_WARNING	176
8973 - MSGID_SCAN_ARCHIVE_UNHANDLED_NOTIF	178
8974 - MSGID_SCAN_AV_ENGINE_LOAD_FAILED_ERROR	181
8975 - MSGID_SCAN_ARCHIVE_PARTIALLYCORRUPTED_WARNING	183
8976 - MSGID_SCAN_ARCHIVE_PARTIALLYCORRUPTED_NOTIF	185
8977 - MSGID_SCAN_ARCHIVE_FILESLIMIT_WARNING	188
8978 - MSGID_SCAN_ARCHIVE_FILESLIMIT_NOTIF	190
8979 - MSGID_SCAN_ARCHIVE_TIMEOUT_WARNING	192
8980 - MSGID_SCAN_ARCHIVE_TIMEOUT_NOTIF	195
9233 - MSGID_ANALYTICS_SUBMITTED	197
9234 - MSGID_ANALYTICS_INFECT_WARNING	199
9235 - MSGID_ANALYTICS_INFECT_NOTIF	202
9236 - MSGID_ANALYTICS_INFECT_MIME_WARNING	204
9237 - MSGID_ANALYTICS_INFECT_MIME_NOTIF	206
9238 - MSGID_ANALYTICS_FSA_RESULT	209
9239 - MSGID_CONTENT_DISARM_NOTIF	210
9240 - MSGID_CONTENT_DISARM_WARNING	212
CIFS	214
63000 - LOG_ID_CIFS_FILE_BLOCK	214
63001 - LOG_ID_CIFS_FILE_PASS	215
DLP	217
24576 - LOG_ID_DLP_WARN	217
24577 - LOG_ID_DLP_NOTIF	219
24578 - LOG_ID_DLP_DOC_SOURCE	221
24579 - LOG_ID_DLP_DOC_SOURCE_ERROR	222

DNS	223
54000 - LOG_ID_DNS_QUERY	223
54200 - LOG_ID_DNS_RESOLV_ERROR	224
54400 - LOG_ID_DNS_URL_FILTER_BLOCK	226
54401 - LOG_ID_DNS_URL_FILTER_ALLOW	228
54600 - LOG_ID_DNS_BOTNET_IP	230
54601 - LOG_ID_DNS_BOTNET_DOMAIN	232
54800 - LOG_ID_DNS_FTGD_WARNING	234
54801 - LOG_ID_DNS_FTGD_ERROR	236
54802 - LOG_ID_DNS_FTGD_CAT_ALLOW	238
54803 - LOG_ID_DNS_FTGD_CAT_BLOCK	240
54804 - LOG_ID_DNS_SAFE_SEARCH	241
Email	243
20480 - LOGID_ANTISPAM_EMAIL_SMTP_NOTIF	243
20481 - LOGID_ANTISPAM_EMAIL_SMTP_BWORD_NOTIF	245
20482 - LOGID_ANTISPAM_EMAIL_POP3_NOTIF	247
20483 - LOGID_ANTISPAM_EMAIL_POP3_BWORD_NOTIF	249
20484 - LOGID_ANTISPAM_EMAIL_IMAP_NOTIF	251
20485 - LOGID_ANTISPAM_ENDPOINT_FILTER_WARNING	253
20486 - LOGID_ANTISPAM_ENDPOINT_FILTER_NOTIF	254
20487 - LOGID_ANTISPAM_ENDPOINT_MM7_WARNING	256
20488 - LOGID_ANTISPAM_ENDPOINT_MM7_NOTIF	258
20489 - LOGID_ANTISPAM_ENDPOINT_MM1_WARNING	260
20490 - LOGID_ANTISPAM_ENDPOINT_MM1_NOTIF	262
20491 - LOGID_ANTISPAM_EMAIL_IMAP_BWORD_NOTIF	264
20492 - LOGID_ANTISPAM_MM1_FLOOD_WARNING	266
20493 - LOGID_ANTISPAM_MM1_FLOOD_NOTIF	267
20494 - LOGID_ANTISPAM_MM4_FLOOD_WARNING	269
20495 - LOGID_ANTISPAM_MM4_FLOOD_NOTIF	271
20496 - LOGID_ANTISPAM_MM1_DUPE_WARNING	273
20497 - LOGID_ANTISPAM_MM1_DUPE_NOTIF	275
20498 - LOGID_ANTISPAM_MM4_DUPE_WARNING	277
20499 - LOGID_ANTISPAM_MM4_DUPE_NOTIF	279
20500 - LOGID_ANTISPAM_EMAIL_MSN_NOTIF	280
20501 - LOGID_ANTISPAM_EMAIL_YAHOO_NOTIF	282
20502 - LOGID_ANTISPAM_EMAIL_GOOGLE_NOTIF	284
20503 - LOGID_EMAIL_SMTP_GENERAL_NOTIF	286
20504 - LOGID_EMAIL_POP3_GENERAL_NOTIF	288
20505 - LOGID_EMAIL_IMAP_GENERAL_NOTIF	290
20506 - LOGID_EMAIL_MAPI_GENERAL_NOTIF	292
20507 - LOGID_ANTISPAM_EMAIL_MAPI_BWORD_NOTIF	293
20508 - LOGID_ANTISPAM_EMAIL_MAPI_NOTIF	295
20509 - LOGID_ANTISPAM_FTGD_ERR	297
Event	299
20002 - LOG_ID_DOMAIN_UNRESOLVABLE	299
20003 - LOG_ID_MAIL_SENT_FAIL	300
20004 - LOG_ID_POLICY_TOO_BIG	301
20005 - LOG_ID_PPP_LINK_UP	301
20006 - LOG_ID_PPP_LINK_DOWN	302

20007 - LOG_ID_SOCKET_EXHAUSTED	303
20008 - LOG_ID_POLICY6_TOO_BIG	304
20010 - LOG_ID_KERNEL_ERROR	305
20016 - LOG_ID_MODEM_EXCEED_REDIAL_COUNT	305
20017 - LOG_ID_MODEM_FAIL_TO_OPEN	306
20020 - LOG_ID_MODEM_USB_DETECTED	307
20021 - LOG_ID_MAIL_RESENT	307
20022 - LOG_ID_MODEM_USB_REMOVED	308
20023 - LOG_ID_MODEM_USBLTE_DETECTED	309
20024 - LOG_ID_MODEM_USBLTE_REMOVED	309
20025 - LOG_ID_REPORTD_REPORT_SUCCESS	310
20026 - LOG_ID_REPORTD_REPORT_FAILURE	311
20027 - LOG_ID_REPORT_DEL_OLD_REC	312
20028 - LOG_ID_REPORT_RECREATE_DB	312
20031 - LOG_ID_RAD_OUT_OF_MEM	313
20032 - LOG_ID_RAD_NOT_FOUND	314
20033 - LOG_ID_RAD_MOBILE_IPV6	314
20034 - LOG_ID_RAD_IPV6_OUT_OF_RANGE	315
20035 - LOG_ID_RAD_MIN_OUT_OF_RANGE	316
20036 - LOG_ID_RAD_MAX_OUT_OF_RANGE	316
20037 - LOG_ID_RAD_MAX_ADV_OUT_OF_RANGE	317
20039 - LOG_ID_RAD_MTU_TOO_SMALL	318
20040 - LOG_ID_RAD_TIME_TOO_SMALL	318
20041 - LOG_ID_RAD_HOP_OUT_OF_RANGE	319
20042 - LOG_ID_RAD_DFT_HOP_OUT_OF_RANGE	320
20043 - LOG_ID_RAD_AGENT_OUT_OF_RANGE	320
20044 - LOG_ID_RAD_AGENT_FLAG_NOT_SET	321
20045 - LOG_ID_RAD_PREFIX_TOO_LONG	322
20046 - LOG_ID_RAD_PREF_TIME_TOO_SMALL	322
20047 - LOG_ID_RAD_FAIL_IPV6_SOCKET	323
20048 - LOG_ID_RAD_FAIL_OPT_IPV6_PKTINFO	324
20049 - LOG_ID_RAD_FAIL_OPT_IPV6_CHECKSUM	324
20050 - LOG_ID_RAD_FAIL_OPT_IPV6_UNICAST_HOPS	325
20051 - LOG_ID_RAD_FAIL_OPT_IPV6_MULTICAST_HOPS	326
20052 - LOG_ID_RAD_FAIL_OPT_IPV6_HOPLIMIT	326
20053 - LOG_ID_RAD_FAIL_OPT_IPPROTO_ICMPV6	327
20054 - LOG_ID_RAD_EXIT_BY_SIGNAL	328
20055 - LOG_ID_RAD_FAIL_CMDB_QUERY	328
20056 - LOG_ID_RAD_FAIL_CMDB_FOR_EACH	329
20057 - LOG_ID_RAD_FAIL_FIND_VIRT_INTF	330
20058 - LOG_ID_RAD_UNLOAD_INTF	330
20061 - LOG_ID_RAD_INV_ICMPV6_TYPE	331
20062 - LOG_ID_RAD_INV_ICMPV6_RA_LEN	332
20063 - LOG_ID_RAD_ICMPV6_NO_SRC_ADDR	332
20064 - LOG_ID_RAD_INV_ICMPV6_RS_LEN	333
20065 - LOG_ID_RAD_INV_ICMPV6_CODE	334
20066 - LOG_ID_RAD_INV_ICMPV6_HOP	334
20067 - LOG_ID_RAD_MISMATCH_HOP	335
20068 - LOG_ID_RAD_MISMATCH_MGR_FLAG	336

20069 - LOG_ID_RAD_MISMATCH_OTH_FLAG	336
20070 - LOG_ID_RAD_MISMATCH_TIME	337
20071 - LOG_ID_RAD_MISMATCH_TIMER	338
20072 - LOG_ID_RAD_EXTRA_DATA	338
20073 - LOG_ID_RAD_NO_OPT_DATA	339
20074 - LOG_ID_RAD_INV_OPT_LEN	340
20075 - LOG_ID_RAD_MISMATCH_MTU	340
20077 - LOG_ID_RAD_MISMATCH_PREF_TIME	341
20078 - LOG_ID_RAD_INV_OPT	342
20079 - LOG_ID_RAD_READY	342
20080 - LOG_ID_RAD_FAIL_TO_RCV	343
20081 - LOG_ID_RAD_INV_HOP	344
20082 - LOG_ID_RAD_INV_PKTINFO	344
20083 - LOG_ID_RAD_FAIL_TO_CHECK	345
20084 - LOG_ID_RAD_FAIL_TO_SEND	346
20085 - LOG_ID_SESSION_CLASH	346
20090 - LOG_ID_INTF_LINK_STA_CHG	347
20099 - LOG_ID_INTF_STA_CHG	348
20100 - LOG_ID_WEB_CAT_UPDATED	349
20101 - LOG_ID_WEB_LIC_EXPIRE	350
20102 - LOG_ID_SPAM_LIC_EXPIRE	350
20103 - LOG_ID_AV_LIC_EXPIRE	351
20104 - LOG_ID_IPS_LIC_EXPIRE	352
20107 - LOG_ID_LOG_UPLOAD_ERR	352
20108 - LOG_ID_LOG_UPLOAD_DONE	353
20109 - LOG_ID_WEB_LIC_EXPIRED	354
20113 - LOG_ID_IPSA_DOWNLOAD_FAIL	355
20115 - LOG_ID_IPSA_STATUSUPD_FAIL	356
20116 - LOG_ID_SPAM_LIC_EXPIRED	356
20117 - LOG_ID_AV_LIC_EXPIRED	357
20118 - LOG_ID_WEBF_STATUS_REACH	358
20119 - LOG_ID_WEBF_STATUS_UNREACH	358
20200 - LOG_ID_FIPS_SELF_TEST	359
20201 - LOG_ID_FIPS_SELF_ALL_TEST	360
20202 - LOG_ID_DISK_FORMAT_ERROR	360
20203 - LOG_ID_DAEMON_SHUTDOWN	361
20204 - LOG_ID_DAEMON_START	362
20205 - LOG_ID_DISK_FORMAT_REQ	363
20206 - LOG_ID_DISK_SCAN_REQ	364
20207 - LOG_ID_RAD_MISMATCH_VALID_TIME	364
20208 - LOG_ID_ZOMBIE_DAEMON_CLEANUP	365
20209 - LOG_ID_DISK_UNAVAIL	366
20210 - LOG_ID_DISK_TRIM_START	366
20211 - LOG_ID_DISK_TRIM_END	367
20212 - LOG_ID_DISK_SCAN_NEEDED	368
20213 - LOG_ID_DISK_LOG_CORRUPTED	369
20220 - LOGID_EVENT_SHAPER_OUTBOUND_MAXED_OUT	369
20221 - LOGID_EVENT_SHAPER_INBOUND_MAXED_OUT	370
20300 - LOG_ID_BGP_NB_STAT_CHG	371

20301 - LOG_ID_VZ_LOG	372
20302 - LOG_ID_OSPF_NB_STAT_CHG	372
20303 - LOG_ID_OSPF6_NB_STAT_CHG	373
20401 - LOG_ID_ROUTER_CLEAR	374
22000 - LOG_ID_INV_PKT_LEN	374
22001 - LOG_ID_UNSUPPORTED_PROT_VER	375
22002 - LOG_ID_INV_REQ_TYPE	376
22003 - LOG_ID_FAIL_SET_SIG_HANDLER	376
22004 - LOG_ID_FAIL_CREATE_SOCKET	377
22005 - LOG_ID_FAIL_CREATE_SOCKET_RETRY	378
22006 - LOG_ID_FAIL_REG_CMDB_EVENT	378
22009 - LOG_ID_FAIL_FIND_AV_PROFILE	379
22010 - LOG_ID_SENDTO_FAIL	380
22011 - LOG_ID_ENTER_MEM_CONSERVE_MODE	380
22012 - LOG_ID_LEAVE_MEM_CONSERVE_MODE	381
22013 - LOG_ID_IPPOOLPBA_BLOCK_EXHAUSTED	382
22014 - LOG_ID_IPPOOLPBA_NATIP_EXHAUSTED	383
22015 - LOG_ID_IPPOOLPBA_CREATE	384
22016 - LOG_ID_IPPOOLPBA_DEALLOCATE	385
22017 - LOG_ID_EXCEED_GLOB_RES_LIMIT	386
22018 - LOG_ID_EXCEED_VD_RES_LIMIT	386
22019 - LOG_ID_LOGRATE_OVER_LIMIT	387
22020 - LOG_ID_FAIL_CREATE_HA_SOCKET	388
22021 - LOG_ID_FAIL_CREATE_HA_SOCKET_RETRY	388
22031 - LOG_ID_SUCCESS_CSF_LOG_SYNC_CONFIG_CHANGED	389
22032 - LOG_ID_CSF_LOOP_FOUND	390
22033 - LOG_ID_FAIL_CSF_LOG_SYNC_NO_VALID_FSA	391
22035 - LOG_ID_CSF_UPSTREAM_SN_CHANGED	391
22036 - LOG_ID_CSF_FGT_CONNECTED	392
22037 - LOG_ID_CSF_FGT_DISCONNECTED	393
22100 - LOG_ID_QUAR_DROP_TRAN_JOB	394
22101 - LOG_ID_QUAR_DROP_TLL_JOB	395
22102 - LOG_ID_LOG_DISK_FAILURE	396
22103 - LOG_ID_QUAR_LIMIT_REACHED	396
22104 - LOG_ID_POWER_RESTORE	397
22105 - LOG_ID_POWER_FAILURE	398
22106 - LOG_ID_POWER_OPTIONAL_NOT_DETECTED	399
22107 - LOG_ID_VOLT_ANOM	399
22108 - LOG_ID_FAN_ANOM	400
22109 - LOG_ID_TEMP_TOO_HIGH	401
22110 - LOG_ID_SPARE_BLOCK_LOW	402
22113 - LOG_ID_FNBAM_FAILURE	402
22150 - LOG_ID_VOLT_NOM	403
22151 - LOG_ID_FAN_NOM	404
22152 - LOG_ID_TEMP_TOO_LOW	405
22153 - LOG_ID_TEMP_NORM	405
22200 - LOG_ID_AUTO_UPT_CERT	406
22201 - LOG_ID_AUTO_GEN_CERT	407
22203 - LOG_ID_AUTO_GEN_CERT_FAIL	408

22204 - LOG_ID_AUTO_GEN_CERT_PENDING	409
22205 - LOG_ID_AUTO_GEN_CERT_SUCC	409
22206 - LOG_ID_CRL_EXPIRED	410
22700 - LOG_ID_IPS_FAIL_OPEN	411
22701 - LOG_ID_IPS_FAIL_OPEN_END	412
22800 - LOG_ID_SCAN_SERV_FAIL	412
22802 - LOG_ID_ENTER_FD_CONSERVE_MODE	413
22803 - LOG_ID_LEAVE_FD_CONSERVE_MODE	414
22804 - LOG_ID_LIC_STATUS_CHG	415
22805 - LOG_ID_FAIL_TO_VALIDATE_LIC	416
22806 - LOG_ID_DUP_LIC	416
22808 - LOG_ID_LIC_EXPIRE	417
22809 - LOG_ID_LIC_WILL_EXPIRE	418
22810 - LOG_ID_SCANUNIT_ERROR_BLOCK	419
22811 - LOG_ID_SCANUNIT_ERROR_PASS	420
22812 - LOG_ID_SCANUNIT_AVENG_RELOAD	421
22813 - LOG_ID_SCANUNIT_AVDB_RELOAD	421
22814 - LOG_ID_SCANUNIT_AVDB_RELOAD_ERROR	422
22815 - LOG_ID_SCANUNIT_AVDB_LOAD	423
22816 - LOG_ID_SCANUNIT_AVDB_LOAD_ERROR	423
22850 - LOG_ID_USER_QUARANTINE_MAC_ADD	424
22851 - LOG_ID_USER_QUARANTINE_MAC_DELETE	425
22852 - LOG_ID_USER_QUARANTINE_MAC_BOUNCE_PORT_HIT	426
22853 - LOG_ID_USER_QUARANTINE_MAC_BOUNCE_PORT_MISS	426
22890 - LOG_ID_FORTILINKD	427
22891 - LOG_ID_FLCFGD_SYNC_ERROR	428
22892 - LOG_ID_FLCFGD_SYNC_COMPLETE	429
22893 - LOG_ID_FLCFGD_SYNC_STATE	430
22894 - LOG_ID_FLCFGD_UPGRADE_ERROR	430
22895 - LOG_ID_FLCFGD_UPGRADE_STATUS	431
22896 - LOG_ID_FORTILINKD_CRITICAL	432
22900 - LOG_ID_CAPUTP_SESSION	433
22901 - LOG_ID_FAZ_CON	433
22902 - LOG_ID_FAZ_DISCON	434
22903 - LOG_ID_FAZ_CON_ERR	435
22904 - LOG_ID_CAPUTP_SESSION_NOTIF	436
22912 - LOG_ID_FDS_SRV_ERRCON	436
22913 - LOG_ID_FDS_SRV_DISCON	437
22914 - LOG_ID_FDS_SRV_CHG	438
22915 - LOG_ID_FDS_SRV_CON	439
22916 - LOG_ID_FDS_STATUS	439
22917 - LOG_ID_FDS_SMS_QUOTA	440
22918 - LOG_ID_FDS_CTRL_STATUS	441
22921 - LOG_ID_EVENT_ROUTE_INFO_CHANGED	441
22922 - LOG_ID_EVENT_LINK_MONITOR_STATUS	442
22923 - LOG_ID_EVENT_VWL_LQTY_STATUS	443
22924 - LOG_ID_EVENT_VWL_VOLUME_STATUS	444
22925 - LOG_ID_EVENT_LINK_MONITOR_SLA_INFO	444
22926 - LOG_ID_EVENT_VWL_NEIGHBOR_STATUS	445

22927 - LOG_ID_EVENT_VWL_NEIGHBOR_STANDALONE	446
22928 - LOG_ID_EVENT_VWL_NEIGHBOR_PRIMARY	447
22929 - LOG_ID_EVENT_VWL_NEIGHBOR_SECONDARY	447
22949 - LOG_ID_FDS_JOIN	448
22950 - LOG_ID_FDS_LOGIN_SUCC	449
22951 - LOG_ID_FDS_LOGOUT	449
22952 - LOG_ID_FDS_LOGIN_FAIL	450
22953 - LOG_ID_IOC_DETECTED	451
23101 - LOG_ID_IPSEC_TUNNEL_UP	452
23102 - LOG_ID_IPSEC_TUNNEL_DOWN	453
23103 - LOG_ID_IPSEC_TUNNEL_STAT	453
26001 - LOG_ID_DHCP_ACK	454
26002 - LOG_ID_DHCP_RELEASE	455
26003 - LOG_ID_DHCP_STAT	456
26004 - LOG_ID_DHCP_CLIENT_LEASE	457
26005 - LOG_ID_DHCP_LEASE_USAGE_HIGH	458
26006 - LOG_ID_DHCP_LEASE_USAGE_FULL	458
26007 - LOG_ID_DHCP_BLOCKED_MAC	459
26008 - LOG_ID_DHCP_DDNS_ADD	460
26009 - LOG_ID_DHCP_DDNS_DELETE	461
26010 - LOG_ID_DHCP_DDNS_COMPLETED	461
26011 - LOG_ID_DHCPV6_REPLY	462
26012 - LOG_ID_DHCPV6_RELEASE	463
27001 - LOG_ID_VRRP_STATE_CHG	464
29001 - LOG_ID_PPPD_MSG	465
29002 - LOG_ID_PPPD_AUTH_SUC	465
29003 - LOG_ID_PPPD_AUTH_FAIL	466
29010 - LOG_ID_PPPOE_STATUS_REPORT_NOTIF	467
29011 - LOG_ID_PPPD_FAIL_TO_EXEC	468
29012 - LOG_ID_PPP_OPT_ERR	469
29013 - LOG_ID_PPPD_START	469
29014 - LOG_ID_PPPD_EXIT	470
29015 - LOG_ID_PPP_RCV_BAD_PEER_IP	471
29016 - LOG_ID_PPP_RCV_BAD_LOCAL_IP	471
29017 - LOG_ID_PPP_OPT_NOTIF	472
29021 - LOG_ID_EVENT_AUTH_SNMP_QUERY_FAILED	473
29022 - LOG_ID_DDNS_UPDATE_FAIL	473
32001 - LOG_ID_ADMIN_LOGIN_SUCC	474
32002 - LOG_ID_ADMIN_LOGIN_FAIL	475
32003 - LOG_ID_ADMIN_LOGOUT	476
32005 - LOG_ID_ADMIN_OVERRIDE_VDOM	477
32006 - LOG_ID_ADMIN_ENTER_VDOM	478
32007 - LOG_ID_ADMIN_LEFT_VDOM	479
32008 - LOG_ID_VIEW_DISK_LOG_FAIL	480
32009 - LOG_ID_SYSTEM_START	480
32010 - LOG_ID_DISK_LOG_FULL	481
32011 - LOG_ID_LOG_ROLL	482
32014 - LOG_ID_CS_LIC_EXPIRE	483
32015 - LOG_ID_DISK_LOG_USAGE	483

32017 - LOG_ID_FDS_DAILY_QUOTA_FULL	484
32018 - LOG_ID_FIPS_ENTER_ERR_MOD	485
32019 - LOG_ID_CC_ENTER_ERR_MOD	485
32020 - LOG_ID_SSH_CORRPUT_MAC	486
32021 - LOG_ID_ADMIN_LOGIN_DISABLE	487
32022 - LOG_ID_VDOM_ENABLED	488
32023 - LOG_ID_MEM_LOG_FIRST_FULL	488
32024 - LOG_ID_ADMIN_PASSWD_EXPIRE	489
32025 - LOG_ID_SSH_REKEY	490
32026 - LOG_ID_SSH_BAD_PACKET_LENGTH	490
32027 - LOG_ID_VIEW_DISK_LOG_SUCC	491
32028 - LOG_ID_LOG_DEL_DIR	492
32029 - LOG_ID_LOG_DEL_FILE	493
32030 - LOG_ID_SEND_FDS_STAT	493
32031 - LOG_ID_VIEW_MEM_LOG_FAIL	494
32032 - LOG_ID_DISK_DLP_ARCH_FULL	495
32033 - LOG_ID_DISK_QUAR_FULL	496
32034 - LOG_ID_DISK_REPORT_FULL	496
32035 - LOG_ID_VDOM_DISABLED	497
32036 - LOG_ID_DISK_IPS_ARCH_FULL	498
32037 - LOG_ID_DISK_LOG_FIRST_FULL	498
32038 - LOG_ID_LOG_ROLL_FORTICRON	499
32039 - LOG_ID_VIEW_MEM_LOG_SUCC	500
32040 - LOG_ID_REPORT_DELETED	501
32041 - LOG_ID_REPORT_DELETED_GUI	501
32042 - LOG_ID_MEM_LOG_SECOND_FULL	502
32043 - LOG_ID_MEM_LOG_FINAL_FULL	503
32044 - LOG_ID_LOG_DELETE	503
32045 - LOG_ID_MGR_LIC_EXPIRE	504
32048 - LOG_ID_SCHEDULE_EXPIRE	505
32049 - LOG_ID_FC_EXPIRE	506
32050 - LOG_ID_POL_PKT_CAPTURE_FULL	506
32051 - LOG_ID_LOG_UPLOAD	507
32052 - LOG_ID_UPLOAD_RUN_SCRIPT	508
32053 - LOG_ID_ADMIN_MTNER_LOGIN_SUCC	508
32054 - LOG_ID_ADMIN_MTNER_LOGOUT	509
32057 - LOG_ID_VIEW_FAZ_LOG_FAIL	510
32058 - LOG_ID_VIEW_FAZ_LOG_SUCC	511
32095 - LOG_ID_GUI_CHG_SUB_MODULE	512
32097 - LOG_ID_DELETE_CAPTURE_PKT	513
32100 - LOG_ID_FORTI_TOKEN_SYNC	513
32102 - LOG_ID_CHG_CONFIG	514
32103 - LOG_ID_NEW_FIRMWARE	515
32104 - LOG_ID_CHG_CONFIG_GUI	516
32105 - LOG_ID_NTP_SVR_STAUS_CHG_REACHABLE	517
32106 - LOG_ID_NTP_SVR_STAUS_CHG_RESOLVABLE	517
32107 - LOG_ID_NTP_SVR_STAUS_CHG_UNRESOLVABLE	518
32108 - LOG_ID_NTP_SVR_STAUS_CHG_UNREACHABLE	519
32109 - LOG_ID_UPD_SIGN_AV_DB	520

32110 - LOG_ID_UPD_SIGN_IPS_DB	521
32111 - LOG_ID_UPD_SIGN_AVIPS_DB	521
32113 - LOG_ID_UPD_SIGN_SRCVIS_DB	522
32114 - LOG_ID_UPD_SIGN_GEOIP_DB	523
32116 - LOG_ID_UPD_SIGN_AVPKG_FAILURE	524
32117 - LOG_ID_UPD_SIGN_AVPKG_SUCCESS	524
32118 - LOG_ID_UPD_ADMIN_AV_DB	525
32119 - LOG_ID_UPD_SCANUNIT_AV_DB	526
32120 - LOG_ID_RPT_ADD_DATASET	527
32122 - LOG_ID_RPT_DEL_DATASET	528
32125 - LOG_ID_RPT_ADD_CHART	528
32126 - LOG_ID_RPT_DEL_CHART	529
32129 - LOG_ID_ADD_GUEST	530
32130 - LOG_ID_CHG_USER	531
32131 - LOG_ID_DEL_GUEST	532
32132 - LOG_ID_ADD_USER	532
32138 - LOG_ID_REBOOT	533
32139 - LOG_ID_WAKE_ON_LAN	534
32140 - LOG_ID_TIME_USER_SETTING_CHG	535
32141 - LOG_ID_TIME_NTP_SETTING_CHG	536
32142 - LOG_ID_BACKUP_CONF	536
32143 - LOG_ID_BACKUP_CONF_BY_SCP	537
32144 - LOG_ID_BACKUP_CONF_ERROR	538
32145 - LOG_ID_BACKUP_CONF_ALERT	539
32146 - LOG_ID_TIME_PTP_SETTING_CHG	539
32148 - LOG_ID_GET_CRL	540
32149 - LOG_ID_COMMAND_FAIL	541
32151 - LOG_ID_ADD_IP6_LOCAL_POL	542
32152 - LOG_ID_CHG_IP6_LOCAL_POL	543
32153 - LOG_ID_DEL_IP6_LOCAL_POL	543
32155 - LOG_ID_ACT_FTOKEN_REQ	544
32156 - LOG_ID_ACT_FTOKEN_SUCC	545
32157 - LOG_ID_SYNC_FTOKEN_SUCC	546
32158 - LOG_ID_SYNC_FTOKEN_FAIL	547
32159 - LOG_ID_ACT_FTOKEN_FAIL	547
32160 - LOG_ID_FTM_PUSH_SUCC	548
32161 - LOG_ID_FTM_PUSH_FAIL	549
32168 - LOG_ID_REACH_VDOM_LIMIT	549
32169 - LOG_ID_ALARM_DLP_DB	550
32170 - LOG_ID_ALARM_MSG	551
32171 - LOG_ID_ALARM_ACK	552
32172 - LOG_ID_ADD_IP4_LOCAL_POL	553
32173 - LOG_ID_CHG_IP4_LOCAL_POL	553
32174 - LOG_ID_DEL_IP4_LOCAL_POL	554
32190 - LOG_ID_UPT_INVALID_IMG	555
32191 - LOG_ID_UPT_INVALID_IMG_CC	556
32192 - LOG_ID_UPT_INVALID_IMG_RSA	556
32193 - LOG_ID_UPT_IMG_RSA	557
32194 - LOG_ID_UPT_IMG_FAIL	558

32199 - LOG_ID_RESTORE_IMG_USB	559
32200 - LOG_ID_SHUTDOWN	560
32201 - LOG_ID_LOAD_IMG_SUCC	560
32202 - LOG_ID_RESTORE_IMG	561
32203 - LOG_ID_RESTORE_CONF	562
32204 - LOG_ID_RESTORE_FGD_SVR	563
32205 - LOG_ID_RESTORE_VDOM_LIC	564
32206 - LOG_ID_RESTORE_SCRIPT	564
32207 - LOG_ID_RETRIEVE_CONF_LIST	565
32208 - LOG_ID_IMP_PKCS12_CERT	566
32209 - LOG_ID_RESTORE_USR_DEF_IPS	567
32210 - LOG_ID_BACKUP_IMG_SUCC	567
32211 - LOG_ID_UPLOAD_REVISION	568
32212 - LOG_ID_DEL_REVISION	569
32213 - LOG_ID_RESTORE_TEMPLATE	570
32214 - LOG_ID_RESTORE_FILE	571
32215 - LOG_ID_UPT_IMG	571
32217 - LOG_ID_UPD_IPS	572
32218 - LOG_ID_UPD_DLP	573
32219 - LOG_ID_BACKUP_OUTPUT	574
32220 - LOG_ID_BACKUP_COMMAND	575
32221 - LOG_ID_UPD_VDOM_LIC	575
32222 - LOG_ID_GLB_SETTING_CHG	576
32223 - LOG_ID_BACKUP_USER_DEF_IPS	577
32224 - LOG_ID_BACKUP_DISK_LOG	578
32225 - LOG_ID_DEL_ALL_REVISION	579
32226 - LOG_ID_LOAD_IMG_FAIL	579
32227 - LOG_ID_UPD_DLP_FAIL	580
32228 - LOG_ID_LOAD_IMG_FAIL_WRONG_IMG	581
32229 - LOG_ID_LOAD_IMG_FAIL_NO_RSA	582
32230 - LOG_ID_LOAD_IMG_FAIL_INVALID_RSA	583
32231 - LOG_ID_RESTORE_FGD_SVR_FAIL	583
32232 - LOG_ID_RESTORE_VDOM_LIC_FAIL	584
32233 - LOG_ID_BACKUP_IMG_FAIL	585
32234 - LOG_ID_RESTORE_IMG_INVALID_CC	586
32235 - LOG_ID_RESTORE_IMG_FORTIGUARD	586
32236 - LOG_ID_BACKUP_MEM_LOG	587
32237 - LOG_ID_BACKUP_MEM_LOG_FAIL	588
32238 - LOG_ID_BACKUP_DISK_LOG_FAIL	589
32239 - LOG_ID_BACKUP_DISK_LOG_USB	590
32240 - LOG_ID_SYS_USB_MODE	590
32241 - LOG_ID_BACKUP_DISK_LOG_USB_FAIL	591
32242 - LOG_ID_UPD_VDOM_LIC_FAIL	592
32243 - LOG_ID_UPD_IPS_SCP	593
32244 - LOG_ID_UPD_IPS_SCP_FAIL	593
32245 - LOG_ID_BACKUP_USER_DEF_IPS_FAIL	594
32246 - LOG_ID_RESTORE_USR_DEF_IPS_CRITICAL	595
32247 - LOG_ID_SSH_NEGOTIATION_FAILURE	596
32248 - LOG_ID_IMG_NOT_SIGNED_NOT_CONFIRM	597

32249 - LOG_ID_IMG_NOT_SIGNED	597
32252 - LOG_ID_FACTORY_RESET	598
32253 - LOG_ID_FORMAT_RAID	599
32254 - LOG_ID_ENABLE_RAID	600
32255 - LOG_ID_DISABLE_RAID	600
32300 - LOG_ID_UPLOAD_RPT_IMG	601
32301 - LOG_ID_ADD_VDOM	602
32302 - LOG_ID_DEL_VDOM	603
32545 - LOG_ID_SYS_RESTART	604
32546 - LOG_ID_APPLICATION_CRASH	604
32547 - LOG_ID_AUTOSCRIPT_START	605
32548 - LOG_ID_AUTOSCRIPT_STOP	606
32549 - LOG_ID_AUTOSCRIPT_STOP_AUTO	607
32550 - LOG_ID_AUTOSCRIPT_DELETE_RSLT	607
32551 - LOG_ID_AUTOSCRIPT_BACKUP_RSLT	608
32552 - LOG_ID_AUTOSCRIPT_CHECK_STATUS	609
32553 - LOG_ID_AUTOSCRIPT_STOP_REACH_LIMIT	610
32561 - LOG_ID_ADMIN_LOGOUT_DISCONNECT	610
32562 - LOG_ID_STORE_CONF_FAIL_SPACE	611
32564 - LOG_ID_RESTORE_CONF_FAIL	612
32565 - LOG_ID_RESTORE_CONF_BY_MGMT	613
32566 - LOG_ID_RESTORE_CONF_BY_SCP	614
32567 - LOG_ID_RESTORE_CONF_BY_USB	614
32568 - LOG_ID_DEL_REVISION_DB	615
32569 - LOG_ID_FSW_SWITCH_LOG_EVENT	616
32570 - LOG_ID_ADMIN_MTNER_LOGOUT_DISCONNECT	617
32601 - LOG_ID_FGT_SWITCH_LOG_DISCOVER	618
32602 - LOG_ID_FGT_SWITCH_LOG_AUTH	619
32603 - LOG_ID_FGT_SWITCH_LOG_DEAUTH	619
32604 - LOG_ID_FGT_SWITCH_LOG_DELETE	620
32605 - LOG_ID_FGT_SWITCH_LOG_TUNNEL_UP	621
32606 - LOG_ID_FGT_SWITCH_LOG_TUNNEL_DOWN	622
32607 - LOG_ID_FGT_SWITCH_PUSH_IMAGE	622
32608 - LOG_ID_FGT_SWITCH_STAGE_IMAGE	623
32609 - LOG_ID_FGT_SWITCH_DISABLE_DISCOVERY	624
32610 - LOG_ID_FGT_SWITCH_LOG_WARNING	625
32611 - LOG_ID_FGT_SWITCH_EXPORT_POOL	625
32612 - LOG_ID_FGT_SWITCH_EXPORT_VDOM	626
32613 - LOG_ID_FGT_SWITCH_REQUEST_PORT	627
32614 - LOG_ID_FGT_SWITCH_RETURN_PORT	628
32615 - LOG_ID_FGT_SWITCH_MAC_ADD	628
32616 - LOG_ID_FGT_SWITCH_MAC_DEL	629
32617 - LOG_ID_FGT_SWITCH_MAC_MOVE	630
32693 - LOG_ID_FGT_SWITCH_GROUP_SWC	631
32694 - LOG_ID_FGT_SWITCH_GROUP_POE	631
32695 - LOG_ID_FGT_SWITCH_GROUP_LINK	632
32696 - LOG_ID_FGT_SWITCH_GROUP_STP	633
32697 - LOG_ID_FGT_SWITCH_GROUP_SWITCH	634
32698 - LOG_ID_FGT_SWITCH_GROUP_ROUTER	635

32699 - LOG_ID_FGT_SWITCH_GROUP_SYSTEM	636
32700 - LOG_ID_DPDK_EARLY_INIT_FAIL	637
34415 - LOG_ID_NP6_IPSEC_ENGINE_BUSY	637
34416 - LOG_ID_NP6_IPSEC_ENGINE_POSSIBLY_LOCKUP	638
34417 - LOG_ID_NP6_IPSEC_ENGINE_LOCKUP	639
34418 - LOG_ID_NP6_HPE_PACKET_DROP	639
34419 - LOG_ID_NP6_HPE_PACKET_FLOOD	640
35001 - LOG_ID_HA_SYNC_VIRDB	641
35002 - LOG_ID_HA_SYNC_ETDB	641
35003 - LOG_ID_HA_SYNC_EXDB	642
35004 - LOG_ID_HA_SYNC_FLDB	643
35005 - LOG_ID_HA_SYNC_IPS	643
35007 - LOG_ID_HA_SYNC_AV	644
35009 - LOG_ID_HA_SYNC_CID	645
35011 - LOG_ID_HA_SYNC_FAIL	645
35012 - LOG_ID_CONF_SYNC_FAIL	646
35013 - LOG_ID_HA_FAILOVER_FAIL	647
35014 - LOG_ID_HA_RESET_UPTIME	647
35015 - LOG_ID_HA_CLEAR_HISTORY	648
35016 - LOG_ID_HA_FAILOVER_SUCCESS	649
36881 - LOG_ID_EVENT_SYSTEM_CFG_REVERT	650
36882 - LOG_ID_EVENT_SYSTEM_CFG_MANUALLY_SAVED	650
37120 - MSGID_NEG_GENERIC_P1_NOTIF	651
37121 - MSGID_NEG_GENERIC_P1_ERROR	652
37122 - MSGID_NEG_GENERIC_P2_NOTIF	653
37123 - MSGID_NEG_GENERIC_P2_ERROR	655
37124 - MSGID_NEG_I_P1_ERROR	656
37125 - MSGID_NEG_I_P2_ERROR	657
37126 - MSGID_NEG_NO_STATE_ERROR	658
37127 - MSGID_NEG_PROGRESS_P1_NOTIF	660
37128 - MSGID_NEG_PROGRESS_P1_ERROR	661
37129 - MSGID_NEG_PROGRESS_P2_NOTIF	663
37130 - MSGID_NEG_PROGRESS_P2_ERROR	664
37131 - MSGID_ESP_ERROR	665
37132 - MSGID_ESP_CRITICAL	667
37133 - MSGID_INSTALL_SA	668
37134 - MSGID_DELETE_P1_SA	669
37135 - MSGID_DELETE_P2_SA	670
37136 - MSGID_DPD_FAILURE	671
37137 - MSGID_CONN_FAILURE	673
37138 - MSGID_CONN_UPDOWN	674
37139 - MSGID_P2_UPDOWN	675
37141 - MSGID_CONN_STATS	676
37889 - MSGID_VC_DELETE	678
37890 - MSGID_VC_MOVE_VDOM	678
37891 - MSGID_VC_ADD_VDOM	679
37892 - MSGID_VC_MOVE_MEMB_STATE	680
37893 - MSGID_VC_DETECT_MEMB_DEAD	681
37894 - MSGID_VC_DETECT_MEMB_JOIN	681

37895 - MESSID_VC_ADD_HADEV	682
37896 - MESSID_VC_DEL_HADEV	683
37897 - MESSID_HADEV_READY	684
37898 - MESSID_HADEV_FAIL	684
37899 - MESSID_HADEV_PEERINFO	685
37900 - MESSID_HBDEV_DELETE	686
37901 - MESSID_HBDEV_DOWN	687
37902 - MESSID_HBDEV_UP	687
37903 - MESSID_SYNC_STATUS	688
37904 - MESSID_HA_ACTIVITY	689
37907 - MESSID_VLAN_HB_UP	690
37908 - MESSID_VLAN_HB_DOWN	690
37909 - MESSID_VLAN_HB_DOWN_SUM	691
38010 - LOG_ID_FIPS_ENCRY_FAIL	692
38011 - LOG_ID_FIPS_DECRY_FAIL	692
38012 - LOG_ID_ENTROPY_TOKEN	693
38031 - LOG_ID_FSSO_LOGON	694
38032 - LOG_ID_FSSO_LOGOFF	695
38033 - LOG_ID_FSSO_SVR_STATUS	696
38400 - LOGID_EVENT_NOTIF_SEND_SUCC	696
38401 - LOGID_EVENT_NOTIF_SEND_FAIL	698
38402 - LOGID_EVENT_NOTIF_DNS_FAIL	699
38403 - LOGID_EVENT_NOTIF_INSUFFICIENT_RESOURCE	700
38404 - LOGID_EVENT_NOTIF_HOSTNAME_ERROR	700
38405 - LOGID_NOTIF_CODE_SENDTO_SMS_PHONE	701
38406 - LOGID_NOTIF_CODE_SENDTO_SMS_TO	702
38407 - LOGID_NOTIF_CODE_SENDTO_EMAIL	702
38408 - LOGID_EVENT_OFTP_SSL_CONNECTED	703
38409 - LOGID_EVENT_OFTP_SSL_DISCONNECTED	704
38410 - LOGID_EVENT_OFTP_SSL_FAILED	705
38411 - LOGID_EVENT_TWO_F_AUTH_CODE_SENDTO	706
38412 - LOGID_EVENT_TOKEN_CODE_SENDTO	706
38656 - LOGID_EVENT_RAD_RPT_PROTO_ERROR	707
38657 - LOGID_EVENT_RAD_RPT_PROF_NOT_FOUND	708
38658 - LOGID_EVENT_RAD_RPT_CTX_NOT_FOUND	709
38659 - LOGID_EVENT_RAD_RPT_ACCT_STOP_MISSED	709
38660 - LOGID_EVENT_RAD_RPT_ACCT_EVENT	710
38661 - LOGID_EVENT_RAD_RPT_OTHER	711
38662 - LOGID_EVENT_RAD_STAT_PROTO_ERROR	712
38663 - LOGID_EVENT_RAD_STAT_PROF_NOT_FOUND	713
38665 - LOGID_EVENT_RAD_STAT_ACCT_STOP_MISSED	713
38666 - LOGID_EVENT_RAD_STAT_ACCT_EVENT	714
38667 - LOGID_EVENT_RAD_STAT_OTHER	715
38668 - LOGID_EVENT_RAD_STAT_EP_BLK	716
39424 - LOG_ID_EVENT_SSL_VPN_USER_TUNNEL_UP	717
39425 - LOG_ID_EVENT_SSL_VPN_USER_TUNNEL_DOWN	718
39426 - LOG_ID_EVENT_SSL_VPN_USER_SSL_LOGIN_FAIL	719
39936 - LOG_ID_EVENT_SSL_VPN_SESSION_WEB_TUNNEL_STATS	720
39937 - LOG_ID_EVENT_SSL_VPN_SESSION_WEBAPP_DENY	721

39938 - LOG_ID_EVENT_SSL_VPN_SESSION_WEBAPP_PASS	722
39939 - LOG_ID_EVENT_SSL_VPN_SESSION_WEBAPP_TIMEOUT	723
39940 - LOG_ID_EVENT_SSL_VPN_SESSION_WEBAPP_CLOSE	724
39941 - LOG_ID_EVENT_SSL_VPN_SESSION_SYS_BUSY	725
39942 - LOG_ID_EVENT_SSL_VPN_SESSION_CERT_OK	726
39943 - LOG_ID_EVENT_SSL_VPN_SESSION_NEW_CON	727
39944 - LOG_ID_EVENT_SSL_VPN_SESSION_ALERT	728
39945 - LOG_ID_EVENT_SSL_VPN_SESSION_EXIT_FAIL	728
39946 - LOG_ID_EVENT_SSL_VPN_SESSION_EXIT_ERR	729
39947 - LOG_ID_EVENT_SSL_VPN_SESSION_TUNNEL_UP	730
39948 - LOG_ID_EVENT_SSL_VPN_SESSION_TUNNEL_DOWN	731
39949 - LOG_ID_EVENT_SSL_VPN_SESSION_TUNNEL_STATS	732
39950 - LOG_ID_EVENT_SSL_VPN_SESSION_TUNNEL_UNKNOWNTAG	733
39951 - LOG_ID_EVENT_SSL_VPN_SESSION_TUNNEL_ERROR	734
39952 - LOG_ID_EVENT_SSL_VPN_SESSION_ENTER_CONSERVE_MODE	735
39953 - LOG_ID_EVENT_SSL_VPN_SESSION_LEAVE_CONSERVE_MODE	736
40001 - LOG_ID_PPTP_TUNNEL_UP	737
40002 - LOG_ID_PPTP_TUNNEL_DOWN	738
40003 - LOG_ID_PPTP_TUNNEL_STAT	739
40014 - LOG_ID_PPTP_REACH_MAX_CON	740
40017 - LOG_ID_L2TPD_CLIENT_CON_FAIL	741
40019 - LOG_ID_L2TPD_CLIENT_DISCON	741
40021 - LOG_ID_PPTP_NOT_CONIG	742
40022 - LOG_ID_PPTP_NO_IP_AVAIL	743
40024 - LOG_ID_PPTP_OUT_MEM	744
40034 - LOG_ID_PPTP_START	744
40035 - LOG_ID_PPTP_START_FAIL	745
40036 - LOG_ID_PPTP_EXIT	746
40037 - LOG_ID_PPTPD_SVR_DISCON	747
40038 - LOG_ID_PPTPD_CLIENT_CON	748
40039 - LOG_ID_PPTPD_CLIENT_DISCON	748
40101 - LOG_ID_L2TP_TUNNEL_UP	749
40102 - LOG_ID_L2TP_TUNNEL_DOWN	750
40103 - LOG_ID_L2TP_TUNNEL_STAT	751
40114 - LOG_ID_L2TPD_START	752
40115 - LOG_ID_L2TPD_EXIT	753
40118 - LOG_ID_L2TPD_CLIENT_CON	753
40704 - LOG_ID_EVENT_SYS_PERF	754
40705 - LOG_ID_EVENT_SYS_CPU_USAGE	755
40706 - LOG_ID_EVENT_SYS_BROKEN_SYMBOLIC_LINK	756
40960 - LOG_ID_EVENT_WAD_WEBPROXY_FWD_SRV_ERROR	757
41000 - LOG_ID_UPD_FGT_SUCC	758
41001 - LOG_ID_UPD_FGT_FAIL	758
41002 - LOG_ID_UPD_SRC_VIS	759
41006 - LOG_ID_UPD_FSA_VIRDB	760
41984 - LOG_ID_EVENT_VPN_CERT_LOAD	760
41985 - LOG_ID_EVENT_VPN_CERT_REMOVAL	761
41986 - LOG_ID_EVENT_VPN_CERT_REGEN	762
41987 - LOG_ID_EVENT_VPN_CERT_UPDATE	763

41988 - LOG_ID_EVENT_SSL_VPN_SETTING_UPDATE	764
41989 - LOG_ID_EVENT_VPN_CERT_ERR	765
41990 - LOG_ID_EVENT_VPN_CERT_UPDATE_FAILED	766
41991 - LOG_ID_EVENT_VPN_CERT_EXPORT	767
42201 - LOG_ID_NETX_VMX_ATTACH	767
42202 - LOG_ID_NETX_VMX_DETACH	768
42203 - LOG_ID_NETX_VMX_DENIED	769
43008 - LOG_ID_EVENT_AUTH_SUCCESS	769
43009 - LOG_ID_EVENT_AUTH_FAILED	770
43010 - LOG_ID_EVENT_AUTH_LOCKOUT	771
43011 - LOG_ID_EVENT_AUTH_TIME_OUT	772
43014 - LOG_ID_EVENT_AUTH_FSAE_LOGON	773
43015 - LOG_ID_EVENT_AUTH_FSAE_LOGOFF	774
43016 - LOG_ID_EVENT_AUTH_NTLM_AUTH_SUCCESS	775
43017 - LOG_ID_EVENT_AUTH_NTLM_AUTH_FAIL	776
43018 - LOG_ID_EVENT_AUTH_FGOVRD_FAIL	777
43020 - LOG_ID_EVENT_AUTH_FGOVRD_SUCCESS	778
43025 - LOG_ID_EVENT_AUTH_PROXY_SUCCESS	779
43026 - LOG_ID_EVENT_AUTH_PROXY_FAILED	780
43027 - LOG_ID_EVENT_AUTH_PROXY_TIME_OUT	781
43028 - LOG_ID_EVENT_AUTH_PROXY_GROUP_INFO_FAILED	782
43029 - LOG_ID_EVENT_AUTH_WARNING_SUCCESS	783
43030 - LOG_ID_EVENT_AUTH_WARNING_TBL_FULL	784
43032 - LOG_ID_EVENT_AUTH_PROXY_USER_LIMIT_REACHED	785
43033 - LOG_ID_EVENT_AUTH_PROXY_MULTIPLE_LOGIN	786
43034 - LOG_ID_EVENT_AUTH_PROXY_NO_RESP	787
43037 - LOG_ID_EVENT_AUTH_IPV4_FLUSH	788
43038 - LOG_ID_EVENT_AUTH_IPV6_FLUSH	788
43039 - LOG_ID_EVENT_AUTH_LOGON	789
43040 - LOG_ID_EVENT_AUTH_LOGOUT	790
43041 - LOG_ID_EVENT_AUTH_DISCLAIMER_ACCEPT	791
43042 - LOG_ID_EVENT_AUTH_DISCLAIMER_DECLINE	792
43043 - LOG_ID_EVENT_AUTH_EMAIL_COLLECTING_SUCCESS	793
43044 - LOG_ID_EVENT_AUTH_EMAIL_COLLECTING_FAIL	794
43045 - LOG_ID_EVENT_AUTH_8021X_SUCCESS	795
43046 - LOG_ID_EVENT_AUTH_8021X_FAIL	796
43050 - LOG_ID_EVENT_AUTH_FSAE_CONNECT	797
43051 - LOG_ID_EVENT_AUTH_FSAE_DISCONNECT	797
43264 - LOGID_MMS_STATS	798
43520 - LOG_ID_EVENT_WIRELESS_SYS	799
43521 - LOG_ID_EVENT_WIRELESS_ROGUE	800
43522 - LOG_ID_EVENT_WIRELESS_WTP	801
43524 - LOG_ID_EVENT_WIRELESS_STA	802
43525 - LOG_ID_EVENT_WIRELESS_ONWIRE	803
43526 - LOG_ID_EVENT_WIRELESS_WTPR	805
43527 - LOG_ID_EVENT_WIRELESS_ROGUE_CFG	806
43528 - LOG_ID_EVENT_WIRELESS_WTPR_ERROR	807
43529 - LOG_ID_EVENT_WIRELESS_CLB	808
43530 - LOG_ID_EVENT_WIRELESS_WIDS_WL_BRIDGE	809

43531 - LOG_ID_EVENT_WIRELESS_WIDS_BR_DEAUTH	810
43532 - LOG_ID_EVENT_WIRELESS_WIDS_NL_PBRESP	811
43533 - LOG_ID_EVENT_WIRELESS_WIDS_MAC_OUI	812
43534 - LOG_ID_EVENT_WIRELESS_WIDS_LONG_DUR	814
43535 - LOG_ID_EVENT_WIRELESS_WIDS_WEP_IV	815
43542 - LOG_ID_EVENT_WIRELESS_WIDS_EAPOL_FLOOD	816
43544 - LOG_ID_EVENT_WIRELESS_WIDS_MGMT_FLOOD	817
43546 - LOG_ID_EVENT_WIRELESS_WIDS_SPOOF_DEAUTH	818
43548 - LOG_ID_EVENT_WIRELESS_WIDS_ASLEAP	819
43550 - LOG_ID_EVENT_WIRELESS_STA_LOCATE	820
43551 - LOG_ID_EVENT_WIRELESS_WTP_JOIN	821
43552 - LOG_ID_EVENT_WIRELESS_WTP_LEAVE	822
43553 - LOG_ID_EVENT_WIRELESS_WTP_FAIL	823
43554 - LOG_ID_EVENT_WIRELESS_WTP_UPDATE	824
43555 - LOG_ID_EVENT_WIRELESS_WTP_RESET	825
43556 - LOG_ID_EVENT_WIRELESS_WTP_KICK	826
43557 - LOG_ID_EVENT_WIRELESS_WTP_ADD_FAILURE	827
43558 - LOG_ID_EVENT_WIRELESS_WTP_CFG_ERR	828
43559 - LOG_ID_EVENT_WIRELESS_WTP_SN_MISMATCH	829
43560 - LOG_ID_EVENT_WIRELESS_SYS_AC_RESTARTED	830
43561 - LOG_ID_EVENT_WIRELESS_SYS_AC_HOSTAPD_UP	831
43562 - LOG_ID_EVENT_WIRELESS_SYS_AC_HOSTAPD_DOWN	831
43563 - LOG_ID_EVENT_WIRELESS_ROGUE_DETECT	832
43564 - LOG_ID_EVENT_WIRELESS_ROGUE_OFFAIR	834
43565 - LOG_ID_EVENT_WIRELESS_ROGUE_ONAIR	835
43566 - LOG_ID_EVENT_WIRELESS_ROGUE_OFFWIRE	836
43567 - LOG_ID_EVENT_WIRELESS_FAKEAP_DETECT	838
43568 - LOG_ID_EVENT_WIRELESS_FAKEAP_ONAIR	839
43569 - LOG_ID_EVENT_WIRELESS_ROGUE_SUPPRESSED	841
43570 - LOG_ID_EVENT_WIRELESS_ROGUE_UNSUPPRESSED	842
43571 - LOG_ID_EVENT_WIRELESS_ROGUE_DETECT_CHG	844
43572 - LOG_ID_EVENT_WIRELESS_STA ASSO	845
43573 - LOG_ID_EVENT_WIRELESS_STA_AUTH	846
43574 - LOG_ID_EVENT_WIRELESS_STA_DASS	848
43575 - LOG_ID_EVENT_WIRELESS_STA_DAUT	849
43576 - LOG_ID_EVENT_WIRELESS_STA_IDLE	850
43577 - LOG_ID_EVENT_WIRELESS_STA_DENY	851
43578 - LOG_ID_EVENT_WIRELESS_STA_KICK	853
43579 - LOG_ID_EVENT_WIRELESS_STA_IP	854
43580 - LOG_ID_EVENT_WIRELESS_STA_LEAVE_WTP	855
43581 - LOG_ID_EVENT_WIRELESS_STA_WTP_DISCONN	856
43582 - LOG_ID_EVENT_WIRELESS_ROGUE_CFG_UNCLASSIFIED	857
43583 - LOG_ID_EVENT_WIRELESS_ROGUE_CFG_ACCEPTED	858
43584 - LOG_ID_EVENT_WIRELESS_ROGUE_CFG_ROGUE	859
43585 - LOG_ID_EVENT_WIRELESS_ROGUE_CFG_SUPPRESSED	860
43586 - LOG_ID_EVENT_WIRELESS_WTPR_DARRP_CHAN	861
43587 - LOG_ID_EVENT_WIRELESS_WTPR_DARRP_START	862
43588 - LOG_ID_EVENT_WIRELESS_WTPR_OPER_CHAN	863
43589 - LOG_ID_EVENT_WIRELESS_WTPR_RADAR	864

43590 - LOG_ID_EVENT_WIRELESS_WTPR_NOL	865
43591 - LOG_ID_EVENT_WIRELESS_WTPR_COUNTRY_CFG_SUCCESS	866
43592 - LOG_ID_EVENT_WIRELESS_WTPR_OPER_COUNTRY	867
43593 - LOG_ID_EVENT_WIRELESS_WTPR_CFG_TXPOWER	868
43594 - LOG_ID_EVENT_WIRELESS_WTPR_OPER_TXPOWER	869
43595 - LOG_ID_EVENT_WIRELESS_CLB_DENY	870
43596 - LOG_ID_EVENT_WIRELESS_CLB_RETRY	871
43597 - LOG_ID_EVENT_WIRELESS_WTP_ADD	872
43598 - LOG_ID_EVENT_WIRELESS_WTP_ADD_XSS	873
43599 - LOG_ID_EVENT_WIRELESS_WTP_DEL	874
43600 - LOG_ID_EVENT_WIRELESS_WTPR_DARRP_STOP	875
43601 - LOG_ID_EVENT_WIRELESS_STA_CAP_SIGNON	876
43602 - LOG_ID_EVENT_WIRELESS_STA_CAP_SIGNON_SUCCESS	877
43603 - LOG_ID_EVENT_WIRELESS_STA_CAP_SIGNON_FAILURE	879
43604 - LOG_ID_EVENT_WIRELESS_STA_CAP_EMAIL_REQUEST	880
43605 - LOG_ID_EVENT_WIRELESS_STA_CAP_EMAIL_SUCCESS	881
43606 - LOG_ID_EVENT_WIRELESS_STA_CAP_EMAIL_FAILURE	882
43607 - LOG_ID_EVENT_WIRELESS_STA_CAP_DISCLAIMER_CHECK	883
43608 - LOG_ID_EVENT_WIRELESS_STA_CAP_DISCLAIMER_DECLINE	885
43609 - LOG_ID_EVENT_WIRELESS_WTPR_DARRP_OPTIMIZATION_START	886
43610 - LOG_ID_EVENT_WIRELESS_WTPR_DARRP_OPTIMIZATION_STOP	887
43611 - LOG_ID_EVENT_WIRELESS_SYS_AC_UP	888
43612 - LOG_ID_EVENT_WIRELESS_SYS_AC_CFG_LOADED	889
43613 - LOG_ID_EVENT_WIRELESS_WTP_ERR	889
43614 - LOG_ID_EVENT_WIRELESS_DHCP_STAVATION	890
43615 - LOG_ID_EVENT_WIRELESS_SYS_AC_IPSEC_FAIL	891
43616 - LOG_ID_EVENT_WIRELESS_WTPR_NOL_ADD	892
43618 - LOG_ID_EVENT_WIRELESS_WTP_IMAGE_RC_SUCCESS	893
43619 - LOG_ID_EVENT_WIRELESS_OFFENDINGAP_DETECT	894
43620 - LOG_ID_EVENT_WIRELESS_OFFENDINGAP_ONAIR	895
43621 - LOG_ID_EVENT_WIRELESS_WTP_DATA_CHAN_CHG	897
43622 - LOG_ID_EVENT_WIRELESS_WTP_VLAN_PROBE	898
43623 - LOG_ID_EVENT_WIRELESS_WTP_VLAN_MISSING	899
43624 - LOG_ID_EVENT_WIRELESS_WTP_VLAN_DETECTED	900
43625 - LOG_ID_EVENT_WIRELESS_STA_CAP_CMCC_SUCCESS	901
43626 - LOG_ID_EVENT_WIRELESS_STA_CAP_CMCC_FAILURE	902
43627 - LOG_ID_EVENT_WIRELESS_STA_CAP_CMCC_TIMEOUT	903
43628 - LOG_ID_EVENT_WIRELESS_STA_CAP_CMCC_MAC_AUTH_SUCCESS	904
43629 - LOG_ID_EVENT_WIRELESS_STA_RADIUS_AUTH_FAILURE	906
43630 - LOG_ID_EVENT_WIRELESS_STA_RADIUS_AUTH_SUCCESS	907
43631 - LOG_ID_EVENT_WIRELESS_STA_RADIUS_AUTH_NO_RESP	908
43632 - LOG_ID_EVENT_WIRELESS_STA_RADIUS_MAC_AUTH_FAILURE	909
43633 - LOG_ID_EVENT_WIRELESS_STA_RADIUS_MAC_AUTH_SUCCESS	910
43634 - LOG_ID_EVENT_WIRELESS_STA_RADIUS_MAC_AUTH_NO_RESP	911
43635 - LOG_ID_EVENT_WIRELESS_STA_OKC_NO_MATCH	912
43636 - LOG_ID_EVENT_WIRELESS_STA_OKC_LOCAL_MATCH	913
43637 - LOG_ID_EVENT_WIRELESS_STA_OKC_INTER_AC_MATCH	914
43638 - LOG_ID_EVENT_WIRELESS_STA_OKC_INTER_AP_MATCH	915
43639 - LOG_ID_EVENT_WIRELESS_STA_FT_INVALID_ACTION_REQ	917

43640 - LOG_ID_EVENT_WIRELESS_STA_FT_INVALID_AUTH_REQ	918
43641 - LOG_ID_EVENT_WIRELESS_STA_FT_INVALID_REASSOC_REQ	919
43642 - LOG_ID_EVENT_WIRELESS_STA_FT_ACTION_REQ	920
43643 - LOG_ID_EVENT_WIRELESS_STA_FT_ACTION_RESP	921
43644 - LOG_ID_EVENT_WIRELESS_STA_FT_AUTH_REQ	922
43645 - LOG_ID_EVENT_WIRELESS_STA_FT_AUTH_RESP	923
43646 - LOG_ID_EVENT_WIRELESS_STA_FT_REASSOC_REQ	924
43647 - LOG_ID_EVENT_WIRELESS_STA_FT_REASSOC_RESP	925
43648 - LOG_ID_EVENT_WIRELESS_STA_WPA_MSG_INVALID_SECOND_MSG	926
43649 - LOG_ID_EVENT_WIRELESS_STA_WPA_MSG_INVALID_FOURTH_MSG	928
43650 - LOG_ID_EVENT_WIRELESS_STA_WPA_MSG_FIRST_MSG	929
43651 - LOG_ID_EVENT_WIRELESS_STA_WPA_MSG_SECOND_MSG	930
43652 - LOG_ID_EVENT_WIRELESS_STA_WPA_MSG_THIRD_MSG	931
43653 - LOG_ID_EVENT_WIRELESS_STA_WPA_MSG_FOURTH_MSG	932
43654 - LOG_ID_EVENT_WIRELESS_STA_WPA_MSG_FIRST_GROUP_MSG	933
43655 - LOG_ID_EVENT_WIRELESS_STA_WPA_MSG_SECOND_GROUP_MSG	934
43656 - LOG_ID_EVENT_WIRELESS_STA_WPA_MSG_MAX_STA_CNT	935
43657 - LOG_ID_EVENT_WIRELESS_STA_ASSOC_FAIL	936
43658 - LOG_ID_EVENT_WIRELESS_STA_DHCP_NO_RESP	937
43659 - LOG_ID_EVENT_WIRELESS_STA_DHCP_DIFF_OFFER	938
43660 - LOG_ID_EVENT_WIRELESS_STA_DHCP_NO_ACK	939
43661 - LOG_ID_EVENT_WIRELESS_STA_DHCP_NAK	940
43662 - LOG_ID_EVENT_WIRELESS_STA_DHCP_DUP_IP	941
43663 - LOG_ID_EVENT_WIRELESS_STA_DHCP_DISCOVER	942
43664 - LOG_ID_EVENT_WIRELESS_STA_DHCP_OFFER	943
43665 - LOG_ID_EVENT_WIRELESS_STA_DHCP_DECLINE	944
43666 - LOG_ID_EVENT_WIRELESS_STA_DHCP_REQUEST	945
43667 - LOG_ID_EVENT_WIRELESS_STA_DHCP_ACK	946
43668 - LOG_ID_EVENT_WIRELESS_STA_DHCP_RELEASE	947
43669 - LOG_ID_EVENT_WIRELESS_STA_DHCP_INFORM	948
43670 - LOG_ID_EVENT_WIRELESS_STA_DHCP_SELF_ASSIGNED	949
43671 - LOG_ID_EVENT_WIRELESS_STA_DNS_NO_RESP	950
43672 - LOG_ID_EVENT_WIRELESS_STA_DNS_SERVER_FAILURE	951
43673 - LOG_ID_EVENT_WIRELESS_STA_DNS_NO_DOMAIN	952
43674 - LOG_ID_EVENT_WIRELESS_STA_WPA_KRACK_FT_REASSOC	953
43675 - LOG_ID_EVENT_WIRELESS_STA_AUTH_REQ	954
43676 - LOG_ID_EVENT_WIRELESS_STA_AUTH_RESP	955
43677 - LOG_ID_EVENT_WIRELESS_STA_ASSOC_REQ	956
43678 - LOG_ID_EVENT_WIRELESS_STA_REASSOC_REQ	958
43679 - LOG_ID_EVENT_WIRELESS_STA_ASSOC_RESP	959
43680 - LOG_ID_EVENT_WIRELESS_STA_REASSOC_RESP	960
43681 - LOG_ID_EVENT_WIRELESS_STA_PROBE_REQ	961
43682 - LOG_ID_EVENT_WIRELESS_STA_PROBE_RESP	962
43683 - LOG_ID_EVENT_WIRELESS_BLE_DEV_LOCATE	963
43684 - LOG_ID_EVENT_WIRELESS_ADDRGRP_DUPLICATE_MAC	964
43685 - LOG_ID_EVENT_WIRELESS_ADDRGRP_ADDR_APPLY	965
43686 - LOG_ID_EVENT_WIRELESS_STA_WPA_MSG_INVALID_SCHEDULE	966
43687 - LOG_ID_EVENT_WIRELESS_STA_WL_BRIDGE_TRAFFIC_STATS	967

43776 - LOG_ID_EVENT_NAC_QUARANTINE	968
43777 - LOG_ID_EVENT_NAC_ANOMALY_QUARANTINE	969
43800 - LOG_ID_EVENT_ELBC_BLADE_JOIN	970
43801 - LOG_ID_EVENT_ELBC_BLADE_LEAVE	971
43802 - LOG_ID_EVENT_ELBC_MASTER_BLADE_FOUND	972
43803 - LOG_ID_EVENT_ELBC_MASTER_BLADE_LOST	973
43804 - LOG_ID_EVENT_ELBC_MASTER_BLADE_CHANGE	974
43805 - LOG_ID_EVENT_ELBC_ACTIVE_CHANNEL_FOUND	974
43806 - LOG_ID_EVENT_ELBC_ACTIVE_CHANNEL_LOST	975
43807 - LOG_ID_EVENT_ELBC_ACTIVE_CHANNEL_CHANGE	976
43808 - LOG_ID_EVENT_ELBC_CHASSIS_ACTIVE	977
43809 - LOG_ID_EVENT_ELBC_CHASSIS_INACTIVE	978
44544 - LOGID_EVENT_CONFIG_PATH	979
44545 - LOGID_EVENT_CONFIG_OBJ	979
44546 - LOGID_EVENT_CONFIG_ATTR	980
44547 - LOGID_EVENT_CONFIG_OBJATTR	981
44548 - LOGID_EVENT_CONFIG_EXEC	982
44549 - LOGID_EVENT_CONFIG_OBJATTR_MTNER	983
44550 - LOGID_EVENT_CONFIG_OBJ_MTNER	984
44551 - LOGID_EVENT_CONFIG_ATTR_MTNER	985
44552 - LOGID_EVENT_CONFIG_PATH_MTNER	986
44553 - LOGID_EVENT_CONFIG_FIXEDPORT_DIS	986
44554 - LOGID_EVENT_CONFIG_POL_CHANGED	987
44555 - LOGID_EVENT_CMDB_DEADLOCK_DETECTED	988
45057 - LOG_ID_FCC_ADD	989
45058 - LOG_ID_FCC_CLOSE	990
45061 - LOG_ID_FCC_CLOSE_BY_TYPE	990
45071 - LOG_ID_FCC_VULN_SCAN	991
45109 - LOG_ID_EC_FTCL_LOGOFF	992
45114 - LOG_ID_EC_REG_QUARANTINE	993
45115 - LOG_ID_EC_REG_UNQUARANTINE	994
45119 - LOG_ID_EC_FTCL_DISCONN	995
46000 - LOG_ID_VIP_REAL_SVR_ENA	996
46001 - LOG_ID_VIP_REAL_SVR_DISA	997
46002 - LOG_ID_VIP_REAL_SVR_UP	997
46003 - LOG_ID_VIP_REAL_SVR_DOWN	998
46004 - LOG_ID_VIP_REAL_SVR_ENT_HOLDDOWN	999
46005 - LOG_ID_VIP_REAL_SVR_FAIL_HOLDDOWN	1000
46006 - LOG_ID_VIP_REAL_SVR_FAIL	1001
46400 - LOG_ID_EVENT_EXT_SYS	1002
46401 - LOG_ID_EVENT_EXT_LOCAL	1002
46402 - LOG_ID_EVENT_EXT_LOCAL_ERROR	1003
46403 - LOG_ID_EVENT_EXT_REMOTE_EMERG	1004
46404 - LOG_ID_EVENT_EXT_REMOTE_ALERT	1004
46405 - LOG_ID_EVENT_EXT_REMOTE_CRITICAL	1005
46406 - LOG_ID_EVENT_EXT_REMOTE_ERROR	1006
46407 - LOG_ID_EVENT_EXT_REMOTE_WARNING	1007
46408 - LOG_ID_EVENT_EXT_REMOTE_NOTIF	1007
46409 - LOG_ID_EVENT_EXT_REMOTE_INFO	1008

46410 - LOG_ID_EVENT_EXT_REMOTE_DEBUG	1009
46501 - LOG_ID_INTERNAL_LTE_MODEM_DETECTION	1010
46502 - LOG_ID_INTERNAL_LTE_MODEM_GPSD	1010
46503 - LOG_ID_INTERNAL_LTE_MODEM_GPS_LOC_ACQUISITION	1011
46504 - LOG_ID_INTERNAL_LTE_MODEM_BILLD	1012
46505 - LOG_ID_INTERNAL_LTE_MODEM_BILLING_PURGED	1012
46506 - LOG_ID_INTERNAL_LTE_MODEM_BILLING_DAILY_LOG	1013
46507 - LOG_ID_INTERNAL_LTE_MODEM_FW_UPGRADE	1014
46508 - LOG_ID_INTERNAL_LTE_MODEM_QDL_DETECTION	1014
46509 - LOG_ID_INTERNAL_LTE_MODEM_REBOOT	1015
46510 - LOG_ID_INTERNAL_LTE_MODEM_OP_MODE	1016
46511 - LOG_ID_INTERNAL_LTE_MODEM_POWER_ON_OFF	1016
46512 - LOG_ID_INTERNAL_LTE_MODEM_SIM_STATE	1017
46513 - LOG_ID_INTERNAL_LTE_MODEM_LINK_CONNECTION	1018
46514 - LOG_ID_INTERNAL_LTE_MODEM_MANUAL_HANOVER	1018
46515 - LOG_ID_INTERNAL_LTE_MODEM_IP_ADDR	1019
46516 - LOG_ID_INTERNAL_LTE_MODEM_BEARER_TECH_CHANGE	1020
46517 - LOG_ID_INTERNAL_LTE_MODEM_HARDWARE_ERROR	1020
46600 - LOG_ID_EVENT_AUTOMATION_TRIGGERED	1021
46900 - LOG_ID_POE_STATUS_REPORT	1022
47000 - LOG_ID_MALWARE_LIST_TRUNCATED_ENTER	1022
47001 - LOG_ID_MALWARE_LIST_TRUNCATED_EXIT	1023
47203 - LOG_ID_ENTER_BYPASS	1024
47204 - LOG_ID_EXIT_BYPASS	1024
48000 - LOG_ID_WAD_SSL_RCV_HS	1025
48001 - LOG_ID_WAD_SSL_RCV_WRG_HS	1026
48002 - LOG_ID_WAD_SSL_SENT_HS	1027
48003 - LOG_ID_WAD_SSL_WRG_HS_LEN	1028
48004 - LOG_ID_WAD_SSL_RCV_CCS	1029
48005 - LOG_ID_WAD_SSL_RSA_DH_FAIL	1030
48006 - LOG_ID_WAD_SSL_SENT_CCS	1031
48007 - LOG_ID_WAD_SSL_BAD_HASH	1032
48009 - LOG_ID_WAD_SSL_DECRY_FAIL	1033
48011 - LOG_ID_WAD_SSL_LESS_MINOR	1034
48013 - LOG_ID_WAD_SSL_NOT_SUPPORT_CS	1035
48016 - LOG_ID_WAD_SSL_HS_FIN	1036
48017 - LOG_ID_WAD_SSL_HS_TOO_LONG	1036
48019 - LOG_ID_WAD_SSL_SENT_ALERT	1037
48023 - LOG_ID_WAD_SSL_RCV_ALERT	1038
48027 - LOG_ID_WAD_SSL_INVALID_CONT_TYPE	1039
48029 - LOG_ID_WAD_SSL_BAD_CCS_LEN	1040
48031 - LOG_ID_WAD_SSL_BAD_DH	1041
48032 - LOG_ID_WAD_SSL_PUB_KEY_TOO_BIG	1042
48034 - LOG_ID_WAD_SSL_SERVER_KEY_HASH_ALGORITHM_MISMATCH ..	1043
48035 - LOG_ID_WAD_SSL_SERVER_KEY_SIGNATURE_ALGORITHM_	
MISMATCH	1044
48038 - LOG_ID_WAD_SSL_RCV_FATAL_ALERT	1045
48039 - LOG_ID_WAD_SSL_SENT_FATAL_ALERT	1046
48101 - LOG_ID_WAD_AUTH_FAIL_PSK	1047

48102 - LOG_ID_WAD_AUTH_FAIL_OTH	1048
48300 - LOG_ID_WRG_SVR_FGT_CONF	1049
48301 - LOG_ID_UNEXP_APP_TYPE	1050
51000 - LOG_ID_NB_TBL_CHG	1051
52000 - LOG_ID_EVENT_SECURITY_AUDIT_FABRIC_SUMMARY	1052
52001 - LOG_ID_EVENT_SECURITY_AUDIT_FABRIC_CHANGE	1052
53000 - LOG_ID_SDNC_CONNECTED	1053
53001 - LOG_ID_SDNC_DISCONNECTED	1054
53002 - LOG_ID_SDNC_SUBSCRIBE	1055
53003 - LOG_ID_SDNC_UNSUBSCRIBE	1055
53100 - LOG_ID_VPN_OCVPN_REGISTERED	1056
53101 - LOG_ID_VPN_OCVPN_UNREGISTERED	1057
53102 - LOG_ID_VPN_OCVPN_COMM_ESTABLISHED	1058
53103 - LOG_ID_VPN_OCVPN_COMM_ERROR	1058
53104 - LOG_ID_VPN_OCVPN_DNS_ERROR	1059
53105 - LOG_ID_VPN_OCVPN_ROUTE_ERROR	1060
53200 - LOG_ID_CONNECTOR_OBJECT_ADD	1060
53201 - LOG_ID_CONNECTOR_OBJECT_REMOVE	1061
FILE-FILTER	1062
64000 - LOG_ID_FILE_FILTER_BLOCK	1062
64001 - LOG_ID_FILE_FILTER_LOG	1064
GTP	1066
41216 - LOGID_GTP_FORWARD	1066
41217 - LOGID_GTP_DENY	1068
41218 - LOGID_GTP_RATE_LIMIT	1070
41219 - LOGID_GTP_STATE_INVALID	1071
41220 - LOGID_GTP_TUNNEL_LIMIT	1073
41221 - LOGID_GTP_TRAFFIC_COUNT	1074
41222 - LOGID_GTP_USER_DATA	1076
41223 - LOGID_GTPV2_FORWARD	1077
41224 - LOGID_GTPV2_DENY	1079
41225 - LOGID_GTPV2_RATE_LIMIT	1080
41226 - LOGID_GTPV2_STATE_INVALID	1082
41227 - LOGID_GTPV2_TUNNEL_LIMIT	1083
41228 - LOGID_GTPV2_TRAFFIC_COUNT	1085
41229 - LOGID_GTPU_FORWARD	1086
41230 - LOGID_GTPU_DENY	1087
IPS	1088
16384 - LOGID_ATTCK_SIGNATURE_TCP_UDP	1088
16385 - LOGID_ATTCK_SIGNATURE_ICMP	1090
16386 - LOGID_ATTCK_SIGNATURE_OTHERS	1092
16399 - LOGID_ATTACK_MALICIOUS_URL	1094
16400 - LOGID_ATTACK_BOTNET_WARNING	1096
16401 - LOGID_ATTACK_BOTNET_NOTIF	1098
SSH	1100
61000 - LOG_ID_SSH_COMMAND_BLOCK	1100
61001 - LOG_ID_SSH_COMMAND_BLOCK_ALERT	1101
61002 - LOG_ID_SSH_COMMAND_PASS	1103
61003 - LOG_ID_SSH_COMMAND_PASS_ALERT	1104

61010 - LOG_ID_SSH_CHANNEL_BLOCK	1106
61011 - LOG_ID_SSH_CHANNEL_PASS	1107
SSL	1109
62000 - LOG_ID_SSL_CERT_BLACKLISTED	1109
62001 - LOG_ID_SSL_CERT_PASS	1110
62002 - LOG_ID_SSL_CERT_BLOCK	1112
62003 - LOG_ID_SSL_EXEMPT	1113
62050 - LOG_ID_SSL_HS_CERT_REQ_EXEMPT	1115
62051 - LOG_ID_SSL_HS_CERT_REQ_BLOCK	1116
62052 - LOG_ID_SSL_HS_UNSUPPROTED_EXEMPT	1118
62053 - LOG_ID_SSL_HS_UNSUPPORTED_BLOCK	1119
62200 - LOG_ID_SSL_EXEMPT_ADDR	1121
62202 - LOG_ID_SSL_EXEMPT_FTGD_CAT	1122
Traffic	1124
2 - LOG_ID_TRAFFIC_ALLOW	1124
3 - LOG_ID_TRAFFIC_DENY	1128
4 - LOG_ID_TRAFFIC_OTHER_START	1133
5 - LOG_ID_TRAFFIC_OTHER_ICMP_ALLOW	1137
6 - LOG_ID_TRAFFIC_OTHER_ICMP_DENY	1141
7 - LOG_ID_TRAFFIC_OTHER_INVALID	1145
8 - LOG_ID_TRAFFIC_WANOPT	1150
9 - LOG_ID_TRAFFIC_WEBCACHE	1154
10 - LOG_ID_TRAFFIC_EXPLICIT_PROXY	1159
11 - LOG_ID_TRAFFIC_FAIL_CONN	1164
12 - LOG_ID_TRAFFIC_MULTICAST	1168
13 - LOG_ID_TRAFFIC_END_FORWARD	1173
14 - LOG_ID_TRAFFIC_END_LOCAL	1177
15 - LOG_ID_TRAFFIC_START_FORWARD	1182
16 - LOG_ID_TRAFFIC_START_LOCAL	1186
17 - LOG_ID_TRAFFIC_SNIFFER	1190
19 - LOG_ID_TRAFFIC_BROADCAST	1195
20 - LOG_ID_TRAFFIC_STAT	1199
21 - LOG_ID_TRAFFIC_SNIFFER_STAT	1203
22 - LOG_ID_TRAFFIC_UTM_CORRELATION	1208
VoIP	1212
44032 - LOGID_EVENT_VOIP_SIP	1212
44033 - LOGID_EVENT_VOIP_SIP_BLOCK	1214
44034 - LOGID_EVENT_VOIP_SIP_FUZZING	1215
44035 - LOGID_EVENT_VOIP_SCCP_REGISTER	1217
44036 - LOGID_EVENT_VOIP_SCCP_UNREGISTER	1218
44037 - LOGID_EVENT_VOIP_SCCP_CALL_BLOCK	1219
44038 - LOGID_EVENT_VOIP_SCCP_CALL_INFO	1220
WAF	1222
30248 - LOGID_WAF_SIGNATURE_BLOCK	1222
30249 - LOGID_WAF_SIGNATURE_PASS	1223
30250 - LOGID_WAF_SIGNATURE_ERASE	1225
30251 - LOGID_WAF_CUSTOM_SIGNATURE_BLOCK	1227
30252 - LOGID_WAF_CUSTOM_SIGNATURE_PASS	1229
30253 - LOGID_WAF_METHOD_BLOCK	1230

30255 - LOGID_WAF_ADDRESS_LIST_BLOCK	1232
30257 - LOGID_WAF_CONSTRAINTS_BLOCK	1234
30258 - LOGID_WAF_CONSTRAINTS_PASS	1236
30259 - LOGID_WAF_URL_ACCESS_PERMIT	1237
30260 - LOGID_WAF_URL_ACCESS_BYPASS	1239
30261 - LOGID_WAF_URL_ACCESS_BLOCK	1241
Web	1243
12288 - LOG_ID_WEB_CONTENT_BANWORD	1243
12289 - LOG_ID_WEB_CONTENT_MMS_BANWORD	1245
12290 - LOG_ID_WEB_CONTENT_EXEMPTWORD	1247
12291 - LOG_ID_WEB_CONTENT_MMS_EXEMPTWORD	1249
12292 - LOG_ID_WEB_CONTENT_KEYWORD	1251
12293 - LOG_ID_WEB_CONTENT_SEARCH	1253
12305 - LOG_ID_WEB_CONTENT_MMS_BANWORD_NOTIF	1255
12544 - LOG_ID_URL_FILTER_BLOCK	1257
12545 - LOG_ID_URL_FILTER_EXEMPT	1259
12546 - LOG_ID_URL_FILTER_ALLOW	1261
12547 - LOG_ID_URL_FILTER_INVALID_HOSTNAME_HTTP_BLK	1263
12548 - LOG_ID_URL_FILTER_INVALID_HOSTNAME_HTTPS_BLK	1265
12549 - LOG_ID_URL_FILTER_INVALID_HOSTNAME_HTTP_PASS	1267
12550 - LOG_ID_URL_FILTER_INVALID_HOSTNAME_HTTPS_PASS	1269
12551 - LOG_ID_URL_FILTER_INVALID_HOSTNAME_SNI_BLK	1271
12552 - LOG_ID_URL_FILTER_INVALID_HOSTNAME_SNI_PASS	1272
12553 - LOG_ID_URL_FILTER_INVALID_CERT	1274
12554 - LOG_ID_URL_FILTER_INVALID_SESSION	1276
12555 - LOG_ID_URL_FILTER_SRV_CERT_ERR_BLK	1278
12556 - LOG_ID_URL_FILTER_SRV_CERT_ERR_PASS	1280
12557 - LOG_ID_URL_FILTER_FAMS_NOT_ACTIVE	1281
12558 - LOG_ID_URL_FILTER_RATING_ERR	1282
12559 - LOG_ID_URL_FILTER_PASS	1283
12560 - LOG_ID_URL_WISP_BLOCK	1285
12561 - LOG_ID_URL_WISP_REDIRECT	1287
12562 - LOG_ID_URL_WISP_ALLOW	1289
12688 - LOG_ID_WEB_SSL_EXEMPT	1291
12800 - LOG_ID_WEB_FTGD_ERR	1293
12801 - LOG_ID_WEB_FTGD_WARNING	1295
12802 - LOG_ID_WEB_FTGD_QUOTA	1297
13056 - LOG_ID_WEB_FTGD_CAT_BLK	1298
13057 - LOG_ID_WEB_FTGD_CAT_WARN	1300
13312 - LOG_ID_WEB_FTGD_CAT_ALLOW	1302
13315 - LOG_ID_WEB_FTGD_QUOTA_COUNTING	1304
13316 - LOG_ID_WEB_FTGD_QUOTA_EXPIRED	1306
13317 - LOG_ID_WEB_URL	1308
13568 - LOG_ID_WEB_SCRIPTFILTER_ACTIVEX	1310
13573 - LOG_ID_WEB_SCRIPTFILTER_COOKIE	1312
13584 - LOG_ID_WEB_SCRIPTFILTER_APPLET	1314
13600 - LOG_ID_WEB_SCRIPTFILTER_OTHER	1316
13601 - LOG_ID_WEB_WF_COOKIE	1318
13602 - LOG_ID_WEB_WF_REFERER	1320

13603 - LOG_ID_WEB_WF_COMMAND_BLOCK	1322
13616 - LOG_ID_CONTENT_TYPE_BLOCK	1324
13632 - LOGID_HTTP_HDR_CHG_REQ	1326
13633 - LOGID_HTTP_HDR_CHG_RESP	1327

Change Log

Date	Change Description
2023-06-08	Initial release.

Introduction

This document provides information about all the log messages applicable to the FortiGate devices running FortiOS version 6.2.15 or higher. The logs are intended for administrators to use as reference for more information about a specific log entry and message generated by FortiOS.

This document also provides information about log fields when FortiOS sends log messages to remote syslog servers in Common Event Format (CEF). See [CEF Support on page 48](#). It also describes how to enable extended logging. See [UTM Extended Logging on page 59](#).



Performance statistics are not logged to disk. Performance statistics can be received by a syslog server or by FortiAnalyzer.

Before you begin

Before you begin using this reference, read the following notes:

- Information in this document applies to all FortiGate units that are currently running FortiOS 6.2.15 or higher.
- Ensure that you have enabled logging for the FortiOS unit.
- Each log message is displayed in the *Log & Report* pane of the GUI. You can also download the RAW format from the *Log & Report* pane.
- Each log message is documented similar to how it appears in the RAW format.



This reference contains detailed information for each log type and subtype; however, this reference contains only information gathered at publication and, as a result, not every log message field contains detailed information.

What's new

This section identifies major changes in the Log Reference from version 6.2.0 and later.

FortiOS 6.2.15

There are no major log changes between FortiOS 6.2.14 and 6.2.15.

FortiOS 6.2.14

There are no major log changes between FortiOS 6.2.13 and 6.2.14.

FortiOS 6.2.13

There are no major log changes between FortiOS 6.2.12 and 6.2.13.

FortiOS 6.2.12

There are no major log changes between FortiOS 6.2.11 and 6.2.12.

FortiOS 6.2.11

There are no major log changes between FortiOS 6.2.10 and 6.2.11.

FortiOS 6.2.10

For more information about new features, please see the [FortiGate 6.2 New Features Guide](#).

- In the Event log type, `system` subtype, log ID 46517 is added.

FortiOS 6.2.9

There are no major log changes between FortiOS 6.2.8 and 6.2.9.

FortiOS 6.2.8

For more information about new features, please see the [FortiGate 6.2 New Features Guide](#).

- In the Event log type, `system` subtype, log IDs 34418, 34419, and 46516 were added.

FortiOS 6.2.7

There are no major log changes between FortiOS 6.2.6 and 6.2.7.

FortiOS 6.2.6

For more information about new features, please see the [FortiGate 6.2 New Features Guide](#).

- In the Event log type:
 - The `useralt` field was added.
 - In the `ha` subtype, log ID 35016 was added.
 - In the `system` subtype, log ID 40706 was added.

FortiOS 6.2.5

For more information about new features, please see the [FortiGate 6.2 New Features Guide](#).

- In the Traffic log type, the `vwlnamefield` was added.
- In the Event log type, `system` subtype, log IDs 32248 and 32249 were added.

FortiOS 6.2.4

For more information about new features, please see the [FortiGate 6.2 New Features Guide](#).

- In the Traffic log type, the `dstauthserver`, `dstgroup`, and `dstuser` fields were added.
- In the Event log type, `system` subtype, log IDs 20100 and 32235 were updated.

FortiOS 6.2.3

For more information about new features, please see the [FortiGate 6.2 New Features Guide](#).

There are no major log changes between FortiOS 6.2.2 and 6.2.3.

FortiOS 6.2.2

For more information about new features, please see the [FortiGate 6.2 New Features Guide](#).

There are no major log changes between FortiOS 6.2.1 and 6.2.2.

FortiOS 6.2.1

For more information about new features, please see the [FortiGate 6.2 New Features Guide](#).

New log types

- File Filter was added as a new log type with a log category ID of 19.

Subtype changes

- In the App log type, the `app-ctrl-all` subtype was split into the following event types: `signature`, `port-violation`, `protocol-violation`.

FortiOS 6.2.0

For more information about new features, please see the [FortiGate 6.2 New Features Guide](#).

New log types

- Secure Socket Layer (SSL) was added as a new log type with a log category ID of 17.
- Common Internet File System (CIFS) was added as a new log type with a log category ID of 18.

Subtype changes

- In the Event log type, the following changes were made:
 - A `FortiExtender` subtype was added. In the FortiOS GUI, you can view logs sent from FortiExtender units on the *Log & Report* pane.
 - A `connector` subtype was added to log dynamic address changes for SDN connectors.
- In the Antivirus log type, the following changes were made:
 - A `malware-list` subtype was added.
 - The `botnet` subtype was deleted.
- In the IPS log type, the `botnet` subtype was added.
- In the Email log type, a `file_filter` subtype was added to log filtering based on metadata (file type).
- In the Webfilter log type, a `file_filter` subtype was added to log filtering based on metadata (file type).

Log Types and Subtypes

This section describes the log types, subtypes, and priority levels. It also describes the log field format.

Type

Each log entry contains a Type (type) or category field that indicates its log type and which log file stores the log entry.

Subtype

Each log entry contains a Sub Type (subtype) or subcategory field within a log type, based on the feature associated with the cause of the log entry.

For example:

- In event logs, some of the subtypes are compliance check, system, and user.
- In traffic logs, the subtypes are forward, local, multicast, and sniffer.

List of log types and subtypes

FortiGate devices can record the following types and subtypes of log entry information:

Type	Description	Subtype
Traffic	Records traffic flow information, such as an HTTP/HTTPS request and its response, if any.	<ul style="list-style-type: none">• FORWARD• LOCAL• MULTICAST• SNIFFER
Event	Records system and administrative events, such as downloading a backup copy of the configuration, or daemon activities.	<ul style="list-style-type: none">• CONNECTOR• ENDPOINT• FORTIEXTENDER• HA• ROUTER• SECURITY-RATING• SYSTEM• USER• VPN

Type	Description	Subtype
		<ul style="list-style-type: none"> • WAD • WIRELESS
UTM	Records UTM events.	See list of UTM log subtypes below

UTM log subtypes

UTM Log Subtypes	Description	Event Type
		<ul style="list-style-type: none"> • CIFS-FILEFILTER
Anomaly	Records intrusion attempts.	<ul style="list-style-type: none"> • ANOMALY
App	Records intrusion attempts. Application control log is output when a signature matches an application pattern.	<ul style="list-style-type: none"> • PORT-VIOLATION • PROTOCOL-VIOLATION • SIGNATURE
AV	Records virus attacks.	<ul style="list-style-type: none"> • ANALYTICS • COMMAND-BLOCKED • CONTENT-DISARM • FILENAME • FILETYPE-EXECUTABLE • INFECTED • MALWARE-LIST • MIMEFRAGMENTED • OUTBREAK-PREVENTION • OVERSIZE • SCANERROR • SWITCHPROTO
DLP	Records data leak prevention events.	<ul style="list-style-type: none"> • DLP
DNS	Records domain name server events.	<ul style="list-style-type: none"> • DNS-QUERY • DNS-RESPONSE
Email	Records email filter events.	<ul style="list-style-type: none"> • CARRIER-ENDPOINT-FILTER • FTGD_ERR • GMAIL • IMAP • MAPI • MASS-MMS • MSN-HOTMAIL • POP3

UTM Log Subtypes	Description	Event Type
		<ul style="list-style-type: none"> SMTP YAHOO-MAIL
FILE-FILTER	Records file filter events.	<ul style="list-style-type: none"> FILE-FILTER
GTP	Records GTP events.	<ul style="list-style-type: none"> GTP-ALL
IPS	Records intrusion prevention events.	<ul style="list-style-type: none"> BOTNET MALICIOUS-URL SIGNATURE
SSH	Records Secure Socket Shell events.	<ul style="list-style-type: none"> SSH-CHANNEL SSH-COMMAND
SSL	Records detected/blocked malicious SSL connections.	<ul style="list-style-type: none"> SSL-ANOMALIES SSL-EXEMPT
VoIP	Records voice over IP events.	<ul style="list-style-type: none"> VOIP
WAF	Records web application firewall information for FortiWeb appliances and virtual appliances.	<ul style="list-style-type: none"> WAF-ADDRESS-LIST WAF-CUSTOM-SIGNATURE WAF-HTTP-CONSTRAINT WAF-HTTP-METHOD WAF-SIGNATURE WAF-URL-ACCESS
Web	Records web filter events.	<ul style="list-style-type: none"> ACTIVEXFILTER APPLETFILTER CONTENT COOKIEFILTER FTGD_ALLOW FTGD_BLK FTGD_ERR FTGD_QUOTA FTGD_QUOTA_COUNTING HTTP_HEADER_CHANGE SCRIPTFILTER SSL-EXEMPT URLFILTER WEBFILTER_COMMAND_BLOCK

FortiOS priority levels

Each log entry contains a Level (level) field that indicates the estimated severity of the event that caused the log entry, such as `level=warning`, and therefore how high a priority it is likely to be. Level (level) associations with the descriptions below are not always uniform. They also may not correspond with your own definitions of how severe each event is. If you require notification when a specific event occurs, either configure SNMP traps or alert email by administrator-defined Severity Level (severity_level) or ID (logid), not by Level (level).

Level (0 is highest)	Name	Description
0	Emergency	The system is unusable or not responding.
1	Alert	Immediate action required. Used in security logs.
2	Critical	Functionality is affected.
3	Error	An error exists and functionality could be affected.
4	Warning	Functionality could be affected.
5	Notification	Information about normal events.
6	Information	General information about system operations. Used in event logs to record configuration changes.

For each location where the FortiGate device can store log files (disk, memory, Syslog or FortiAnalyzer), you can define a severity threshold. FortiOS stores all log messages equal to or exceeding the log severity level selected. For example, if you select Error, FortiOS will store log messages whose log severity level is Error, Critical, Alert, and Emergency.

Log field format

The following table describes the standard format in which each log type is described in this document. For documentation purposes, all log types and subtypes follow this generic table format to present the log entry information.

Log Field Name	Description	Data Type	Length
appact	The security action from app control	string	16

Log Schema Structure

This section describes the schema of the FortiOS log messages.

Log message fields

Each log message consists of several sections of fields. In the FortiOS GUI, you can view the logs in the *Log & Report* pane, which displays the formatted view. If you want to view logs in raw format, you must download the log and view it in a text editor.

Following is an example of a traffic log message in raw format:

```
date=2017-11-15 time=11:44:16 logid="0000000013" type="traffic" subtype="forward"
level="notice" vd="vdom1" eventtime=1510775056 srcip=10.1.100.155 srcname="pc1"
srcport=40772 srcintf="port12" srcintfrole="undefined" dstip=35.197.51.42
dstname="fortiguard.com" dstport=443 dstintf="port11" dstintfrole="undefined"
poluid="707a0d88-c972-51e7-bbc7-4d421660557b" sessionid=8058 proto=6 action="close"
policyid=1 policytype="policy" policymode="learn" service="HTTPS" dstcountry="United
States" srccountry="Reserved" trandisp="snat" transip=172.16.200.2 transport=40772
appid=40568 app="HTTPS.BROWSER" appcat="Web.Client" apprisk="medium" duration=2
sentbyte=1850 rcvdbyte=39898 sentpkt=25 rcvdpkt=37 utmaction="allow" countapp=1
devtype="Linux PC" oiname="Linux" mastersrcmac="a2:e9:00:ec:40:01"
srcmac="a2:e9:00:ec:40:01" srcserver=0 utmref=0-220586
```

The following table provides an example of the log field information in the FortiOS GUI in the detailed view of the *Log & Report* pane and in the downloaded, raw log file.

GUI Field Name (Raw Field Name)	Field Description	Example Field Value in Raw Format
General		
Date (date)	Day, month, and year when the log message was recorded.	date=2017-11-15
Direction (direction)	Indicates message/packets direction.	direction=incoming
Time (time)	Hour clock when the log message was recorded.	time=11:44:16
Duration (seconds)	Duration of the session, in seconds.	duration=2
Session ID (sessionid)	ID for the session.	sessionid=8058
Virtual Domain (vd)	Name of the virtual domain in which the log message was recorded.	vd="vdom1"

GUI Field Name (Raw Field Name)	Field Description	Example Field Value in Raw Format
NAT Translation (transport)	NAT source port.	transport=40772
Source		
IP (srcip)	IP address of the traffic's origin. The source varies by the direction: <ul style="list-style-type: none"> In HTTP requests, this is the web browser or other client. In HTTP responses, this is the physical server. 	srcip=10.1.100.155
NAT IP (transip)	NAT source IP.	transip=172.16.200.2
Source Port (srcport)	Port number of the traffic's origin.	srcport=40772
Country (srccountry)	Name of the source country.	srccountry="Reserved"
Source Interface(srcintf)	Interface name of the traffic's origin.	srcintf="port12"
Source Name (srcname)	Name of the source.	srcname="pc1"
Source Interface Name (srcintfrole)	Name of the source interface.	srcintfrole="undefined"
Device Type (devtype)	Device type of the source.	devtype="Linux PC"
OS Name (osname)	OS of the source.	osname="Linux"
Master Source MAC (mastersrcmac)	The master MAC address for a host that has multiple network interfaces.	mastersrcmac="a2:e9:00:ec:40:01"
Source MAC (srcmac)	MAC address associated with the source IP address.	srcmac="a2:e9:00:ec:40:01"
Source Server (srcserver)	Server of the source.	srcserver=0
Device ID (devid)	Serial number of the device for the traffic's origin.	devid="FGVM02Q105060010"
Destination		
IP (dstip)	Destination IP address for the web.	dstip=35.197.51.42
Port (dstport)	Port number of the traffic's destination.	dstport=443
Country (dstcountry)	Name of the destination country.	dstcountry="United States"
Destination Interface (dstintf)	Interface of the traffic's destination.	dstintf="port11"

GUI Field Name (Raw Field Name)	Field Description	Example Field Value in Raw Format
Destination Name (dstname)	Name of the destination.	dstname="fortiguard.com"
Destination Interface Name (dstinfole)	Name of the destination interface.	dstinfole="undefined"
Application		
Application Name (app)	Name of the application.	app="HTTPS.BROWSER"
Category (appcat)	Category of the application.	appcat="Web.Client"
Service (service)	Name of the service.	service="HTTPS"
Application ID (appid)	ID of the application.	appid=40568
Application Risk (apprisk)	Risk level of the application.	apprisk="medium"
countapp	Number of App Ctrl logs associated with the session.	countapp=1
Data		
Received bytes (rcvdbyte)	Number of bytes received.	rcvdbyte=39898
Received packets (rcvdpkt)	Number of packets received.	rcvdpkt=37
Sent bytes (sentbyte)	Number of bytes sent.	sentbyte=1850
Sent packets (sentpkt)	Number of packets sent.	sentpkt=25
Action		
Action (action)	Status of the session. Uses following definitions: <ul style="list-style-type: none"> Deny: blocked by firewall policy Start: session start log (special option to enable logging at start of a session). This means firewall allowed. All Others: allowed by Firewall Policy and the status indicates how it was closed. 	action=close
Policy (policyid)	Name of the firewall policy governing the traffic which caused the log message.	policyid=1
Policy UUID (poluuid)	UUID for the firewall policy.	poluuid="707a0d88-c972-51e7-bbc7-4d421660557b"

GUI Field Name (Raw Field Name)	Field Description	Example Field Value in Raw Format
Policy Type (policytype)		policytype="policy"
Policy Mode (policymode)	Firewall policy mode.	policymode="learn"
Security		
Level (level)	Security level rating.	level="notice"
Other		
Event Time (eventtime)	Epoch time the log was triggered by FortiGate. If you convert the epoch time to human readable time, it might not match the Date and Time in the header owing to a small delay between the time the log was triggered and recorded. The Log Time field is the same for the same log among all log devices, but the Date and Time might differ.	eventtime=1510775056
Protocol Number (proto)	tcp: The protocol used by web traffic (tcp by default)	proto=6
Type (type)	Log type. See Type on page 34	type="traffic"
Log ID (logid)	Log ID. See Log ID definitions on page 42	logid="0000000013"
Sub Type(subtype)	Subtype of the traffic. See Subtype on page 34 .	subtype="forward"
trandisp	NAT translation type.	trandisp="snat"
UTM Action (utmaction)	Security action performed by UTM.	utmaction="allow"
UTM Reference (utmref)	UTM reference number.	utmref=0-220586
UTM Reference (utmref)	UTM reference number.	utmref=0-220586

Log ID numbers

The ID (logid) is a 10-digit field. It is a unique identifier for that specific log and includes the following information about the log entry.

Log ID number components	Description	Examples
Log Type	Represented by the first two digits of the log ID.	<ul style="list-style-type: none"> Traffic log IDs begin with "00". Event log IDs begin with "01".
Sub Type or Event Type	Represented by the second two digits of the log ID.	<ul style="list-style-type: none"> VPN log subtype is represented with "01" which belongs to the Event log type that is represented with "01". Therefore, all VPN related Event log IDs will begin with the 0101 log ID series.
Message ID	The last six digits of the log ID represent the message ID.	<ul style="list-style-type: none"> An administrator account always has the log ID 0000003401.

The logid field is a number assigned to all permutations of the same message. It classifies a log entry by the nature of the cause of the log message, such as administrator authentication failures or traffic. Other log messages that share the same cause will share the same logid.

Log ID definitions

Following are the definitions for the log type IDs and subtype IDs applicable to FortiOS:

Log Category IDs	Subtype IDs
traffic: 0	<ul style="list-style-type: none"> forward: 0 local: 1 multicast: 2 sniffer: 4
event: 1	<ul style="list-style-type: none"> system: 0 vpn: 1 user: 2 router: 3 wireless: 4 wad: 5 endpoint: 7 ha: 8 security-rating: 10 fortiextender: 11 connector: 12
voip: 2	<ul style="list-style-type: none"> voip: 14
av: 3	<ul style="list-style-type: none"> analytics: 1 filetype-executable: 3 outbreak-prevention: 4

Log Category IDs	Subtype IDs
	<ul style="list-style-type: none"> • content-disarm: 5 • command-blocked: 6 • malware-list: 7 • infected: 11 • filename: 12 • oversize: 13 • mimefragmented: 61 • scanerror: 62 • switchproto: 63
web: 4	<ul style="list-style-type: none"> • content: 14 • urlfilter: 15 • ftgd_blk: 16 • ftgd_allow: 17 • ftgd_err: 18 • activexfilter: 35 • cookiefilter: 36 • appletfilter: 37 • ftgd_quota_counting: 38 • ftgd_quota: 40 • scriptfilter: 41 • webfilter_command_block: 43 • http_header_change: 44 • ssl-exempt: 45
ips: 5	<ul style="list-style-type: none"> • signature: 19 • malicious-url: 21 • botnet: 22
anomaly: 6	<ul style="list-style-type: none"> • anomaly: 20
email: 7	<ul style="list-style-type: none"> • msn-hotmail: 5 • yahoo-mail: 6 • gmail: 7 • smtp: 8 • pop3: 9 • imap: 10 • mapi: 11 • carrier-endpoint-filter: 47 • mass-mms: 52 • ftgd_err: 53
dlp: 8	<ul style="list-style-type: none"> • dlp: 54

Log Category IDs	Subtype IDs
app: 9	<ul style="list-style-type: none">signature: 59port-violation: 60protocol-violation: 61
waf: 10	<ul style="list-style-type: none">waf-signature: 0waf-custom-signature: 1waf-http-method: 2waf-http-constraint: 3waf-address-list: 4waf-url-access: 5
gtp: 11	<ul style="list-style-type: none">gtp-all: 0
dns: 12	<ul style="list-style-type: none">dns-query: 0dns-response: 1
ssh: 13	<ul style="list-style-type: none">ssh-command: 0ssh-channel: 1
ssl: 14	<ul style="list-style-type: none">ssl-anomalies: 0ssl-exempt: 1
: 15	<ul style="list-style-type: none">cifs-filefilter: 0
file-filter: 16	<ul style="list-style-type: none">file-filter: 0

FortiGuard Web Filter Categories

The below details the mapping between FortiGuard Web Filter category names and numbers.

Number	Category
0	Unrated
1	Drug abuse
2	Alternative beliefs
3	Hacking
4	Illegal or unethical
5	Discrimination
6	Explicit violence
7	Abortion
8	Other adult materials
9	Advocacy organizations
11	Gambling
12	Extremist groups
13	Nudity and risque
14	Pornography
15	Dating
16	Weapons (sales)
17	Advertising
18	Brokerage and trading
19	Freeware and software downloads
20	Games
23	Web-based email
24	File sharing and storage
25	Streaming media and download
26	Malicious websites
28	Entertainment
29	Arts and culture
30	Education

Number	Category
31	Finance and banking
33	Health and wellness
34	Job search
35	Medicine
36	News and media
37	Social networking
38	Political organizations
39	Reference
40	Global religion
41	Search engines and portals
42	Shopping
43	General organizations
44	Society and lifestyles
46	Sports
47	Travel
48	Personal vehicles
49	Business
50	Information and computer security
51	Government and legal organizations
52	Information technology
53	Armed forces
54	Dynamic content
55	Meaningless content
56	Web hosting
57	Marijuana
58	Folklore
59	Proxy avoidance
61	Phishing
62	Plagiarism
63	Sex education

Number	Category
64	Alcohol
65	Tobacco
66	Lingerie and swimsuit
67	Sports hunting and war games
68	Web chat
69	Instant messaging
70	Newsgroups and message boards
71	Digital postcards
72	Peer-to-peer file sharing
75	Internet radio and TV
76	Internet telephony
77	Child education
78	Real estate
79	Restaurant and dining
80	Personal websites and blogs
81	Secure websites
82	Content servers
83	Child abuse
84	Web-based applications
85	Domain parking
86	Spam URLs
87	Personal privacy
88	Dynamic DNS
89	Auction
90	Newly observed domain
91	Newly registered domain
92	Charitable organizations
93	Remote access
94	Web analytics
95	Online meeting

CEF Support

You can configure FortiOS 6.2.15 to send logs to remote syslog servers in Common Event Format (CEF) by using the `config log syslogd setting command`.

When CEF is enabled, FortiOS sends logs to syslog servers in CEF. This section describes how FortiOS logs support CEF.



You can view logs in CEF on remote syslog servers or FortiAnalyzer, but not in the FortiOS GUI.

FortiOS to CEF log field mapping guidelines

The following CEF format:

```
Date/Time host CEF:Version|Device Vendor|Device Product|Device Version|Signature
ID|Name|Severity| [Extension]
```

Displays as following in FortiOS logs with CEF enabled:

```
"MMM dd HH:mm:ss" "hostname of the fortigate"
CEF:0|Fortinet|Fortigate|version|logid|type:subtype +[eventtype] +[action] +
[status]|reversed level|...
```

The `SignatureId` field in FortiOS logs maps to the `logid` field in CEF and should be last 5 digits of `logid`.

The `Name` field in CEF uses the following formula:

```
type:subtype + [eventtype] + [action] + [status]
```

Following is an example of the header and one key-value pair for extension from the Event VPN log in CEF:

```
#Feb 12 10:31:04 syslog-800c CEF:0|Fortinet|Fortigate|v5.6.0|37127|event:vpn negotiate
success|3|FTNTFGTlogid=0101037127
```

The `type:subtype` field in FortiOS logs maps to the `cat` field in CEF.

Any fields in FortiOS logs that are unmatched to fields in CEF include the `FTNTFGT` prefix.

Quotes (") are removed from FortiOS logs to support CEF.

Forward slashes (/) in string values as well as the equal sign (=) and backward slashes (\) are escaped in FortiOS logs to support CEF.

CEF priority levels

Following are the CEF priority levels. They are opposite of FortiOS priority levels. See also [FortiOS priority levels on page 37](#).

Level (8 is highest)	Name	Description
8	Emergency	The system is unusable or not responding.
7	Alert	Immediate action required. Used in security logs.
6	Critical	Functionality is affected.
5	Error	An error exists and functionality could be affected.
4	Warning	Functionality could be affected.
3	Notification	Information about normal events.
2	Information	General information about system operations. Used in event logs to record configuration changes.
1	Debug	Debug information.

Examples of CEF support

This section includes examples of how the different types of log message support CEF.

Traffic log support for CEF

The following is an example of a traffic log on the FortiGate disk:

```
date=2018-12-27 time=11:07:55 logid="0000000013" type="traffic" subtype="forward"
level="notice" vd="vdom1" eventtime=1545937675 srcip=10.1.100.11 srcport=54190
srcintf="port12" srcintfrole="undefined" dstip=52.53.140.235 dstport=443
dstintf="port11" dstintfrole="undefined" poluuid="c2d460aa-fe6f-51e8-9505-41b5117dfdd4"
sessionid=402 proto=6 action="close" policyid=1 policytype="policy"
service="HTTPS" dstcountry="United States" srccountry="Reserved"trandisp="snat"
transip=172.16.200.1 transport=54190 appid=40568 app="HTTPS.BROWSER"
appcat="Web.Client" apprisk="medium" applist="g-default" duration=2 sentbyte=3652
rcvbyte=146668 sentpkt=58 rcvpkt=105 utmaction="allow" countapp=2 utmref=65532-56
```

The following is an example of a traffic log sent in CEF format to a syslog server:

```
Dec 27 11:07:55 FGT-A-LOG CEF: 0|Fortinet|Fortigate|v6.0.3|00013|traffic:forward
close|3|deviceExternalId=FGT5HD3915800610 FTNTFGTlogid=0000000013
cat=traffic:forward FTNTFGTsubtype=forward FTNTFGTlevel=notice FTNTFGTvd=vdom1
FTNTFGTeventtime=1545937675 src=10.1.100.11 spt=54190 deviceInboundInterface=port12
FTNTFGTsrcintfrole=undefined dst=52.53.140.235 dpt=443
deviceOutboundInterface=port11 FTNTFGTdstintfrole=undefined FTNTFGTpoluuid=c2d460aa-
fe6f-51e8-9505-41b5117dfdd4 externalId=402 proto=6 act=close FTNTFGTpolicyid=1
FTNTFGTpolicytype=policy app=HTTPS FTNTFGTdstcountry=United States
FTNTFGTsrccountry=Reserved FTNTFGTtrandisp=snat sourceTranslatedAddress=172.16.200.1
sourceTranslatedPort=54190 FTNTFGTappid=40568 FTNTFGTapp=HTTPS.BROWSER
FTNTFGTappcat=Web.Client FTNTFGTapprisk=medium FTNTFGTapplist=g-default
FTNTFGTduration=2 out=3652 in=146668 FTNTFGTsentpkt=58 FTNTFGTrcvdpkt=105
FTNTFGTutmaction=allow FTNTFGTcountapp=2
```

The following table maps FortiOS log field names to CEF field names.

FortiOS Log Field Name	CEF Field Name
type: subtype	cat
srcip	src
srcport	spt
srcintf	deviceInboundInterface
dstip	dst
dstport	dpt
dstintf	deviceOutboundInterface
sessionid	externalID
proto	proto
action	act
transip	sourceTranslatedAddress
transport	sourceTranslatedPort
service	app
sentbyte	out
rcvdbyte	in

Custom fields

To configure the traffic log with custom fields, enter the following CLI commands:

```
config log custom-field
  edit 1
    set name "custom_name1"
    set value "HN123456"
  next
  edit 2
    set name "custom_name2"
    set value "accounting_dpt"
  next
end
config firewall policy
  edit 1
    set name "A-v4-out"
    set uuid c2d460aa-fe6f-51e8-9505-41b5117dfdd4
    set srcintf "port12"
    set dstintf "port11"
    set srcaddr "all"
    set dstaddr "all"
    set action accept
    set schedule "always"
    set service "ALL"
    set utm-status enable
    set logtraffic all
```

```

set custom-log-fields "1" "2"
set application-list "g-default"
set ssl-ssh-profile "certificate-inspection"
set nat enable
next
end

```

The following is an example of a traffic log with custom fields on the FortiGate disk:

```

date=2018-12-27 time=11:12:30 logid="0000000013" type="traffic" subtype="forward"
level="notice" vd="vdom1" eventtime=1545937950 srcip=10.1.100.11 srcport=58843
srcintf="port12" srcintfrole="undefined" dstip=172.16.200.55 dstport=53
dstintf="port11" dstintfrole="undefined" poluid="c2d460aa-fe6f-51e8-9505-41b5117dfdd4"
sessionid=440 proto=17 action="accept" policyid=1 policytype="policy"
service="DNS" dstcountry="Reserved" srccountry="Reserved" trandisp="snat"
transip=172.16.200.1 transport=58843 appid=16195 app="DNS" appcat="Network.Service"
apprisk="elevated" applist="g-default" duration=180 sentbyte=70 rcvdbyte=528
sentpkt=1 rcvdpkt=1 custom_name1="HN123456" custom_name2="accounting_dpt"

```

The following is an example of a traffic log with custom fields sent in CEF format to a syslog server:

```

Dec 27 11:12:30 FGT-A-LOG CEF: 0|Fortinet|Fortigate|v6.0.3|00013|traffic:forward
accept|3|deviceExternalId=FGT5HD3915800610 FTNTFGTlogid=0000000013
cat=traffic:forward FTNTFGTsubtype=forward FTNTFGTlevel=notice FTNTFGTvd=vdom1
FTNTFGTeventtime=1545937950 src=10.1.100.11 spt=58843 deviceInboundInterface=port12
FTNTFGTsrcintfrole=undefined dst=172.16.200.55 dpt=53 deviceOutboundInterface=port11
FTNTFGTdstintfrole=undefined FTNTFGTpoluid=c2d460aa-fe6f-51e8-9505-41b5117dfdd4
externalId=440 proto=17 act=accept FTNTFGTpolicyid=1 FTNTFGTpolicytype=policy
app=DNS FTNTFGTdstcountry=Reserved FTNTFGTsrccountry=Reserved FTNTFGTtrandisp=snat
sourceTranslatedAddress=172.16.200.1 sourceTranslatedPort=58843 FTNTFGTappid=16195
FTNTFGTapp=DNS FTNTFGTappcat=Network.Service FTNTFGTapprisk=elevated
FTNTFGTapplist=g-default FTNTFGTduration=180 out=70 in=528 FTNTFGTsentpkt=1
FTNTFGTrcvdpkt=1 FTNTFGTcustom_name1=HN123456 FTNTFGTcustom_name2=accounting_dpt

```

The following table maps FortiOS custom log field names to CEF field names.

FortiOS Log Field Name	CEF Field Name
custom_name1	FTNTFGTcustom_name1
custom_name2	FTNTFGTcustom_name2

Event log support for CEF

The following table maps FortiOS log field names to CEF field names.

FortiOS Log Field Name	CEF Field Name
msg	msg
cookies	requestCookies
user	duser
status	outcome
role	sourceServiceName

FortiOS Log Field Name	CEF Field Name
ui	sproc
reason	reason
action	act

system subtype

The following is an example of a system subtype event log on the FortiGate disk:

```
date=2018-12-27 time=11:15:40 logid="0100032002" type="event" subtype="system"
level="alert" vd="vdom1" eventtime=1545938140 logdesc="Admin login failed" sn="0"
user="admin1" ui="https(172.16.200.254)" method="https" srcip=172.16.200.254
dstip=172.16.200.1 action="login" status="failed" reason="name_invalid"
msg="Administrator admin1 login failed from https(172.16.200.254) because of invalid
user name"
```

The following is an example of a system subtype event log sent in CEF format to a syslog server:

```
Dec 27 11:15:40 FGT-A-LOG CEF: 0|Fortinet|Fortigate|v6.0.3|32002|event:system login
failed|7|deviceExternalId=FGT5HD3915800610 FTNTFGTlogid=0100032002 cat=event:system
FTNTFGTsubtype=system FTNTFGTlevel=alert FTNTFGTvd=vdom1 FTNTFGTeventtime=1545938140
FTNTFGTlogdesc=Admin login failed FTNTFGTsn=0 duser=admin1 sproc=https
(172.16.200.254) FTNTFGTmethod=https src=172.16.200.254 dst=172.16.200.1 act=login
outcome=failed reason=name_invalid msg=Administrator admin1 login failed from https
(172.16.200.254) because of invalid user name
```

user subtype

The following is an example of a user subtype log on the FortiGate disk:

```
date=2018-12-27 time=11:17:35 logid="0102043008" type="event" subtype="user"
level="notice" vd="vdom1" eventtime=1545938255 logdesc="Authentication success"
srcip=10.1.100.11 dstip=172.16.200.55 policyid=1 interface="port12" user="bob"
group="N/A" authproto="TELNET(10.1.100.11)" action="authentication" status="success"
reason="N/A" msg="User bob succeeded in authentication"
```

The following is an example of a user subtype log sent in CEF format to a syslog server:

```
Dec 27 11:17:35 FGT-A-LOG CEF: 0|Fortinet|Fortigate|v6.0.3|43008|event:user
authentication success|3|deviceExternalId=FGT5HD3915800610 FTNTFGTlogid=0102043008
cat=event:user FTNTFGTsubtype=user FTNTFGTlevel=notice FTNTFGTvd=vdom1
FTNTFGTeventtime=1545938255 FTNTFGTlogdesc=Authentication success src=10.1.100.11
dst=172.16.200.55 FTNTFGTpolicyid=1 deviceInboundInterface=port12 duser=bob
FTNTFGTgroup=N/A FTNTFGTauthproto=TELNET(10.1.100.11) act=authentication
outcome=success reason=N/A msg=User bob succeeded in authentication
```

Antivirus log support for CEF

The following is an example of an antivirus log on the FortiGate disk:

```
date=2018-12-27 time=11:20:49 logid="0211008192" type="utm" subtype="virus"
eventtype="infected" level="warning" vd="vdom1" eventtime=1545938448 msg="File is
infected." action="blocked" service="HTTP" sessionid=695 srcip=10.1.100.11
dstip=172.16.200.55 srcport=44356 dstport=80 srcintf="port12"
srcintfrole="undefined" dstintf="port11" dstintfrole="undefined" policyid=1 proto=6
```

```
direction="incoming" filename="eicar.com" quarskip="File-was-not-quarantined."
virus="EICAR_TEST_FILE" dtype="Virus" ref="http://www.fortinet.com/ve?vn=EICAR_TEST_
FILE" virusid=2172 url="http://172.16.200.55/virus/eicar.com" profile="g-default"
user="bob" agent="curl/7.47.0"
analyticsscksum="275a021bbfb6489e54d471899f7db9d1663fc695ec2fe2a2c4538aabf651fd0f"
analyticsssubmit="false" crscore=50 crlevel="critical"
```

The following is an example of an antivirus log sent in CEF format to a syslog server:

```
Dec 27 11:20:48 FGT-A-LOG CEF: 0|Fortinet|Fortigate|v6.0.3|08192|utm:virus infected
blocked|4|deviceExternalId=FGT5HD3915800610 FTNTFGTlogid=0211008192 cat=utm:virus
FTNTFGTsubtype=virus FTNTFGTeventtype=infected FTNTFGTlevel=warning FTNTFGTvd=vdom1
FTNTFGTeventtime=1545938448 msg=File is infected. act=blocked app=HTTP
externalId=695 src=10.1.100.11 dst=172.16.200.55 spt=44356 dpt=80
deviceInboundInterface=port12 FTNTFGTsrcintfrole=undefined
deviceOutboundInterface=port11 FTNTFGTdstintfrole=undefined FTNTFGTpolicyid=1
proto=6 deviceDirection=0 fname=eicar.com FTNTFGTquarskip=File-was-not-quarantined.
FTNTFGTvirus=EICAR_TEST_FILE FTNTFGTdtype=Virus
FTNTFGTref=http://www.fortinet.com/ve?vn=EICAR_TEST_FILE FTNTFGTvirusid=2172
request=http://172.16.200.55/virus/eicar.com FTNTFGTprofile=g-default duser=bob
requestClientApplication=curl/7.47.0
FTNTFGTanalyticsscksum=275a021bbfb6489e54d471899f7db9d1663fc695ec2fe2a2c4538aabf651fd
0f FTNTFGTanalyticsssubmit=false FTNTFGTcrscore=50 FTNTFGTcrlevel=critical
```

The following table maps FortiOS log field names to CEF field names.

FortiOS Log Field Name	CEF Field Name
direction	deviceDirection (inbound/outbound mapping to 0/1)
filename	fname
ref	FTNTFGTref (There is \ added to escape =)
url	request
agent	requestClientApplication

Webfilter log support for CEF

The following is an example of a webfilter log on the FortiGate disk:

```
date=2018-12-27 time=11:23:50 logid="0316013056" type="utm" subtype="webfilter"
eventtype="ftgd_blk" level="warning" vd="vdom1" eventtime=1545938629 policyid=1
sessionid=764 user="bob" srcip=10.1.100.11 srcport=59194 srcintf="port12"
srcintfrole="undefined" dstip=185.230.61.185 dstport=80 dstintf="port11"
dstintfrole="undefined" proto=6 service="HTTP" hostname="ambrishsriv.wixsite.com"
profile="g-default" action="blocked" retype="direct" url="/bizsquads" sentbyte=96
rcvdbyte=0 direction="outgoing" msg="URL belongs to a denied category in policy"
method="domain" cat=26 catdesc="Malicious Websites" crscore=60 crlevel="high"
```

The following is an example of a webfilter log sent in CEF format to a syslog server:

```
Dec 27 11:23:49 FGT-A-LOG CEF: 0|Fortinet|Fortigate|v6.0.3|13056|utm:webfilter ftgd_blk
blocked|4|deviceExternalId=FGT5HD3915800610 FTNTFGTlogid=0316013056
cat=utm:webfilter FTNTFGTsubtype=webfilter FTNTFGTeventtype=ftgd_blk
FTNTFGTlevel=warning FTNTFGTvd=vdom1 FTNTFGTeventtime=1545938629 FTNTFGTpolicyid=1
externalId=764 duser=bob src=10.1.100.11 spt=59194 deviceInboundInterface=port12
FTNTFGTsrcintfrole=undefined dst=185.230.61.185 dpt=80
deviceOutboundInterface=port11 FTNTFGTdstintfrole=undefined proto=6 app=HTTP
dhost=ambrishsriv.wixsite.com FTNTFGTprofile=g-default act=blocked
```

```
FTNTFGTreqtype=direct request=/bizsquads out=96 in=0 deviceDirection=1 msg=URL
belongs to a denied category in policy FTNTFGTmethod=domain FTNTFGTcat=26
requestContext=Malicious Websites FTNTFGTcrscore=60 FTNTFGTcrlevel=high
```

The following table maps FortiOS log field names to CEF field names.

FortiOS Log Field Name	CEF Field Name
hostname	dhost
catdesc	requestContext

IPS log support for CEF

The following is an example of an IPS log on the FortiGate disk:

```
date=2018-12-27 time=11:28:07 logid="0419016384" type="utm" subtype="ips"
eventtype="signature" level="alert" vd="vdom1" eventtime=1545938887 severity="info"
srcip=172.16.200.55 srccountry="Reserved" dstip=10.1.100.11 srcintf="port11"
srcintfrole="undefined" dstintf="port12" dstintfrole="undefined" sessionid=901
action="reset" proto=6 service="HTTP" policyid=1 attack="Eicar.Virus.Test.File"
srcport=80 dstport=44362 hostname="172.16.200.55" url="/virus/eicar.com"
direction="incoming" attackid=29844 profile="test-ips"
ref="http://www.fortinet.com/ids/VID29844" user="bob" incidentserialno=877326946
msg="file_transfer: Eicar.Virus.Test.File,"
```

The following is an example of an IPS sent in CEF format to a syslog server:

```
Dec 27 11:28:07 FGT-A-LOG CEF: 0|Fortinet|Fortigate|v6.0.3|16384|utm:ips signature
reset|7|deviceExternalId=FGT5HD3915800610 FTNTFGTlogid=0419016384 cat=utm:ips
FTNTFGTsubtype=ips FTNTFGTeventtype=signature FTNTFGTlevel=alert FTNTFGTvd=vdom1
FTNTFGTeventtime=1545938887 FTNTFGTseverity=info src=172.16.200.55
FTNTFGTsrccountry=Reserved dst=10.1.100.11 deviceInboundInterface=port11
FTNTFGTsrcintfrole=undefined deviceOutboundInterface=port12
FTNTFGTdstintfrole=undefined externalId=901 act=reset proto=6 app=HTTP
FTNTFGTpolicyid=1 FTNTFGTattack=Eicar.Virus.Test.File spt=80 dpt=44362
dhost=172.16.200.55 request=/virus/eicar.com deviceDirection=0 FTNTFGTattackid=29844
FTNTFGTprofile=test-ips FTNTFGTref=http://www.fortinet.com/ids/VID29844 duser=bob
FTNTFGTincidentserialno=877326946 msg=file_transfer: Eicar.Virus.Test.File,
```

Email Spamfilter log support for CEF

The following is an example of an email spamfilter log on the FortiGate disk:

```
date=2018-12-27 time=11:36:58 logid="0508020503" type="utm" subtype="emailfilter"
eventtype="smtp" level="information" vd="vdom1" eventtime=1545939418 policyid=1
sessionid=1135 user="bob" srcip=10.1.100.11 srcport=35969 srcintf="port12"
srcintfrole="undefined" dstip=172.18.62.158 dstport=25 dstintf="port11"
dstintfrole="undefined" proto=6 service="SMTP" profile="test-spam" action="log-only"
from="testpcl@qa.fortinet.com" to="test1@server88.qa.fortinet.com"
sender="testpcl@qa.fortinet.com" recipient="test1@server88.qa.fortinet.com"
direction="outgoing" msg="general email log" subject="hello_world2" size="216"
attachment="no"
```

The following is an example of an email spamfilter log sent in CEF format to a syslog server:

```
Dec 27 11:36:58 FGT-A-LOG CEF: 0|Fortinet|Fortigate|v6.0.3|20503|utm:emailfilter smtp
log-only|2|deviceExternalId=FGT5HD3915800610 FTNTFGTlogid=0508020503
cat=utm:emailfilter FTNTFGTsubtype=emailfilter FTNTFGTeventtype=smtp
```

```

FTNTFGTlevel=information FTNTFGTvd=vdom1 FTNTFGTeventtime=1545939418
FTNTFGTpolicyid=1 externalId=1135 duser=bob src=10.1.100.11 spt=35969
deviceInboundInterface=port12 FTNTFGTsrcintfrole=undefined dst=172.18.62.158 dpt=25
deviceOutboundInterface=port11 FTNTFGTdstintfrole=undefined proto=6 app=SMTP
FTNTFGTprofile=test-spam act=log-only suser=testpcl@qa.fortinet.com
duser=test1@server88.qa.fortinet.com FTNTFGTsender=testpcl@qa.fortinet.com
FTNTFGTrecipient=test1@server88.qa.fortinet.com deviceDirection=1 msg=general email
log FTNTFGTsubject=hello_world2 FTNTFGTsize=216 FTNTFGTattachment=no

```

The following table maps FortiOS log field names to CEF field names.

FortiOS Log Field Name	CEF Field Name
from	suser
to	duser

Anomaly log support for CEF

The following is an example of an anomaly log on the FortiGate disk:

```

date=2018-12-27 time=11:40:04 logid="0720018433" type="utm" subtype="anomaly"
eventtype="anomaly" level="alert" vd="vdom1" eventtime=1545939604
severity="critical" srcip=10.1.100.11 srccountry="Reserved" dstip=172.16.200.55
srcintf="port12" srcintfrole="undefined" sessionid=0 action="clear_session" proto=1
service="PING" count=1 attack="icmp_flood" icmpid="0x3053" icmptype="0x08"
icmpcode="0x00" attackid=16777316 policyid=1 policytype="DoS-policy"
ref="http://www.fortinet.com/ids/VID16777316" msg="anomaly: icmp_flood, 51 >
threshold 50" crscore=50 crlevel="critical"

```

The following is an example of an anomaly log sent in CEF format to a syslog server:

```

Dec 27 11:40:04 FGT-A-LOG CEF: 0|Fortinet|Fortigate|v6.0.3|18433|utm:anomaly anomaly
clear_session|7|deviceExternalId=FGT5HD3915800610 FTNTFGTlogid=0720018433
cat=utm:anomaly FTNTFGTsubtype=anomaly FTNTFGTeventtype=anomaly FTNTFGTlevel=alert
FTNTFGTvd=vdom1 FTNTFGTeventtime=1545939604 FTNTFGTseverity=critical src=10.1.100.11
FTNTFGTsrccountry=Reserved dst=172.16.200.55 deviceInboundInterface=port12
FTNTFGTsrcintfrole=undefined externalId=0 act=clear_session proto=1 app=PING cnt=1
FTNTFGTattack=icmp_flood FTNTFGTicmpid=0x3053 FTNTFGTicmptype=0x08
FTNTFGTicmpcode=0x00 FTNTFGTattackid=16777316 FTNTFGTpolicyid=1
FTNTFGTpolicytype=DoS-policy FTNTFGTref=http://www.fortinet.com/ids/VID16777316
msg=anomaly: icmp_flood, 51 > threshold 50 FTNTFGTcrscore=50 FTNTFGTcrlevel=critical

```

The following table maps FortiOS log field names to CEF field names.

FortiOS Log Field Name	CEF Field Name
count	cnt

VoIP log support for CEF

The following is an example of a VoIP log on the FortiGate disk:

```

date=2018-12-27 time=16:47:09 logid="0814044032" type="utm" subtype="voip"
eventtype="voip" level="information" vd="vdom1" eventtime=1545958028 session_
id=18975 epoch=0 event_id=6857 srcip=10.1.100.11 src_port=5060 dstip=172.16.200.55
dst_port=5060 proto=17 src_int="port12" dst_int="port11" policy_id=1
profile="default" voip_proto="sip" kind="call" action="permit" status="start"

```

```
duration=0 dir="session_origin" call_id="3444-13134@127.0.0.1"
from="sip:sipp@127.0.0.1:5060" to="sip:service@172.16.200.55:5060"
```

The following is an example of an VoIP sent in CEF format to a syslog server:

```
Dec 27 16:47:08 FGT-A-LOG CEF: 0|Fortinet|Fortigate|v6.0.3|44032|utm:voip voip permit
start|2|deviceExternalId=FGT5HD3915800610 FTNTFGTlogid=0814044032 cat=utm:voip
FTNTFGTsubtype=voip FTNTFGTeventtype=voip FTNTFGTlevel=information FTNTFGTvd=vdom1
FTNTFGTeventtime=1545958028 externalId=18975 FTNTFGTepoch=0 FTNTFGTevent_id=6857
src=10.1.100.11 spt=5060 dst=172.16.200.55 dpt=5060 proto=17
deviceInboundInterface=port12 deviceOutboundInterface=port11 FTNTFGTpolicy_id=1
FTNTFGTprofile=default FTNTFGTvoip_proto=sip FTNTFGTkind=call act=permit
outcome=start FTNTFGTduration=0 FTNTFGTdir=session_origin FTNTFGTcall_id=3444-
13134@127.0.0.1 suser=sip:sipp@127.0.0.1:5060 duser=sip:service@172.16.200.55:5060
```

The following table maps FortiOS log field names to CEF field names.

FortiOS Log Field Name	CEF Field Name
status	outcome
from	suser
to	duser

DLP log support for CEF

The following is an example of a DLP log on the FortiGate disk:

```
date=2018-12-27 time=14:29:36 logid="0954024576" type="utm" subtype="dlp" eventtype="dlp"
level="warning" vd="vdom1" eventtime=1545949776 filteridx=1 dlpeextra="test-dlp3"
filtertype="file-type" filtercat="file" severity="medium" policyid=1 sessionid=12680
epoch=418303178 eventid=0 user="bob" srcip=10.1.100.11 srcport=33638
srcintf="port12" srcintfrole="undefined" dstip=172.18.62.158 dstport=80
dstintf="port11" dstintfrole="undefined" proto=6 service="HTTP" filetype="gif"
direction="incoming" action="block" hostname="172.18.62.158" url="/dlp/flower.gif"
agent="curl/7.47.0" filename="flower.gif" filesize=1209 profile="test-dlp"
```

The following is an example of a DLP log sent in CEF format to a syslog server:

```
Dec 27 14:29:36 FGT-A-LOG CEF: 0|Fortinet|Fortigate|v6.0.3|24576|utm:dlp dlp
block|4|deviceExternalId=FGT5HD3915800610 FTNTFGTlogid=0954024576 cat=utm:dlp
FTNTFGTsubtype=dlp FTNTFGTeventtype=dlp FTNTFGTlevel=warning FTNTFGTvd=vdom1
FTNTFGTeventtime=1545949776 FTNTFGTfilteridx=1 FTNTFGTdlpeextra=test-dlp3
FTNTFGTfiltertype=file-type FTNTFGTfiltercat=file FTNTFGTseverity=medium
FTNTFGTpolicyid=1 externalId=12680 FTNTFGTepoch=418303178 FTNTFGTeventid=0 duser=bob
src=10.1.100.11 spt=33638 deviceInboundInterface=port12 FTNTFGTsrcintfrole=undefined
dst=172.18.62.158 dpt=80 deviceOutboundInterface=port11 FTNTFGTdstintfrole=undefined
proto=6 app=HTTP FTNTFGTfiletype=gif deviceDirection=0 act=block dhost=172.18.62.158
request=/dlp/flower.gif requestClientApplication=curl/7.47.0 fname=flower.gif
fsize=1209 FTNTFGTprofile=test-dlp
```

The following table maps FortiOS log field names to CEF field names.

FortiOS Log Field Name	CEF Field Name
filename	fname

Application log support for CEF

The following is an example of an application log on the FortiGate disk:

```
date=2018-12-27 time=14:28:08 logid="1059028704" type="utm" subtype="app-ctrl"
eventtype="app-ctrl-all" level="information" vd="vdom1" eventtime=1545949688
appid=34050 srcip=10.1.100.11 dstip=104.80.89.24 srcport=56826 dstport=80
srcintf="port12" srcintfrole="undefined" dstintf="port11" dstintfrole="undefined"
proto=6 service="HTTP" direction="outgoing" policyid=1 sessionid=12567 applist="g-
default" appcat="Web.Client" app="HTTP.BROWSER_Firefox" action="pass"
hostname="detectportal.firefox.com" incidentserialno=1702350499 url="/success.txt"
msg="Web.Client: HTTP.BROWSER_Firefox," aprisk="elevated"
```

The following is an example of an application sent in CEF format to a syslog server:

```
Dec 27 14:28:08 FGT-A-LOG CEF: 0|Fortinet|Fortigate|v6.0.3|28704|utm:app-ctrl app-ctrl-
all pass|2|deviceExternalId=FGT5HD3915800610 FTNTFGTlogid=1059028704 cat=utm:app-
ctrl FTNTFGTsubtype=app-ctrl FTNTFGTeventtype=app-ctrl-all FTNTFGTlevel=information
FTNTFGTvd=vdom1 FTNTFGTeventtime=1545949688 FTNTFGTappid=34050 src=10.1.100.11
dst=104.80.89.24 spt=56826 dpt=80 deviceInboundInterface=port12
FTNTFGTsrcintfrole=undefined deviceOutboundInterface=port11
FTNTFGTdstintfrole=undefined proto=6 app=HTTP deviceDirection=1 FTNTFGTpolicyid=1
externalId=12567 FTNTFGTapplist=g-default FTNTFGTappcat=Web.Client
FTNTFGTapp=HTTP.BROWSER_Firefox act=pass dhost=detectportal.firefox.com
FTNTFGTincidentserialno=1702350499 request=/success.txt msg=Web.Client:
HTTP.BROWSER_Firefox, FTNTFGTaprisk=elevated
```

WAF log support for CEF

The following is an example of a WAF log on the FortiGate disk:

```
date=2018-12-27 time=14:55:20 logid="1203030258" type="utm" subtype="waf" eventtype="waf-
http-constraint" level="warning" vd="vdom1" eventtime=1545951320 policyid=1
sessionid=13614 user="bob" profile="waf_test" srcip=10.1.100.11 srcport=57304
dstip=172.16.200.55 dstport=80 srcintf="port12" srcintfrole="lan" dstintf="port11"
dstintfrole="wan" proto=6 service="HTTP"
url="http://172.16.200.55/index.html?a=0123456789&b=0123456789&c=0123456789"
severity="medium" action="passthrough" direction="request" agent="curl/7.47.0"
constraint="url-param-num" rawdata="Method=GET|User-Agent=curl/7.47.0"
```

The following is an example of a WAF sent in CEF format to a syslog server:

```
Dec 27 14:55:20 FGT-A-LOG CEF: 0|Fortinet|Fortigate|v6.0.3|30258|utm:waf waf-http-
constraint passthrough|4|deviceExternalId=FGT5HD3915800610 FTNTFGTlogid=1203030258
cat=utm:waf FTNTFGTsubtype=waf FTNTFGTeventtype=waf-http-constraint
FTNTFGTlevel=warning FTNTFGTvd=vdom1 FTNTFGTeventtime=1545951320 FTNTFGTpolicyid=1
externalId=13614 duser=bob FTNTFGTprofile=waf_test src=10.1.100.11 spt=57304
dst=172.16.200.55 dpt=80 deviceInboundInterface=port12 FTNTFGTsrcintfrole=lan
deviceOutboundInterface=port11 FTNTFGTdstintfrole=wan proto=6 app=HTTP
request=http://172.16.200.55/index.html?a\=0123456789&b\=0123456789&c\=0123456789
FTNTFGTseverity=medium act=passthrough deviceDirection=0
requestClientApplication=curl/7.47.0 FTNTFGTconstraint=url-param-num
FTNTFGTrawdata=Method\=GET|User-Agent\=curl/7.47.0
```

DNS log support for CEF

The following is an example of a DNS log on the FortiGate disk:

```

date=2018-12-27 time=14:45:26 logid="1501054802" type="dns" subtype="dns-response"
level="notice" vd="vdom1" eventtime=1545950726 policyid=1 sessionid=13355 user="bob"
srcip=10.1.100.11 srcport=54621 srcintf="port12" srcintfrole="lan"
dstip=172.16.200.55 dstport=53 dstintf="port11" dstintfrole="wan" proto=17
profile="default" srcmac="a2:e9:00:ec:40:01" xid=5137
qname="detectportal.firefox.com" qtype="A" qtypeval=1 qclass="IN"
ipaddr="104.80.89.26, 104.80.89.24" msg="Domain is monitored" action="pass" cat=52
catdesc="Information Technology"

```

The following is an example of an DNS sent in CEF format to a syslog server:

```

Dec 27 14:45:26 FGT-A-LOG CEF: 0|Fortinet|Fortigate|v6.0.3|54802|dns:dns-response
pass|3|deviceExternalId=FGT5HD3915800610 FTNTFGTlogid=1501054802 cat=dns:dns-
response FTNTFGTsubtype=dns-response FTNTFGTlevel=notice FTNTFGTvd=vdom1
FTNTFGTeventtime=1545950726 FTNTFGTpolicyid=1 externalId=13355 duser=bob
src=10.1.100.11 spt=54621 deviceInboundInterface=port12 FTNTFGTsrcintfrole=lan
dst=172.16.200.55 dpt=53 deviceOutboundInterface=port11 FTNTFGTdstintfrole=wan
proto=17 FTNTFGTprofile=default FTNTFGTsrcmac=a2:e9:00:ec:40:01 FTNTFGTxid=5137
FTNTFGTqname=detectportal.firefox.com FTNTFGTqtype=A FTNTFGTqtypeval=1
FTNTFGTqclass=IN FTNTFGTipaddr=104.80.89.26, 104.80.89.24 msg=Domain is monitored
act=pass FTNTFGTcat=52 FTNTFGTcatdesc=Information Technology

```

SSH log support for CEF

The following is an example of an SSH log on the FortiGate disk:

```

date=2018-12-27 time=14:36:15 logid="1600061002" type="utm" subtype="ssh" eventtype="ssh-
command" level="notice" vd="vdom1" eventtime=1545950175 policyid=1 sessionid=12921
user="bob" profile="test-ssh" srcip=10.1.100.11 srcport=56698 dstip=172.16.200.55
dstport=22 srcintf="port12" srcintfrole="lan" dstintf="port11" dstintfrole="wan"
proto=6 action="passthrough" direction="outgoing" login="root" command="ls"
severity="low"

```

The following is an example of an SSH sent in CEF format to a syslog server:

```

Dec 27 14:36:15 FGT-A-LOG CEF: 0|Fortinet|Fortigate|v6.0.3|61002|utm:ssh ssh-command
passthrough|3|deviceExternalId=FGT5HD3915800610 FTNTFGTlogid=1600061002 cat=utm:ssh
FTNTFGTsubtype=ssh FTNTFGTeventtype=ssh-command FTNTFGTlevel=notice FTNTFGTvd=vdom1
FTNTFGTeventtime=1545950175 FTNTFGTpolicyid=1 externalId=12921 duser=bob
FTNTFGTprofile=test-ssh src=10.1.100.11 spt=56698 dst=172.16.200.55 dpt=22
deviceInboundInterface=port12 FTNTFGTsrcintfrole=lan deviceOutboundInterface=port11
FTNTFGTdstintfrole=wan proto=6 act=passthrough FTNTFGTlogin=root FTNTFGTcommand=ls
FTNTFGTseverity=low

```

UTM Extended Logging

FortiOS 6.0.0 and later supports extended logging for UTM log types to reliable Syslog servers over TCP. Extended logging adds HTTP header information to the `rawdata` field in UTM log types. You must enable extended logging before you can use the feature.

When extended logging is enabled, the following HTTP header information can be added to the `rawdata` field in UTM logs:

- Method
- X-Forwarded-For
- Request-Content-Type | Response-Content-Type
- Referer
- User-Agent

The full `rawdata` field of 20KB is only sent to reliable Syslog servers. Other logging devices, such as disk, FortiAnalyzer, and UDP Syslog servers, receive the information, but only keep a maximum of 2KB total log length, including the `rawdata` field, and discard the rest of the extended log information.

Enabling extended logging

You can enable extended logging for the following UTM profiles:

- antivirus
- application
- dlp
- ips
- waf
- webfilter

When you enable the `extended-log` option for UTM profiles, all HTTP header information for HTTP-deny traffic is logged.

When you enable the `web-extended-all-action-log-enable` option for webfilter profile, all HTTP header information for HTTP-allow traffic is logged.

Extended logging option in UTM profiles

The `extended-log` option has been added to all UTM profiles, for example:

```
# webfilter profile
config webfilter profile
    edit "test-webfilter"
        set extended-log enable
        set web-extended-all-action-log enable
    next
end
# av profile
```

```
config antivirus profile
  edit "av-proxy-test"
    set extended-log enable
  next
end
# waf profile
config waf profile
  edit "test-waf"
    set extended-log enable
  next
end
```

Syslog server mode

The Syslog server mode changed to `udp`, `reliable`, and `legacy-reliable`. You must set the mode to `reliable` to support extended logging, for example:

```
config log syslogd setting
  set status enable
  set server "<ip address>"
  set mode reliable
  set facility local6
end
```

Example of an extended log

Following is an example extended log for a `utm` log type with a `webfilter` subtype for a reliable Syslog server. The `rawdata` field contains the extended log data.

```
Dec 18 15:40:15 10.6.30.254 date=2017-12-18 time=15:40:14 devname="600D-9"
devid="FGT6HD3915800120" logid="0316013056" type="utm" subtype="webfilter"
eventtype="ftgd_blk" level="warning" vd="vdom1" eventtime=1513640414 policyid=2
sessionid=440522 srcip=10.1.100.128 srcport=60995 srcintf="port2" srcintfrole="lan"
dstip=209.121.139.177 dstport=80 dstintf="port1" dstintfrole="wan" proto=6
service="HTTP" hostname="detectportal.firefox.com" profile="test-webfilter"
action="blocked" reqtype="direct" url="/success.txt" sentbyte=285 rcvdbyte=0
direction="outgoing" msg="URL belongs to a denied category in policy"
method="domain" cat=52 catdesc="Information Technology" crscore=30 crlevel="high"
rawdata="Method=GET|User-Agent=Mozilla/5.0 (Windows NT 6.1; rv:57.0) Gecko/20100101
Firefox/57.0"
```

Log Messages

The following sections list the FortiOS 6.2.11 log messages by log ID number.

Anomaly

18432 - LOGID_ATTCK_ANOMALY_TCP_UDP

Message ID: 18432

Message Description: LOGID_ATTCK_ANOMALY_TCP_UDP

Message Meaning: Attack detected by UCP/TCP anomaly

Type: Anomaly

Category: ANOMALY

Severity: Alert

Log Field Name	Description	Data Type	Length
action	Action	string	16
attack	Attack	string	256
attackid	Attack ID	uint32	10
count	Count	uint32	10
craction	Client Reputation Action	uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event Type	string	32
fctuid		string	32

Log Field Name	Description	Data Type	Length
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	518
policyid	Policy ID	uint32	10
policytype		string	24
proto	Protocol	uint8	3
ref	Reference	string	4096
service	Name of Service	string	80
sessionid	Session ID	uint32	10
severity	Severity	string	8
srccountry		string	64
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User	string	256
vd	Virtual Domain Name	string	32
vrf		uint8	3

18433 - LOGID_ATTCK_ANOMALY_ICMP

Message ID: 18433

Message Description: LOGID_ATTCK_ANOMALY_ICMP

Message Meaning: Attack detected by ICMP anomaly

Type: Anomaly**Category:** ANOMALY**Severity:** Alert

Log Field Name	Description	Data Type	Length
action	Action	string	16
attack	Attack	string	256
attackid	Attack ID	uint32	10
count	Count	uint32	10
craction	Client Reputation Action	uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
eventtime		uint64	20
eventtype	Event Type	string	32
fctuid		string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	518
policyid	Policy ID	uint32	10
policytype		string	24
proto	Protocol	uint8	3
ref	Reference	string	4096
service	Name of Service	string	80
sessionid	Session ID	uint32	10
severity	Severity	string	8
srccountry		string	64
srcdomain		string	255

Log Field Name	Description	Data Type	Length
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User	string	256
vd	Virtual Domain Name	string	32
vrf		uint8	3
icmpcode	ICMP code	string	6
icmpid	ICMP ID	string	8
icmptype	ICMP Type	string	6

18434 - LOGID_ATTCK_ANOMALY_OTHERS

Message ID: 18434

Message Description: LOGID_ATTCK_ANOMALY_OTHERS

Message Meaning: Attack detected by other anomaly

Type: Anomaly

Category: ANOMALY

Severity: Alert

Log Field Name	Description	Data Type	Length
action	Action	string	16
attack	Attack	string	256
attackid	Attack ID	uint32	10
count	Count	uint32	10
craction	Client Reputation Action	uint32	10
crlevel	Client Reputation Level	string	10

Log Field Name	Description	Data Type	Length
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event Type	string	32
fctuid		string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	518
policyid	Policy ID	uint32	10
policytype		string	24
proto	Protocol	uint8	3
ref	Reference	string	4096
service	Name of Service	string	80
sessionid	Session ID	uint32	10
severity	Severity	string	8
srccountry		string	64
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User	string	256
vd	Virtual Domain Name	string	32
vrf		uint8	3

App

28672 - LOGID_APP_CTRL_IM_BASIC

Message ID: 28672

Message Description: LOGID_APP_CTRL_IM_BASIC

Message Meaning: Application control IM-basic

Type: App

Category: SIGNATURE

Severity: Information

Log Field Name	Description	Data Type	Length
action		string	16
app		string	96
appcat		string	64
applist		string	64
authserver		string	32
date		string	10
devid		string	16
direction		string	8
dstintf		string	64
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
eventtype		string	32
fctuid		string	32
group		string	64
level		string	11
logid		string	10
policyid		uint32	10
profile		string	36
profiletype		string	36
proto		uint8	3
service		string	80
sessionid		uint32	10
srcdomain		string	255
srcintf		string	64
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32
vrf		uint8	3

28673 - LOGID_APP_CTRL_IM_BASIC_WITH_STATUS

Message ID: 28673

Message Description: LOGID_APP_CTRL_IM_BASIC_WITH_STATUS

Message Meaning: Application control IM

Type: App

Category: SIGNATURE

Severity: Information

Log Field Name	Description	Data Type	Length
action		string	16
app		string	96
appcat		string	64
applist		string	64
authserver		string	32
date		string	10
devid		string	16
direction		string	8
dstintf		string	64
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
group		string	64
level		string	11
logid		string	10
policyid		uint32	10
profile		string	36
profiletype		string	36
proto		uint8	3
service		string	80
sessionid		uint32	10
srcdomain		string	255
srcintf		string	64
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20

Log Field Name	Description	Data Type	Length
time		string	8
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32
vrf		uint8	3

28674 - LOGID_APP_CTRL_IM_BASIC_WITH_COUNT

Message ID: 28674

Message Description: LOGID_APP_CTRL_IM_BASIC_WITH_COUNT

Message Meaning: Application control IM (chat message count)

Type: App

Category: SIGNATURE

Severity: Information

Log Field Name	Description	Data Type	Length
action		string	16
app		string	96
appcat		string	64
applist		string	64
authserver		string	32
date		string	10
devid		string	16
direction		string	8
dstintf		string	64
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
eventtype		string	32
fctuid		string	32
group		string	64
level		string	11
logid		string	10
policyid		uint32	10
profile		string	36
profiletype		string	36
proto		uint8	3
service		string	80
sessionid		uint32	10
srcdomain		string	255
srcintf		string	64
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32
vrf		uint8	3

28675 - LOGID_APP_CTRL_IM_FILE

Message ID: 28675

Message Description: LOGID_APP_CTRL_IM_FILE

Message Meaning: Application control IM (file)

Type: App

Category: SIGNATURE

Severity: Information

Log Field Name	Description	Data Type	Length
action		string	16
app		string	96
appcat		string	64
applist		string	64
authserver		string	32
date		string	10
devid		string	16
direction		string	8
dstintf		string	64
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
group		string	64
level		string	11
logid		string	10
policyid		uint32	10
profile		string	36
profiletype		string	36
proto		uint8	3
service		string	80
sessionid		uint32	10
srcdomain		string	255
srcintf		string	64
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20

Log Field Name	Description	Data Type	Length
time		string	8
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32
vrf		uint8	3

28676 - LOGID_APP_CTRL_IM_CHAT

Message ID: 28676

Message Description: LOGID_APP_CTRL_IM_CHAT

Message Meaning: Application control IM (chat)

Type: App

Category: SIGNATURE

Severity: Information

Log Field Name	Description	Data Type	Length
action		string	16
app		string	96
appcat		string	64
applist		string	64
authserver		string	32
date		string	10
devid		string	16
direction		string	8
dstintf		string	64
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
eventtype		string	32
fctuid		string	32
group		string	64
level		string	11
logid		string	10
policyid		uint32	10
profile		string	36
profiletype		string	36
proto		uint8	3
service		string	80
sessionid		uint32	10
srcdomain		string	255
srcintf		string	64
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32
vrf		uint8	3

28677 - LOGID_APP_CTRL_IM_CHAT_BLOCK

Message ID: 28677

Message Description: LOGID_APP_CTRL_IM_CHAT_BLOCK

Message Meaning: Application control IM (chat blocked)

Type: App

Category: SIGNATURE

Severity: Information

Log Field Name	Description	Data Type	Length
action		string	16
app		string	96
appcat		string	64
applist		string	64
authserver		string	32
date		string	10
devid		string	16
direction		string	8
dstintf		string	64
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
group		string	64
level		string	11
logid		string	10
policyid		uint32	10
profile		string	36
profiletype		string	36
proto		uint8	3
service		string	80
sessionid		uint32	10
srcdomain		string	255
srcintf		string	64
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20

Log Field Name	Description	Data Type	Length
time		string	8
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32
vrf		uint8	3

28678 - LOGID_APP_CTRL_IM_BLOCK

Message ID: 28678

Message Description: LOGID_APP_CTRL_IM_BLOCK

Message Meaning: Application control IM (blocked)

Type: App

Category: SIGNATURE

Severity: Information

Log Field Name	Description	Data Type	Length
action		string	16
app		string	96
appcat		string	64
applist		string	64
authserver		string	32
date		string	10
devid		string	16
direction		string	8
dstintf		string	64
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
eventtype		string	32
fctuid		string	32
group		string	64
level		string	11
logid		string	10
policyid		uint32	10
profile		string	36
profiletype		string	36
proto		uint8	3
service		string	80
sessionid		uint32	10
srcdomain		string	255
srcintf		string	64
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32
vrf		uint8	3

28704 - LOGID_APP_CTRL_IPS_PASS

Message ID: 28704

Message Description: LOGID_APP_CTRL_IPS_PASS

Message Meaning: Application control (IPS) (pass)

Type: App

Category: SIGNATURE

Severity: Information

Log Field Name	Description	Data Type	Length
action		string	16
app		string	96
appcat		string	64
applist		string	64
authserver		string	32
date		string	10
devid		string	16
direction		string	8
dstintf		string	64
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
group		string	64
level		string	11
logid		string	10
policyid		uint32	10
profile		string	36
profiletype		string	36
proto		uint8	3
service		string	80
sessionid		uint32	10
srcdomain		string	255
srcintf		string	64
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20

Log Field Name	Description	Data Type	Length
time		string	8
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32
vrf		uint8	3
appid		uint32	10
apprisk		string	16
ccertissuer		string	64
cloudaction		string	32
clouduser		string	256
craction		uint32	10
crlevel		string	10
crscore		uint32	10
filename		string	256
filesize		uint64	10
forwardedfor		string	128
hostname		string	256
incidentserialno		uint32	10
msg		string	512
rawdata		string	20480
rawdataid		string	10
scertcname		string	64
scertissuer		string	64
trueclntip		ip	39
url		string	512

28705 - LOGID_APP_CTRL_IPS_BLOCK

Message ID: 28705

Message Description: LOGID_APP_CTRL_IPS_BLOCK**Message Meaning:** Application control (IPS) (block)**Type:** App**Category:** SIGNATURE**Severity:** Warning

Log Field Name	Description	Data Type	Length
action		string	16
app		string	96
appcat		string	64
applist		string	64
authserver		string	32
date		string	10
devid		string	16
direction		string	8
dstintf		string	64
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
group		string	64
level		string	11
logid		string	10
policyid		uint32	10
profile		string	36
profiletype		string	36
proto		uint8	3
service		string	80
sessionid		uint32	10
srcdomain		string	255
srcintf		string	64

Log Field Name	Description	Data Type	Length
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32
vrf		uint8	3
appid		uint32	10
apprisk		string	16
ccertissuer		string	64
cloudaction		string	32
clouduser		string	256
craction		uint32	10
crlevel		string	10
crscore		uint32	10
filename		string	256
filesize		uint64	10
forwardedfor		string	128
hostname		string	256
incidentserialno		uint32	10
msg		string	512
rawdata		string	20480
rawdataid		string	10
scertcname		string	64
scertissuer		string	64

Log Field Name	Description	Data Type	Length
trueclntip		ip	39
url		string	512

28706 - LOGID_APP_CTRL_IPS_RESET

Message ID: 28706

Message Description: LOGID_APP_CTRL_IPS_RESET

Message Meaning: Application control (IPS) (reset)

Type: App

Category: SIGNATURE

Severity: Warning

Log Field Name	Description	Data Type	Length
action		string	16
app		string	96
appcat		string	64
applist		string	64
authserver		string	32
date		string	10
devid		string	16
direction		string	8
dstintf		string	64
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
group		string	64
level		string	11
logid		string	10
policyid		uint32	10

Log Field Name	Description	Data Type	Length
profile		string	36
profiletype		string	36
proto		uint8	3
service		string	80
sessionid		uint32	10
srcdomain		string	255
srcintf		string	64
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32
vrf		uint8	3
appid		uint32	10
apprisk		string	16
ccertissuer		string	64
cloudaction		string	32
clouduser		string	256
craction		uint32	10
crlevel		string	10
crscore		uint32	10
filename		string	256
filesize		uint64	10
forwardedfor		string	128

Log Field Name	Description	Data Type	Length
hostname		string	256
incidentserialno		uint32	10
msg		string	512
rawdata		string	20480
rawdataid		string	10
scertcname		string	64
scertissuer		string	64
trueclntip		ip	39
url		string	512

28720 - LOGID_APP_CTRL_SSH_PASS

Message ID: 28720

Message Description: LOGID_APP_CTRL_SSH_PASS

Message Meaning: Application control IM (SSH) (pass)

Type: App

Category: SIGNATURE

Severity: Information

Log Field Name	Description	Data Type	Length
action		string	16
app		string	96
appcat		string	64
applist		string	64
authserver		string	32
date		string	10
devid		string	16
direction		string	8
dstintf		string	64
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
group		string	64
level		string	11
logid		string	10
policyid		uint32	10
profile		string	36
profiletype		string	36
proto		uint8	3
service		string	80
sessionid		uint32	10
srcdomain		string	255
srcintf		string	64
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32
vrf		uint8	3

28721 - LOGID_APP_CTRL_SSH_BLOCK

Message ID: 28721

Message Description: LOGID_APP_CTRL_SSH_BLOCK

Message Meaning: Application control IM (SSH) (block)

Type: App**Category:** SIGNATURE**Severity:** Warning

Log Field Name	Description	Data Type	Length
action		string	16
app		string	96
appcat		string	64
applist		string	64
authserver		string	32
date		string	10
devid		string	16
direction		string	8
dstintf		string	64
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
group		string	64
level		string	11
logid		string	10
policyid		uint32	10
profile		string	36
profiletype		string	36
proto		uint8	3
service		string	80
sessionid		uint32	10
srcdomain		string	255
srcintf		string	64
srcintfrole		string	10
srcip		ip	39

Log Field Name	Description	Data Type	Length
srcport		uint16	5
subtype		string	20
time		string	8
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32
vrf		uint8	3

28736 - LOGID_APP_CTRL_PORT_ENF

Message ID: 28736

Message Description: LOGID_APP_CTRL_PORT_ENF

Message Meaning: Application control port enforcement

Type: App

Category: PORT-VIOLATION

Severity: Warning

Log Field Name	Description	Data Type	Length
action		string	16
app		string	96
appcat		string	64
appid		uint32	10
applist		string	64
apprisk		string	16
authserver		string	32
ccertissuer		string	64
cloudaction		string	32
clouduser		string	256
craction		uint32	10

Log Field Name	Description	Data Type	Length
crlevel		string	10
crscore		uint32	10
date		string	10
devid		string	16
direction		string	8
dstintf		string	64
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
filename		string	256
filesize		uint64	10
forwardedfor		string	128
group		string	64
hostname		string	256
incidentserialno		uint32	10
level		string	11
logid		string	10
msg		string	512
policyid		uint32	10
profile		string	36
profiletype		string	36
proto		uint8	3
rawdata		string	20480
rawdataid		string	10
scertcname		string	64
scertissuer		string	64
service		string	80

Log Field Name	Description	Data Type	Length
sessionid		uint32	10
srcdomain		string	255
srcintf		string	64
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
trueclntip		ip	39
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url		string	512
user		string	256
vd		string	32
vrf		uint8	3

28737 - LOGID_APP_CTRL_PROTO_ENF

Message ID: 28737

Message Description: LOGID_APP_CTRL_PROTO_ENF

Message Meaning: Application control protocol enforcement

Type: App

Category: PROTOCOL-VIOLATION

Severity: Warning

Log Field Name	Description	Data Type	Length
action		string	16
app		string	96
appcat		string	64
appid		uint32	10

Log Field Name	Description	Data Type	Length
applist		string	64
apprisk		string	16
authserver		string	32
ccertissuer		string	64
cloudaction		string	32
clouduser		string	256
craction		uint32	10
crlevel		string	10
crscore		uint32	10
date		string	10
devid		string	16
direction		string	8
dstintf		string	64
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
filename		string	256
filesize		uint64	10
forwardedfor		string	128
group		string	64
hostname		string	256
incidentserialno		uint32	10
level		string	11
logid		string	10
msg		string	512
policyid		uint32	10
profile		string	36

Log Field Name	Description	Data Type	Length
profiletype		string	36
proto		uint8	3
rawdata		string	20480
rawdataid		string	10
scertcname		string	64
scertissuer		string	64
service		string	80
sessionid		uint32	10
srcdomain		string	255
srcintf		string	64
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
trueclntip		ip	39
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url		string	512
user		string	256
vd		string	32
vrf		uint8	3

AV

8192 - MESGID_INFECT_WARNING

Message ID: 8192

Message Description: MESGID_INFECT_WARNING

Message Meaning: Infected file detected by the FortiGate unit and blocked

Type: AV**Category:** INFECTED**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256
checksum	The checksum of the scanned file	string	16
contentdisarmed		string	13
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128

Log Field Name	Description	Data Type	Length
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
rawdata		string	20480
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256

Log Field Name	Description	Data Type	Length
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

8193 - MESGID_INFECT_NOTIF

Message ID: 8193

Message Description: MESGID_INFECT_NOTIF

Message Meaning: Infected file detected by the FortiGate unit and it passed

Type: AV

Category: INFECTED

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256
checksum	The checksum of the scanned file	string	16
contentdisarmed		string	13
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39

Log Field Name	Description	Data Type	Length
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
rawdata		string	20480
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5

Log Field Name	Description	Data Type	Length
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

8194 - MESGID_INFECT_MIME_WARNING

Message ID: 8194

Message Description: MESGID_INFECT_MIME_WARNING

Message Meaning: MIME header detected to have a virus and blocked

Type: AV

Category: INFECTED

Severity: Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256

Log Field Name	Description	Data Type	Length
checksum	The checksum of the scanned file	string	16
contentdisarmed		string	13
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46

Log Field Name	Description	Data Type	Length
rawdata		string	20480
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

8195 - MESGID_INFECT_MIME_NOTIF

Message ID: 8195

Message Description: MESGID_INFECT_MIME_NOTIF

Message Meaning: MIME header infected and passed

Type: AV**Category:** INFECTED**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256
checksum	The checksum of the scanned file	string	16
contentdisarmed		string	13
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128

Log Field Name	Description	Data Type	Length
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
rawdata		string	20480
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256

Log Field Name	Description	Data Type	Length
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

8200 - MESGID_MIME_FILETYPE_EXE_WARNING

Message ID: 8200

Message Description: MESGID_MIME_FILETYPE_EXE_WARNING

Message Meaning: File is an executable (warning)

Type: AV

Category: FILETYPE-EXECUTABLE

Severity: Warning

Log Field Name	Description	Data Type	Length
action		string	16
analyticscksum		string	64
analyticssubmit		string	10
authserver		string	32
checksum		string	16
craction		uint32	10
crlevel		string	10
crscore		uint32	10
date		string	10
devid		string	16
direction		string	8
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
dtype		string	32
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
eventtype		string	32
fctuid		string	32
filename		string	256
forwardedfor		string	128
from		string	128
group		string	64
level		string	11
logid		string	10
msg		string	4096
policyid		uint32	10
profile		string	64
proto		uint8	3
quarskip		string	46
recipient		string	512
sender		string	128
service		string	5
sessionid		uint32	10
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subservice		string	16
subtype		string	20
time		string	8
to		string	512
trueclntip		ip	39
type		string	16
tz		string	5
unauthuser		string	66

Log Field Name	Description	Data Type	Length
unauthusersource		string	66
user		string	256
vd		string	32
vrf		uint8	3

8201 - MESGID_MIME_FILETYPE_EXE_NOTIF

Message ID: 8201

Message Description: MESGID_MIME_FILETYPE_EXE_NOTIF

Message Meaning: File is an executable (notice)

Type: AV

Category: FILETYPE-EXECUTABLE

Severity: Notice

Log Field Name	Description	Data Type	Length
action		string	16
analyticscksum		string	64
analyticssubmit		string	10
authserver		string	32
checksum		string	16
craction		uint32	10
crlevel		string	10
crscore		uint32	10
date		string	10
devid		string	16
direction		string	8
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
dtype		string	32
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
eventtype		string	32
fctuid		string	32
filename		string	256
forwardedfor		string	128
from		string	128
group		string	64
level		string	11
logid		string	10
msg		string	4096
policyid		uint32	10
profile		string	64
proto		uint8	3
quarskip		string	46
recipient		string	512
sender		string	128
service		string	5
sessionid		uint32	10
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subservice		string	16
subtype		string	20
time		string	8
to		string	512
trueclntip		ip	39
type		string	16
tz		string	5
unauthuser		string	66

Log Field Name	Description	Data Type	Length
unauthusersource		string	66
user		string	256
vd		string	32
vrf		uint8	3

8202 - MESGID_AVQUERY_WARNING

Message ID: 8202

Message Description: MESGID_AVQUERY_WARNING

Message Meaning: File reported infected by Outbreak Prevention (warning)

Type: AV

Category: OUTBREAK-PREVENTION

Severity: Warning

Log Field Name	Description	Data Type	Length
action		string	16
agent		string	64
analyticscksum		string	64
analyticssubmit		string	10
authserver		string	32
cdrcontent		string	256
checksum		string	16
contentdisarmed		string	13
craction		uint32	10
crlevel		string	10
crscore		uint32	10
date		string	10
devid		string	16
direction		string	8
dstintf		string	32
dstintfrole		string	10
dstip		ip	39

Log Field Name	Description	Data Type	Length
dstport		uint16	5
dtype		string	32
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename		string	256
filetype		string	16
forwardedfor		string	128
from		string	128
group		string	64
level		string	11
logid		string	10
msg		string	4096
policyid		uint32	10
profile		string	64
proto		uint8	3
quarskip		string	46
rawdata		string	20480
recipient		string	512
ref		string	512
sender		string	128
service		string	5
sessionid		uint32	10
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5

Log Field Name	Description	Data Type	Length
subservice		string	16
subtype		string	20
time		string	8
to		string	512
trueclntip		ip	39
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url		string	512
user		string	256
vd		string	32
virus		string	128
virusid		uint32	10
vrf		uint8	3

8203 - MESGID_AVQUERY_NOTIF

Message ID: 8203

Message Description: MESGID_AVQUERY_NOTIF

Message Meaning: File reported infected by Outbreak Prevention (notice)

Type: AV

Category: OUTBREAK-PREVENTION

Severity: Notice

Log Field Name	Description	Data Type	Length
action		string	16
agent		string	64
analyticscksum		string	64
analyticssubmit		string	10
authserver		string	32
cdrcontent		string	256

Log Field Name	Description	Data Type	Length
checksum		string	16
contentdisarmed		string	13
craction		uint32	10
crlevel		string	10
crscore		uint32	10
date		string	10
devid		string	16
direction		string	8
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
dtype		string	32
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename		string	256
filetype		string	16
forwardedfor		string	128
from		string	128
group		string	64
level		string	11
logid		string	10
msg		string	4096
policyid		uint32	10
profile		string	64
proto		uint8	3
quarskip		string	46

Log Field Name	Description	Data Type	Length
rawdata		string	20480
recipient		string	512
ref		string	512
sender		string	128
service		string	5
sessionid		uint32	10
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subservice		string	16
subtype		string	20
time		string	8
to		string	512
trueclntip		ip	39
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url		string	512
user		string	256
vd		string	32
virus		string	128
virusid		uint32	10
vrf		uint8	3

8204 - MESGID_MIME_AVQUERY_WARNING

Message ID: 8204

Message Description: MESGID_MIME_AVQUERY_WARNING

Message Meaning: MIME data reported infected by Outbreak Prevention (warning)

Type: AV**Category:** OUTBREAK-PREVENTION**Severity:** Warning

Log Field Name	Description	Data Type	Length
action		string	16
agent		string	64
analyticscksum		string	64
analyticssubmit		string	10
authserver		string	32
cdrcontent		string	256
checksum		string	16
contentdisarmed		string	13
craction		uint32	10
crlevel		string	10
crscore		uint32	10
date		string	10
devid		string	16
direction		string	8
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
dtype		string	32
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename		string	256
filetype		string	16
forwardedfor		string	128
from		string	128

Log Field Name	Description	Data Type	Length
group		string	64
level		string	11
logid		string	10
msg		string	4096
policyid		uint32	10
profile		string	64
proto		uint8	3
quarskip		string	46
rawdata		string	20480
recipient		string	512
ref		string	512
sender		string	128
service		string	5
sessionid		uint32	10
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subservice		string	16
subtype		string	20
time		string	8
to		string	512
trueclntip		ip	39
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url		string	512
user		string	256

Log Field Name	Description	Data Type	Length
vd		string	32
virus		string	128
virusid		uint32	10
vrf		uint8	3

8205 - MESGID_MIME_AVQUERY_NOTIF

Message ID: 8205

Message Description: MESGID_MIME_AVQUERY_NOTIF

Message Meaning: MIME data reported infected by Outbreak Prevention (notice)

Type: AV

Category: OUTBREAK-PREVENTION

Severity: Notice

Log Field Name	Description	Data Type	Length
action		string	16
agent		string	64
analyticscksum		string	64
analyticssubmit		string	10
authserver		string	32
cdrcontent		string	256
checksum		string	16
contentdisarmed		string	13
craction		uint32	10
crlevel		string	10
crscore		uint32	10
date		string	10
devid		string	16
direction		string	8
dstintf		string	32
dstintfrole		string	10
dstip		ip	39

Log Field Name	Description	Data Type	Length
dstport		uint16	5
dtype		string	32
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename		string	256
filetype		string	16
forwardedfor		string	128
from		string	128
group		string	64
level		string	11
logid		string	10
msg		string	4096
policyid		uint32	10
profile		string	64
proto		uint8	3
quarskip		string	46
rawdata		string	20480
recipient		string	512
ref		string	512
sender		string	128
service		string	5
sessionid		uint32	10
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5

Log Field Name	Description	Data Type	Length
subservice		string	16
subtype		string	20
time		string	8
to		string	512
trueclntip		ip	39
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url		string	512
user		string	256
vd		string	32
virus		string	128
virusid		uint32	10
vrf		uint8	3

8212 - MESGID_MALWARE_LIST_WARNING

Message ID: 8212

Message Description: MESGID_MALWARE_LIST_WARNING

Message Meaning: File reported infected by external malware list (warning)

Type: AV

Category: MALWARE-LIST

Severity: Warning

Log Field Name	Description	Data Type	Length
action		string	16
agent		string	64
analyticscksum		string	64
analyticssubmit		string	10
authserver		string	32
cdrcontent		string	256

Log Field Name	Description	Data Type	Length
checksum		string	16
contentdisarmed		string	13
craction		uint32	10
crlevel		string	10
crscore		uint32	10
date		string	10
devid		string	16
direction		string	8
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
dtype		string	32
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename		string	256
filetype		string	16
forwardedfor		string	128
from		string	128
group		string	64
level		string	11
logid		string	10
msg		string	4096
policyid		uint32	10
profile		string	64
proto		uint8	3
quarskip		string	46

Log Field Name	Description	Data Type	Length
rawdata		string	20480
recipient		string	512
ref		string	512
sender		string	128
service		string	5
sessionid		uint32	10
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subservice		string	16
subtype		string	20
time		string	8
to		string	512
trueclntip		ip	39
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url		string	512
user		string	256
vd		string	32
virus		string	128
virusid		uint32	10
vrf		uint8	3

8213 - MESGID_MALWARE_LIST_NOTIF

Message ID: 8213

Message Description: MESGID_MALWARE_LIST_NOTIF

Message Meaning: File reported infected by external malware list (notice)

Type: AV**Category:** MALWARE-LIST**Severity:** Notice

Log Field Name	Description	Data Type	Length
action		string	16
agent		string	64
analyticscksum		string	64
analyticssubmit		string	10
authserver		string	32
cdrcontent		string	256
checksum		string	16
contentdisarmed		string	13
craction		uint32	10
crlevel		string	10
crscore		uint32	10
date		string	10
devid		string	16
direction		string	8
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
dtype		string	32
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename		string	256
filetype		string	16
forwardedfor		string	128
from		string	128

Log Field Name	Description	Data Type	Length
group		string	64
level		string	11
logid		string	10
msg		string	4096
policyid		uint32	10
profile		string	64
proto		uint8	3
quarskip		string	46
rawdata		string	20480
recipient		string	512
ref		string	512
sender		string	128
service		string	5
sessionid		uint32	10
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subservice		string	16
subtype		string	20
time		string	8
to		string	512
trueclntip		ip	39
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url		string	512
user		string	256

Log Field Name	Description	Data Type	Length
vd		string	32
virus		string	128
virusid		uint32	10
vrf		uint8	3

8214 - MESGID_MIME_MALWARE_LIST_WARNING

Message ID: 8214

Message Description: MESGID_MIME_MALWARE_LIST_WARNING

Message Meaning: MIME data reported infected by external malware list (warning)

Type: AV

Category: MALWARE-LIST

Severity: Warning

Log Field Name	Description	Data Type	Length
action		string	16
agent		string	64
analyticscksum		string	64
analyticssubmit		string	10
authserver		string	32
cdrcontent		string	256
checksum		string	16
contentdisarmed		string	13
craction		uint32	10
crlevel		string	10
crscore		uint32	10
date		string	10
devid		string	16
direction		string	8
dstintf		string	32
dstintfrole		string	10
dstip		ip	39

Log Field Name	Description	Data Type	Length
dstport		uint16	5
dtype		string	32
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename		string	256
filetype		string	16
forwardedfor		string	128
from		string	128
group		string	64
level		string	11
logid		string	10
msg		string	4096
policyid		uint32	10
profile		string	64
proto		uint8	3
quarskip		string	46
rawdata		string	20480
recipient		string	512
ref		string	512
sender		string	128
service		string	5
sessionid		uint32	10
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5

Log Field Name	Description	Data Type	Length
subservice		string	16
subtype		string	20
time		string	8
to		string	512
trueclntip		ip	39
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url		string	512
user		string	256
vd		string	32
virus		string	128
virusid		uint32	10
vrf		uint8	3

8215 - MESGID_MIME_MALWARE_LIST_NOTIF

Message ID: 8215

Message Description: MESGID_MIME_MALWARE_LIST_NOTIF

Message Meaning: MIME data reported infected by external malware list (notice)

Type: AV

Category: MALWARE-LIST

Severity: Notice

Log Field Name	Description	Data Type	Length
action		string	16
agent		string	64
analyticscksum		string	64
analyticssubmit		string	10
authserver		string	32
cdrcontent		string	256

Log Field Name	Description	Data Type	Length
checksum		string	16
contentdisarmed		string	13
craction		uint32	10
crlevel		string	10
crscore		uint32	10
date		string	10
devid		string	16
direction		string	8
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
dtype		string	32
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename		string	256
filetype		string	16
forwardedfor		string	128
from		string	128
group		string	64
level		string	11
logid		string	10
msg		string	4096
policyid		uint32	10
profile		string	64
proto		uint8	3
quarskip		string	46

Log Field Name	Description	Data Type	Length
rawdata		string	20480
recipient		string	512
ref		string	512
sender		string	128
service		string	5
sessionid		uint32	10
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subservice		string	16
subtype		string	20
time		string	8
to		string	512
trueclntip		ip	39
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url		string	512
user		string	256
vd		string	32
virus		string	128
virusid		uint32	10
vrf		uint8	3

8448 - MESGID_BLOCK_WARNING

Message ID: 8448

Message Description: MESGID_BLOCK_WARNING

Message Meaning: FortiGate unit blocked a file because it contains a virus

Type: AV**Category:** FILENAME**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
authserver		string	32
checksum	The checksum of the scanned file	string	16
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filefilter	The filter used to identify the affected file	string	12
filename	File name	string	256
filetype	File type	string	16
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3

Log Field Name	Description	Data Type	Length
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
vrf		uint8	3

8450 - MESGID_BLOCK_MIME_WARNING

Message ID: 8450

Message Description: MESGID_BLOCK_MIME_WARNING

Message Meaning: FortiGate unit blocked a file because it contains a virus (MIME)

Type: AV

Category: MIMEFRAGMENTED

Severity: Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
authserver		string	32
checksum	The checksum of the scanned file	string	16
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filefilter	The filter used to identify the affected file	string	12
filename	File name	string	256
filetype	File type	string	16
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512

Log Field Name	Description	Data Type	Length
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
vrf		uint8	3

8451 - MESGID_BLOCK_MIME_NOTIF

Message ID: 8451

Message Description: MESGID_BLOCK_MIME_NOTIF

Message Meaning: FortiGate unit blocked a file because it contains a virus (MIME)

Type: AV

Category: MIMEFRAGMENTED

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16

Log Field Name	Description	Data Type	Length
agent	User agent - eg. agent="Mozilla/5.0"	string	64
authserver		string	32
checksum	The checksum of the scanned file	string	16
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filefilter	The filter used to identify the affected file	string	12
filename	File name	string	256
filetype	File type	string	16
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128

Log Field Name	Description	Data Type	Length
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
vrf		uint8	3

8452 - MESGID_BLOCK_COMMAND

Message ID: 8452

Message Description: MESGID_BLOCK_COMMAND

Message Meaning: FortiGate unit blocked a virus command

Type: AV

Category: COMMAND-BLOCKED

Severity: Warning

Log Field Name	Description	Data Type	Length
action		string	16
agent		string	64

Log Field Name	Description	Data Type	Length
authserver		string	32
command		string	16
craction		uint32	10
crlevel		string	10
crscore		uint32	10
date		string	10
devid		string	16
direction		string	8
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
group		string	64
level		string	11
logid		string	10
msg		string	4096
policyid		uint32	10
profile		string	64
proto		uint8	3
service		string	5
sessionid		uint32	10
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subservice		string	16

Log Field Name	Description	Data Type	Length
subtype		string	20
time		string	8
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url		string	512
user		string	256
vd		string	32
vrf		uint8	3

8457 - MESGID_MMS_CHECKSUM

Message ID: 8457

Message Description: MESGID_MMS_CHECKSUM

Message Meaning: MMS content checksum blocked an infected file

Type: AV

Category: FILENAME

Severity: Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
authserver		string	32
checksum	The checksum of the scanned file	string	16
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32

Log Field Name	Description	Data Type	Length
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5

Log Field Name	Description	Data Type	Length
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
vrf		uint8	3

8458 - MESGID_MMS_CHECKSUM_NOTIF

Message ID: 8458

Message Description: MESGID_MMS_CHECKSUM_NOTIF

Message Meaning: MMS content checksum was matched

Type: AV

Category: FILENAME

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
authserver		string	32
checksum	The checksum of the scanned file	string	16
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256

Log Field Name	Description	Data Type	Length
vd	VDOM name	string	32
vrf		uint8	3

8704 - MESGID_OVERSIZE_WARNING

Message ID: 8704

Message Description: MESGID_OVERSIZE_WARNING

Message Meaning: Defined file size limit was exceeded

Type: AV

Category: OVERSIZE

Severity: Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
authserver		string	32
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128

Log Field Name	Description	Data Type	Length
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
vrf		uint8	3

8705 - MESGID_OVERSIZE_NOTIF

Message ID: 8705

Message Description: MESGID_OVERSIZE_NOTIF

Message Meaning: File size limit was exceeded

Type: AV

Category: OVERSIZE

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
authserver		string	32
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096

Log Field Name	Description	Data Type	Length
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
vrf		uint8	3

8706 - MESGID_OVERSIZE_MIME_WARNING

Message ID: 8706

Message Description: MESGID_OVERSIZE_MIME_WARNING

Message Meaning: File (MIME) size exceed the defined size limit

Type: AV

Category: OVERSIZE**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
authserver		string	32
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5

Log Field Name	Description	Data Type	Length
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
vrf		uint8	3

8707 - MESGID_OVERSIZE_MIME_NOTIF

Message ID: 8707

Message Description: MESGID_OVERSIZE_MIME_NOTIF

Message Meaning: File (MIME) size exceed the defined size limit

Type: AV

Category: OVERSIZE

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64

Log Field Name	Description	Data Type	Length
authserver		string	32
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32

Log Field Name	Description	Data Type	Length
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
vrf		uint8	3

8708 - MESGID_OVERSIZE_STREAM_UNCOMP_WARNING

Message ID: 8708

Message Description: MESGID_OVERSIZE_STREAM_UNCOMP_WARNING

Message Meaning: stream-based uncompression reached size limit

Type: AV

Category: OVERSIZE

Severity: Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10

Log Field Name	Description	Data Type	Length
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512

Log Field Name	Description	Data Type	Length
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
vrf		uint8	3

8709 - MESGID_OVERSIZE_STREAM_UNCOMP_NOTIF

Message ID: 8709

Message Description: MESGID_OVERSIZE_STREAM_UNCOMP_NOTIF

Message Meaning: stream-based uncompression reached size limit

Type: AV

Category: OVERSIZE

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32

Log Field Name	Description	Data Type	Length
filename	File name	string	256
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
vrf		uint8	3

8720 - MESGID_SWITCH_PROTO_WARNING

Message ID: 8720

Message Description: MESGID_SWITCH_PROTO_WARNING

Message Meaning: Switching protocols request (warning)

Type: AV

Category: SWITCHPROTO

Severity: Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
authserver		string	32
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64

Log Field Name	Description	Data Type	Length
proto	Protocol number	uint8	3
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
switchproto	Protocol change information	string	128
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
vrf		uint8	3

8721 - MESGID_SWITCH_PROTO_NOTIF

Message ID: 8721

Message Description: MESGID_SWITCH_PROTO_NOTIF

Message Meaning: Switching protocols request (notice)

Type: AV

Category: SWITCHPROTO

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
authserver		string	32
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39

Log Field Name	Description	Data Type	Length
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
switchproto	Protocol change information	string	128
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
vrf		uint8	3

8960 - MESGID_SCAN_UNCOMPSizeLIMIT_WARNING

Message ID: 8960

Message Description: MESGID_SCAN_UNCOMPSizeLIMIT_WARNING

Message Meaning: File reached the uncompressed nested limit

Type: AV

Category: SCANERROR

Severity: Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256
checksum	The checksum of the scanned file	string	16

Log Field Name	Description	Data Type	Length
contentdisarmed		string	13
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
rawdata		string	20480

Log Field Name	Description	Data Type	Length
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

8961 - MESGID_SCAN_UNCOMPSizeLIMIT_NOTIF

Message ID: 8961

Message Description: MESGID_SCAN_UNCOMPSizeLIMIT_NOTIF

Message Meaning: File reached the uncompressed size limit

Type: AV

Category: SCANERROR**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256
checksum	The checksum of the scanned file	string	16
contentdisarmed		string	13
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64

Log Field Name	Description	Data Type	Length
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
rawdata		string	20480
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32

Log Field Name	Description	Data Type	Length
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

8962 - MESGID_SCAN_ARCHIVE_ENCRYPTED_WARNING

Message ID: 8962

Message Description: MESGID_SCAN_ARCHIVE_ENCRYPTED_WARNING

Message Meaning: Archived file is corrupted

Type: AV

Category: SCANERROR

Severity: Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256
checksum	The checksum of the scanned file	string	16
contentdisarmed		string	13
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5

Log Field Name	Description	Data Type	Length
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
rawdata		string	20480
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16

Log Field Name	Description	Data Type	Length
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

8963 - MESGID_SCAN_ARCHIVE_ENCRYPTED_NOTIF

Message ID: 8963

Message Description: MESGID_SCAN_ARCHIVE_ENCRYPTED_NOTIF

Message Meaning: Archived file is encrypted

Type: AV

Category: SCANERROR

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256
checksum	The checksum of the scanned file	string	16

Log Field Name	Description	Data Type	Length
contentdisarmed		string	13
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
rawdata		string	20480

Log Field Name	Description	Data Type	Length
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

8964 - MESGID_SCAN_ARCHIVE_CORRUPTED_WARNING

Message ID: 8964

Message Description: MESGID_SCAN_ARCHIVE_CORRUPTED_WARNING

Message Meaning: Corrupted archive (warning)

Type: AV

Category: SCANERROR**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256
checksum	The checksum of the scanned file	string	16
contentdisarmed		string	13
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64

Log Field Name	Description	Data Type	Length
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
rawdata		string	20480
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32

Log Field Name	Description	Data Type	Length
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

8965 - MESGID_SCAN_ARCHIVE_CORRUPTED_NOTIF

Message ID: 8965

Message Description: MESGID_SCAN_ARCHIVE_CORRUPTED_NOTIF

Message Meaning: Corrupted archive (notice)

Type: AV

Category: SCANERROR

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256
checksum	The checksum of the scanned file	string	16
contentdisarmed		string	13
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5

Log Field Name	Description	Data Type	Length
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
rawdata		string	20480
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16

Log Field Name	Description	Data Type	Length
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

8966 - MESGID_SCAN_ARCHIVE_MULTIPART_WARNING

Message ID: 8966

Message Description: MESGID_SCAN_ARCHIVE_MULTIPART_WARNING

Message Meaning: File is a multipart archive or contains multiple files within the archive

Type: AV

Category: SCANERROR

Severity: Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256
checksum	The checksum of the scanned file	string	16

Log Field Name	Description	Data Type	Length
contentdisarmed		string	13
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
rawdata		string	20480

Log Field Name	Description	Data Type	Length
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

8967 - MESGID_SCAN_ARCHIVE_MULTIPART_NOTIF

Message ID: 8967

Message Description: MESGID_SCAN_ARCHIVE_MULTIPART_NOTIF

Message Meaning: File is a multipart archive or contains multiple files within the archive

Type: AV

Category: SCANERROR**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256
checksum	The checksum of the scanned file	string	16
contentdisarmed		string	13
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64

Log Field Name	Description	Data Type	Length
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
rawdata		string	20480
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32

Log Field Name	Description	Data Type	Length
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

8968 - MESGID_SCAN_ARCHIVE_NESTED_WARNING

Message ID: 8968

Message Description: MESGID_SCAN_ARCHIVE_NESTED_WARNING

Message Meaning: File is a nested archived file

Type: AV

Category: SCANERROR

Severity: Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256
checksum	The checksum of the scanned file	string	16
contentdisarmed		string	13
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5

Log Field Name	Description	Data Type	Length
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
rawdata		string	20480
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16

Log Field Name	Description	Data Type	Length
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

8969 - MESGID_SCAN_ARCHIVE_NESTED_NOTIF

Message ID: 8969

Message Description: MESGID_SCAN_ARCHIVE_NESTED_NOTIF

Message Meaning: File is an archived type unhandled

Type: AV

Category: SCANERROR

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256
checksum	The checksum of the scanned file	string	16

Log Field Name	Description	Data Type	Length
contentdisarmed		string	13
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
rawdata		string	20480

Log Field Name	Description	Data Type	Length
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

8970 - MESGID_SCAN_ARCHIVE_OVERSIZE_WARNING

Message ID: 8970

Message Description: MESGID_SCAN_ARCHIVE_OVERSIZE_WARNING

Message Meaning: Archived file is oversized

Type: AV

Category: SCANERROR**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256
checksum	The checksum of the scanned file	string	16
contentdisarmed		string	13
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64

Log Field Name	Description	Data Type	Length
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
rawdata		string	20480
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32

Log Field Name	Description	Data Type	Length
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

8971 - MESGID_SCAN_ARCHIVE_OVERSIZE_NOTIF

Message ID: 8971

Message Description: MESGID_SCAN_ARCHIVE_OVERSIZE_NOTIF

Message Meaning: Archived file is oversized

Type: AV

Category: SCANERROR

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256
checksum	The checksum of the scanned file	string	16
contentdisarmed		string	13
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5

Log Field Name	Description	Data Type	Length
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
rawdata		string	20480
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16

Log Field Name	Description	Data Type	Length
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

8972 - MESGID_SCAN_ARCHIVE_UNHANDLED_WARNING

Message ID: 8972

Message Description: MESGID_SCAN_ARCHIVE_UNHANDLED_WARNING

Message Meaning: Unhandled archive (warning)

Type: AV

Category: SCANERROR

Severity: Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256
checksum	The checksum of the scanned file	string	16

Log Field Name	Description	Data Type	Length
contentdisarmed		string	13
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
rawdata		string	20480

Log Field Name	Description	Data Type	Length
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

8973 - MESGID_SCAN_ARCHIVE_UNHANDLED_NOTIF

Message ID: 8973

Message Description: MESGID_SCAN_ARCHIVE_UNHANDLED_NOTIF

Message Meaning: Unhandled archive (notice)

Type: AV

Category: SCANERROR**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256
checksum	The checksum of the scanned file	string	16
contentdisarmed		string	13
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64

Log Field Name	Description	Data Type	Length
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
rawdata		string	20480
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32

Log Field Name	Description	Data Type	Length
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

8974 - MESGID_SCAN_AV_ENGINE_LOAD_FAILED_ERROR

Message ID: 8974

Message Description: MESGID_SCAN_AV_ENGINE_LOAD_FAILED_ERROR

Message Meaning: AV Engine load failed

Type: AV

Category: SCANERROR

Severity: Error

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256
checksum	The checksum of the scanned file	string	16
contentdisarmed		string	13
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5

Log Field Name	Description	Data Type	Length
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
rawdata		string	20480
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16

Log Field Name	Description	Data Type	Length
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

8975 - MESGID_SCAN_ARCHIVE_PARTIALLYCORRUPTED_WARNING

Message ID: 8975

Message Description: MESGID_SCAN_ARCHIVE_PARTIALLYCORRUPTED_WARNING

Message Meaning: Partially corrupted archive (warning)

Type: AV

Category: SCANERROR

Severity: Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256
checksum	The checksum of the scanned file	string	16

Log Field Name	Description	Data Type	Length
contentdisarmed		string	13
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
rawdata		string	20480

Log Field Name	Description	Data Type	Length
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

8976 - MESGID_SCAN_ARCHIVE_PARTIALLYCORRUPTED_NOTIF

Message ID: 8976

Message Description: MESGID_SCAN_ARCHIVE_PARTIALLYCORRUPTED_NOTIF

Message Meaning: Partially corrupted archive (notice)

Type: AV

Category: SCANERROR**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256
checksum	The checksum of the scanned file	string	16
contentdisarmed		string	13
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64

Log Field Name	Description	Data Type	Length
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
rawdata		string	20480
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32

Log Field Name	Description	Data Type	Length
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

8977 - MESGID_SCAN_ARCHIVE_FILESLIMIT_WARNING

Message ID: 8977

Message Description: MESGID_SCAN_ARCHIVE_FILESLIMIT_WARNING

Message Meaning: Exceeded archive files limit (warning)

Type: AV

Category: SCANERROR

Severity: Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256
checksum	The checksum of the scanned file	string	16
contentdisarmed		string	13
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5

Log Field Name	Description	Data Type	Length
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
rawdata		string	20480
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16

Log Field Name	Description	Data Type	Length
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

8978 - MESGID_SCAN_ARCHIVE_FILESLIMIT_NOTIF

Message ID: 8978

Message Description: MESGID_SCAN_ARCHIVE_FILESLIMIT_NOTIF

Message Meaning: Exceeded archive files limit (notice)

Type: AV

Category: SCANERROR

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256
checksum	The checksum of the scanned file	string	16

Log Field Name	Description	Data Type	Length
contentdisarmed		string	13
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
rawdata		string	20480

Log Field Name	Description	Data Type	Length
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

8979 - MESGID_SCAN_ARCHIVE_TIMEOUT_WARNING

Message ID: 8979

Message Description: MESGID_SCAN_ARCHIVE_TIMEOUT_WARNING

Message Meaning: Archive scan timeout (warning)

Type: AV

Category: SCANERROR**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256
checksum	The checksum of the scanned file	string	16
contentdisarmed		string	13
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64

Log Field Name	Description	Data Type	Length
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
rawdata		string	20480
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32

Log Field Name	Description	Data Type	Length
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

8980 - MESGID_SCAN_ARCHIVE_TIMEOUT_NOTIF

Message ID: 8980

Message Description: MESGID_SCAN_ARCHIVE_TIMEOUT_NOTIF

Message Meaning: Archive scan timeout (notice)

Type: AV

Category: SCANERROR

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256
checksum	The checksum of the scanned file	string	16
contentdisarmed		string	13
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5

Log Field Name	Description	Data Type	Length
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
rawdata		string	20480
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16

Log Field Name	Description	Data Type	Length
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

9233 - MESGID_ANALYTICS_SUBMITTED

Message ID: 9233

Message Description: MESGID_ANALYTICS_SUBMITTED

Message Meaning: File submitted to Sandbox

Type: AV

Category: ANALYTICS

Severity: Information

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256
checksum	The checksum of the scanned file	string	16

Log Field Name	Description	Data Type	Length
contentdisarmed		string	13
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
rawdata		string	20480

Log Field Name	Description	Data Type	Length
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

9234 - MESGID_ANALYTICS_INFECT_WARNING

Message ID: 9234

Message Description: MESGID_ANALYTICS_INFECT_WARNING

Message Meaning: File reported infected by FortiSandbox (warning)

Type: AV

Category: INFECTED**Severity:** Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256
checksum	The checksum of the scanned file	string	16
contentdisarmed		string	13
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64

Log Field Name	Description	Data Type	Length
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
rawdata		string	20480
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32

Log Field Name	Description	Data Type	Length
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

9235 - MESGID_ANALYTICS_INFECT_NOTIF

Message ID: 9235

Message Description: MESGID_ANALYTICS_INFECT_NOTIF

Message Meaning: File reported infected by FortiSandbox (notice)

Type: AV

Category: INFECTED

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256
checksum	The checksum of the scanned file	string	16
contentdisarmed		string	13
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5

Log Field Name	Description	Data Type	Length
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
rawdata		string	20480
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16

Log Field Name	Description	Data Type	Length
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

9236 - MESGID_ANALYTICS_INFECT_MIME_WARNING

Message ID: 9236

Message Description: MESGID_ANALYTICS_INFECT_MIME_WARNING

Message Meaning: File reported infected by FortiSandbox (warning)

Type: AV

Category: INFECTED

Severity: Warning

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256
checksum	The checksum of the scanned file	string	16

Log Field Name	Description	Data Type	Length
contentdisarmed		string	13
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
rawdata		string	20480

Log Field Name	Description	Data Type	Length
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

9237 - MESGID_ANALYTICS_INFECT_MIME_NOTIF

Message ID: 9237

Message Description: MESGID_ANALYTICS_INFECT_MIME_NOTIF

Message Meaning: File reported infected by FortiSandbox (notice)

Type: AV

Category: INFECTED**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
agent	User agent - eg. agent="Mozilla/5.0"	string	64
analyticscksum	The checksum of the file submitted for analytics	string	64
analyticssubmit	The flag for analytics submission	string	10
authserver		string	32
cdrcontent		string	256
checksum	The checksum of the scanned file	string	16
contentdisarmed		string	13
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Message/packets direction	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filehash		string	64
filehashsrc		string	32
filename	File name	string	256
filetype		string	16
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	Group name (authentication)	string	64

Log Field Name	Description	Data Type	Length
level	Log level	string	11
logid	Log ID	string	10
msg	Log message	string	4096
policyid	Policy ID	uint32	10
profile	The name of the profile that was used to detect and take action	string	64
proto	Protocol number	uint8	3
quarskip	Quarantine skip explanation	string	46
rawdata		string	20480
recipient	Email addresses from the SMTP envelope	string	512
ref	The URL of the FortiGuard IPS database entry for the attack	string	512
sender	Email address from the SMTP envelope	string	128
service	Proxy service which scanned this traffic	string	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subservice		string	16
subtype	subtype of the virus log	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The url address	string	512
user	Username (authentication)	string	256
vd	VDOM name	string	32

Log Field Name	Description	Data Type	Length
virus	Virus Name	string	128
virusid	Virus ID (unique virus identifier)	uint32	10
vrf		uint8	3

9238 - MESGID_ANALYTICS_FSA_RESULT

Message ID: 9238

Message Description: MESGID_ANALYTICS_FSA_RESULT

Message Meaning: File verdict returned from FortiSandbox

Type: AV

Category: ANALYTICS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	The security action performed by AV	string	16
analyticscksum	The checksum of the file submitted for analytics	string	64
date	Date	string	10
devid		string	16
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
dtype	Data type for virus category	string	32
eventtime		uint64	20
eventtype	Event type of AV	string	32
fctuid		string	32
filename	File name	string	256
level	Log level	string	11
logid	Log ID	string	10
service	Proxy service which scanned this traffic	string	5
srcdomain		string	255
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	subtype of the virus log	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
vd	VDOM name	string	32
fsaverdict		string	32

9239 - MESGID_CONTENT_DISARM_NOTIF

Message ID: 9239

Message Description: MESGID_CONTENT_DISARM_NOTIF

Message Meaning: Active content detected by Content Disarm engine

Type: AV

Category: CONTENT-DISARM

Severity: Notice

Log Field Name	Description	Data Type	Length
action		string	16
analyticscksum		string	64
authserver		string	32
cdrcontent		string	256
checksum		string	16
contentdisarmed		string	13
craction		uint32	10
crlevel		string	10
crscore		uint32	10
date		string	10
devid		string	16
direction		string	8
dstintf		string	32
dstintfrole		string	10

Log Field Name	Description	Data Type	Length
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
filename		string	256
forwardedfor		string	128
from		string	128
group		string	64
level		string	11
logid		string	10
msg		string	4096
policyid		uint32	10
profile		string	64
proto		uint8	3
rawdata		string	20480
recipient		string	512
sender		string	128
service		string	5
sessionid		uint32	10
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subservice		string	16
subtype		string	20
time		string	8
to		string	512
trueclntip		ip	39

Log Field Name	Description	Data Type	Length
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url		string	512
user		string	256
vd		string	32
vrf		uint8	3

9240 - MESGID_CONTENT_DISARM_WARNING

Message ID: 9240

Message Description: MESGID_CONTENT_DISARM_WARNING

Message Meaning: File was disarmed by Content Disarm engine

Type: AV

Category: CONTENT-DISARM

Severity: Warning

Log Field Name	Description	Data Type	Length
action		string	16
analyticscksum		string	64
authserver		string	32
cdrcontent		string	256
checksum		string	16
contentdisarmed		string	13
craction		uint32	10
crlevel		string	10
crscore		uint32	10
date		string	10
devid		string	16
direction		string	8
dstintf		string	32

Log Field Name	Description	Data Type	Length
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
filename		string	256
forwardedfor		string	128
from		string	128
group		string	64
level		string	11
logid		string	10
msg		string	4096
policyid		uint32	10
profile		string	64
proto		uint8	3
rawdata		string	20480
recipient		string	512
sender		string	128
service		string	5
sessionid		uint32	10
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subservice		string	16
subtype		string	20
time		string	8
to		string	512

Log Field Name	Description	Data Type	Length
trueclntip		ip	39
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url		string	512
user		string	256
vd		string	32
vrf		uint8	3

CIFS

63000 - LOG_ID_CIFS_FILE_BLOCK

Message ID: 63000

Message Description: LOG_ID_CIFS_FILE_BLOCK

Message Meaning: File was blocked by file filter

Type: CIFS

Category: CIFS-FILEFILTER

Severity: Warning

Log Field Name	Description	Data Type	Length
date		string	10
devid		string	16
domainctrlauthstate		uint32	5
domainctrlauthtype		uint32	5
domainctrldomain		string	80
domainctrlip		ip	39
domainctrlname		string	64
domainctrlprotocoltype		uint32	5
domainctrlusername		string	65
dstintf		string	32

Log Field Name	Description	Data Type	Length
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
errorcode		string	20
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
level		string	11
logid		string	10
msg		string	4096
policyid		uint32	10
profile		string	64
service		string	5
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
vd		string	32

63001 - LOG_ID_CIFS_FILE_PASS

Message ID: 63001

Message Description: LOG_ID_CIFS_FILE_PASS

Message Meaning: File detected by file-type filter

Type: CIFS

Category: CIFS-FILEFILTER

Severity: Notice

Log Field Name	Description	Data Type	Length
date		string	10
devid		string	16
domainctrlauthstate		uint32	5
domainctrlauthtype		uint32	5
domainctrldomain		string	80
domainctrlip		ip	39
domainctrlname		string	64
domainctrlprotocoltype		uint32	5
domainctrlusername		string	65
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
errorcode		string	20
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
level		string	11
logid		string	10
msg		string	4096
policyid		uint32	10
profile		string	64
service		string	5
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8

Log Field Name	Description	Data Type	Length
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
vd		string	32

DLP

24576 - LOG_ID_DLP_WARN

Message ID: 24576

Message Description: LOG_ID_DLP_WARN

Message Meaning: Data leak detected by specified DLP sensor rule

Type: DLP

Category: DLP

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by DLP	string	20
agent	User agent - eg. agent="Mozilla/5.0"	string	64
authserver		string	32
date	Date	string	10
devid		string	16
direction	Direction of packets	string	8
dlpextra	DLP extra information	string	256
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
epoch	Epoch used for locating file	uint32	10
eventid	The serial number of the dlparchive file in the same epoch	uint32	10
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
eventtype	DLP event type	string	32
fctuid		string	32
filename	File name	string	256
filesize	File size in bytes	uint64	10
filetype	File type	string	23
filtercat	DLP filter category	string	8
filteridx	DLP filter ID	uint32	10
filtername	DLP rule name	string	128
filtertype	DLP filter type	string	23
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
infectedfilelevel		uint32	10
infectedfilename		string	256
infectedfilesize		uint64	10
infectedfiletype		string	23
level	Log Level	string	11
logid	Log ID	string	10
policyid	Policy ID	uint32	10
profile	DLP profile name	string	64
proto	Protocol number	uint8	3
rawdata		string	20480
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Service name	string	36
sessionid	Session ID	uint32	10
severity	Severity level of a DLP rule	string	8
srcdomain		string	255
srcintf	Source Interface	string	32

Log Field Name	Description	Data Type	Length
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subservice		string	16
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

24577 - LOG_ID_DLP_NOTIF

Message ID: 24577

Message Description: LOG_ID_DLP_NOTIF

Message Meaning: Data leak detected by specified DLP sensor rule

Type: DLP

Category: DLP

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by DLP	string	20
agent	User agent - eg. agent="Mozilla/5.0"	string	64
authserver		string	32
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid		string	16
direction	Direction of packets	string	8
dlpextra	DLP extra information	string	256
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
epoch	Epoch used for locating file	uint32	10
eventid	The serial number of the dlparchive file in the same epoch	uint32	10
eventtime		uint64	20
eventtype	DLP event type	string	32
fctuid		string	32
filename	File name	string	256
filesize	File size in bytes	uint64	10
filetype	File type	string	23
filtercat	DLP filter category	string	8
filteridx	DLP filter ID	uint32	10
filtername	DLP rule name	string	128
filtertype	DLP filter type	string	23
forwardedfor		string	128
from	Email address from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
infectedfilelevel		uint32	10
infectedfilename		string	256
infectedfilesize		uint64	10
infectedfiletype		string	23
level	Log Level	string	11
logid	Log ID	string	10
policyid	Policy ID	uint32	10

Log Field Name	Description	Data Type	Length
profile	DLP profile name	string	64
proto	Protocol number	uint8	3
rawdata		string	20480
recipient	Email addresses from the SMTP envelope	string	512
sender	Email address from the SMTP envelope	string	128
service	Service name	string	36
sessionid	Session ID	uint32	10
severity	Severity level of a DLP rule	string	8
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subservice		string	16
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

24578 - LOG_ID_DLP_DOC_SOURCE

Message ID: 24578

Message Description: LOG_ID_DLP_DOC_SOURCE

Message Meaning: DLP fingerprint document source notice

Type: DLP

Category: DLP

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid		string	16
dlpextra	DLP extra information	string	256
eventtime		uint64	20
eventtype	DLP event type	string	32
level	Log Level	string	11
logid	Log ID	string	10
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
tz		string	5
vd	Virtual domain name	string	32
docsource	DLP fingerprint document source	string	515
sensitivity	Sensitivity for document fingerprint	string	36

24579 - LOG_ID_DLP_DOC_SOURCE_ERROR

Message ID: 24579

Message Description: LOG_ID_DLP_DOC_SOURCE_ERROR

Message Meaning: DLP fingerprint document source error

Type: DLP

Category: DLP

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid		string	16
dlpextra	DLP extra information	string	256

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
eventtype	DLP event type	string	32
level	Log Level	string	11
logid	Log ID	string	10
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
tz		string	5
vd	Virtual domain name	string	32
docsource	DLP fingerprint document source	string	515
sensitivity	Sensitivity for document fingerprint	string	36

DNS

54000 - LOG_ID_DNS_QUERY

Message ID: 54000

Message Description: LOG_ID_DNS_QUERY

Message Meaning: DNS query message

Type: DNS

Category: DNS-QUERY

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid		string	16
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype		string	32

Log Field Name	Description	Data Type	Length
fctuid		string	32
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
policyid	Policy ID	uint32	10
profile	Profile name for DNS filter	string	64
proto	Protocol number	uint8	3
qclass	Query class	string	32
qname	Query domain name	string	256
qtype	Query type description	string	32
qtypeval		uint16	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual Domain Name	string	32
xid	Transaction ID	uint16	5

54200 - LOG_ID_DNS_RESOLV_ERROR

Message ID: 54200

Message Description: LOG_ID_DNS_RESOLV_ERROR

Message Meaning: DNS resolution error message

Type: DNS

Category: DNS-RESPONSE

Severity: Error

Log Field Name	Description	Data Type	Length
action	Security action performed by DNS filter	string	16
botnetdomain	Botnet domain name	string	256
botnetip	Botnet IP address	ip	39
cat	DNS category ID	uint8	3
catdesc	DNS category description	string	64
date	Date	string	10
devid		string	16
domainfilteridx	Domain filter ID	uint8	3
domainfilterlist	Domain filter name	string	512
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
error	DNS filter error message	string	256
eventtime		uint64	20
eventtype		string	32
exchange	Mail Exchanges from DNS response answer section	string	256
fctuid		string	32
group	User group name	string	64
ipaddr	IP addresses from DNS response answer section	string	512
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Profile name for DNS filter	string	64
proto	Protocol number	uint8	3
qclass	Query class	string	32

Log Field Name	Description	Data Type	Length
qname	Query domain name	string	256
qtype	Query type description	string	32
qtypeval		uint16	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcport	Source Port	uint16	5
sscname		string	256
subtype	Log Subtype	string	20
time	Time	string	8
translationid		uint32	10
type	Log Type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual Domain Name	string	32
xid	Transaction ID	uint16	5

54400 - LOG_ID_DNS_URL_FILTER_BLOCK

Message ID: 54400

Message Description: LOG_ID_DNS_URL_FILTER_BLOCK

Message Meaning: Domain blocked because it is in the domain-filter list

Type: DNS

Category: DNS-RESPONSE

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by DNS filter	string	16
botnetdomain	Botnet domain name	string	256
botnetip	Botnet IP address	ip	39
cat	DNS category ID	uint8	3
catdesc	DNS category description	string	64
date	Date	string	10
devid		string	16
domainfilteridx	Domain filter ID	uint8	3
domainfilterlist	Domain filter name	string	512
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
error	DNS filter error message	string	256
eventtime		uint64	20
eventtype		string	32
exchange	Mail Exchanges from DNS response answer section	string	256
fctuid		string	32
group	User group name	string	64
ipaddr	IP addresses from DNS response answer section	string	512
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Profile name for DNS filter	string	64
proto	Protocol number	uint8	3
qclass	Query class	string	32
qname	Query domain name	string	256
qtype	Query type description	string	32
qtypeval		uint16	5

Log Field Name	Description	Data Type	Length
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcport	Source Port	uint16	5
sscname		string	256
subtype	Log Subtype	string	20
time	Time	string	8
translationid		uint32	10
type	Log Type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual Domain Name	string	32
xid	Transaction ID	uint16	5

54401 - LOG_ID_DNS_URL_FILTER_ALLOW

Message ID: 54401

Message Description: LOG_ID_DNS_URL_FILTER_ALLOW

Message Meaning: Domain allowed because it is in the domain-filter list

Type: DNS

Category: DNS-RESPONSE

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action performed by DNS filter	string	16
botnetdomain	Botnet domain name	string	256
botnetip	Botnet IP address	ip	39

Log Field Name	Description	Data Type	Length
cat	DNS category ID	uint8	3
catdesc	DNS category description	string	64
date	Date	string	10
devid		string	16
domainfilteridx	Domain filter ID	uint8	3
domainfilterlist	Domain filter name	string	512
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
error	DNS filter error message	string	256
eventtime		uint64	20
eventtype		string	32
exchange	Mail Exchanges from DNS response answer section	string	256
fctuid		string	32
group	User group name	string	64
ipaddr	IP addresses from DNS response answer section	string	512
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Profile name for DNS filter	string	64
proto	Protocol number	uint8	3
qclass	Query class	string	32
qname	Query domain name	string	256
qtype	Query type description	string	32
qtypeval		uint16	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32

Log Field Name	Description	Data Type	Length
srcintfrole		string	10
srcip	Source IP	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcport	Source Port	uint16	5
sscname		string	256
subtype	Log Subtype	string	20
time	Time	string	8
translationid		uint32	10
type	Log Type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual Domain Name	string	32
xid	Transaction ID	uint16	5

54600 - LOG_ID_DNS_BOTNET_IP

Message ID: 54600

Message Description: LOG_ID_DNS_BOTNET_IP

Message Meaning: Domain blocked by DNS botnet C&C (IP)

Type: DNS

Category: DNS-RESPONSE

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by DNS filter	string	16
botnetdomain	Botnet domain name	string	256
botnetip	Botnet IP address	ip	39
cat	DNS category ID	uint8	3
catdesc	DNS category description	string	64
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid		string	16
domainfilteridx	Domain filter ID	uint8	3
domainfilterlist	Domain filter name	string	512
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
error	DNS filter error message	string	256
eventtime		uint64	20
eventtype		string	32
exchange	Mail Exchanges from DNS response answer section	string	256
fctuid		string	32
group	User group name	string	64
ipaddr	IP addresses from DNS response answer section	string	512
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Profile name for DNS filter	string	64
proto	Protocol number	uint8	3
qclass	Query class	string	32
qname	Query domain name	string	256
qtype	Query type description	string	32
qtypeval		uint16	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcmac	MAC address associated with the Source IP	string	17

Log Field Name	Description	Data Type	Length
srcport	Source Port	uint16	5
sscname		string	256
subtype	Log Subtype	string	20
time	Time	string	8
translationid		uint32	10
type	Log Type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual Domain Name	string	32
xid	Transaction ID	uint16	5

54601 - LOG_ID_DNS_BOTNET_DOMAIN

Message ID: 54601

Message Description: LOG_ID_DNS_BOTNET_DOMAIN

Message Meaning: Domain blocked by DNS botnet C&C (Domain)

Type: DNS

Category: DNS-RESPONSE

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by DNS filter	string	16
botnetdomain	Botnet domain name	string	256
botnetip	Botnet IP address	ip	39
cat	DNS category ID	uint8	3
catdesc	DNS category description	string	64
date	Date	string	10
devid		string	16
domainfilteridx	Domain filter ID	uint8	3
domainfilterlist	Domain filter name	string	512

Log Field Name	Description	Data Type	Length
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
error	DNS filter error message	string	256
eventtime		uint64	20
eventtype		string	32
exchange	Mail Exchanges from DNS response answer section	string	256
fctuid		string	32
group	User group name	string	64
ipaddr	IP addresses from DNS response answer section	string	512
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Profile name for DNS filter	string	64
proto	Protocol number	uint8	3
qclass	Query class	string	32
qname	Query domain name	string	256
qtype	Query type description	string	32
qtypeval		uint16	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcport	Source Port	uint16	5
sscname		string	256
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
translationid		uint32	10
type	Log Type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual Domain Name	string	32
xid	Transaction ID	uint16	5

54800 - LOG_ID_DNS_FTGD_WARNING

Message ID: 54800

Message Description: LOG_ID_DNS_FTGD_WARNING

Message Meaning: FortiGuard rating error warning

Type: DNS

Category: DNS-RESPONSE

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by DNS filter	string	16
botnetdomain	Botnet domain name	string	256
botnetip	Botnet IP address	ip	39
cat	DNS category ID	uint8	3
catdesc	DNS category description	string	64
date	Date	string	10
devid		string	16
domainfilteridx	Domain filter ID	uint8	3
domainfilterlist	Domain filter name	string	512
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39

Log Field Name	Description	Data Type	Length
dstport	Destination Port	uint16	5
error	DNS filter error message	string	256
eventtime		uint64	20
eventtype		string	32
exchange	Mail Exchanges from DNS response answer section	string	256
fctuid		string	32
group	User group name	string	64
ipaddr	IP addresses from DNS response answer section	string	512
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Profile name for DNS filter	string	64
proto	Protocol number	uint8	3
qclass	Query class	string	32
qname	Query domain name	string	256
qtype	Query type description	string	32
qtypeval		uint16	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcport	Source Port	uint16	5
sscname		string	256
subtype	Log Subtype	string	20
time	Time	string	8
translationid		uint32	10
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual Domain Name	string	32
xid	Transaction ID	uint16	5

54801 - LOG_ID_DNS_FTGD_ERROR

Message ID: 54801

Message Description: LOG_ID_DNS_FTGD_ERROR

Message Meaning: FortiGuard rating error occurred

Type: DNS

Category: DNS-RESPONSE

Severity: Error

Log Field Name	Description	Data Type	Length
action	Security action performed by DNS filter	string	16
botnetdomain	Botnet domain name	string	256
botnetip	Botnet IP address	ip	39
cat	DNS category ID	uint8	3
catdesc	DNS category description	string	64
date	Date	string	10
devid		string	16
domainfilteridx	Domain filter ID	uint8	3
domainfilterlist	Domain filter name	string	512
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
error	DNS filter error message	string	256
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
eventtype		string	32
exchange	Mail Exchanges from DNS response answer section	string	256
fctuid		string	32
group	User group name	string	64
ipaddr	IP addresses from DNS response answer section	string	512
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Profile name for DNS filter	string	64
proto	Protocol number	uint8	3
qclass	Query class	string	32
qname	Query domain name	string	256
qtype	Query type description	string	32
qtypeval		uint16	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcport	Source Port	uint16	5
sscname		string	256
subtype	Log Subtype	string	20
time	Time	string	8
translationid		uint32	10
type	Log Type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66

Log Field Name	Description	Data Type	Length
user	User name	string	256
vd	Virtual Domain Name	string	32
xid	Transaction ID	uint16	5

54802 - LOG_ID_DNS_FTGD_CAT_ALLOW

Message ID: 54802

Message Description: LOG_ID_DNS_FTGD_CAT_ALLOW

Message Meaning: Domain is monitored

Type: DNS

Category: DNS-RESPONSE

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by DNS filter	string	16
botnetdomain	Botnet domain name	string	256
botnetip	Botnet IP address	ip	39
cat	DNS category ID	uint8	3
catdesc	DNS category description	string	64
date	Date	string	10
devid		string	16
domainfilteridx	Domain filter ID	uint8	3
domainfilterlist	Domain filter name	string	512
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
error	DNS filter error message	string	256
eventtime		uint64	20
eventtype		string	32
exchange	Mail Exchanges from DNS response answer section	string	256
fctuid		string	32

Log Field Name	Description	Data Type	Length
group	User group name	string	64
ipaddr	IP addresses from DNS response answer section	string	512
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Profile name for DNS filter	string	64
proto	Protocol number	uint8	3
qclass	Query class	string	32
qname	Query domain name	string	256
qtype	Query type description	string	32
qtypeval		uint16	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcport	Source Port	uint16	5
sscname		string	256
subtype	Log Subtype	string	20
time	Time	string	8
translationid		uint32	10
type	Log Type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual Domain Name	string	32
xid	Transaction ID	uint16	5

54803 - LOG_ID_DNS_FTGD_CAT_BLOCK

Message ID: 54803

Message Description: LOG_ID_DNS_FTGD_CAT_BLOCK

Message Meaning: Domain belongs to a denied category in policy

Type: DNS

Category: DNS-RESPONSE

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by DNS filter	string	16
botnetdomain	Botnet domain name	string	256
botnetip	Botnet IP address	ip	39
cat	DNS category ID	uint8	3
catdesc	DNS category description	string	64
date	Date	string	10
devid		string	16
domainfilteridx	Domain filter ID	uint8	3
domainfilterlist	Domain filter name	string	512
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
error	DNS filter error message	string	256
eventtime		uint64	20
eventtype		string	32
exchange	Mail Exchanges from DNS response answer section	string	256
fctuid		string	32
group	User group name	string	64
ipaddr	IP addresses from DNS response answer section	string	512
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512

Log Field Name	Description	Data Type	Length
policyid	Policy ID	uint32	10
profile	Profile name for DNS filter	string	64
proto	Protocol number	uint8	3
qclass	Query class	string	32
qname	Query domain name	string	256
qtype	Query type description	string	32
qtypeval		uint16	5
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcport	Source Port	uint16	5
sscname		string	256
subtype	Log Subtype	string	20
time	Time	string	8
translationid		uint32	10
type	Log Type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual Domain Name	string	32
xid	Transaction ID	uint16	5

54804 - LOG_ID_DNS_SAFE_SEARCH

Message ID: 54804

Message Description: LOG_ID_DNS_SAFE_SEARCH

Message Meaning: DNS Safe Search enforced

Type: DNS

Category: DNS-RESPONSE

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by DNS filter	string	16
botnetdomain	Botnet domain name	string	256
botnetip	Botnet IP address	ip	39
cat	DNS category ID	uint8	3
catdesc	DNS category description	string	64
date	Date	string	10
devid		string	16
domainfilteridx	Domain filter ID	uint8	3
domainfilterlist	Domain filter name	string	512
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
error	DNS filter error message	string	256
eventtime		uint64	20
eventtype		string	32
exchange	Mail Exchanges from DNS response answer section	string	256
fctuid		string	32
group	User group name	string	64
ipaddr	IP addresses from DNS response answer section	string	512
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Profile name for DNS filter	string	64
proto	Protocol number	uint8	3
qclass	Query class	string	32
qname	Query domain name	string	256
qtype	Query type description	string	32
qtypeval		uint16	5

Log Field Name	Description	Data Type	Length
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcport	Source Port	uint16	5
sscname		string	256
subtype	Log Subtype	string	20
time	Time	string	8
translationid		uint32	10
type	Log Type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual Domain Name	string	32
xid	Transaction ID	uint16	5

Email

20480 - LOGID_ANTISPAM_EMAIL_SMTP_NOTIF

Message ID: 20480

Message Description: LOGID_ANTISPAM_EMAIL_SMTP_NOTIF

Message Meaning: SMTP warning

Type: Email

Category: SMTP

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8

Log Field Name	Description	Data Type	Length
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
authserver		string	32
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	4096
date	Date	string	10
devid		string	16
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16

Log Field Name	Description	Data Type	Length
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

20481 - LOGID_ANTISPAM_EMAIL_SMTP_BWORD_NOTIF

Message ID: 20481

Message Description: LOGID_ANTISPAM_EMAIL_SMTP_BWORD_NOTIF

Message Meaning: SMTP warning

Type: Email

Category: SMTP

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
authserver		string	32
banword	Banned word	string	128

Log Field Name	Description	Data Type	Length
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	4096
date	Date	string	10
devid		string	16
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39

Log Field Name	Description	Data Type	Length
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

20482 - LOGID_ANTISPAM_EMAIL_POP3_NOTIF

Message ID: 20482

Message Description: LOGID_ANTISPAM_EMAIL_POP3_NOTIF

Message Meaning: POP3 warning

Type: Email

Category: POP3

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
authserver		string	32
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	4096
date	Date	string	10
devid		string	16

Log Field Name	Description	Data Type	Length
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

20483 - LOGID_ANTISPAM_EMAIL_POP3_BWORD_NOTIF

Message ID: 20483

Message Description: LOGID_ANTISPAM_EMAIL_POP3_BWORD_NOTIF

Message Meaning: POP3 notice

Type: Email

Category: POP3

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
authserver		string	32
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	4096
date	Date	string	10
devid		string	16
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrold		string	10
dstip	Destination IP	ip	39

Log Field Name	Description	Data Type	Length
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5

Log Field Name	Description	Data Type	Length
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

20484 - LOGID_ANTISPAM_EMAIL_IMAP_NOTIF

Message ID: 20484

Message Description: LOGID_ANTISPAM_EMAIL_IMAP_NOTIF

Message Meaning: IMAP notice

Type: Email

Category: IMAP

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
authserver		string	32
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	4096
date	Date	string	10
devid		string	16
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32

Log Field Name	Description	Data Type	Length
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

20485 - LOGID_ANTISPAM_ENDPOINT_FILTER_WARNING

Message ID: 20485

Message Description: LOGID_ANTISPAM_ENDPOINT_FILTER_WARNING

Message Meaning: Endpoint filter warning

Type: Email

Category: CARRIER-ENDPOINT-FILTER

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
authserver		string	32
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	4096
date	Date	string	10
devid		string	16
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512

Log Field Name	Description	Data Type	Length
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

20486 - LOGID_ANTISPAM_ENDPOINT_FILTER_NOTIF

Message ID: 20486

Message Description: LOGID_ANTISPAM_ENDPOINT_FILTER_NOTIF

Message Meaning: Endpoint filter notice

Type: Email

Category: CARRIER-ENDPOINT-FILTER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
authserver		string	32
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	4096
date	Date	string	10
devid		string	16
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
service	Service name	string	36

Log Field Name	Description	Data Type	Length
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

20487 - LOGID_ANTISPAM_ENDPOINT_MM7_WARNING

Message ID: 20487

Message Description: LOGID_ANTISPAM_ENDPOINT_MM7_WARNING

Message Meaning: MM7 warning

Type: Email

Category: CARRIER-ENDPOINT-FILTER

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3

Log Field Name	Description	Data Type	Length
authserver		string	32
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	4096
date	Date	string	10
devid		string	16
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcdomain		string	255
srcintf	Source Interface	string	64

Log Field Name	Description	Data Type	Length
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

20488 - LOGID_ANTISPAM_ENDPOINT_MM7_NOTIF

Message ID: 20488

Message Description: LOGID_ANTISPAM_ENDPOINT_MM7_NOTIF

Message Meaning: MM7 notice

Type: Email

Category: CARRIER-ENDPOINT-FILTER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
authserver		string	32
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	4096

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid		string	16
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256

Log Field Name	Description	Data Type	Length
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

20489 - LOGID_ANTISPAM_ENDPOINT_MM1_WARNING

Message ID: 20489

Message Description: LOGID_ANTISPAM_ENDPOINT_MM1_WARNING

Message Meaning: MM1 warning

Type: Email

Category: CARRIER-ENDPOINT-FILTER

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
authserver		string	32
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	4096
date	Date	string	10
devid		string	16
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64

Log Field Name	Description	Data Type	Length
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512

Log Field Name	Description	Data Type	Length
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

20490 - LOGID_ANTISPAM_ENDPOINT_MM1_NOTIF

Message ID: 20490

Message Description: LOGID_ANTISPAM_ENDPOINT_MM1_NOTIF

Message Meaning: MM1 notice

Type: Email

Category: CARRIER-ENDPOINT-FILTER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
authserver		string	32
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	4096
date	Date	string	10
devid		string	16
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66

Log Field Name	Description	Data Type	Length
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

20491 - LOGID_ANTISPAM_EMAIL_IMAP_BWORD_NOTIF

Message ID: 20491

Message Description: LOGID_ANTISPAM_EMAIL_IMAP_BWORD_NOTIF

Message Meaning: IMAP banned word notice

Type: Email

Category: IMAP

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
authserver		string	32
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	4096
date	Date	string	10
devid		string	16
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512

Log Field Name	Description	Data Type	Length
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

20492 - LOGID_ANTISPAM_MM1_FLOOD_WARNING

Message ID: 20492

Message Description: LOGID_ANTISPAM_MM1_FLOOD_WARNING

Message Meaning: MM1 flood detection warning

Type: Email

Category: MASS-MMS

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
authserver		string	32
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	4096
date	Date	string	10
devid		string	16
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512

Log Field Name	Description	Data Type	Length
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

20493 - LOGID_ANTISPAM_MM1_FLOOD_NOTIF

Message ID: 20493

Message Description: LOGID_ANTISPAM_MM1_FLOOD_NOTIF

Message Meaning: MM1 flood detection notice

Type: Email

Category: MASS-MMS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
authserver		string	32
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	4096
date	Date	string	10
devid		string	16
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
service	Service name	string	36

Log Field Name	Description	Data Type	Length
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

20494 - LOGID_ANTISPAM_MM4_FLOOD_WARNING

Message ID: 20494

Message Description: LOGID_ANTISPAM_MM4_FLOOD_WARNING

Message Meaning: MM4 flood detection warning

Type: Email

Category: MASS-MMS

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3

Log Field Name	Description	Data Type	Length
authserver		string	32
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	4096
date	Date	string	10
devid		string	16
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcdomain		string	255
srcintf	Source Interface	string	64

Log Field Name	Description	Data Type	Length
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

20495 - LOGID_ANTISPAM_MM4_FLOOD_NOTIF

Message ID: 20495

Message Description: LOGID_ANTISPAM_MM4_FLOOD_NOTIF

Message Meaning: MM4 flood detection notice

Type: Email

Category: MASS-MMS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
authserver		string	32
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	4096

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid		string	16
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256

Log Field Name	Description	Data Type	Length
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

20496 - LOGID_ANTISPAM_MM1_DUPE_WARNING

Message ID: 20496

Message Description: LOGID_ANTISPAM_MM1_DUPE_WARNING

Message Meaning: MM1 duplicate detection warning

Type: Email

Category: MASS-MMS

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
authserver		string	32
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	4096
date	Date	string	10
devid		string	16
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64

Log Field Name	Description	Data Type	Length
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512

Log Field Name	Description	Data Type	Length
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

20497 - LOGID_ANTISPAM_MM1_DUPE_NOTIF

Message ID: 20497

Message Description: LOGID_ANTISPAM_MM1_DUPE_NOTIF

Message Meaning: MM1 duplicate detection notice

Type: Email

Category: MASS-MMS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
authserver		string	32
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	4096
date	Date	string	10
devid		string	16
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66

Log Field Name	Description	Data Type	Length
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

20498 - LOGID_ANTISPAM_MM4_DUPE_WARNING

Message ID: 20498

Message Description: LOGID_ANTISPAM_MM4_DUPE_WARNING

Message Meaning: MM4 duplicate detection warning

Type: Email

Category: MASS-MMS

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
authserver		string	32
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	4096
date	Date	string	10
devid		string	16
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512

Log Field Name	Description	Data Type	Length
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

20499 - LOGID_ANTISPAM_MM4_DUPE_NOTIF

Message ID: 20499

Message Description: LOGID_ANTISPAM_MM4_DUPE_NOTIF

Message Meaning: MM4 duplicate detection notice

Type: Email

Category: MASS-MMS

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
authserver		string	32
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	4096
date	Date	string	10
devid		string	16
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512

Log Field Name	Description	Data Type	Length
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

20500 - LOGID_ANTISPAM_EMAIL_MSN_NOTIF

Message ID: 20500

Message Description: LOGID_ANTISPAM_EMAIL_MSN_NOTIF

Message Meaning: MSN Hotmail email message

Type: Email

Category: MSN-HOTMAIL

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
authserver		string	32
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	4096
date	Date	string	10
devid		string	16
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
service	Service name	string	36

Log Field Name	Description	Data Type	Length
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

20501 - LOGID_ANTISPAM_EMAIL_YAHOO_NOTIF

Message ID: 20501

Message Description: LOGID_ANTISPAM_EMAIL_YAHOO_NOTIF

Message Meaning: Yahoo! email message

Type: Email

Category: YAHOO-MAIL

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3

Log Field Name	Description	Data Type	Length
authserver		string	32
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	4096
date	Date	string	10
devid		string	16
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcdomain		string	255
srcintf	Source Interface	string	64

Log Field Name	Description	Data Type	Length
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

20502 - LOGID_ANTISPAM_EMAIL_GOOGLE_NOTIF

Message ID: 20502

Message Description: LOGID_ANTISPAM_EMAIL_GOOGLE_NOTIF

Message Meaning: Gmail email message

Type: Email

Category: GMAIL

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
authserver		string	32
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	4096

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid		string	16
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256

Log Field Name	Description	Data Type	Length
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

20503 - LOGID_EMAIL_SMTP_GENERAL_NOTIF

Message ID: 20503

Message Description: LOGID_EMAIL_SMTP_GENERAL_NOTIF

Message Meaning: SMTP warning

Type: Email

Category: SMTP

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachment	string	3
authserver		string	32
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	4096
date	Date	string	10
devid		string	16
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64

Log Field Name	Description	Data Type	Length
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512

Log Field Name	Description	Data Type	Length
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

20504 - LOGID_EMAIL_POP3_GENERAL_NOTIF

Message ID: 20504

Message Description: LOGID_EMAIL_POP3_GENERAL_NOTIF

Message Meaning: POP3 warning

Type: Email

Category: POP3

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
authserver		string	32
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	4096
date	Date	string	10
devid		string	16
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66

Log Field Name	Description	Data Type	Length
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

20505 - LOGID_EMAIL_IMAP_GENERAL_NOTIF

Message ID: 20505

Message Description: LOGID_EMAIL_IMAP_GENERAL_NOTIF

Message Meaning: IMAP notice

Type: Email

Category: IMAP

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
authserver		string	32
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	4096
date	Date	string	10
devid		string	16
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512

Log Field Name	Description	Data Type	Length
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

20506 - LOGID_EMAIL_MAPI_GENERAL_NOTIF

Message ID: 20506

Message Description: LOGID_EMAIL_MAPI_GENERAL_NOTIF

Message Meaning: MAPI notice

Type: Email

Category: MAPI

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
authserver		string	32
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	4096
date	Date	string	10
devid		string	16
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512

Log Field Name	Description	Data Type	Length
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

20507 - LOGID_ANTISPAM_EMAIL_MAPI_BWORD_NOTIF

Message ID: 20507

Message Description: LOGID_ANTISPAM_EMAIL_MAPI_BWORD_NOTIF

Message Meaning: MAPI banned word notice

Type: Email

Category: MAPI

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3
authserver		string	32
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	4096
date	Date	string	10
devid		string	16
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
service	Service name	string	36

Log Field Name	Description	Data Type	Length
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

20508 - LOGID_ANTISPAM_EMAIL_MAPI_NOTIF

Message ID: 20508

Message Description: LOGID_ANTISPAM_EMAIL_MAPI_NOTIF

Message Meaning: MAPI email message

Type: Email

Category: MAPI

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action of the email filter	string	8
agent	User agent - eg. agent="Mozilla/5.0"	string	64
attachment	The flag for email attachement	string	3

Log Field Name	Description	Data Type	Length
authserver		string	32
banword	Banned word	string	128
cc	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	4096
date	Date	string	10
devid		string	16
direction	Direction of packets	string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Email Filter event type	string	32
fctuid		string	32
fortiguardresp		string	512
from	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	128
group	User group name	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log Message	string	512
policyid	Policy ID	uint32	10
profile	Email Filter profile name	string	64
proto	Protocol number	uint8	3
recipient	Email addresses from the SMTP envelope	string	512
sender	Email addresses from the SMTP envelope	string	128
service	Service name	string	36
sessionid	Session ID	uint32	10
size	Email size in Bytes?	string	16
srcdomain		string	255
srcintf	Source Interface	string	64

Log Field Name	Description	Data Type	Length
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subject	The subject title of the email message	string	256
subtype	Log subtype	string	20
time	Time	string	8
to	Email address(es) from the Email Headers (IMAP/POP3/SMTP)	string	512
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

20509 - LOGID_ANTISPAM_FTGD_ERR

Message ID: 20509

Message Description: LOGID_ANTISPAM_FTGD_ERR

Message Meaning: FortiGuard error message

Type: Email

Category: FTGD_ERR

Severity: Information

Log Field Name	Description	Data Type	Length
action		string	8
agent		string	64
attachment		string	3
authserver		string	32
banword		string	128
cc		string	4096
date		string	10

Log Field Name	Description	Data Type	Length
devid		string	16
direction		string	8
dstintf		string	64
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
fortiguardresp		string	512
from		string	128
group		string	64
level		string	11
logid		string	10
msg		string	512
policyid		uint32	10
profile		string	64
proto		uint8	3
recipient		string	512
sender		string	128
service		string	36
sessionid		uint32	10
size		string	16
srcdomain		string	255
srcintf		string	64
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subject		string	256
subtype		string	20

Log Field Name	Description	Data Type	Length
time		string	8
to		string	512
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32
vrf		uint8	3

Event

20002 - LOG_ID_DOMAIN_UNRESOLVABLE

Message ID: 20002

Message Description: LOG_ID_DOMAIN_UNRESOLVABLE

Message Meaning: Domain name of alert email sender unresolvable

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096

20003 - LOG_ID_MAIL_SENT_FAIL

Message ID: 20003

Message Description: LOG_ID_MAIL_SENT_FAIL

Message Meaning: Alert email send status failed

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
status	Status	string	23

Log Field Name	Description	Data Type	Length
msg	Message Text	string	4096
count	Count	uint32	10

20004 - LOG_ID_POLICY_TOO_BIG

Message ID: 20004

Message Description: LOG_ID_POLICY_TOO_BIG

Message Meaning: Policy too big for installation

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
status	Status	string	23
msg	Message Text	string	4096

20005 - LOG_ID_PPP_LINK_UP

Message ID: 20005

Message Description: LOG_ID_PPP_LINK_UP

Message Meaning: Modem PPP link up

Type: Event**Category:** SYSTEM**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20006 - LOG_ID_PPP_LINK_DOWN

Message ID: 20006**Message Description:** LOG_ID_PPP_LINK_DOWN**Message Meaning:** Modem PPP link down**Type:** Event**Category:** SYSTEM**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20007 - LOG_ID_SOCKET_EXHAUSTED

Message ID: 20007

Message Description: LOG_ID_SOCKET_EXHAUSTED

Message Meaning: NAT port exhausted

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
status	Status	string	23
msg	Message Text	string	4096
service	Name of Service	string	64
proto	Protocol Number	uint8	3

Log Field Name	Description	Data Type	Length
vrf		uint8	3
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
nat	NAT IP Address	ip	39
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5

20008 - LOG_ID_POLICY6_TOO_BIG

Message ID: 20008

Message Description: LOG_ID_POLICY6_TOO_BIG

Message Meaning: IPv6 policy too big for installation

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
status	Status	string	23
msg	Message Text	string	4096

20010 - LOG_ID_KERNEL_ERROR

Message ID: 20010

Message Description: LOG_ID_KERNEL_ERROR

Message Meaning: Kernel error

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20016 - LOG_ID_MODEM_EXCEED_REDIAL_COUNT

Message ID: 20016

Message Description: LOG_ID_MODEM_EXCEED_REDIAL_COUNT

Message Meaning: Modem exceeded redial limit

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20017 - LOG_ID_MODEM_FAIL_TO_OPEN

Message ID: 20017

Message Description: LOG_ID_MODEM_FAIL_TO_OPEN

Message Meaning: Modem failed to open

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20020 - LOG_ID_MODEM_USB_DETECTED

Message ID: 20020

Message Description: LOG_ID_MODEM_USB_DETECTED

Message Meaning: USB modem detected

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20021 - LOG_ID_MAIL_RESENT

Message ID: 20021

Message Description: LOG_ID_MAIL_RESENT

Message Meaning: Alert email resent

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096
count	Count	uint32	10

20022 - LOG_ID_MODEM_USB_REMOVED

Message ID: 20022

Message Description: LOG_ID_MODEM_USB_REMOVED

Message Meaning: USB modem removed

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20023 - LOG_ID_MODEM_USBLTE_DETECTED

Message ID: 20023

Message Description: LOG_ID_MODEM_USBLTE_DETECTED

Message Meaning: USB LTE modem detected

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20024 - LOG_ID_MODEM_USBLTE_REMOVED

Message ID: 20024

Message Description: LOG_ID_MODEM_USBLTE_REMOVED

Message Meaning: USB LTE modem removed

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20025 - LOG_ID_REPORTD_REPORT_SUCCESS

Message ID: 20025

Message Description: LOG_ID_REPORTD_REPORT_SUCCESS

Message Meaning: Report generated successfully

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096
file	File Name for Generated Report?	string	256
filesize	Report File Size in Bytes	uint32	10
datarange	data range for reports	string	50
reporttype	Report Type	string	20
processtime	process time for reports	uint32	10

20026 - LOG_ID_REPORTD_REPORT_FAILURE

Message ID: 20026

Message Description: LOG_ID_REPORTD_REPORT_FAILURE

Message Meaning: Report generation failed

Type: Event

Category: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20027 - LOG_ID_REPORT_DEL_OLD_REC

Message ID: 20027

Message Description: LOG_ID_REPORT_DEL_OLD_REC

Message Meaning: Outdated report files deleted

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20028 - LOG_ID_REPORT_RECREATE_DB

Message ID: 20028

Message Description: LOG_ID_REPORT_RECREATE_DB

Message Meaning: Report database recreated

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20031 - LOG_ID_RAD_OUT_OF_MEM

Message ID: 20031**Message Description:** LOG_ID_RAD_OUT_OF_MEM**Message Meaning:** RADVD out of memory**Type:** Event**Category:** SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20032 - LOG_ID_RAD_NOT_FOUND

Message ID: 20032

Message Description: LOG_ID_RAD_NOT_FOUND

Message Meaning: RADVD interface not found

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20033 - LOG_ID_RAD_MOBILE_IPV6

Message ID: 20033

Message Description: LOG_ID_RAD_MOBILE_IPV6

Message Meaning: RADVD mobile IPv6 extensions used

Type: Event

Category: SYSTEM**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20034 - LOG_ID_RAD_IPV6_OUT_OF_RANGE

Message ID: 20034**Message Description:** LOG_ID_RAD_IPV6_OUT_OF_RANGE**Message Meaning:** RADVD mobile IPv6 MinRtrAdvInterval out of range**Type:** Event**Category:** SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20035 - LOG_ID_RAD_MIN_OUT_OF_RANGE

Message ID: 20035

Message Description: LOG_ID_RAD_MIN_OUT_OF_RANGE

Message Meaning: RADVD MinRtrAdvInterval out of range

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20036 - LOG_ID_RAD_MAX_OUT_OF_RANGE

Message ID: 20036

Message Description: LOG_ID_RAD_MAX_OUT_OF_RANGE

Message Meaning: RADVD mobile IPv6 MaxRtrAdvInterval out of range

Type: Event

Category: SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20037 - LOG_ID_RAD_MAX_ADV_OUT_OF_RANGE

Message ID: 20037**Message Description:** LOG_ID_RAD_MAX_ADV_OUT_OF_RANGE**Message Meaning:** RADVD MaxRtrAdvInterval out of range**Type:** Event**Category:** SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20039 - LOG_ID_RAD_MTU_TOO_SMALL

Message ID: 20039

Message Description: LOG_ID_RAD_MTU_TOO_SMALL

Message Meaning: RADVD AdvLinkMTU too small

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20040 - LOG_ID_RAD_TIME_TOO_SMALL

Message ID: 20040

Message Description: LOG_ID_RAD_TIME_TOO_SMALL

Message Meaning: RADVD AdvReachableTime too small

Type: Event

Category: SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20041 - LOG_ID_RAD_HOP_OUT_OF_RANGE

Message ID: 20041**Message Description:** LOG_ID_RAD_HOP_OUT_OF_RANGE**Message Meaning:** RADVD AdvCurHopLimit too big**Type:** Event**Category:** SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20042 - LOG_ID_RAD_DFT_HOP_OUT_OF_RANGE

Message ID: 20042

Message Description: LOG_ID_RAD_DFT_HOP_OUT_OF_RANGE

Message Meaning: RADVD AdvCurHopLimit out of range

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20043 - LOG_ID_RAD_AGENT_OUT_OF_RANGE

Message ID: 20043

Message Description: LOG_ID_RAD_AGENT_OUT_OF_RANGE

Message Meaning: RADVD HomeAgentLifetime out of range

Type: Event

Category: SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20044 - LOG_ID_RAD_AGENT_FLAG_NOT_SET

Message ID: 20044**Message Description:** LOG_ID_RAD_AGENT_FLAG_NOT_SET**Message Meaning:** RADVD AdvHomeAgentFlag not set**Type:** Event**Category:** SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20045 - LOG_ID_RAD_PREFIX_TOO_LONG

Message ID: 20045

Message Description: LOG_ID_RAD_PREFIX_TOO_LONG

Message Meaning: RADVD invalid prefix length

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20046 - LOG_ID_RAD_PREF_TIME_TOO_SMALL

Message ID: 20046

Message Description: LOG_ID_RAD_PREF_TIME_TOO_SMALL

Message Meaning: RADVD AdvValidLifetime less than AdvPreferredLifetime

Type: Event

Category: SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20047 - LOG_ID_RAD_FAIL_IPV6_SOCKET

Message ID: 20047**Message Description:** LOG_ID_RAD_FAIL_IPV6_SOCKET**Message Meaning:** RADVD failed to create an IPv6 socket**Type:** Event**Category:** SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20048 - LOG_ID_RAD_FAIL_OPT_IPV6_PKTINFO

Message ID: 20048

Message Description: LOG_ID_RAD_FAIL_OPT_IPV6_PKTINFO

Message Meaning: RADVD failed to set IPv6 packet info

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20049 - LOG_ID_RAD_FAIL_OPT_IPV6_CHECKSUM

Message ID: 20049

Message Description: LOG_ID_RAD_FAIL_OPT_IPV6_CHECKSUM

Message Meaning: RADVD failed to set IPv6 checksum

Type: Event

Category: SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20050 - LOG_ID_RAD_FAIL_OPT_IPV6_UNICAST_HOPS

Message ID: 20050**Message Description:** LOG_ID_RAD_FAIL_OPT_IPV6_UNICAST_HOPS**Message Meaning:** RADVD failed to set IPv6 unicast hops**Type:** Event**Category:** SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20051 - LOG_ID_RAD_FAIL_OPT_IPV6_MULTICAST_HOPS

Message ID: 20051

Message Description: LOG_ID_RAD_FAIL_OPT_IPV6_MULTICAST_HOPS

Message Meaning: RADVD failed to set IPv6 multicast hops

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20052 - LOG_ID_RAD_FAIL_OPT_IPV6_HOPLIMIT

Message ID: 20052

Message Description: LOG_ID_RAD_FAIL_OPT_IPV6_HOPLIMIT

Message Meaning: RADVD failed to set IPv6 hop limit

Type: Event

Category: SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20053 - LOG_ID_RAD_FAIL_OPT_IPPROTO_ICMPV6

Message ID: 20053**Message Description:** LOG_ID_RAD_FAIL_OPT_IPPROTO_ICMPV6**Message Meaning:** RADVD failed to set ICMPv6 filter**Type:** Event**Category:** SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20054 - LOG_ID_RAD_EXIT_BY_SIGNAL

Message ID: 20054

Message Description: LOG_ID_RAD_EXIT_BY_SIGNAL

Message Meaning: RADVD exited due to received signal

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20055 - LOG_ID_RAD_FAIL_CMDB_QUERY

Message ID: 20055

Message Description: LOG_ID_RAD_FAIL_CMDB_QUERY

Message Meaning: RADVD interface query creation failed

Type: Event

Category: SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20056 - LOG_ID_RAD_FAIL_CMDB_FOR_EACH

Message ID: 20056**Message Description:** LOG_ID_RAD_FAIL_CMDB_FOR_EACH**Message Meaning:** RADVD query error**Type:** Event**Category:** SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20057 - LOG_ID_RAD_FAIL_FIND_VIRT_INTF

Message ID: 20057

Message Description: LOG_ID_RAD_FAIL_FIND_VIRT_INTF

Message Meaning: RADVD virtual interface not found

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20058 - LOG_ID_RAD_UNLOAD_INTF

Message ID: 20058

Message Description: LOG_ID_RAD_UNLOAD_INTF

Message Meaning: RADVD unloaded interface

Type: Event

Category: SYSTEM**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20061 - LOG_ID_RAD_INV_ICMPV6_TYPE

Message ID: 20061**Message Description:** LOG_ID_RAD_INV_ICMPV6_TYPE**Message Meaning:** RADVD received unwanted ICMPv6 packet**Type:** Event**Category:** SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20062 - LOG_ID_RAD_INV_ICMPV6_RA_LEN

Message ID: 20062

Message Description: LOG_ID_RAD_INV_ICMPV6_RA_LEN

Message Meaning: RADVD received ICMPv6 RA packet with invalid length

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20063 - LOG_ID_RAD_ICMPV6_NO_SRC_ADDR

Message ID: 20063

Message Description: LOG_ID_RAD_ICMPV6_NO_SRC_ADDR

Message Meaning: RADVD received ICMPv6 RA packet with non-link local source address

Type: Event

Category: SYSTEM**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20064 - LOG_ID_RAD_INV_ICMPV6_RS_LEN

Message ID: 20064**Message Description:** LOG_ID_RAD_INV_ICMPV6_RS_LEN**Message Meaning:** RADVD received ICMPv6 RS packet with invalid length**Type:** Event**Category:** SYSTEM**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20065 - LOG_ID_RAD_INV_ICMPV6_CODE

Message ID: 20065

Message Description: LOG_ID_RAD_INV_ICMPV6_CODE

Message Meaning: RADVD received ICMPv6 RS/RA packet with invalid code

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20066 - LOG_ID_RAD_INV_ICMPV6_HOP

Message ID: 20066

Message Description: LOG_ID_RAD_INV_ICMPV6_HOP

Message Meaning: RADVD received ICMPv6 RS/RA packet with invalid hop limit

Type: Event

Category: SYSTEM**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20067 - LOG_ID_RAD_MISMATCH_HOP

Message ID: 20067**Message Description:** LOG_ID_RAD_MISMATCH_HOP**Message Meaning:** RADVD local AdvCurHopLimit disagrees with remote site**Type:** Event**Category:** SYSTEM**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20068 - LOG_ID_RAD_MISMATCH_MGR_FLAG

Message ID: 20068

Message Description: LOG_ID_RAD_MISMATCH_MGR_FLAG

Message Meaning: RADVD local AdvManagedFlag disagrees with remote site

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20069 - LOG_ID_RAD_MISMATCH_OTH_FLAG

Message ID: 20069

Message Description: LOG_ID_RAD_MISMATCH_OTH_FLAG

Message Meaning: RADVD local AdvOtherConfigFlag disagrees with remote site

Type: Event

Category: SYSTEM**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20070 - LOG_ID_RAD_MISMATCH_TIME

Message ID: 20070**Message Description:** LOG_ID_RAD_MISMATCH_TIME**Message Meaning:** RADVD local AdvReachableTime disagrees with remote site**Type:** Event**Category:** SYSTEM**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20071 - LOG_ID_RAD_MISMATCH_TIMER

Message ID: 20071

Message Description: LOG_ID_RAD_MISMATCH_TIMER

Message Meaning: RADVD local AdvRetransTimer disagrees with remote site

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20072 - LOG_ID_RAD_EXTRA_DATA

Message ID: 20072

Message Description: LOG_ID_RAD_EXTRA_DATA

Message Meaning: RADVD extra data in RA packet found

Type: Event

Category: SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20073 - LOG_ID_RAD_NO_OPT_DATA

Message ID: 20073**Message Description:** LOG_ID_RAD_NO_OPT_DATA**Message Meaning:** RADVD RA packet option length zero**Type:** Event**Category:** SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20074 - LOG_ID_RAD_INV_OPT_LEN

Message ID: 20074

Message Description: LOG_ID_RAD_INV_OPT_LEN

Message Meaning: RADVD RA packet option length greater than total length

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20075 - LOG_ID_RAD_MISMATCH_MTU

Message ID: 20075

Message Description: LOG_ID_RAD_MISMATCH_MTU

Message Meaning: RADVD local AdvLinkMTU disagrees with remote site

Type: Event

Category: SYSTEM**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20077 - LOG_ID_RAD_MISMATCH_PREF_TIME

Message ID: 20077**Message Description:** LOG_ID_RAD_MISMATCH_PREF_TIME**Message Meaning:** Interface AdvPreferredLifetime on our interface does not agree with a remote site**Type:** Event**Category:** SYSTEM**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20078 - LOG_ID_RAD_INV_OPT

Message ID: 20078

Message Description: LOG_ID_RAD_INV_OPT

Message Meaning: RADVD found invalid option in RA packet from remote site

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20079 - LOG_ID_RAD_READY

Message ID: 20079

Message Description: LOG_ID_RAD_READY

Message Meaning: RADVD daemon started

Type: Event

Category: SYSTEM**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20080 - LOG_ID_RAD_FAIL_TO_RCV

Message ID: 20080**Message Description:** LOG_ID_RAD_FAIL_TO_RCV**Message Meaning:** RADVD receive message failed**Type:** Event**Category:** SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20081 - LOG_ID_RAD_INV_HOP

Message ID: 20081

Message Description: LOG_ID_RAD_INV_HOP

Message Meaning: RADVD received invalid IPv6 hop limit

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20082 - LOG_ID_RAD_INV_PKTINFO

Message ID: 20082

Message Description: LOG_ID_RAD_INV_PKTINFO

Message Meaning: RADVD received invalid IPv6 packet info

Type: Event

Category: SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20083 - LOG_ID_RAD_FAIL_TO_CHECK

Message ID: 20083**Message Description:** LOG_ID_RAD_FAIL_TO_CHECK**Message Meaning:** RADVD all-routers membership check failed**Type:** Event**Category:** SYSTEM**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20084 - LOG_ID_RAD_FAIL_TO_SEND

Message ID: 20084

Message Description: LOG_ID_RAD_FAIL_TO_SEND

Message Meaning: RADVD send message failed

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20085 - LOG_ID_SESSION_CLASH

Message ID: 20085

Message Description: LOG_ID_SESSION_CLASH

Message Meaning: Session clashed

Type: Event

Category: SYSTEM**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
status	Status	string	23
msg	Message Text	string	4096
proto	Protocol Number	uint8	3
trace_id		string	32

20090 - LOG_ID_INTF_LINK_STA_CHG

Message ID: 20090**Message Description:** LOG_ID_INTF_LINK_STA_CHG**Message Meaning:** Interface link status changed**Type:** Event**Category:** SYSTEM**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
status	Status	string	23
msg	Message Text	string	4096
intf	Interface	string	16

20099 - LOG_ID_INTF_STA_CHG

Message ID: 20099

Message Description: LOG_ID_INTF_STA_CHG

Message Meaning: Interface status changed

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65

Log Field Name	Description	Data Type	Length
status	Status	string	23
msg	Message Text	string	4096

20100 - LOG_ID_WEB_CAT_UPDATED

Message ID: 20100

Message Description: LOG_ID_WEB_CAT_UPDATED

Message Meaning: FortiGuard web filter category list updated

Type: Event

Category: SYSTEM

Severity: Debug

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Message Text	string	4096
dstport	Destination Port	uint16	5
file	File Name for Generated Report?	string	256
filesize	Report File Size in Bytes	uint32	10
created		string	64
informationsource	Information Source	string	4096
new_status	New Status	string	512

Log Field Name	Description	Data Type	Length
profile	Profile Name	string	64
hostname	Hostname	string	128
host		string	256
path		string	512
old_status	Original Status	string	512

20101 - LOG_ID_WEB_LIC_EXPIRE

Message ID: 20101

Message Description: LOG_ID_WEB_LIC_EXPIRE

Message Meaning: FortiGuard web filter license expiring

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20102 - LOG_ID_SPAM_LIC_EXPIRE

Message ID: 20102

Message Description: LOG_ID_SPAM_LIC_EXPIRE

Message Meaning: FortiGuard antispam license expiring

Type: Event**Category:** SYSTEM**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20103 - LOG_ID_AV_LIC_EXPIRE

Message ID: 20103**Message Description:** LOG_ID_AV_LIC_EXPIRE**Message Meaning:** FortiGuard antivirus license expiring**Type:** Event**Category:** SYSTEM**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20104 - LOG_ID_IPS_LIC_EXPIRE

Message ID: 20104

Message Description: LOG_ID_IPS_LIC_EXPIRE

Message Meaning: FortiGuard IPS license expiring

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20107 - LOG_ID_LOG_UPLOAD_ERR

Message ID: 20107

Message Description: LOG_ID_LOG_UPLOAD_ERR

Message Meaning: Log upload error

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
action	Action	string	65
msg	Message Text	string	4096
error	Error Reason for Log Upload to Forticloud	string	256
server	Server IP Address	string	64
port	Port Number	uint16	5

20108 - LOG_ID_LOG_UPLOAD_DONE

Message ID: 20108

Message Description: LOG_ID_LOG_UPLOAD_DONE

Message Meaning: Log upload completed

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096
server	Server IP Address	string	64
port	Port Number	uint16	5

20109 - LOG_ID_WEB_LIC_EXPIRED

Message ID: 20109

Message Description: LOG_ID_WEB_LIC_EXPIRED

Message Meaning: FortiGuard web filter license expired

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20113 - LOG_ID_IPSA_DOWNLOAD_FAIL

Message ID: 20113

Message Description: LOG_ID_IPSA_DOWNLOAD_FAIL

Message Meaning: IPSA database download failed

Type: Event

Category: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20115 - LOG_ID_IPSA_STATUSUPD_FAIL

Message ID: 20115

Message Description: LOG_ID_IPSA_STATUSUPD_FAIL

Message Meaning: IPSA driver update failed

Type: Event

Category: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20116 - LOG_ID_SPAM_LIC_EXPIRED

Message ID: 20116

Message Description: LOG_ID_SPAM_LIC_EXPIRED

Message Meaning: FortiGuard antispam license expired

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20117 - LOG_ID_AV_LIC_EXPIRED

Message ID: 20117

Message Description: LOG_ID_AV_LIC_EXPIRED

Message Meaning: FortiGuard antivirus license expired

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20118 - LOG_ID_WEBF_STATUS_REACH

Message ID: 20118

Message Description: LOG_ID_WEBF_STATUS_REACH

Message Meaning: FortiGuard webfilter reachable

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20119 - LOG_ID_WEBF_STATUS_UNREACH

Message ID: 20119

Message Description: LOG_ID_WEBF_STATUS_UNREACH

Message Meaning: FortiGuard webfilter unreachable

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20200 - LOG_ID_FIPS_SELF_TEST

Message ID: 20200

Message Description: LOG_ID_FIPS_SELF_TEST

Message Meaning: FIPS CC self-test initiated

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096

Log Field Name	Description	Data Type	Length
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

20201 - LOG_ID_FIPS_SELF_ALL_TEST

Message ID: 20201

Message Description: LOG_ID_FIPS_SELF_ALL_TEST

Message Meaning: FIPS ALL CC self-tests initiated

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

20202 - LOG_ID_DISK_FORMAT_ERROR

Message ID: 20202

Message Description: LOG_ID_DISK_FORMAT_ERROR**Message Meaning:** Disk partitioning or formatting Error**Type:** Event**Category:** SYSTEM**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20203 - LOG_ID_DAEMON_SHUTDOWN

Message ID: 20203**Message Description:** LOG_ID_DAEMON_SHUTDOWN**Message Meaning:** Daemon shutdown**Type:** Event**Category:** SYSTEM**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Message Text	string	4096
daemon	Daemon Name	string	32
pid	Process ID	uint32	10

20204 - LOG_ID_DAEMON_START

Message ID: 20204

Message Description: LOG_ID_DAEMON_START

Message Meaning: Daemon started

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	4096
action	Action	string	65
msg	Message Text	string	4096
daemon	Daemon Name	string	32
pid	Process ID	uint32	10

20205 - LOG_ID_DISK_FORMAT_REQ

Message ID: 20205

Message Description: LOG_ID_DISK_FORMAT_REQ

Message Meaning: Format disk requested

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

20206 - LOG_ID_DISK_SCAN_REQ

Message ID: 20206

Message Description: LOG_ID_DISK_SCAN_REQ

Message Meaning: Scan disk requested

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

20207 - LOG_ID_RAD_MISMATCH_VALID_TIME

Message ID: 20207

Message Description: LOG_ID_RAD_MISMATCH_VALID_TIME

Message Meaning: RADVD local AdvValidLifetime disagrees with remote site

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20208 - LOG_ID_ZOMBIE_DAEMON_CLEANUP

Message ID: 20208

Message Description: LOG_ID_ZOMBIE_DAEMON_CLEANUP

Message Meaning: Zombie daemon cleanup

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Message Text	string	4096
daemon	Daemon Name	string	32
pid	Process ID	uint32	10

20209 - LOG_ID_DISK_UNAVAIL

Message ID: 20209

Message Description: LOG_ID_DISK_UNAVAIL

Message Meaning: Disk unavailable

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20210 - LOG_ID_DISK_TRIM_START

Message ID: 20210

Message Description: LOG_ID_DISK_TRIM_START

Message Meaning: SSD TRIM started

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

20211 - LOG_ID_DISK_TRIM_END

Message ID: 20211

Message Description: LOG_ID_DISK_TRIM_END

Message Meaning: SSD TRIM finished

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

20212 - LOG_ID_DISK_SCAN_NEEDED

Message ID: 20212

Message Description: LOG_ID_DISK_SCAN_NEEDED

Message Meaning: Disk scan is needed

Type: Event

Category: SYSTEM

Severity: Alert

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20213 - LOG_ID_DISK_LOG_CORRUPTED

Message ID: 20213

Message Description: LOG_ID_DISK_LOG_CORRUPTED

Message Meaning: Log file on disk is corrupted

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

20220 - LOGID_EVENT_SHAPER_OUTBOUND_MAXED_OUT

Message ID: 20220

Message Description: LOGID_EVENT_SHAPER_OUTBOUND_MAXED_OUT

Message Meaning: Outbound bandwidth rate exceeded

Type: Event

Category: SYSTEM**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096
intf	Interface	string	16
limit	Virtual Domain Resource Limit	uint32	10

20221 - LOGID_EVENT_SHAPER_INBOUND_MAXED_OUT

Message ID: 20221**Message Description:** LOGID_EVENT_SHAPER_INBOUND_MAXED_OUT**Message Meaning:** Inbound bandwidth rate exceeded**Type:** Event**Category:** SYSTEM**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096
intf	Interface	string	16
limit	Virtual Domain Resource Limit	uint32	10

20300 - LOG_ID_BGP_NB_STAT_CHG

Message ID: 20300

Message Description: LOG_ID_BGP_NB_STAT_CHG

Message Meaning: BGP neighbor status changed

Type: Event

Category: ROUTER

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message	string	4096

20301 - LOG_ID_VZ_LOG

Message ID: 20301

Message Description: LOG_ID_VZ_LOG

Message Meaning: Routing log

Type: Event

Category: ROUTER

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message	string	4096

20302 - LOG_ID_OSPF_NB_STAT_CHG

Message ID: 20302

Message Description: LOG_ID_OSPF_NB_STAT_CHG

Message Meaning: OSPF neighbor status changed

Type: Event

Category: ROUTER

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message	string	4096

20303 - LOG_ID_OSPF6_NB_STAT_CHG

Message ID: 20303

Message Description: LOG_ID_OSPF6_NB_STAT_CHG

Message Meaning: OSPF6 neighbor status changed

Type: Event

Category: ROUTER

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message	string	4096

20401 - LOG_ID_ROUTER_CLEAR

Message ID: 20401

Message Description: LOG_ID_ROUTER_CLEAR

Message Meaning: Router cleared

Type: Event

Category: ROUTER

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message	string	4096
user		string	256
ui		string	64
action	Action	string	65

22000 - LOG_ID_INV_PKT_LEN

Message ID: 22000

Message Description: LOG_ID_INV_PKT_LEN

Message Meaning: Packet length mismatch

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

22001 - LOG_ID_UNSUPPORTED_PROT_VER

Message ID: 22001

Message Description: LOG_ID_UNSUPPORTED_PROT_VER

Message Meaning: Protocol version unsupported

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

22002 - LOG_ID_INV_REQ_TYPE

Message ID: 22002

Message Description: LOG_ID_INV_REQ_TYPE

Message Meaning: Request type not supported

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

22003 - LOG_ID_FAIL_SET_SIG_HANDLER

Message ID: 22003

Message Description: LOG_ID_FAIL_SET_SIG_HANDLER

Message Meaning: Signal handler setup failed

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

22004 - LOG_ID_FAIL_CREATE_SOCKET

Message ID: 22004**Message Description:** LOG_ID_FAIL_CREATE_SOCKET**Message Meaning:** Socket creation failed**Type:** Event**Category:** SYSTEM**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096

22005 - LOG_ID_FAIL_CREATE_SOCKET_RETRY

Message ID: 22005

Message Description: LOG_ID_FAIL_CREATE_SOCKET_RETRY

Message Meaning: Socket creation retry failed

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096

22006 - LOG_ID_FAIL_REG_CMDB_EVENT

Message ID: 22006

Message Description: LOG_ID_FAIL_REG_CMDB_EVENT

Message Meaning: Registration for CMDB events failed

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

22009 - LOG_ID_FAIL_FIND_AV_PROFILE

Message ID: 22009

Message Description: LOG_ID_FAIL_FIND_AV_PROFILE

Message Meaning: AntiVirus profile not found

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
tz		string	5
logdesc	Log Description	string	4096
status	Status	string	23
msg	Message Text	string	4096
name	Name	string	128

22010 - LOG_ID_SENDTO_FAIL

Message ID: 22010

Message Description: LOG_ID_SENDTO_FAIL

Message Meaning: URL filter packet send failure

Type: Event

Category: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096
process	Process	string	4096
reason	Reason	string	256

22011 - LOG_ID_ENTER_MEM_CONSERVE_MODE

Message ID: 22011

Message Description: LOG_ID_ENTER_MEM_CONSERVE_MODE

Message Meaning: Memory conserve mode entered

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096
service	Name of Service	string	64
conserve	Flag for Conserve Mode	string	32
total	Total	uint32	10
used	Number of Used IPs	uint32	10
red		string	32
green		string	32

22012 - LOG_ID_LEAVE_MEM_CONSERVE_MODE

Message ID: 22012

Message Description: LOG_ID_LEAVE_MEM_CONSERVE_MODE

Message Meaning: Memory conserve mode exited

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096
service	Name of Service	string	64
conserve	Flag for Conserve Mode	string	32
total	Total	uint32	10
used	Number of Used IPs	uint32	10
red		string	32
green		string	32

22013 - LOG_ID_IPPOOLPBA_BLOCK_EXHAUSTED

Message ID: 22013

Message Description: LOG_ID_IPPOOLPBA_BLOCK_EXHAUSTED

Message Meaning: IP pool PBA block exhausted

Type: Event

Category: SYSTEM

Severity: Alert

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Message Text	string	4096
saddr	Source Address IP	string	80
poolname	IP Pool Name	string	36

22014 - LOG_ID_IPPOOLPBA_NATIP_EXHAUSTED

Message ID: 22014

Message Description: LOG_ID_IPPOOLPBA_NATIP_EXHAUSTED

Message Meaning: IP pool PBA NAT IP exhausted

Type: Event

Category: SYSTEM

Severity: Alert

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Message Text	string	4096
saddr	Source Address IP	string	80
poolname	IP Pool Name	string	36

22015 - LOG_ID_IPPOOLPBA_CREATE

Message ID: 22015

Message Description: LOG_ID_IPPOOLPBA_CREATE

Message Meaning: IP pool PBA created

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Message Text	string	4096
nat	NAT IP Address	ip	39
saddr	Source Address IP	string	80

Log Field Name	Description	Data Type	Length
poolname	IP Pool Name	string	36
portbegin	Port Number to Begin	uint16	5
portend	Port Number to End	uint16	5

22016 - LOG_ID_IPPOOLPBA_DEALLOCATE

Message ID: 22016

Message Description: LOG_ID_IPPOOLPBA_DEALLOCATE

Message Meaning: Deallocate IP pool PBA

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Message Text	string	4096
nat	NAT IP Address	ip	39
saddr	Source Address IP	string	80
poolname	IP Pool Name	string	36
portbegin	Port Number to Begin	uint16	5
portend	Port Number to End	uint16	5
duration	Duration	uint32	10

22017 - LOG_ID_EXCEED_GLOB_RES_LIMIT

Message ID: 22017

Message Description: LOG_ID_EXCEED_GLOB_RES_LIMIT

Message Meaning: Global resource limit exceeded

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096
service	Name of Service	string	64

22018 - LOG_ID_EXCEED_VD_RES_LIMIT

Message ID: 22018

Message Description: LOG_ID_EXCEED_VD_RES_LIMIT

Message Meaning: VDOM resource limit exceeded

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10

Log Field Name	Description	Data Type	Length
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096
service	Name of Service	string	64

22019 - LOG_ID_LOGRATE_OVER_LIMIT

Message ID: 22019

Message Description: LOG_ID_LOGRATE_OVER_LIMIT

Message Meaning: Log rate limit exceeded

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

22020 - LOG_ID_FAIL_CREATE_HA_SOCKET

Message ID: 22020

Message Description: LOG_ID_FAIL_CREATE_HA_SOCKET

Message Meaning: HA socket creation failed

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

22021 - LOG_ID_FAIL_CREATE_HA_SOCKET_RETRY

Message ID: 22021

Message Description: LOG_ID_FAIL_CREATE_HA_SOCKET_RETRY

Message Meaning: UDP socket creation to relay URL request failed

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

22031 - LOG_ID_SUCCESS_CSF_LOG_SYNC_CONFIG_CHANGED

Message ID: 22031**Message Description:** LOG_ID_SUCCESS_CSF_LOG_SYNC_CONFIG_CHANGED**Message Meaning:** Settings modified by Security Fabric service**Type:** Event**Category:** SYSTEM**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096
sn	Serial Number	string	64

22032 - LOG_ID_CSF_LOOP_FOUND

Message ID: 22032

Message Description: LOG_ID_CSF_LOOP_FOUND

Message Meaning: Looped configuration in Security Fabric service

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
status	Status	string	23
msg	Message Text	string	4096
path		string	512

Log Field Name	Description	Data Type	Length
reason	Reason	string	256
sn	Serial Number	string	64

22033 - LOG_ID_FAIL_CSF_LOG_SYNC_NO_VALID_FSA

Message ID: 22033

Message Description: LOG_ID_FAIL_CSF_LOG_SYNC_NO_VALID_FSA

Message Meaning: CSF root FSA configuration is not properly set

Type: Event

Category: SYSTEM

Severity: Alert

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
status	Status	string	23
msg	Message Text	string	4096
server	Server IP Address	string	64
reason	Reason	string	256
sn	Serial Number	string	64

22035 - LOG_ID_CSF_UPSTREAM_SN_CHANGED

Message ID: 22035

Message Description: LOG_ID_CSF_UPSTREAM_SN_CHANGED

Message Meaning: Serial number of upstream is changed

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096
sn	Serial Number	string	64
ip		ip	39
oldsn		string	64

22036 - LOG_ID_CSF_FGT_CONNECTED

Message ID: 22036

Message Description: LOG_ID_CSF_FGT_CONNECTED

Message Meaning: Connection with CSF member established and authorized

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096
sn	Serial Number	string	64
ip		ip	39
direction		string	16

22037 - LOG_ID_CSF_FGT_DISCONNECTED

Message ID: 22037

Message Description: LOG_ID_CSF_FGT_DISCONNECTED

Message Meaning: Connection with authorized CSF member terminated

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096
reason	Reason	string	256
sn	Serial Number	string	64
ip		ip	39
direction		string	16

22100 - LOG_ID_QUAR_DROP_TRAN_JOB

Message ID: 22100

Message Description: LOG_ID_QUAR_DROP_TRAN_JOB

Message Meaning: Files dropped by quarantine daemon

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
status	Status	string	23

Log Field Name	Description	Data Type	Length
msg	Message Text	string	4096
count	Count	uint32	10
limit	Virtual Domain Resource Limit	uint32	10
reason	Reason	string	256
used	Number of Used IPs	uint32	10
duration	Duration	uint32	10
fams_pause	Fortinet Analysis and Management Service Pause	uint32	10

22101 - LOG_ID_QUAR_DROP_TLL_JOB

Message ID: 22101

Message Description: LOG_ID_QUAR_DROP_TLL_JOB

Message Meaning: Files dropped due to poor network connection

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096

Log Field Name	Description	Data Type	Length
count	Count	uint32	10
reason	Reason	string	256

22102 - LOG_ID_LOG_DISK_FAILURE

Message ID: 22102

Message Description: LOG_ID_LOG_DISK_FAILURE

Message Meaning: Log disk failure imminent

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

22103 - LOG_ID_QUAR_LIMIT_REACHED

Message ID: 22103

Message Description: LOG_ID_QUAR_LIMIT_REACHED

Message Meaning: Sandbox limit reached

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Message Text	string	4096
count	Count	uint32	10
limit	Virtual Domain Resource Limit	uint32	10

22104 - LOG_ID_POWER_RESTORE

Message ID: 22104

Message Description: LOG_ID_POWER_RESTORE

Message Meaning: Power supply restored

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096
unit	Unit	uint32	10

22105 - LOG_ID_POWER_FAILURE

Message ID: 22105

Message Description: LOG_ID_POWER_FAILURE

Message Meaning: Power supply failed

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65

Log Field Name	Description	Data Type	Length
status	Status	string	23
msg	Message Text	string	4096
unit	Unit	uint32	10

22106 - LOG_ID_POWER_OPTIONAL_NOT_DETECTED

Message ID: 22106

Message Description: LOG_ID_POWER_OPTIONAL_NOT_DETECTED

Message Meaning: Optional power supply not detected

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096

22107 - LOG_ID_VOLT_ANOM

Message ID: 22107

Message Description: LOG_ID_VOLT_ANOM

Message Meaning: Voltage anomaly

Type: Event**Category:** SYSTEM**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096

22108 - LOG_ID_FAN_ANOM

Message ID: 22108**Message Description:** LOG_ID_FAN_ANOM**Message Meaning:** Fan anomaly**Type:** Event**Category:** SYSTEM**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096

22109 - LOG_ID_TEMP_TOO_HIGH

Message ID: 22109

Message Description: LOG_ID_TEMP_TOO_HIGH

Message Meaning: Temperature too high

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096

Log Field Name	Description	Data Type	Length
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096

22110 - LOG_ID_SPARE_BLOCK_LOW

Message ID: 22110

Message Description: LOG_ID_SPARE_BLOCK_LOW

Message Meaning: Spare blocks availability low

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

22113 - LOG_ID_FNBAM_FAILURE

Message ID: 22113

Message Description: LOG_ID_FNBAM_FAILURE

Message Meaning: Authentication error

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096
service	Name of Service	string	64

22150 - LOG_ID_VOLT_NOM

Message ID: 22150**Message Description:** LOG_ID_VOLT_NOM**Message Meaning:** Voltage normal**Type:** Event**Category:** SYSTEM**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096

22151 - LOG_ID_FAN_NOM

Message ID: 22151

Message Description: LOG_ID_FAN_NOM

Message Meaning: Fan normal

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096

22152 - LOG_ID_TEMP_TOO_LOW

Message ID: 22152

Message Description: LOG_ID_TEMP_TOO_LOW

Message Meaning: Temperature too low

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096

22153 - LOG_ID_TEMP_NORM

Message ID: 22153

Message Description: LOG_ID_TEMP_NORM

Message Meaning: Temperature normal

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096

22200 - LOG_ID_AUTO_UPT_CERT

Message ID: 22200

Message Description: LOG_ID_AUTO_UPT_CERT

Message Meaning: Certificate will be auto-updated

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096
cert	Certificate	string	36

22201 - LOG_ID_AUTO_GEN_CERT

Message ID: 22201

Message Description: LOG_ID_AUTO_GEN_CERT

Message Meaning: Certificate will be auto-regenerated

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256

Log Field Name	Description	Data Type	Length
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096
cert	Certificate	string	36

22203 - LOG_ID_AUTO_GEN_CERT_FAIL

Message ID: 22203

Message Description: LOG_ID_AUTO_GEN_CERT_FAIL

Message Meaning: Certificate failed to auto-generate

Type: Event

Category: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096
name	Name	string	128

22204 - LOG_ID_AUTO_GEN_CERT_PENDING

Message ID: 22204

Message Description: LOG_ID_AUTO_GEN_CERT_PENDING

Message Meaning: Certificate pending to auto-generate

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096
name	Name	string	128

22205 - LOG_ID_AUTO_GEN_CERT_SUCC

Message ID: 22205

Message Description: LOG_ID_AUTO_GEN_CERT_SUCC

Message Meaning: Certificate succeed to auto-generate

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096
name	Name	string	128

22206 - LOG_ID_CRL_EXPIRED

Message ID: 22206

Message Description: LOG_ID_CRL_EXPIRED

Message Meaning: CRL is expired

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096

22700 - LOG_ID_IPS_FAIL_OPEN

Message ID: 22700

Message Description: LOG_ID_IPS_FAIL_OPEN

Message Meaning: IPS session scan paused

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096

Log Field Name	Description	Data Type	Length
action	Action	string	65
msg	Message Text	string	4096

22701 - LOG_ID_IPS_FAIL_OPEN_END

Message ID: 22701

Message Description: LOG_ID_IPS_FAIL_OPEN_END

Message Meaning: IPS session scan resumed

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

22800 - LOG_ID_SCAN_SERV_FAIL

Message ID: 22800

Message Description: LOG_ID_SCAN_SERV_FAIL

Message Meaning: Scan services session failed

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096
service	Name of Service	string	64
mode	Mode	string	12

22802 - LOG_ID_ENTER_FD_CONSERVE_MODE

Message ID: 22802

Message Description: LOG_ID_ENTER_FD_CONSERVE_MODE

Message Meaning: File descriptor conserve mode entered

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096
daemon	Daemon Name	string	32
conserve	Flag for Conserve Mode	string	32
total	Total	uint32	10
used	Number of Used IPs	uint32	10
red		string	32
green		string	32

22803 - LOG_ID_LEAVE_FD_CONSERVE_MODE

Message ID: 22803

Message Description: LOG_ID_LEAVE_FD_CONSERVE_MODE

Message Meaning: File descriptor conserve mode exited

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	4096
msg	Message Text	string	4096
daemon	Daemon Name	string	32
conserve	Flag for Conserve Mode	string	32
total	Total	uint32	10
used	Number of Used IPs	uint32	10
red		string	32
green		string	32

22804 - LOG_ID_LIC_STATUS_CHG

Message ID: 22804

Message Description: LOG_ID_LIC_STATUS_CHG

Message Meaning: License status changed

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
status	Status	string	23
msg	Message Text	string	4096
service	Name of Service	string	64

22805 - LOG_ID_FAIL_TO_VALIDATE_LIC

Message ID: 22805

Message Description: LOG_ID_FAIL_TO_VALIDATE_LIC

Message Meaning: License validation failure

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
status	Status	string	23
msg	Message Text	string	4096
service	Name of Service	string	64

22806 - LOG_ID_DUP_LIC

Message ID: 22806

Message Description: LOG_ID_DUP_LIC

Message Meaning: Duplicate license detected

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
status	Status	string	23
msg	Message Text	string	4096
service	Name of Service	string	64

22808 - LOG_ID_LIC_EXPIRE

Message ID: 22808

Message Description: LOG_ID_LIC_EXPIRE

Message Meaning: VM license expired

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
status	Status	string	23
msg	Message Text	string	4096
service	Name of Service	string	64

22809 - LOG_ID_LIC_WILL_EXPIRE

Message ID: 22809

Message Description: LOG_ID_LIC_WILL_EXPIRE

Message Meaning: VM license expiring

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
status	Status	string	23
msg	Message Text	string	4096
service	Name of Service	string	64

22810 - LOG_ID_SCANUNIT_ERROR_BLOCK

Message ID: 22810

Message Description: LOG_ID_SCANUNIT_ERROR_BLOCK

Message Meaning: Scan error - traffic blocked

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096
service	Name of Service	string	64
proto	Protocol Number	uint8	3
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
file	File Name for Generated Report?	string	256
session_id		uint32	10
src_int	Source Interface	string	64
dst_int	Destination Interface	string	64
dir		string	8

22811 - LOG_ID_SCANUNIT_ERROR_PASS

Message ID: 22811

Message Description: LOG_ID_SCANUNIT_ERROR_PASS

Message Meaning: Scan error - traffic passed

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096
service	Name of Service	string	64
proto	Protocol Number	uint8	3
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
file	File Name for Generated Report?	string	256
session_id		uint32	10
src_int	Source Interface	string	64
dst_int	Destination Interface	string	64
dir		string	8

22812 - LOG_ID_SCANUNIT_AVENG_RELOAD

Message ID: 22812

Message Description: LOG_ID_SCANUNIT_AVENG_RELOAD

Message Meaning: Scanunit is reloading AV engine

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Message Text	string	4096

22813 - LOG_ID_SCANUNIT_AVDB_RELOAD

Message ID: 22813

Message Description: LOG_ID_SCANUNIT_AVDB_RELOAD

Message Meaning: Scanunit reloaded AV Database

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10

Log Field Name	Description	Data Type	Length
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Message Text	string	4096

22814 - LOG_ID_SCANUNIT_AVDB_RELOAD_ERROR

Message ID: 22814

Message Description: LOG_ID_SCANUNIT_AVDB_RELOAD_ERROR

Message Meaning: Scanunit AV Database reload error

Type: Event

Category: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Message Text	string	4096

22815 - LOG_ID_SCANUNIT_AVDB_LOAD

Message ID: 22815

Message Description: LOG_ID_SCANUNIT_AVDB_LOAD

Message Meaning: Scanunit loaded AV Database

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Message Text	string	4096

22816 - LOG_ID_SCANUNIT_AVDB_LOAD_ERROR

Message ID: 22816

Message Description: LOG_ID_SCANUNIT_AVDB_LOAD_ERROR

Message Meaning: Scanunit AV Database load error

Type: Event**Category:** SYSTEM**Severity:** Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Message Text	string	4096

22850 - LOG_ID_USER_QUARANTINE_MAC_ADD

Message ID: 22850**Message Description:** LOG_ID_USER_QUARANTINE_MAC_ADD**Message Meaning:** User quarantine MAC added**Type:** Event**Category:** SYSTEM**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

22851 - LOG_ID_USER_QUARANTINE_MAC_DELETE

Message ID: 22851

Message Description: LOG_ID_USER_QUARANTINE_MAC_DELETE

Message Meaning: User quarantine MAC deleted

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096

Log Field Name	Description	Data Type	Length
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

22852 - LOG_ID_USER_QUARANTINE_MAC_BOUNCE_PORT_HIT

Message ID: 22852

Message Description: LOG_ID_USER_QUARANTINE_MAC_BOUNCE_PORT_HIT

Message Meaning: User quarantine MAC bounce port hit

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

22853 - LOG_ID_USER_QUARANTINE_MAC_BOUNCE_PORT_MISS

Message ID: 22853

Message Description: LOG_ID_USER_QUARANTINE_MAC_BOUNCE_PORT_MISS**Message Meaning:** User quarantine MAC bounce port miss**Type:** Event**Category:** SYSTEM**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

22890 - LOG_ID_FORTILINKD

Message ID: 22890**Message Description:** LOG_ID_FORTILINKD**Message Meaning:** Switch-Controller Daemon Log (Notification)**Type:** Event**Category:** SYSTEM**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10

Log Field Name	Description	Data Type	Length
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
msg	Message Text	string	4096

22891 - LOG_ID_FLCFGD_SYNC_ERROR

Message ID: 22891

Message Description: LOG_ID_FLCFGD_SYNC_ERROR

Message Meaning: Switch-Controller Switch Sync Error

Type: Event

Category: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
msg	Message Text	string	4096
name	Name	string	128
sn	Serial Number	string	64

22892 - LOG_ID_FLCFGD_SYNC_COMPLETE

Message ID: 22892

Message Description: LOG_ID_FLCFGD_SYNC_COMPLETE

Message Meaning: Switch-Controller Switch Sync Complete

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
msg	Message Text	string	4096

22893 - LOG_ID_FLCFGD_SYNC_STATE

Message ID: 22893

Message Description: LOG_ID_FLCFGD_SYNC_STATE

Message Meaning: Switch-Controller Switch Sync State

Type: Event

Category: SYSTEM

Severity: Debug

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
msg	Message Text	string	4096

22894 - LOG_ID_FLCFGD_UPGRADE_ERROR

Message ID: 22894

Message Description: LOG_ID_FLCFGD_UPGRADE_ERROR

Message Meaning: Switch-Controller Switch Upgrade Error

Type: Event

Category: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
msg	Message Text	string	4096

22895 - LOG_ID_FLCFGD_UPGRADE_STATUS

Message ID: 22895

Message Description: LOG_ID_FLCFGD_UPGRADE_STATUS

Message Meaning: Switch-Controller Switch Upgrade Status

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
msg	Message Text	string	4096

22896 - LOG_ID_FORTILINKD_CRITICAL

Message ID: 22896

Message Description: LOG_ID_FORTILINKD_CRITICAL

Message Meaning: Switch-Controller Daemon Log (Critical)

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
msg	Message Text	string	4096

22900 - LOG_ID_CAPUTP_SESSION

Message ID: 22900

Message Description: LOG_ID_CAPUTP_SESSION

Message Meaning: CAPUTP session status

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

22901 - LOG_ID_FAZ_CON

Message ID: 22901

Message Description: LOG_ID_FAZ_CON

Message Meaning: FortiAnalyzer connection up

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096

22902 - LOG_ID_FAZ_DISCON

Message ID: 22902

Message Description: LOG_ID_FAZ_DISCON

Message Meaning: FortiAnalyzer connection down

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096
reason	Reason	string	256

22903 - LOG_ID_FAZ_CON_ERR

Message ID: 22903

Message Description: LOG_ID_FAZ_CON_ERR

Message Meaning: FortiAnalyzer connection failed

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096
reason	Reason	string	256

22904 - LOG_ID_CAPUTP_SESSION_NOTIF

Message ID: 22904

Message Description: LOG_ID_CAPUTP_SESSION_NOTIF

Message Meaning: CAPUTP session status notification

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096
srcip	Source IP	ip	39

22912 - LOG_ID_FDS_SRV_ERRCON

Message ID: 22912

Message Description: LOG_ID_FDS_SRV_ERRCON

Message Meaning: FortiCloud server connection failed

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Message Text	string	4096
server	Server IP Address	string	64
reason	Reason	string	256

22913 - LOG_ID_FDS_SRV_DISCON

Message ID: 22913

Message Description: LOG_ID_FDS_SRV_DISCON

Message Meaning: FortiCloud server disconnected

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Message Text	string	4096
server	Server IP Address	string	64
reason	Reason	string	256

22914 - LOG_ID_FDS_SRV_CHG

Message ID: 22914

Message Description: LOG_ID_FDS_SRV_CHG

Message Meaning: FortiCloud server changed

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65

Log Field Name	Description	Data Type	Length
msg	Message Text	string	4096
server	Server IP Address	string	64

22915 - LOG_ID_FDS_SRV_CON

Message ID: 22915

Message Description: LOG_ID_FDS_SRV_CON

Message Meaning: FortiCloud server connected

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Message Text	string	4096
server	Server IP Address	string	64

22916 - LOG_ID_FDS_STATUS

Message ID: 22916

Message Description: LOG_ID_FDS_STATUS

Message Meaning: FortiGuard Message Service status

Type: Event

Category: SYSTEM**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
status	Status	string	23
msg	Message Text	string	4096

22917 - LOG_ID_FDS_SMS_QUOTA

Message ID: 22917**Message Description:** LOG_ID_FDS_SMS_QUOTA**Message Meaning:** SMS quota reached**Type:** Event**Category:** SYSTEM**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
msg	Message Text	string	4096

22918 - LOG_ID_FDS_CTRL_STATUS

Message ID: 22918

Message Description: LOG_ID_FDS_CTRL_STATUS

Message Meaning: FortiGuard Message Service controller status

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
status	Status	string	23
msg	Message Text	string	4096

22921 - LOG_ID_EVENT_ROUTE_INFO_CHANGED

Message ID: 22921

Message Description: LOG_ID_EVENT_ROUTE_INFO_CHANGED**Message Meaning:** Routing information changed**Type:** Event**Category:** SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
status	Status	string	23
msg	Message Text	string	4096
name	Name	string	128
interface	Interface	string	32

22922 - LOG_ID_EVENT_LINK_MONITOR_STATUS

Message ID: 22922**Message Description:** LOG_ID_EVENT_LINK_MONITOR_STATUS**Message Meaning:** Link monitor status**Type:** Event**Category:** SYSTEM**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10

Log Field Name	Description	Data Type	Length
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096
name	Name	string	128
interface	Interface	string	32
probeprotocol	Link Monitor Probe Protocol	string	16

22923 - LOG_ID_EVENT_VWL_LQTY_STATUS

Message ID: 22923

Message Description: LOG_ID_EVENT_VWL_LQTY_STATUS

Message Meaning: Virtual WAN Link status

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096
interface	Interface	string	32

22924 - LOG_ID_EVENT_VWL_VOLUME_STATUS

Message ID: 22924

Message Description: LOG_ID_EVENT_VWL_VOLUME_STATUS

Message Meaning: Virtual WAN Link volume status

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096
interface	Interface	string	32

22925 - LOG_ID_EVENT_LINK_MONITOR_SLA_INFO

Message ID: 22925

Message Description: LOG_ID_EVENT_LINK_MONITOR_SLA_INFO**Message Meaning:** Link monitor SLA information**Type:** Event**Category:** SYSTEM**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
status	Status	string	23
msg	Message Text	string	4096
name	Name	string	128
interface	Interface	string	32

22926 - LOG_ID_EVENT_VWL_NEIGHBOR_STATUS

Message ID: 22926**Message Description:** LOG_ID_EVENT_VWL_NEIGHBOR_STATUS**Message Meaning:** Virtual WAN Link Neighbor status**Type:** Event**Category:** SYSTEM**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10

Log Field Name	Description	Data Type	Length
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

22927 - LOG_ID_EVENT_VWL_NEIGHBOR_STANDALONE

Message ID: 22927

Message Description: LOG_ID_EVENT_VWL_NEIGHBOR_STANDALONE

Message Meaning: Virtual WAN Link Neighbor standalone

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	4096
msg	Message Text	string	4096

22928 - LOG_ID_EVENT_VWL_NEIGHBOR_PRIMARY

Message ID: 22928

Message Description: LOG_ID_EVENT_VWL_NEIGHBOR_PRIMARY

Message Meaning: Virtual WAN Link Neighbor primary

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

22929 - LOG_ID_EVENT_VWL_NEIGHBOR_SECONDARY

Message ID: 22929

Message Description: LOG_ID_EVENT_VWL_NEIGHBOR_SECONDARY

Message Meaning: Virtual WAN Link Neighbor secondary

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

22949 - LOG_ID_FDS_JOIN

Message ID: 22949

Message Description: LOG_ID_FDS_JOIN

Message Meaning: FortiCloud auto-join attempted

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
action	Action	string	65
msg	Message Text	string	4096

22950 - LOG_ID_FDS_LOGIN_SUCC

Message ID: 22950

Message Description: LOG_ID_FDS_LOGIN_SUCC

Message Meaning: FortiCloud activation successful

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
action	Action	string	65
msg	Message Text	string	4096

22951 - LOG_ID_FDS_LOGOUT

Message ID: 22951

Message Description: LOG_ID_FDS_LOGOUT**Message Meaning:** FortiCloud logout**Type:** Event**Category:** SYSTEM**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
action	Action	string	65
msg	Message Text	string	4096

22952 - LOG_ID_FDS_LOGIN_FAIL

Message ID: 22952**Message Description:** LOG_ID_FDS_LOGIN_FAIL**Message Meaning:** FortiCloud activation failed**Type:** Event**Category:** SYSTEM**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
action	Action	string	65
msg	Message Text	string	4096

22953 - LOG_ID_IOC_DETECTED

Message ID: 22953

Message Description: LOG_ID_IOC_DETECTED

Message Meaning: Compromised host detected

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
tz		string	5
logdesc	Log Description	string	4096

23101 - LOG_ID_IPSEC_TUNNEL_UP

Message ID: 23101

Message Description: LOG_ID_IPSEC_TUNNEL_UP

Message Meaning: IPsec VPN tunnel up

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
remip	Remote IP	ip	39
tunnelip	Tunnel IP	ip	39
user	User Name	string	256
group	User Group Name	string	64
msg	Message	string	4096

23102 - LOG_ID_IPSEC_TUNNEL_DOWN

Message ID: 23102

Message Description: LOG_ID_IPSEC_TUNNEL_DOWN

Message Meaning: IPsec VPN tunnel down

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
remip	Remote IP	ip	39
tunnelip	Tunnel IP	ip	39
user	User Name	string	256
group	User Group Name	string	64
msg	Message	string	4096

23103 - LOG_ID_IPSEC_TUNNEL_STAT

Message ID: 23103

Message Description: LOG_ID_IPSEC_TUNNEL_STAT

Message Meaning: IPsec VPN tunnel statistics

Type: Event**Category:** VPN**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
remip	Remote IP	ip	39
tunnelip	Tunnel IP	ip	39
user	User Name	string	256
group	User Group Name	string	64
msg	Message	string	4096

26001 - LOG_ID_DHCP_ACK

Message ID: 26001**Message Description:** LOG_ID_DHCP_ACK**Message Meaning:** DHCP Ack log**Type:** Event**Category:** SYSTEM**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096
hostname	Hostname	string	128
ip		ip	39
interface	Interface	string	32
dhcp_msg	DHCP Message	string	4096
mac	Mac Address	string	17
lease	DHCP Lease	uint32	10

26002 - LOG_ID_DHCP_RELEASE

Message ID: 26002

Message Description: LOG_ID_DHCP_RELEASE

Message Meaning: DHCP Release log

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096
hostname	Hostname	string	128
ip		ip	39
interface	Interface	string	32
dhcp_msg	DHCP Message	string	4096
mac	Mac Address	string	17

26003 - LOG_ID_DHCP_STAT

Message ID: 26003

Message Description: LOG_ID_DHCP_STAT

Message Meaning: DHCP statistics

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096
total	Total	uint32	10
used	Number of Used IPs	uint32	10
interface	Interface	string	32

26004 - LOG_ID_DHCP_CLIENT_LEASE

Message ID: 26004

Message Description: LOG_ID_DHCP_CLIENT_LEASE

Message Meaning: DHCP client lease granted

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

26005 - LOG_ID_DHCP_LEASE_USAGE_HIGH

Message ID: 26005

Message Description: LOG_ID_DHCP_LEASE_USAGE_HIGH

Message Meaning: DHCP lease usage high

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096
interface	Interface	string	32

26006 - LOG_ID_DHCP_LEASE_USAGE_FULL

Message ID: 26006

Message Description: LOG_ID_DHCP_LEASE_USAGE_FULL

Message Meaning: DHCP lease usage full

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10

Log Field Name	Description	Data Type	Length
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096
interface	Interface	string	32

26007 - LOG_ID_DHCP_BLOCKED_MAC

Message ID: 26007

Message Description: LOG_ID_DHCP_BLOCKED_MAC

Message Meaning: DHCP client blocked log

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096
interface	Interface	string	32
mac	Mac Address	string	17

26008 - LOG_ID_DHCP_DDNS_ADD

Message ID: 26008

Message Description: LOG_ID_DHCP_DDNS_ADD

Message Meaning: DHCP DDNS add query

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096
ip		ip	39
dhcp_msg	DHCP Message	string	4096
ddnsserver	DDNS Server	ip	39
fqdn		string	256

26009 - LOG_ID_DHCP_DDNS_DELETE

Message ID: 26009

Message Description: LOG_ID_DHCP_DDNS_DELETE

Message Meaning: DHCP DDNS delete query

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096
ip		ip	39
dhcp_msg	DHCP Message	string	4096
ddnsserver	DDNS Server	ip	39
fqdn		string	256

26010 - LOG_ID_DHCP_DDNS_COMPLETED

Message ID: 26010

Message Description: LOG_ID_DHCP_DDNS_COMPLETED

Message Meaning: DHCP DDNS query completed

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096
ip		ip	39
dhcp_msg	DHCP Message	string	4096
ddnsserver	DDNS Server	ip	39
fqdn		string	256

26011 - LOG_ID_DHCPV6_REPLY

Message ID: 26011

Message Description: LOG_ID_DHCPV6_REPLY

Message Meaning: DHCPv6 Ack log

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096
ip		ip	39
interface	Interface	string	32
dhcp_msg	DHCP Message	string	4096
lease	DHCP Lease	uint32	10
duid		string	128
iaid		uint32	10

26012 - LOG_ID_DHCPV6_RELEASE

Message ID: 26012

Message Description: LOG_ID_DHCPV6_RELEASE

Message Meaning: DHCPv6 Release log

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096
ip		ip	39
interface	Interface	string	32
dhcp_msg	DHCP Message	string	4096
lease	DHCP Lease	uint32	10
duid		string	128
iaid		uint32	10

27001 - LOG_ID_VRRP_STATE_CHG

Message ID: 27001

Message Description: LOG_ID_VRRP_STATE_CHG

Message Meaning: VRRP state changed

Type: Event

Category: ROUTER

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096

Log Field Name	Description	Data Type	Length
msg	Message	string	4096
interface		string	32

29001 - LOG_ID_PPPD_MSG

Message ID: 29001

Message Description: LOG_ID_PPPD_MSG

Message Meaning: PPP status

Type: Event

Category: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
status	Status	string	23
msg	Message Text	string	4096
local	Local IP for a PPPD Connection	ip	39
remote	Remote IP Address	ip	39
assigned	Assigned IP Address	ip	39

29002 - LOG_ID_PPPD_AUTH_SUC

Message ID: 29002

Message Description: LOG_ID_PPPD_AUTH_SUC**Message Meaning:** PPP authentication successful**Type:** Event**Category:** SYSTEM**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
action	Action	string	65
msg	Message Text	string	4096
local	Local IP for a PPPD Connection	ip	39
remote	Remote IP Address	ip	39
assigned	Assigned IP Address	ip	39

29003 - LOG_ID_PPPD_AUTH_FAIL

Message ID: 29003**Message Description:** LOG_ID_PPPD_AUTH_FAIL**Message Meaning:** PPP authentication failed**Type:** Event**Category:** SYSTEM**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Message Text	string	4096
local	Local IP for a PPPD Connection	ip	39
remote	Remote IP Address	ip	39
assigned	Assigned IP Address	ip	39

29010 - LOG_ID_PPPOE_STATUS_REPORT_NOTIF

Message ID: 29010

Message Description: LOG_ID_PPPOE_STATUS_REPORT_NOTIF

Message Meaning: PPPoE status report

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096
assigned	Assigned IP Address	ip	39
gateway	gateway ip address for PPPoE status report	ip	39
mtu	Max Transmission Unit Value	uint32	10

29011 - LOG_ID_PPPD_FAIL_TO_EXEC

Message ID: 29011

Message Description: LOG_ID_PPPD_FAIL_TO_EXEC

Message Meaning: PPP execution failed

Type: Event

Category: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

29012 - LOG_ID_PPP_OPT_ERR

Message ID: 29012

Message Description: LOG_ID_PPP_OPT_ERR

Message Meaning: PPP received incorrect options

Type: Event

Category: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096

29013 - LOG_ID_PPPD_START

Message ID: 29013

Message Description: LOG_ID_PPPD_START

Message Meaning: PPP daemon started

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

29014 - LOG_ID_PPPD_EXIT

Message ID: 29014

Message Description: LOG_ID_PPPD_EXIT

Message Meaning: PPP daemon exited

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

29015 - LOG_ID_PPP_RCV_BAD_PEER_IP

Message ID: 29015

Message Description: LOG_ID_PPP_RCV_BAD_PEER_IP

Message Meaning: PPP received invalid peer IP

Type: Event

Category: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

29016 - LOG_ID_PPP_RCV_BAD_LOCAL_IP

Message ID: 29016

Message Description: LOG_ID_PPP_RCV_BAD_LOCAL_IP

Message Meaning: PPP received invalid local IP

Type: Event

Category: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

29017 - LOG_ID_PPP_OPT_NOTIF

Message ID: 29017

Message Description: LOG_ID_PPP_OPT_NOTIF

Message Meaning: PPP received incorrect notifications

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096

29021 - LOG_ID_EVENT_AUTH_SNMP_QUERY_FAILED

Message ID: 29021

Message Description: LOG_ID_EVENT_AUTH_SNMP_QUERY_FAILED

Message Meaning: SNMP query failed

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
msg	Message Text	string	4096
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
community	Community	string	36
version	Version	string	64

29022 - LOG_ID_DDNS_UPDATE_FAIL

Message ID: 29022

Message Description: LOG_ID_DDNS_UPDATE_FAIL

Message Meaning: DDNS update failed

Type: Event**Category:** SYSTEM**Severity:** Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

32001 - LOG_ID_ADMIN_LOGIN_SUCC

Message ID: 32001**Message Description:** LOG_ID_ADMIN_LOGIN_SUCC**Message Meaning:** Admin login successful**Type:** Event**Category:** SYSTEM**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096
srcip	Source IP	ip	39
dstip	Destination IP	ip	39
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial number for login or logout events. Used to correlate login and logout events.	string	64
method		string	64

32002 - LOG_ID_ADMIN_LOGIN_FAIL

Message ID: 32002

Message Description: LOG_ID_ADMIN_LOGIN_FAIL

Message Meaning: Admin login failed

Type: Event

Category: SYSTEM

Severity: Alert

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096
srcip	Source IP	ip	39
dstip	Destination IP	ip	39
reason	Reason	string	256
sn	Serial number for login or logout events. Used to correlate login and logout events.	string	64
method		string	64

32003 - LOG_ID_ADMIN_LOGOUT

Message ID: 32003

Message Description: LOG_ID_ADMIN_LOGOUT

Message Meaning: Admin logout successful

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096
srcip	Source IP	ip	39
dstip	Destination IP	ip	39
reason	Reason	string	256
duration	Duration	uint32	10
sn	Serial number for login or logout events. Used to correlate login and logout events.	string	64
method		string	64
state		string	64

32005 - LOG_ID_ADMIN_OVERRIDE_VDOM

Message ID: 32005

Message Description: LOG_ID_ADMIN_OVERRIDE_VDOM

Message Meaning: Admin overrode VDOM

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096
reason	Reason	string	256

32006 - LOG_ID_ADMIN_ENTER_VDOM

Message ID: 32006

Message Description: LOG_ID_ADMIN_ENTER_VDOM

Message Meaning: Super admin entered VDOM

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096
reason	Reason	string	256

32007 - LOG_ID_ADMIN_LEFT_VDOM

Message ID: 32007

Message Description: LOG_ID_ADMIN_LEFT_VDOM

Message Meaning: Super admin left VDOM

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64

Log Field Name	Description	Data Type	Length
action	Action	string	65
msg	Message Text	string	4096
reason	Reason	string	256

32008 - LOG_ID_VIEW_DISK_LOG_FAIL

Message ID: 32008

Message Description: LOG_ID_VIEW_DISK_LOG_FAIL

Message Meaning: Disk log access failed

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
msg	Message Text	string	4096

32009 - LOG_ID_SYSTEM_START

Message ID: 32009

Message Description: LOG_ID_SYSTEM_START

Message Meaning: FortiGate started

Type: Event**Category:** SYSTEM**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

32010 - LOG_ID_DISK_LOG_FULL

Message ID: 32010**Message Description:** LOG_ID_DISK_LOG_FULL**Message Meaning:** Disk full**Type:** Event**Category:** SYSTEM**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

32011 - LOG_ID_LOG_ROLL

Message ID: 32011

Message Description: LOG_ID_LOG_ROLL

Message Meaning: Disk log rolled

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Message Text	string	4096
reason	Reason	string	256
log	Log Name for Log Rotation	string	32

32014 - LOG_ID_CS_LIC_EXPIRE

Message ID: 32014

Message Description: LOG_ID_CS_LIC_EXPIRE

Message Meaning: Support license expiring

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

32015 - LOG_ID_DISK_LOG_USAGE

Message ID: 32015

Message Description: LOG_ID_DISK_LOG_USAGE

Message Meaning: Log disk full

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

32017 - LOG_ID_FDS_DAILY_QUOTA_FULL

Message ID: 32017

Message Description: LOG_ID_FDS_DAILY_QUOTA_FULL

Message Meaning: FortiCloud daily quota full

Type: Event

Category: SYSTEM

Severity: Alert

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

32018 - LOG_ID_FIPS_ENTER_ERR_MOD

Message ID: 32018

Message Description: LOG_ID_FIPS_ENTER_ERR_MOD

Message Meaning: FIPS CC entered error mode

Type: Event

Category: SYSTEM

Severity: Emergency

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Message Text	string	4096
reason	Reason	string	256

32019 - LOG_ID_CC_ENTER_ERR_MOD

Message ID: 32019

Message Description: LOG_ID_CC_ENTER_ERR_MOD

Message Meaning: CC entered error mode

Type: Event

Category: SYSTEM

Severity: Emergency

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Message Text	string	4096

32020 - LOG_ID_SSH_CORRPUT_MAC

Message ID: 32020

Message Description: LOG_ID_SSH_CORRPUT_MAC

Message Meaning: Message Authentication Code corrupted

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
ui	User Interface	string	64
msg	Message Text	string	4096

32021 - LOG_ID_ADMIN_LOGIN_DISABLE

Message ID: 32021

Message Description: LOG_ID_ADMIN_LOGIN_DISABLE

Message Meaning: Admin login disabled

Type: Event

Category: SYSTEM

Severity: Alert

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096
reason	Reason	string	256

32022 - LOG_ID_VDOM_ENABLED

Message ID: 32022

Message Description: LOG_ID_VDOM_ENABLED

Message Meaning: VDOM enabled

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
msg	Message Text	string	4096

32023 - LOG_ID_MEM_LOG_FIRST_FULL

Message ID: 32023

Message Description: LOG_ID_MEM_LOG_FIRST_FULL

Message Meaning: Memory log full over first warning level

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

32024 - LOG_ID_ADMIN_PASSWD_EXPIRE

Message ID: 32024

Message Description: LOG_ID_ADMIN_PASSWD_EXPIRE

Message Meaning: Admin password expired

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096

32025 - LOG_ID_SSH_REKEY

Message ID: 32025

Message Description: LOG_ID_SSH_REKEY

Message Meaning: SSH server re-key

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
ui	User Interface	string	64
msg	Message Text	string	4096

32026 - LOG_ID_SSH_BAD_PACKET_LENGTH

Message ID: 32026

Message Description: LOG_ID_SSH_BAD_PACKET_LENGTH

Message Meaning: SSH server received bad length packet

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
ui	User Interface	string	64
msg	Message Text	string	4096

32027 - LOG_ID_VIEW_DISK_LOG_SUCC

Message ID: 32027

Message Description: LOG_ID_VIEW_DISK_LOG_SUCC

Message Meaning: Disk logs viewed successfully

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
msg	Message Text	string	4096

32028 - LOG_ID_LOG_DEL_DIR

Message ID: 32028

Message Description: LOG_ID_LOG_DEL_DIR

Message Meaning: Disk log directory deleted

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	4096
msg	Message Text	string	4096

32029 - LOG_ID_LOG_DEL_FILE

Message ID: 32029

Message Description: LOG_ID_LOG_DEL_FILE

Message Meaning: Disk log file deleted

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Message Text	string	4096
filesize	Report File Size in Bytes	uint32	10

32030 - LOG_ID_SEND_FDS_STAT

Message ID: 32030

Message Description: LOG_ID_SEND_FDS_STAT

Message Meaning: FDS statistics sent

Type: Event

Category: SYSTEM**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

32031 - LOG_ID_VIEW_MEM_LOG_FAIL

Message ID: 32031**Message Description:** LOG_ID_VIEW_MEM_LOG_FAIL**Message Meaning:** Memory log access failed**Type:** Event**Category:** SYSTEM**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
msg	Message Text	string	4096

32032 - LOG_ID_DISK_DLP_ARCH_FULL

Message ID: 32032

Message Description: LOG_ID_DISK_DLP_ARCH_FULL

Message Meaning: DLP archive full

Type: Event

Category: SYSTEM

Severity: Emergency

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

32033 - LOG_ID_DISK_QUAR_FULL

Message ID: 32033

Message Description: LOG_ID_DISK_QUAR_FULL

Message Meaning: Quarantine full

Type: Event

Category: SYSTEM

Severity: Emergency

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

32034 - LOG_ID_DISK_REPORT_FULL

Message ID: 32034

Message Description: LOG_ID_DISK_REPORT_FULL

Message Meaning: Report full

Type: Event

Category: SYSTEM

Severity: Emergency

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

32035 - LOG_ID_VDOM_DISABLED

Message ID: 32035

Message Description: LOG_ID_VDOM_DISABLED

Message Meaning: VDOM disabled

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096

Log Field Name	Description	Data Type	Length
user	User Name	string	256
ui	User Interface	string	64
msg	Message Text	string	4096

32036 - LOG_ID_DISK_IPS_ARCH_FULL

Message ID: 32036

Message Description: LOG_ID_DISK_IPS_ARCH_FULL

Message Meaning: IPS archive full

Type: Event

Category: SYSTEM

Severity: Emergency

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

32037 - LOG_ID_DISK_LOG_FIRST_FULL

Message ID: 32037

Message Description: LOG_ID_DISK_LOG_FIRST_FULL

Message Meaning: Disk log full over first warning

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

32038 - LOG_ID_LOG_ROLL_FORTICRON**Message ID:** 32038**Message Description:** LOG_ID_LOG_ROLL_FORTICRON**Message Meaning:** Log rotation requested by FortiCron**Type:** Event**Category:** SYSTEM**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Message Text	string	4096
reason	Reason	string	256
log	Log Name for Log Rotation	string	32

32039 - LOG_ID_VIEW_MEM_LOG_SUCC

Message ID: 32039

Message Description: LOG_ID_VIEW_MEM_LOG_SUCC

Message Meaning: Memory logs viewed successfully

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
msg	Message Text	string	4096
log	Log Name for Log Rotation	string	32

32040 - LOG_ID_REPORT_DELETED

Message ID: 32040

Message Description: LOG_ID_REPORT_DELETED

Message Meaning: Report deleted

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Message Text	string	4096

32041 - LOG_ID_REPORT_DELETED_GUI

Message ID: 32041

Message Description: LOG_ID_REPORT_DELETED_GUI

Message Meaning: Report deleted from GUI

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10

Log Field Name	Description	Data Type	Length
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Message Text	string	4096

32042 - LOG_ID_MEM_LOG_SECOND_FULL

Message ID: 32042

Message Description: LOG_ID_MEM_LOG_SECOND_FULL

Message Meaning: Memory log full over second warning level

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

32043 - LOG_ID_MEM_LOG_FINAL_FULL

Message ID: 32043

Message Description: LOG_ID_MEM_LOG_FINAL_FULL

Message Meaning: Memory log full over final warning level

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

32044 - LOG_ID_LOG_DELETE

Message ID: 32044

Message Description: LOG_ID_LOG_DELETE

Message Meaning: Log deleted by user

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096
log	Log Name for Log Rotation	string	32

32045 - LOG_ID_MGR_LIC_EXPIRE

Message ID: 32045**Message Description:** LOG_ID_MGR_LIC_EXPIRE**Message Meaning:** FortiGuard management service license expiring**Type:** Event**Category:** SYSTEM**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

32048 - LOG_ID_SCHEDULE_EXPIRE

Message ID: 32048

Message Description: LOG_ID_SCHEDULE_EXPIRE

Message Meaning: One time schedule expiring

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

32049 - LOG_ID_FC_EXPIRE

Message ID: 32049

Message Description: LOG_ID_FC_EXPIRE

Message Meaning: FortiCloud license expiring

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

32050 - LOG_ID_POL_PKT_CAPTURE_FULL

Message ID: 32050

Message Description: LOG_ID_POL_PKT_CAPTURE_FULL

Message Meaning: Policy packet capture full

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

32051 - LOG_ID_LOG_UPLOAD

Message ID: 32051

Message Description: LOG_ID_LOG_UPLOAD

Message Meaning: Disk logs upload started

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096

Log Field Name	Description	Data Type	Length
ui	User Interface	string	64
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096

32052 - LOG_ID_UPLOAD_RUN_SCRIPT

Message ID: 32052

Message Description: LOG_ID_UPLOAD_RUN_SCRIPT

Message Meaning: Upload and run a script

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
msg	Message Text	string	4096

32053 - LOG_ID_ADMIN_MTNER_LOGIN_SUCC

Message ID: 32053

Message Description: LOG_ID_ADMIN_MTNER_LOGIN_SUCC

Message Meaning: Admin monitor login successful

Type: Event

Category: SYSTEM

Severity: Alert

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096
srcip	Source IP	ip	39
dstip	Destination IP	ip	39
profile	Profile Name	string	64
reason	Reason	string	256
sn	Serial Number	string	64
method		string	64

32054 - LOG_ID_ADMIN_MTNER_LOGOUT

Message ID: 32054

Message Description: LOG_ID_ADMIN_MTNER_LOGOUT

Message Meaning: Admin monitor logout successful

Type: Event

Category: SYSTEM**Severity:** Alert

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096
srcip	Source IP	ip	39
dstip	Destination IP	ip	39
reason	Reason	string	256
duration	Duration	uint32	10
sn	Serial Number	string	64
method		string	64
state		string	64

32057 - LOG_ID_VIEW_FAZ_LOG_FAIL

Message ID: 32057**Message Description:** LOG_ID_VIEW_FAZ_LOG_FAIL**Message Meaning:** FortiAnalyzer log access failed**Type:** Event

Category: SYSTEM**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
msg	Message Text	string	4096

32058 - LOG_ID_VIEW_FAZ_LOG_SUCC

Message ID: 32058**Message Description:** LOG_ID_VIEW_FAZ_LOG_SUCC**Message Meaning:** FortiAnalyzer logs viewed successfully**Type:** Event**Category:** SYSTEM**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
msg	Message Text	string	4096

32095 - LOG_ID_GUI_CHG_SUB_MODULE

Message ID: 32095

Message Description: LOG_ID_GUI_CHG_SUB_MODULE

Message Meaning: Admin performed an action from GUI

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64

Log Field Name	Description	Data Type	Length
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096

32097 - LOG_ID_DELETE_CAPTURE_PKT

Message ID: 32097

Message Description: LOG_ID_DELETE_CAPTURE_PKT

Message Meaning: Policy packet capture file deleted

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096

32100 - LOG_ID_FORTI_TOKEN_SYNC

Message ID: 32100

Message Description: LOG_ID_FORTI_TOKEN_SYNC**Message Meaning:** FortiToken synchronized**Type:** Event**Category:** SYSTEM**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
action	Action	string	65
msg	Message Text	string	4096

32102 - LOG_ID_CHG_CONFIG

Message ID: 32102**Message Description:** LOG_ID_CHG_CONFIG**Message Meaning:** Configuration changed**Type:** Event**Category:** SYSTEM**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
msg	Message Text	string	4096
module	Configuration Module Name	string	32
submodule	Configuration Sub-Module Name	string	32

32103 - LOG_ID_NEW_FIRMWARE

Message ID: 32103

Message Description: LOG_ID_NEW_FIRMWARE

Message Meaning: New firmware available on FortiGuard

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096

32104 - LOG_ID_CHG_CONFIG_GUI

Message ID: 32104

Message Description: LOG_ID_CHG_CONFIG_GUI

Message Meaning: Configuration changed via GUI

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64

Log Field Name	Description	Data Type	Length
msg	Message Text	string	4096
module	Configuration Module Name	string	32
submodule	Configuration Sub-Module Name	string	32

32105 - LOG_ID_NTP_SVR_STAUS_CHG_REACHABLE

Message ID: 32105

Message Description: LOG_ID_NTP_SVR_STAUS_CHG_REACHABLE

Message Meaning: NTP server status changes to reachable

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
msg	Message Text	string	4096
field		string	32

32106 - LOG_ID_NTP_SVR_STAUS_CHG_RESOLVABLE

Message ID: 32106

Message Description: LOG_ID_NTP_SVR_STAUS_CHG_RESOLVABLE

Message Meaning: NTP server status changes to resolvable

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
msg	Message Text	string	4096
field		string	32

32107 - LOG_ID_NTP_SVR_STAUS_CHG_UNRESOLVABLE

Message ID: 32107

Message Description: LOG_ID_NTP_SVR_STAUS_CHG_UNRESOLVABLE

Message Meaning: NTP server status changes to unresolvable

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
msg	Message Text	string	4096
field		string	32

32108 - LOG_ID_NTP_SVR_STAUS_CHG_UNREACHABLE

Message ID: 32108

Message Description: LOG_ID_NTP_SVR_STAUS_CHG_UNREACHABLE

Message Meaning: NTP server status changes to unreachable

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
msg	Message Text	string	4096
field		string	32

32109 - LOG_ID_UPD_SIGN_AV_DB

Message ID: 32109

Message Description: LOG_ID_UPD_SIGN_AV_DB

Message Meaning: Updating virus database

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

32110 - LOG_ID_UPD_SIGN_IPS_DB

Message ID: 32110

Message Description: LOG_ID_UPD_SIGN_IPS_DB

Message Meaning: IPS database updated

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

32111 - LOG_ID_UPD_SIGN_AVIPS_DB

Message ID: 32111

Message Description: LOG_ID_UPD_SIGN_AVIPS_DB

Message Meaning: AV, IPS, GeoIP, SRC-VIS, FortiFlow, URL White-list, Certificate databases updated

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

32113 - LOG_ID_UPD_SIGN_SRCVIS_DB

Message ID: 32113

Message Description: LOG_ID_UPD_SIGN_SRCVIS_DB

Message Meaning: SRC-VIS object updated

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

32114 - LOG_ID_UPD_SIGN_GEOIP_DB

Message ID: 32114

Message Description: LOG_ID_UPD_SIGN_GEOIP_DB

Message Meaning: GeoIP object updated

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256

Log Field Name	Description	Data Type	Length
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

32116 - LOG_ID_UPD_SIGN_AVPKG_FAILURE

Message ID: 32116

Message Description: LOG_ID_UPD_SIGN_AVPKG_FAILURE

Message Meaning: AV package update by SCP failed

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

32117 - LOG_ID_UPD_SIGN_AVPKG_SUCCESS

Message ID: 32117

Message Description: LOG_ID_UPD_SIGN_AVPKG_SUCCESS

Message Meaning: AV package update by SCP successful

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

32118 - LOG_ID_UPD_ADMIN_AV_DB

Message ID: 32118

Message Description: LOG_ID_UPD_ADMIN_AV_DB

Message Meaning: AV updated by admin

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
status	Status	string	23
msg	Message Text	string	4096

32119 - LOG_ID_UPD_SCANUNIT_AV_DB

Message ID: 32119

Message Description: LOG_ID_UPD_SCANUNIT_AV_DB

Message Meaning: AV database updated by scanunit

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

32120 - LOG_ID_RPT_ADD_DATASET

Message ID: 32120

Message Description: LOG_ID_RPT_ADD_DATASET

Message Meaning: Report data set added

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
msg	Message Text	string	4096
name	Name	string	128

32122 - LOG_ID_RPT_DEL_DATASET

Message ID: 32122

Message Description: LOG_ID_RPT_DEL_DATASET

Message Meaning: Report data set deleted

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
msg	Message Text	string	4096
name	Name	string	128

32125 - LOG_ID_RPT_ADD_CHART

Message ID: 32125

Message Description: LOG_ID_RPT_ADD_CHART

Message Meaning: Report chart widget added

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
msg	Message Text	string	4096
name	Name	string	128

32126 - LOG_ID_RPT_DEL_CHART

Message ID: 32126

Message Description: LOG_ID_RPT_DEL_CHART

Message Meaning: Report chart widget deleted

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
msg	Message Text	string	4096
name	Name	string	128

32129 - LOG_ID_ADD_GUEST

Message ID: 32129

Message Description: LOG_ID_ADD_GUEST

Message Meaning: Guest user added

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256

Log Field Name	Description	Data Type	Length
ui	User Interface	string	64
status	Status	string	23
msg	Message Text	string	4096
name	Name	string	128

32130 - LOG_ID_CHG_USER

Message ID: 32130

Message Description: LOG_ID_CHG_USER

Message Meaning: User changed

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
msg	Message Text	string	4096
new_status	New Status	string	512
old_status	Original Status	string	512
name	Name	string	128
passwd	Password	string	20

32131 - LOG_ID_DEL_GUEST

Message ID: 32131

Message Description: LOG_ID_DEL_GUEST

Message Meaning: Guest user deleted

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
status	Status	string	23
msg	Message Text	string	4096
name	Name	string	128

32132 - LOG_ID_ADD_USER

Message ID: 32132

Message Description: LOG_ID_ADD_USER

Message Meaning: Local user added

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
status	Status	string	23
msg	Message Text	string	4096
name	Name	string	128

32138 - LOG_ID_REBOOT

Message ID: 32138

Message Description: LOG_ID_REBOOT

Message Meaning: Device rebooted

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

32139 - LOG_ID_WAKE_ON_LAN

Message ID: 32139

Message Description: LOG_ID_WAKE_ON_LAN

Message Meaning: Wake on LAN device

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096

Log Field Name	Description	Data Type	Length
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

32140 - LOG_ID_TIME_USER_SETTING_CHG

Message ID: 32140

Message Description: LOG_ID_TIME_USER_SETTING_CHG

Message Meaning: Global time setting changed by user

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096
srcip	Source IP	ip	39
field		string	32

32141 - LOG_ID_TIME_NTP_SETTING_CHG

Message ID: 32141

Message Description: LOG_ID_TIME_NTP_SETTING_CHG

Message Meaning: Global time setting changed by NTP

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
msg	Message Text	string	4096
field		string	32

32142 - LOG_ID_BACKUP_CONF

Message ID: 32142

Message Description: LOG_ID_BACKUP_CONF

Message Meaning: System configuration backed up

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096

32143 - LOG_ID_BACKUP_CONF_BY_SCP

Message ID: 32143

Message Description: LOG_ID_BACKUP_CONF_BY_SCP

Message Meaning: System configuration backed up by SCP

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

32144 - LOG_ID_BACKUP_CONF_ERROR

Message ID: 32144

Message Description: LOG_ID_BACKUP_CONF_ERROR

Message Meaning: System configuration backed up error

Type: Event

Category: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096

Log Field Name	Description	Data Type	Length
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096

32145 - LOG_ID_BACKUP_CONF_ALERT

Message ID: 32145

Message Description: LOG_ID_BACKUP_CONF_ALERT

Message Meaning: System configuration backed up alert

Type: Event

Category: SYSTEM

Severity: Alert

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096

32146 - LOG_ID_TIME_PTP_SETTING_CHG

Message ID: 32146

Message Description: LOG_ID_TIME_PTP_SETTING_CHG**Message Meaning:** Global time setting changed by PTP**Type:** Event**Category:** SYSTEM**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096
field		string	32

32148 - LOG_ID_GET_CRL

Message ID: 32148**Message Description:** LOG_ID_GET_CRL**Message Meaning:** CRL update requested**Type:** Event**Category:** SYSTEM**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096
crl		string	4096

32149 - LOG_ID_COMMAND_FAIL

Message ID: 32149

Message Description: LOG_ID_COMMAND_FAIL

Message Meaning: Command failed

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
msg	Message Text	string	4096

32151 - LOG_ID_ADD_IP6_LOCAL_POL

Message ID: 32151

Message Description: LOG_ID_ADD_IP6_LOCAL_POL

Message Meaning: IPv6 firewall local in policy added

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
act		string	16
daddr		string	80
dintf		string	36
iptype		string	16

32152 - LOG_ID_CHG_IP6_LOCAL_POL

Message ID: 32152

Message Description: LOG_ID_CHG_IP6_LOCAL_POL

Message Meaning: IPv6 firewall local in policy setting changed

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
act		string	16
daddr		string	80
dintf		string	36
iptype		string	16

32153 - LOG_ID_DEL_IP6_LOCAL_POL

Message ID: 32153

Message Description: LOG_ID_DEL_IP6_LOCAL_POL

Message Meaning: IPv6 firewall local in policy deleted

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
act		string	16
daddr		string	80
dintf		string	36
iptype		string	16

32155 - LOG_ID_ACT_FTOKEN_REQ

Message ID: 32155

Message Description: LOG_ID_ACT_FTOKEN_REQ

Message Meaning: FortiToken activation requested

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096
serialno	Serial Number	string	16

32156 - LOG_ID_ACT_FTOKEN_SUCC

Message ID: 32156

Message Description: LOG_ID_ACT_FTOKEN_SUCC

Message Meaning: FortiToken activation successful

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096

Log Field Name	Description	Data Type	Length
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096
serialno	Serial Number	string	16

32157 - LOG_ID_SYNC_FTOKEN_SUCC

Message ID: 32157

Message Description: LOG_ID_SYNC_FTOKEN_SUCC

Message Meaning: FortiToken re-synchronized

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096
serialno	Serial Number	string	16

32158 - LOG_ID_SYNC_FTOKEN_FAIL

Message ID: 32158

Message Description: LOG_ID_SYNC_FTOKEN_FAIL

Message Meaning: FortiToken re-synchronization failed

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096
serialno	Serial Number	string	16

32159 - LOG_ID_ACT_FTOKEN_FAIL

Message ID: 32159

Message Description: LOG_ID_ACT_FTOKEN_FAIL

Message Meaning: FortiToken activation failed

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096
serialno	Serial Number	string	16

32160 - LOG_ID_FTM_PUSH_SUCC

Message ID: 32160**Message Description:** LOG_ID_FTM_PUSH_SUCC**Message Meaning:** FortiToken mobile push message succeeded**Type:** Event**Category:** SYSTEM**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

32161 - LOG_ID_FTM_PUSH_FAIL

Message ID: 32161

Message Description: LOG_ID_FTM_PUSH_FAIL

Message Meaning: FortiToken mobile push message failed

Type: Event

Category: SYSTEM

Severity: Alert

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

32168 - LOG_ID_REACH_VDOM_LIMIT

Message ID: 32168

Message Description: LOG_ID_REACH_VDOM_LIMIT**Message Meaning:** VDOM limit reached**Type:** Event**Category:** SYSTEM**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
msg	Message Text	string	4096

32169 - LOG_ID_ALARM_DLP_DB

Message ID: 32169**Message Description:** LOG_ID_ALARM_DLP_DB**Message Meaning:** DLP database space alarm**Type:** Event**Category:** SYSTEM**Severity:** Alert

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Message Text	string	4096

32170 - LOG_ID_ALARM_MSG

Message ID: 32170

Message Description: LOG_ID_ALARM_MSG

Message Meaning: Alarm created

Type: Event

Category: SYSTEM

Severity: Alert

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	4096
action	Action	string	65
msg	Message Text	string	4096
alarmid	Alarm ID	uint32	10
groupid	User Group ID	uint32	10

32171 - LOG_ID_ALARM_ACK

Message ID: 32171

Message Description: LOG_ID_ALARM_ACK

Message Meaning: Alarm acknowledged

Type: Event

Category: SYSTEM

Severity: Alert

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096
alarmid	Alarm ID	uint32	10
acktime	Alarm Acknowledge Time	string	24

32172 - LOG_ID_ADD_IP4_LOCAL_POL

Message ID: 32172

Message Description: LOG_ID_ADD_IP4_LOCAL_POL

Message Meaning: IPv4 firewall local in policy added

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
act		string	16
daddr		string	80
dintf		string	36
iptype		string	16

32173 - LOG_ID_CHG_IP4_LOCAL_POL

Message ID: 32173

Message Description: LOG_ID_CHG_IP4_LOCAL_POL

Message Meaning: IPv4 firewall local in policy's setting changed

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
act		string	16
daddr		string	80
dintf		string	36
iptype		string	16

32174 - LOG_ID_DEL_IP4_LOCAL_POL

Message ID: 32174

Message Description: LOG_ID_DEL_IP4_LOCAL_POL

Message Meaning: IPv4 firewall local in policy deleted

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
act		string	16
daddr		string	80
dintf		string	36
iptype		string	16

32190 - LOG_ID_UPT_INVALID_IMG

Message ID: 32190

Message Description: LOG_ID_UPT_INVALID_IMG

Message Meaning: Invalid image loaded

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256

Log Field Name	Description	Data Type	Length
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

32191 - LOG_ID_UPT_INVALID_IMG_CC

Message ID: 32191

Message Description: LOG_ID_UPT_INVALID_IMG_CC

Message Meaning: Image with invalid CC signature loaded

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

32192 - LOG_ID_UPT_INVALID_IMG_RSA

Message ID: 32192

Message Description: LOG_ID_UPT_INVALID_IMG_RSA

Message Meaning: Image with invalid RSA signature loaded

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

32193 - LOG_ID_UPT_IMG_RSA

Message ID: 32193

Message Description: LOG_ID_UPT_IMG_RSA

Message Meaning: Image with valid RSA signature loaded

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

32194 - LOG_ID_UPT_IMG_FAIL

Message ID: 32194

Message Description: LOG_ID_UPT_IMG_FAIL

Message Meaning: System upgrade failed due to file operation failure

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

32199 - LOG_ID_RESTORE_IMG_USB

Message ID: 32199

Message Description: LOG_ID_RESTORE_IMG_USB

Message Meaning: Image restored from USB

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

32200 - LOG_ID_SHUTDOWN

Message ID: 32200

Message Description: LOG_ID_SHUTDOWN

Message Meaning: Device shutdown

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

32201 - LOG_ID_LOAD_IMG_SUCC

Message ID: 32201

Message Description: LOG_ID_LOAD_IMG_SUCC

Message Meaning: Image loaded successfully

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096

32202 - LOG_ID_RESTORE_IMG

Message ID: 32202

Message Description: LOG_ID_RESTORE_IMG

Message Meaning: Image restored

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096

32203 - LOG_ID_RESTORE_CONF

Message ID: 32203

Message Description: LOG_ID_RESTORE_CONF

Message Meaning: Configuration restored

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

32204 - LOG_ID_RESTORE_FGD_SVR

Message ID: 32204

Message Description: LOG_ID_RESTORE_FGD_SVR

Message Meaning: FortiGuard service restored

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

32205 - LOG_ID_RESTORE_VDOM_LIC

Message ID: 32205

Message Description: LOG_ID_RESTORE_VDOM_LIC

Message Meaning: VM license restored

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

32206 - LOG_ID_RESTORE_SCRIPT

Message ID: 32206

Message Description: LOG_ID_RESTORE_SCRIPT

Message Meaning: Script restored from management station

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

32207 - LOG_ID_RETRIEVE_CONF_LIST

Message ID: 32207

Message Description: LOG_ID_RETRIEVE_CONF_LIST

Message Meaning: Configuration list retrieval failed

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

32208 - LOG_ID_IMP_PKCS12_CERT

Message ID: 32208

Message Description: LOG_ID_IMP_PKCS12_CERT

Message Meaning: PKCS12 certificate imported

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256

Log Field Name	Description	Data Type	Length
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

32209 - LOG_ID_RESTORE_USR_DEF_IPS

Message ID: 32209

Message Description: LOG_ID_RESTORE_USR_DEF_IPS

Message Meaning: IPS custom signatures restored

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096

32210 - LOG_ID_BACKUP_IMG_SUCC

Message ID: 32210

Message Description: LOG_ID_BACKUP_IMG_SUCC

Message Meaning: Firmware image backed up successfully

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096

32211 - LOG_ID_UPLOAD_REVISION

Message ID: 32211

Message Description: LOG_ID_UPLOAD_REVISION

Message Meaning: Revision uploaded to flash disk

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096

32212 - LOG_ID_DEL_REVISION

Message ID: 32212

Message Description: LOG_ID_DEL_REVISION

Message Meaning: Revision deleted

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096

32213 - LOG_ID_RESTORE_TEMPLATE

Message ID: 32213

Message Description: LOG_ID_RESTORE_TEMPLATE

Message Meaning: Template restored

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	4096
user	User Name	string	256
action	Action	string	65
msg	Message Text	string	4096

32214 - LOG_ID_RESTORE_FILE

Message ID: 32214

Message Description: LOG_ID_RESTORE_FILE

Message Meaning: File restore failed

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
action	Action	string	65
msg	Message Text	string	4096

32215 - LOG_ID_UPT_IMG

Message ID: 32215

Message Description: LOG_ID_UPT_IMG

Message Meaning: Image updated

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

32217 - LOG_ID_UPD_IPS

Message ID: 32217

Message Description: LOG_ID_UPD_IPS

Message Meaning: IPS package - Admin update successful

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
status	Status	string	23
msg	Message Text	string	4096

32218 - LOG_ID_UPD_DLP

Message ID: 32218

Message Description: LOG_ID_UPD_DLP

Message Meaning: DLP fingerprint database update via SCP failed

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

32219 - LOG_ID_BACKUP_OUTPUT

Message ID: 32219

Message Description: LOG_ID_BACKUP_OUTPUT

Message Meaning: Error output backup via SCP successful

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

32220 - LOG_ID_BACKUP_COMMAND

Message ID: 32220

Message Description: LOG_ID_BACKUP_COMMAND

Message Meaning: Batch mode command output backup via SCP successful

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

32221 - LOG_ID_UPD_VDOM_LIC

Message ID: 32221

Message Description: LOG_ID_UPD_VDOM_LIC

Message Meaning: VM license installed via SCP

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

32222 - LOG_ID_GLB_SETTING_CHG

Message ID: 32222

Message Description: LOG_ID_GLB_SETTING_CHG

Message Meaning: Global setting changed

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096
field		string	32
old_value	Original Virtual Domain name	string	128
new_value	New Virtual Domain Name	string	128

32223 - LOG_ID_BACKUP_USER_DEF_IPS

Message ID: 32223

Message Description: LOG_ID_BACKUP_USER_DEF_IPS

Message Meaning: IPS custom signatures backup success

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096

32224 - LOG_ID_BACKUP_DISK_LOG

Message ID: 32224

Message Description: LOG_ID_BACKUP_DISK_LOG

Message Meaning: Disk logs backed up

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65

Log Field Name	Description	Data Type	Length
msg	Message Text	string	4096
file	File Name for Generated Report?	string	256
hash	Hash Value of Downloaded File	string	32

32225 - LOG_ID_DEL_ALL_REVISION

Message ID: 32225

Message Description: LOG_ID_DEL_ALL_REVISION

Message Meaning: Revision database reset due to data corruption

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096

32226 - LOG_ID_LOAD_IMG_FAIL

Message ID: 32226

Message Description: LOG_ID_LOAD_IMG_FAIL

Message Meaning: Image failed to load

Type: Event**Category:** SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096

32227 - LOG_ID_UPD_DLP_FAIL

Message ID: 32227**Message Description:** LOG_ID_UPD_DLP_FAIL**Message Meaning:** DLP fingerprint database failed to update by SCP**Type:** Event**Category:** SYSTEM**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

32228 - LOG_ID_LOAD_IMG_FAIL_WRONG_IMG

Message ID: 32228

Message Description: LOG_ID_LOAD_IMG_FAIL_WRONG_IMG

Message Meaning: Firmware image loaded incorrect

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
action	Action	string	65
msg	Message Text	string	4096

32229 - LOG_ID_LOAD_IMG_FAIL_NO_RSA

Message ID: 32229

Message Description: LOG_ID_LOAD_IMG_FAIL_NO_RSA

Message Meaning: Firmware image without valid RSA signature loaded

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
action	Action	string	65
msg	Message Text	string	4096

32230 - LOG_ID_LOAD_IMG_FAIL_INVALID_RSA

Message ID: 32230

Message Description: LOG_ID_LOAD_IMG_FAIL_INVALID_RSA

Message Meaning: Firmware image with invalid RSA signature loaded

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
action	Action	string	65
msg	Message Text	string	4096

32231 - LOG_ID_RESTORE_FGD_SVR_FAIL

Message ID: 32231

Message Description: LOG_ID_RESTORE_FGD_SVR_FAIL

Message Meaning: FortiGuard service failed to restore

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

32232 - LOG_ID_RESTORE_VDOM_LIC_FAIL

Message ID: 32232

Message Description: LOG_ID_RESTORE_VDOM_LIC_FAIL

Message Meaning: VM license failed to restore

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

32233 - LOG_ID_BACKUP_IMG_FAIL

Message ID: 32233

Message Description: LOG_ID_BACKUP_IMG_FAIL

Message Meaning: Firmware image backup failed

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256

Log Field Name	Description	Data Type	Length
ui	User Interface	string	64
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096

32234 - LOG_ID_RESTORE_IMG_INVALID_CC

Message ID: 32234

Message Description: LOG_ID_RESTORE_IMG_INVALID_CC

Message Meaning: Image with invalid CC signature restored

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
action	Action	string	65
msg	Message Text	string	4096

32235 - LOG_ID_RESTORE_IMG_FORTIGUARD

Message ID: 32235

Message Description: LOG_ID_RESTORE_IMG_FORTIGUARD

Message Meaning: Image restored from FortiGuard Management

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
action	Action	string	65
msg	Message Text	string	4096

32236 - LOG_ID_BACKUP_MEM_LOG

Message ID: 32236

Message Description: LOG_ID_BACKUP_MEM_LOG

Message Meaning: Memory logs backed up

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

32237 - LOG_ID_BACKUP_MEM_LOG_FAIL

Message ID: 32237

Message Description: LOG_ID_BACKUP_MEM_LOG_FAIL

Message Meaning: Memory logs failed to back up

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

32238 - LOG_ID_BACKUP_DISK_LOG_FAIL

Message ID: 32238

Message Description: LOG_ID_BACKUP_DISK_LOG_FAIL

Message Meaning: Disk logs failed to back up

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

32239 - LOG_ID_BACKUP_DISK_LOG_USB

Message ID: 32239

Message Description: LOG_ID_BACKUP_DISK_LOG_USB

Message Meaning: Disk logs backed up to USB

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

32240 - LOG_ID_SYS_USB_MODE

Message ID: 32240

Message Description: LOG_ID_SYS_USB_MODE

Message Meaning: System operating in USB mode

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096

32241 - LOG_ID_BACKUP_DISK_LOG_USB_FAIL

Message ID: 32241

Message Description: LOG_ID_BACKUP_DISK_LOG_USB_FAIL

Message Meaning: Disk logs failed to back up to USB

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

32242 - LOG_ID_UPD_VDOM_LIC_FAIL

Message ID: 32242

Message Description: LOG_ID_UPD_VDOM_LIC_FAIL

Message Meaning: VM license failed to install via SCP

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64

Log Field Name	Description	Data Type	Length
action	Action	string	65
msg	Message Text	string	4096

32243 - LOG_ID_UPD_IPS_SCP

Message ID: 32243

Message Description: LOG_ID_UPD_IPS_SCP

Message Meaning: IPS package updated via SCP

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

32244 - LOG_ID_UPD_IPS_SCP_FAIL

Message ID: 32244

Message Description: LOG_ID_UPD_IPS_SCP_FAIL

Message Meaning: IPS package failed to update via SCP

Type: Event**Category:** SYSTEM**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

32245 - LOG_ID_BACKUP_USER_DEF_IPS_FAIL

Message ID: 32245**Message Description:** LOG_ID_BACKUP_USER_DEF_IPS_FAIL**Message Meaning:** IPS custom signatures backup failed**Type:** Event**Category:** SYSTEM**Severity:** Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096

32246 - LOG_ID_RESTORE_USR_DEF_IPS_CRITICAL

Message ID: 32246

Message Description: LOG_ID_RESTORE_USR_DEF_IPS_CRITICAL

Message Meaning: IPS custom signatures restored critical

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096

32247 - LOG_ID_SSH_NEGOTIATION_FAILURE

Message ID: 32247

Message Description: LOG_ID_SSH_NEGOTIATION_FAILURE

Message Meaning: SSH protocol cannot be negotiated

Type: Event

Category: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096
port	Port Number	uint16	5
addr	IP Address	string	80

32248 - LOG_ID_IMG_NOT_SIGNED_NOT_CONFIRM

Message ID: 32248

Message Description: LOG_ID_IMG_NOT_SIGNED_NOT_CONFIRM

Message Meaning: Log description is not available

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
action	Action	string	65
msg	Message Text	string	4096

32249 - LOG_ID_IMG_NOT_SIGNED

Message ID: 32249

Message Description: LOG_ID_IMG_NOT_SIGNED

Message Meaning: Log description is not available

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
action	Action	string	65
msg	Message Text	string	4096

32252 - LOG_ID_FACTORY_RESET

Message ID: 32252

Message Description: LOG_ID_FACTORY_RESET

Message Meaning: Factory settings reset

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

32253 - LOG_ID_FORMAT_RAID

Message ID: 32253

Message Description: LOG_ID_FORMAT_RAID

Message Meaning: RAID disk formatted

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64

Log Field Name	Description	Data Type	Length
action	Action	string	65
msg	Message Text	string	4096

32254 - LOG_ID_ENABLE_RAID

Message ID: 32254

Message Description: LOG_ID_ENABLE_RAID

Message Meaning: RAID enabled

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

32255 - LOG_ID_DISABLE_RAID

Message ID: 32255

Message Description: LOG_ID_DISABLE_RAID

Message Meaning: RAID disabled

Type: Event**Category:** SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

32300 - LOG_ID_UPLOAD_RPT_IMG

Message ID: 32300**Message Description:** LOG_ID_UPLOAD_RPT_IMG**Message Meaning:** Report image file uploaded**Type:** Event**Category:** SYSTEM**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096
reason	Reason	string	256

32301 - LOG_ID_ADD_VDOM

Message ID: 32301

Message Description: LOG_ID_ADD_VDOM

Message Meaning: VDOM added

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

32302 - LOG_ID_DEL_VDOM

Message ID: 32302

Message Description: LOG_ID_DEL_VDOM

Message Meaning: VDOM deleted

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64

Log Field Name	Description	Data Type	Length
action	Action	string	65
msg	Message Text	string	4096

32545 - LOG_ID_SYS_RESTART

Message ID: 32545

Message Description: LOG_ID_SYS_RESTART

Message Meaning: Scheduled daily reboot started

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

32546 - LOG_ID_APPLICATION_CRASH

Message ID: 32546

Message Description: LOG_ID_APPLICATION_CRASH

Message Meaning: Application crashed

Type: Event**Category:** SYSTEM**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Message Text	string	4096

32547 - LOG_ID_AUTOSCRIPRT_START

Message ID: 32547**Message Description:** LOG_ID_AUTOSCRIPRT_START**Message Meaning:** Autoscript start**Type:** Event**Category:** SYSTEM**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

32548 - LOG_ID_AUTOSCRIPT_STOP

Message ID: 32548

Message Description: LOG_ID_AUTOSCRIPT_STOP

Message Meaning: Autoscript stop

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096

Log Field Name	Description	Data Type	Length
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

32549 - LOG_ID_AUTOSCRIPT_STOP_AUTO

Message ID: 32549

Message Description: LOG_ID_AUTOSCRIPT_STOP_AUTO

Message Meaning: Autoscript stop automatically

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

32550 - LOG_ID_AUTOSCRIPT_DELETE_RSLT

Message ID: 32550

Message Description: LOG_ID_AUTOSCRIPT_DELETE_RSLT

Message Meaning: Autoscript delete result

Type: Event

Category: SYSTEM**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

32551 - LOG_ID_AUTOSCRIPRT_BACKUP_RSLT

Message ID: 32551**Message Description:** LOG_ID_AUTOSCRIPRT_BACKUP_RSLT**Message Meaning:** Autoscript backup result**Type:** Event**Category:** SYSTEM**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

32552 - LOG_ID_AUTOSCRIPT_CHECK_STATUS

Message ID: 32552

Message Description: LOG_ID_AUTOSCRIPT_CHECK_STATUS

Message Meaning: Autoscript check status

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096

Log Field Name	Description	Data Type	Length
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

32553 - LOG_ID_AUTOSCRIPPT_STOP_REACH_LIMIT

Message ID: 32553

Message Description: LOG_ID_AUTOSCRIPPT_STOP_REACH_LIMIT

Message Meaning: Autoscript stop due to limit reached

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

32561 - LOG_ID_ADMIN_LOGOUT_DISCONNECT

Message ID: 32561

Message Description: LOG_ID_ADMIN_LOGOUT_DISCONNECT

Message Meaning: Admin disconnected

Type: Event

Category: SYSTEM**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096
srcip	Source IP	ip	39
dstip	Destination IP	ip	39
reason	Reason	string	256
duration	Duration	uint32	10
sn	Serial Number	string	64
method		string	64
state		string	64

32562 - LOG_ID_STORE_CONF_FAIL_SPACE

Message ID: 32562**Message Description:** LOG_ID_STORE_CONF_FAIL_SPACE**Message Meaning:** Store config failed - not enough flash space**Type:** Event

Category: SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

32564 - LOG_ID_RESTORE_CONF_FAIL

Message ID: 32564**Message Description:** LOG_ID_RESTORE_CONF_FAIL**Message Meaning:** Configuration failed to restore**Type:** Event**Category:** SYSTEM**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

32565 - LOG_ID_RESTORE_CONF_BY_MGMT

Message ID: 32565

Message Description: LOG_ID_RESTORE_CONF_BY_MGMT

Message Meaning: Configuration restored from management station

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

32566 - LOG_ID_RESTORE_CONF_BY_SCP

Message ID: 32566

Message Description: LOG_ID_RESTORE_CONF_BY_SCP

Message Meaning: Configuration restored by SCP

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

32567 - LOG_ID_RESTORE_CONF_BY_USB

Message ID: 32567

Message Description: LOG_ID_RESTORE_CONF_BY_USB

Message Meaning: Configuration restored by USB

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

32568 - LOG_ID_DEL_REVISION_DB

Message ID: 32568

Message Description: LOG_ID_DEL_REVISION_DB

Message Meaning: Revision Database deletion

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096

32569 - LOG_ID_FSW_SWITCH_LOG_EVENT

Message ID: 32569

Message Description: LOG_ID_FSW_SWITCH_LOG_EVENT

Message Meaning: Switch-Controller

Type: Event

Category: SYSTEM

Severity: Unknown

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64

Log Field Name	Description	Data Type	Length
msg	Message Text	string	4096
cfgtid	config transaction id	uint32	10
cfgpath	configuration path	string	128
cfgattr	configuration attribute	string	4096
cfgobj	configuration object	string	256

32570 - LOG_ID_ADMIN_MTNER_LOGOUT_DISCONNECT

Message ID: 32570

Message Description: LOG_ID_ADMIN_MTNER_LOGOUT_DISCONNECT

Message Meaning: Admin monitor disconnected

Type: Event

Category: SYSTEM

Severity: Alert

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096

Log Field Name	Description	Data Type	Length
srcip	Source IP	ip	39
dstip	Destination IP	ip	39
reason	Reason	string	256
duration	Duration	uint32	10
sn	Serial Number	string	64
method		string	64
state		string	64

32601 - LOG_ID_FGT_SWITCH_LOG_DISCOVER

Message ID: 32601

Message Description: LOG_ID_FGT_SWITCH_LOG_DISCOVER

Message Meaning: Switch-Controller discovered

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
msg	Message Text	string	4096

32602 - LOG_ID_FGT_SWITCH_LOG_AUTH

Message ID: 32602

Message Description: LOG_ID_FGT_SWITCH_LOG_AUTH

Message Meaning: Switch-Controller authorized

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
msg	Message Text	string	4096

32603 - LOG_ID_FGT_SWITCH_LOG_DEAUTH

Message ID: 32603

Message Description: LOG_ID_FGT_SWITCH_LOG_DEAUTH

Message Meaning: Switch-Controller deauthorized

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
msg	Message Text	string	4096

32604 - LOG_ID_FGT_SWITCH_LOG_DELETE

Message ID: 32604

Message Description: LOG_ID_FGT_SWITCH_LOG_DELETE

Message Meaning: Switch-Controller deleted

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
msg	Message Text	string	4096

32605 - LOG_ID_FGT_SWITCH_LOG_TUNNEL_UP

Message ID: 32605

Message Description: LOG_ID_FGT_SWITCH_LOG_TUNNEL_UP

Message Meaning: Switch-Controller Tunnel Up

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
msg	Message Text	string	4096

32606 - LOG_ID_FGT_SWITCH_LOG_TUNNEL_DOWN

Message ID: 32606

Message Description: LOG_ID_FGT_SWITCH_LOG_TUNNEL_DOWN

Message Meaning: Switch-Controller Tunnel Down

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
msg	Message Text	string	4096

32607 - LOG_ID_FGT_SWITCH_PUSH_IMAGE

Message ID: 32607

Message Description: LOG_ID_FGT_SWITCH_PUSH_IMAGE

Message Meaning: Image push to FortiSwitch

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
msg	Message Text	string	4096

32608 - LOG_ID_FGT_SWITCH_STAGE_IMAGE

Message ID: 32608

Message Description: LOG_ID_FGT_SWITCH_STAGE_IMAGE

Message Meaning: Image stage to FortiSwitch

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
msg	Message Text	string	4096

32609 - LOG_ID_FGT_SWITCH_DISABLE_DISCOVERY

Message ID: 32609

Message Description: LOG_ID_FGT_SWITCH_DISABLE_DISCOVERY

Message Meaning: Disable FortiSwitch Discovery

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
msg	Message Text	string	4096

32610 - LOG_ID_FGT_SWITCH_LOG_WARNING

Message ID: 32610

Message Description: LOG_ID_FGT_SWITCH_LOG_WARNING

Message Meaning: Switch-Controller warning

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
msg	Message Text	string	4096

32611 - LOG_ID_FGT_SWITCH_EXPORT_POOL

Message ID: 32611

Message Description: LOG_ID_FGT_SWITCH_EXPORT_POOL

Message Meaning: Export port to pool

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
msg	Message Text	string	4096

32612 - LOG_ID_FGT_SWITCH_EXPORT_VDOM

Message ID: 32612

Message Description: LOG_ID_FGT_SWITCH_EXPORT_VDOM

Message Meaning: Export port to vdom

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
msg	Message Text	string	4096

32613 - LOG_ID_FGT_SWITCH_REQUEST_PORT

Message ID: 32613

Message Description: LOG_ID_FGT_SWITCH_REQUEST_PORT

Message Meaning: Request port from pool

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
msg	Message Text	string	4096

32614 - LOG_ID_FGT_SWITCH_RETURN_PORT

Message ID: 32614

Message Description: LOG_ID_FGT_SWITCH_RETURN_PORT

Message Meaning: Return port to pool

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
msg	Message Text	string	4096

32615 - LOG_ID_FGT_SWITCH_MAC_ADD

Message ID: 32615

Message Description: LOG_ID_FGT_SWITCH_MAC_ADD

Message Meaning: FortiSwitch MAC add

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
msg	Message Text	string	4096

32616 - LOG_ID_FGT_SWITCH_MAC_DEL

Message ID: 32616

Message Description: LOG_ID_FGT_SWITCH_MAC_DEL

Message Meaning: FortiSwitch MAC delete

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
msg	Message Text	string	4096

32617 - LOG_ID_FGT_SWITCH_MAC_MOVE

Message ID: 32617

Message Description: LOG_ID_FGT_SWITCH_MAC_MOVE

Message Meaning: FortiSwitch MAC move

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
msg	Message Text	string	4096

32693 - LOG_ID_FGT_SWITCH_GROUP_SWC

Message ID: 32693

Message Description: LOG_ID_FGT_SWITCH_GROUP_SWC

Message Meaning: FortiSwitch switch controller

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
msg	Message Text	string	4096
cfgtid	config transaction id	uint32	10
cfgpath	configuration path	string	128
cfgattr	configuration attribute	string	4096
cfgobj	configuration object	string	256

32694 - LOG_ID_FGT_SWITCH_GROUP_POE

Message ID: 32694

Message Description: LOG_ID_FGT_SWITCH_GROUP_POE

Message Meaning: FortiSwitch PoE

Type: Event

Category: SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
msg	Message Text	string	4096
cfgtid	config transaction id	uint32	10
cfgpath	configuration path	string	128
cfgattr	configuration attribute	string	4096
cfgobj	configuration object	string	256

32695 - LOG_ID_FGT_SWITCH_GROUP_LINK

Message ID: 32695**Message Description:** LOG_ID_FGT_SWITCH_GROUP_LINK**Message Meaning:** FortiSwitch link**Type:** Event**Category:** SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
msg	Message Text	string	4096
cfgtid	config transaction id	uint32	10
cfgpath	configuration path	string	128
cfgattr	configuration attribute	string	4096
cfgobj	configuration object	string	256

32696 - LOG_ID_FGT_SWITCH_GROUP_STP

Message ID: 32696

Message Description: LOG_ID_FGT_SWITCH_GROUP_STP

Message Meaning: FortiSwitch spanning Tree

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
msg	Message Text	string	4096
cfgtid	config transaction id	uint32	10
cfgpath	configuration path	string	128
cfgattr	configuration attribute	string	4096
cfgobj	configuration object	string	256

32697 - LOG_ID_FGT_SWITCH_GROUP_SWITCH

Message ID: 32697

Message Description: LOG_ID_FGT_SWITCH_GROUP_SWITCH

Message Meaning: FortiSwitch switch

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
msg	Message Text	string	4096
cfgtid	config transaction id	uint32	10
cfgpath	configuration path	string	128
cfgattr	configuration attribute	string	4096
cfgobj	configuration object	string	256

32698 - LOG_ID_FGT_SWITCH_GROUP_ROUTER

Message ID: 32698

Message Description: LOG_ID_FGT_SWITCH_GROUP_ROUTER

Message Meaning: FortiSwitch router

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096

Log Field Name	Description	Data Type	Length
user	User Name	string	256
ui	User Interface	string	64
msg	Message Text	string	4096
cfgtid	config transaction id	uint32	10
cfgpath	configuration path	string	128
cfgattr	configuration attribute	string	4096
cfgobj	configuration object	string	256

32699 - LOG_ID_FGT_SWITCH_GROUP_SYSTEM

Message ID: 32699

Message Description: LOG_ID_FGT_SWITCH_GROUP_SYSTEM

Message Meaning: FortiSwitch system

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
msg	Message Text	string	4096

Log Field Name	Description	Data Type	Length
cfgtid	config transaction id	uint32	10
cfgpath	configuration path	string	128
cfgattr	configuration attribute	string	4096
cfgobj	configuration object	string	256

32700 - LOG_ID_DPDK_EARLY_INIT_FAIL

Message ID: 32700

Message Description: LOG_ID_DPDK_EARLY_INIT_FAIL

Message Meaning: Log description is not available

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

34415 - LOG_ID_NP6_IPSEC_ENGINE_BUSY

Message ID: 34415

Message Description: LOG_ID_NP6_IPSEC_ENGINE_BUSY

Message Meaning: NP6 IPsec engine is busy

Type: Event

Category: SYSTEM**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

34416 - LOG_ID_NP6_IPSEC_ENGINE_POSSIBLY_LOCKUP

Message ID: 34416**Message Description:** LOG_ID_NP6_IPSEC_ENGINE_POSSIBLY_LOCKUP**Message Meaning:** NP6 IPsec engine is possibly locked up**Type:** Event**Category:** SYSTEM**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

34417 - LOG_ID_NP6_IPSEC_ENGINE_LOCKUP

Message ID: 34417

Message Description: LOG_ID_NP6_IPSEC_ENGINE_LOCKUP

Message Meaning: NP6 IPsec engine is locked up

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

34418 - LOG_ID_NP6_HPE_PACKET_DROP

Message ID: 34418

Message Description: LOG_ID_NP6_HPE_PACKET_DROP

Message Meaning: NP6 HPE is dropping packets

Type: Event

Category: SYSTEM**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

34419 - LOG_ID_NP6_HPE_PACKET_FLOOD

Message ID: 34419**Message Description:** LOG_ID_NP6_HPE_PACKET_FLOOD**Message Meaning:** NP6 HPE under a packets flood**Type:** Event**Category:** SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

35001 - LOG_ID_HA_SYNC_VIRDB

Message ID: 35001

Message Description: LOG_ID_HA_SYNC_VIRDB

Message Meaning: HA slave synchronized Virus database

Type: Event

Category: HA

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Log Message	string	4096

35002 - LOG_ID_HA_SYNC_ETDB

Message ID: 35002

Message Description: LOG_ID_HA_SYNC_ETDB

Message Meaning: HA slave synchronized Extended database

Type: Event

Category: HA**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Log Message	string	4096

35003 - LOG_ID_HA_SYNC_EXDB

Message ID: 35003**Message Description:** LOG_ID_HA_SYNC_EXDB**Message Meaning:** HA slave synchronized Extreme database**Type:** Event**Category:** HA**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Log Message	string	4096

35004 - LOG_ID_HA_SYNC_FLDB

Message ID: 35004

Message Description: LOG_ID_HA_SYNC_FLDB

Message Meaning: HA slave synchronized FLDB

Type: Event

Category: HA

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Log Message	string	4096

35005 - LOG_ID_HA_SYNC_IPS

Message ID: 35005

Message Description: LOG_ID_HA_SYNC_IPS

Message Meaning: HA slave synchronized IDS package

Type: Event

Category: HA**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Log Message	string	4096

35007 - LOG_ID_HA_SYNC_AV

Message ID: 35007**Message Description:** LOG_ID_HA_SYNC_AV**Message Meaning:** HA slave synchronized AntiVirus package**Type:** Event**Category:** HA**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Log Message	string	4096

35009 - LOG_ID_HA_SYNC_CID

Message ID: 35009

Message Description: LOG_ID_HA_SYNC_CID

Message Meaning: HA slave synchronized CID package

Type: Event

Category: HA

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Log Message	string	4096

35011 - LOG_ID_HA_SYNC_FAIL

Message ID: 35011

Message Description: LOG_ID_HA_SYNC_FAIL

Message Meaning: HA slave synchronization failed

Type: Event

Category: HA**Severity:** Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Log Message	string	4096

35012 - LOG_ID_CONF_SYNC_FAIL

Message ID: 35012**Message Description:** LOG_ID_CONF_SYNC_FAIL**Message Meaning:** Slave sync failed**Type:** Event**Category:** HA**Severity:** Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Log Message	string	4096

35013 - LOG_ID_HA_FAILOVER_FAIL

Message ID: 35013

Message Description: LOG_ID_HA_FAILOVER_FAIL

Message Meaning: HA failover failed

Type: Event

Category: HA

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Log Message	string	4096

35014 - LOG_ID_HA_RESET_UPTIME

Message ID: 35014

Message Description: LOG_ID_HA_RESET_UPTIME

Message Meaning: HA reset uptime

Type: Event

Category: HA**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Log Message	string	4096
user		string	256
ui		string	64

35015 - LOG_ID_HA_CLEAR_HISTORY

Message ID: 35015**Message Description:** LOG_ID_HA_CLEAR_HISTORY**Message Meaning:** HA clear history**Type:** Event**Category:** HA**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Log Message	string	4096
user		string	256
ui		string	64

35016 - LOG_ID_HA_FAILOVER_SUCCESS

Message ID: 35016

Message Description: LOG_ID_HA_FAILOVER_SUCCESS

Message Meaning: HA failover success

Type: Event

Category: HA

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Log Message	string	4096

36881 - LOG_ID_EVENT_SYSTEM_CFG_REVERT

Message ID: 36881

Message Description: LOG_ID_EVENT_SYSTEM_CFG_REVERT

Message Meaning: Configuration reverted due to timeout

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

36882 - LOG_ID_EVENT_SYSTEM_CFG_MANUALLY_SAVED

Message ID: 36882

Message Description: LOG_ID_EVENT_SYSTEM_CFG_MANUALLY_SAVED

Message Meaning: Configuration manually saved

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
msg	Message Text	string	4096

37120 - MESGID_NEG_GENERIC_P1_NOTIF

Message ID: 37120

Message Description: MESGID_NEG_GENERIC_P1_NOTIF

Message Meaning: Negotiate IPsec phase 1

Type: Event

Category: VPN

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
remip	Remote IP	ip	39
user	User Name	string	256
group	User Group Name	string	64
msg	Message	string	4096
locip	Local IP	ip	39
remport	Remote Port	uint16	5
locport	Local Port	uint16	5
outintf	Out interface	string	32
cookies	Cookie	string	64
useralt		string	256
xauthuser	XAuth User Name	string	256
xauthgroup	XAuth Group Name	string	128
assignip	Assigned IP Address	ip	39
vpntunnel	IPsec Vpn Tunnel Name	string	128
status	Status	string	23
result	Result	string	31
peer_notif	Peer Notification	string	25

37121 - MESGID_NEG_GENERIC_P1_ERROR

Message ID: 37121

Message Description: MESGID_NEG_GENERIC_P1_ERROR

Message Meaning: Negotiate IPsec phase 1

Type: Event

Category: VPN

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10

Log Field Name	Description	Data Type	Length
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
remip	Remote IP	ip	39
user	User Name	string	256
group	User Group Name	string	64
msg	Message	string	4096
locip	Local IP	ip	39
remport	Remote Port	uint16	5
locport	Local Port	uint16	5
outintf	Out interface	string	32
cookies	Cookie	string	64
useralt		string	256
xauthuser	XAuth User Name	string	256
xauthgroup	XAuth Group Name	string	128
assignip	Assigned IP Address	ip	39
vpntunnel	IPsec Vpn Tunnel Name	string	128
status	Status	string	23
result	Result	string	31
peer_notif	Peer Notification	string	25

37122 - MESGID_NEG_GENERIC_P2_NOTIF

Message ID: 37122

Message Description: MESGID_NEG_GENERIC_P2_NOTIF**Message Meaning:** Negotiate IPsec phase 2**Type:** Event**Category:** VPN**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
remip	Remote IP	ip	39
user	User Name	string	256
group	User Group Name	string	64
msg	Message	string	4096
locip	Local IP	ip	39
remport	Remote Port	uint16	5
locport	Local Port	uint16	5
outintf	Out interface	string	32
cookies	Cookie	string	64
useralt		string	256
xauthuser	XAuth User Name	string	256
xauthgroup	XAuth Group Name	string	128
assignip	Assigned IP Address	ip	39
vpntunnel	IPsec Vpn Tunnel Name	string	128

Log Field Name	Description	Data Type	Length
status	Status	string	23
role	Role	string	9
esptransform	ESP Transform	string	21
espauth	ESP Authentication	string	17

37123 - MESGID_NEG_GENERIC_P2_ERROR

Message ID: 37123

Message Description: MESGID_NEG_GENERIC_P2_ERROR

Message Meaning: Negotiate IPsec phase 2

Type: Event

Category: VPN

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
remip	Remote IP	ip	39
user	User Name	string	256
group	User Group Name	string	64
msg	Message	string	4096
locip	Local IP	ip	39

Log Field Name	Description	Data Type	Length
remport	Remote Port	uint16	5
locport	Local Port	uint16	5
outintf	Out interface	string	32
cookies	Cookie	string	64
useralt		string	256
xauthuser	XAuth User Name	string	256
xauthgroup	XAuth Group Name	string	128
assignip	Assigned IP Address	ip	39
vpntunnel	IPsec Vpn Tunnel Name	string	128
status	Status	string	23
role	Role	string	9
esptransform	ESP Transform	string	21
espauth	ESP Authentication	string	17

37124 - MESGID_NEG_I_P1_ERROR

Message ID: 37124

Message Description: MESGID_NEG_I_P1_ERROR

Message Meaning: IPsec phase 1 error

Type: Event

Category: VPN

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
remip	Remote IP	ip	39
user	User Name	string	256
group	User Group Name	string	64
msg	Message	string	4096
locip	Local IP	ip	39
remport	Remote Port	uint16	5
locport	Local Port	uint16	5
outintf	Out interface	string	32
cookies	Cookie	string	64
useralt		string	256
xauthuser	XAuth User Name	string	256
xauthgroup	XAuth Group Name	string	128
assignip	Assigned IP Address	ip	39
vpntunnel	IPsec Vpn Tunnel Name	string	128
status	Status	string	23
peer_notif	Peer Notification	string	25
reason	Reason	string	256

37125 - MESGID_NEG_I_P2_ERROR

Message ID: 37125

Message Description: MESGID_NEG_I_P2_ERROR

Message Meaning: IPsec phase 2 error

Type: Event

Category: VPN

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
remip	Remote IP	ip	39
user	User Name	string	256
group	User Group Name	string	64
msg	Message	string	4096
locip	Local IP	ip	39
remport	Remote Port	uint16	5
locport	Local Port	uint16	5
outintf	Out interface	string	32
cookies	Cookie	string	64
useralt		string	256
xauthuser	XAuth User Name	string	256
xauthgroup	XAuth Group Name	string	128
assignip	Assigned IP Address	ip	39
vpntunnel	IPsec Vpn Tunnel Name	string	128
status	Status	string	23
reason	Reason	string	256

37126 - MESGID_NEG_NO_STATE_ERROR

Message ID: 37126

Message Description: MESGID_NEG_NO_STATE_ERROR**Message Meaning:** IPsec no state error**Type:** Event**Category:** VPN**Severity:** Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
remip	Remote IP	ip	39
user	User Name	string	256
group	User Group Name	string	64
msg	Message	string	4096
locip	Local IP	ip	39
remport	Remote Port	uint16	5
locport	Local Port	uint16	5
outintf	Out interface	string	32
cookies	Cookie	string	64
useralt		string	256
xauthuser	XAuth User Name	string	256
xauthgroup	XAuth Group Name	string	128
assignip	Assigned IP Address	ip	39
vpntunnel	IPsec Vpn Tunnel Name	string	128

Log Field Name	Description	Data Type	Length
status	Status	string	23
reason	Reason	string	256

37127 - MESGID_NEG_PROGRESS_P1_NOTIF

Message ID: 37127

Message Description: MESGID_NEG_PROGRESS_P1_NOTIF

Message Meaning: Progress IPsec phase 1

Type: Event

Category: VPN

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
remip	Remote IP	ip	39
user	User Name	string	256
group	User Group Name	string	64
msg	Message	string	4096
locip	Local IP	ip	39
remport	Remote Port	uint16	5
locport	Local Port	uint16	5

Log Field Name	Description	Data Type	Length
outintf	Out interface	string	32
cookies	Cookie	string	64
useralt		string	256
xauthuser	XAuth User Name	string	256
xauthgroup	XAuth Group Name	string	128
assignip	Assigned IP Address	ip	39
vpntunnel	IPsec Vpn Tunnel Name	string	128
status	Status	string	23
result	Result	string	31
role	Role	string	9
init		string	6
mode	Mode	string	12
dir	Direction	string	8
stage		uint8	3
exch		string	14
version		string	64

37128 - MESGID_NEG_PROGRESS_P1_ERROR

Message ID: 37128

Message Description: MESGID_NEG_PROGRESS_P1_ERROR

Message Meaning: Progress IPsec phase 1

Type: Event

Category: VPN

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
remip	Remote IP	ip	39
user	User Name	string	256
group	User Group Name	string	64
msg	Message	string	4096
locip	Local IP	ip	39
remport	Remote Port	uint16	5
locport	Local Port	uint16	5
outintf	Out interface	string	32
cookies	Cookie	string	64
useralt		string	256
xauthuser	XAuth User Name	string	256
xauthgroup	XAuth Group Name	string	128
assignip	Assigned IP Address	ip	39
vpntunnel	IPsec Vpn Tunnel Name	string	128
status	Status	string	23
result	Result	string	31
role	Role	string	9
init		string	6
mode	Mode	string	12
dir	Direction	string	8
stage		uint8	3
exch		string	14
version		string	64

37129 - MESGID_NEG_PROGRESS_P2_NOTIF

Message ID: 37129

Message Description: MESGID_NEG_PROGRESS_P2_NOTIF

Message Meaning: Progress IPsec phase 2

Type: Event

Category: VPN

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
remip	Remote IP	ip	39
user	User Name	string	256
group	User Group Name	string	64
msg	Message	string	4096
locip	Local IP	ip	39
remport	Remote Port	uint16	5
locport	Local Port	uint16	5
outintf	Out interface	string	32
cookies	Cookie	string	64
useralt		string	256
xauthuser	XAuth User Name	string	256

Log Field Name	Description	Data Type	Length
xauthgroup	XAuth Group Name	string	128
assignip	Assigned IP Address	ip	39
vpntunnel	IPsec Vpn Tunnel Name	string	128
status	Status	string	23
result	Result	string	31
role	Role	string	9
init		string	6
mode	Mode	string	12
dir	Direction	string	8
stage		uint8	3
exch		string	14
version		string	64

37130 - MESGID_NEG_PROGRESS_P2_ERROR

Message ID: 37130

Message Description: MESGID_NEG_PROGRESS_P2_ERROR

Message Meaning: Progress IPsec phase 2

Type: Event

Category: VPN

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
remip	Remote IP	ip	39
user	User Name	string	256
group	User Group Name	string	64
msg	Message	string	4096
locip	Local IP	ip	39
remport	Remote Port	uint16	5
locport	Local Port	uint16	5
outintf	Out interface	string	32
cookies	Cookie	string	64
useralt		string	256
xauthuser	XAuth User Name	string	256
xauthgroup	XAuth Group Name	string	128
assignip	Assigned IP Address	ip	39
vpntunnel	IPsec Vpn Tunnel Name	string	128
status	Status	string	23
result	Result	string	31
role	Role	string	9
init		string	6
mode	Mode	string	12
dir	Direction	string	8
stage		uint8	3
exch		string	14
version		string	64

37131 - MESGID_ESP_ERROR

Message ID: 37131

Message Description: MESGID_ESP_ERROR

Message Meaning: IPsec ESP

Type: Event**Category:** VPN**Severity:** Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
remip	Remote IP	ip	39
user	User Name	string	256
group	User Group Name	string	64
msg	Message	string	4096
locip	Local IP	ip	39
remport	Remote Port	uint16	5
locport	Local Port	uint16	5
outintf	Out interface	string	32
cookies	Cookie	string	64
useralt		string	256
xauthuser	XAuth User Name	string	256
xauthgroup	XAuth Group Name	string	128
assignip	Assigned IP Address	ip	39
vpntunnel	IPsec Vpn Tunnel Name	string	128
status	Status	string	23
error_num	Error Number	string	53

Log Field Name	Description	Data Type	Length
spi		string	16
seq	Sequence	string	16

37132 - MESGID_ESP_CRITICAL

Message ID: 37132

Message Description: MESGID_ESP_CRITICAL

Message Meaning: IPsec ESP

Type: Event

Category: VPN

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
remip	Remote IP	ip	39
user	User Name	string	256
group	User Group Name	string	64
msg	Message	string	4096
locip	Local IP	ip	39
remport	Remote Port	uint16	5
locport	Local Port	uint16	5

Log Field Name	Description	Data Type	Length
outintf	Out interface	string	32
cookies	Cookie	string	64
useralt		string	256
xauthuser	XAuth User Name	string	256
xauthgroup	XAuth Group Name	string	128
assignip	Assigned IP Address	ip	39
vpntunnel	IPsec Vpn Tunnel Name	string	128
status	Status	string	23
error_num	Error Number	string	53
spi		string	16
seq	Sequence	string	16

37133 - MESGID_INSTALL_SA

Message ID: 37133

Message Description: MESGID_INSTALL_SA

Message Meaning: IPsec SA installed

Type: Event

Category: VPN

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	4096
action	Action	string	65
remip	Remote IP	ip	39
user	User Name	string	256
group	User Group Name	string	64
msg	Message	string	4096
locip	Local IP	ip	39
remport	Remote Port	uint16	5
locport	Local Port	uint16	5
outintf	Out interface	string	32
cookies	Cookie	string	64
useralt		string	256
xauthuser	XAuth User Name	string	256
xauthgroup	XAuth Group Name	string	128
assignip	Assigned IP Address	ip	39
vpntunnel	IPsec Vpn Tunnel Name	string	128
role	Role	string	9
in_spi		string	16
out_spi	Out SPI	string	16

37134 - MESGID_DELETE_P1_SA

Message ID: 37134

Message Description: MESGID_DELETE_P1_SA

Message Meaning: IPsec phase 1 SA deleted

Type: Event

Category: VPN

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
remip	Remote IP	ip	39
user	User Name	string	256
group	User Group Name	string	64
msg	Message	string	4096
locip	Local IP	ip	39
remport	Remote Port	uint16	5
locport	Local Port	uint16	5
outintf	Out interface	string	32
cookies	Cookie	string	64
useralt		string	256
xauthuser	XAuth User Name	string	256
xauthgroup	XAuth Group Name	string	128
assignip	Assigned IP Address	ip	39
vpntunnel	IPsec Vpn Tunnel Name	string	128

37135 - MESGID_DELETE_P2_SA

Message ID: 37135

Message Description: MESGID_DELETE_P2_SA

Message Meaning: IPsec phase 2 SA deleted

Type: Event

Category: VPN

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
remip	Remote IP	ip	39
user	User Name	string	256
group	User Group Name	string	64
msg	Message	string	4096
locip	Local IP	ip	39
remport	Remote Port	uint16	5
locport	Local Port	uint16	5
outintf	Out interface	string	32
cookies	Cookie	string	64
useralt		string	256
xauthuser	XAuth User Name	string	256
xauthgroup	XAuth Group Name	string	128
assignip	Assigned IP Address	ip	39
vpntunnel	IPsec Vpn Tunnel Name	string	128
in_spi		string	16
out_spi	Out SPI	string	16

37136 - MESGID_DPD_FAILURE

Message ID: 37136

Message Description: MESGID_DPD_FAILURE**Message Meaning:** IPsec DPD failed**Type:** Event**Category:** VPN**Severity:** Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
remip	Remote IP	ip	39
user	User Name	string	256
group	User Group Name	string	64
msg	Message	string	4096
locip	Local IP	ip	39
remport	Remote Port	uint16	5
locport	Local Port	uint16	5
outintf	Out interface	string	32
cookies	Cookie	string	64
useralt		string	256
xauthuser	XAuth User Name	string	256
xauthgroup	XAuth Group Name	string	128
assignip	Assigned IP Address	ip	39
vpntunnel	IPsec Vpn Tunnel Name	string	128
status	Status	string	23

37137 - MESGID_CONN_FAILURE

Message ID: 37137

Message Description: MESGID_CONN_FAILURE

Message Meaning: IPsec connection failed

Type: Event

Category: VPN

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
remip	Remote IP	ip	39
user	User Name	string	256
group	User Group Name	string	64
msg	Message	string	4096
locip	Local IP	ip	39
remport	Remote Port	uint16	5
locport	Local Port	uint16	5
outintf	Out interface	string	32
cookies	Cookie	string	64
useralt		string	256
xauthuser	XAuth User Name	string	256

Log Field Name	Description	Data Type	Length
xauthgroup	XAuth Group Name	string	128
assignip	Assigned IP Address	ip	39
vpntunnel	IPsec Vpn Tunnel Name	string	128
status	Status	string	23

37138 - MESGID_CONN_UPDOWN

Message ID: 37138

Message Description: MESGID_CONN_UPDOWN

Message Meaning: IPsec connection status changed

Type: Event

Category: VPN

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
remip	Remote IP	ip	39
tunnelip	Tunnel IP	ip	39
user	User Name	string	256

Log Field Name	Description	Data Type	Length
group	User Group Name	string	64
msg	Message	string	4096
locip	Local IP	ip	39
remport	Remote Port	uint16	5
locport	Local Port	uint16	5
outintf	Out interface	string	32
cookies	Cookie	string	64
useralt		string	256
xauthuser	XAuth User Name	string	256
xauthgroup	XAuth Group Name	string	128
assignip	Assigned IP Address	ip	39
vpntunnel	IPsec Vpn Tunnel Name	string	128
duration	Duration	uint32	10
sentbyte	Bytes Sent	uint64	20
rcvdbyte	Received Bytes	uint64	20
nextstat	Time interval in seconds for the next statistics	uint32	10

37139 - MESGID_P2_UPDOWN

Message ID: 37139

Message Description: MESGID_P2_UPDOWN

Message Meaning: IPsec phase 2 status changed

Type: Event

Category: VPN

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
remip	Remote IP	ip	39
user	User Name	string	256
group	User Group Name	string	64
msg	Message	string	4096
locip	Local IP	ip	39
remport	Remote Port	uint16	5
locport	Local Port	uint16	5
outintf	Out interface	string	32
cookies	Cookie	string	64
useralt		string	256
xauthuser	XAuth User Name	string	256
xauthgroup	XAuth Group Name	string	128
assignip	Assigned IP Address	ip	39
vpntunnel	IPsec Vpn Tunnel Name	string	128
phase2_name	Phase 2 Name	string	128

37141 - MESGID_CONN_STATS

Message ID: 37141

Message Description: MESGID_CONN_STATS

Message Meaning: IPsec tunnel statistics

Type: Event

Category: VPN

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
remip	Remote IP	ip	39
tunnelip	Tunnel IP	ip	39
user	User Name	string	256
group	User Group Name	string	64
msg	Message	string	4096
locip	Local IP	ip	39
remport	Remote Port	uint16	5
locport	Local Port	uint16	5
outintf	Out interface	string	32
cookies	Cookie	string	64
useralt		string	256
xauthuser	XAuth User Name	string	256
xauthgroup	XAuth Group Name	string	128
assignip	Assigned IP Address	ip	39
vpntunnel	IPsec Vpn Tunnel Name	string	128
duration	Duration	uint32	10

Log Field Name	Description	Data Type	Length
sentbyte	Bytes Sent	uint64	20
rcvdbyte	Received Bytes	uint64	20
nextstat	Time interval in seconds for the next statistics	uint32	10

37889 - MESGID_VC_DELETE

Message ID: 37889

Message Description: MESGID_VC_DELETE

Message Meaning: Virtual cluster deleted

Type: Event

Category: HA

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Log Message	string	4096
vcluster	virtual cluster id	uint32	10

37890 - MESGID_VC_MOVE_VDOM

Message ID: 37890

Message Description: MESGID_VC_MOVE_VDOM

Message Meaning: Virtual cluster VDOM moved

Type: Event

Category: HA**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Log Message	string	4096
from_vcluster	source virtual cluster number	uint32	10
to_vcluster	destination virtual cluster number	uint32	10
vdname	vdom name	string	32

37891 - MESSGID_VC_ADD_VDOM

Message ID: 37891**Message Description:** MESSGID_VC_ADD_VDOM**Message Meaning:** Virtual cluster VDOM added**Type:** Event**Category:** HA**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Log Message	string	4096
to_vcluster	destination virtual cluster number	uint32	10
vdname	vdom name	string	32

37892 - MESGID_VC_MOVE_MEMB_STATE

Message ID: 37892

Message Description: MESGID_VC_MOVE_MEMB_STATE

Message Meaning: Virtual cluster member state moved

Type: Event

Category: HA

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
vcluster_member		uint32	10
vcluster_state		string	7

37893 - MESGID_VC_DETECT_MEMB_DEAD

Message ID: 37893

Message Description: MESGID_VC_DETECT_MEMB_DEAD

Message Meaning: Virtual cluster member dead

Type: Event

Category: HA

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Log Message	string	4096
vcluster	virtual cluster id	uint32	10
ha_group	HA Group Number - can be 1 - 256	uint8	3
sn	Serial Number	string	64

37894 - MESGID_VC_DETECT_MEMB_JOIN

Message ID: 37894

Message Description: MESGID_VC_DETECT_MEMB_JOIN

Message Meaning: Virtual cluster member joined

Type: Event

Category: HA

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Log Message	string	4096
vcluster	virtual cluster id	uint32	10
ha_group	HA Group Number - can be 1 - 256	uint8	3
sn	Serial Number	string	64

37895 - MESGID_VC_ADD_HADEV

Message ID: 37895

Message Description: MESGID_VC_ADD_HADEV

Message Meaning: Virtual cluster added HA device interface

Type: Event

Category: HA

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Log Message	string	4096
vcluster	virtual cluster id	uint32	10
devintfname	HA device Interface Name	string	32

37896 - MESGID_VC_DEL_HADEV

Message ID: 37896

Message Description: MESGID_VC_DEL_HADEV

Message Meaning: Virtual cluster deleted HA device interface

Type: Event

Category: HA

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Log Message	string	4096
vcluster	virtual cluster id	uint32	10
devintfname	HA device Interface Name	string	32

37897 - MESGID_HADEV_READY

Message ID: 37897

Message Description: MESGID_HADEV_READY

Message Meaning: HA device interface ready

Type: Event

Category: HA

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Log Message	string	4096
devintfname	HA device Interface Name	string	32
ha_role	The HA role in the cluster	string	6

37898 - MESGID_HADEV_FAIL

Message ID: 37898

Message Description: MESGID_HADEV_FAIL

Message Meaning: HA device interface failed

Type: Event

Category: HA

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Log Message	string	4096
devintfname	HA device Interface Name	string	32
ha_role	The HA role in the cluster	string	6

37899 - MESGID_HADEV_PEERINFO

Message ID: 37899

Message Description: MESGID_HADEV_PEERINFO

Message Meaning: HA device interface peer information

Type: Event

Category: HA

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Log Message	string	4096
devintfname	HA device Interface Name	string	32
ha_role	The HA role in the cluster	string	6

37900 - MESGID_HBDEV_DELETE

Message ID: 37900

Message Description: MESGID_HBDEV_DELETE

Message Meaning: Heartbeat device interface deleted

Type: Event

Category: HA

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Log Message	string	4096
devintfname	HA device Interface Name	string	32

37901 - MESGID_HBDEV_DOWN

Message ID: 37901

Message Description: MESGID_HBDEV_DOWN

Message Meaning: Heartbeat device interface down

Type: Event

Category: HA

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Log Message	string	4096
devintfname	HA device Interface Name	string	32
ha_role	The HA role in the cluster	string	6
hbdn_reason	heartbeat down reason	string	18

37902 - MESGID_HBDEV_UP

Message ID: 37902

Message Description: MESGID_HBDEV_UP

Message Meaning: Heartbeat device interface up

Type: Event

Category: HA

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Log Message	string	4096
devintfname	HA device Interface Name	string	32
ha_role	The HA role in the cluster	string	6

37903 - MESGID_SYNC_STATUS

Message ID: 37903

Message Description: MESGID_SYNC_STATUS

Message Meaning: Synchronization status with master

Type: Event

Category: HA

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Log Message	string	4096
sync_type	The sync type with the primary	string	14
sync_status	The sync status with the primary	string	11

37904 - MESGID_HA_ACTIVITY

Message ID: 37904

Message Description: MESGID_HA_ACTIVITY

Message Meaning: Device set as HA master

Type: Event

Category: HA

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Log Message	string	4096
activity	HA activity message	string	128
ip		ip	39
ha-prio	HA Priority	uint8	3

37907 - MESGID_VLAN_HB_UP

Message ID: 37907

Message Description: MESGID_VLAN_HB_UP

Message Meaning: VLAN heartbeat started

Type: Event

Category: HA

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Log Message	string	4096

37908 - MESGID_VLAN_HB_DOWN

Message ID: 37908

Message Description: MESGID_VLAN_HB_DOWN

Message Meaning: VLAN heartbeat lost

Type: Event

Category: HA

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Log Message	string	4096

37909 - MESGID_VLAN_HB_DOWN_SUM

Message ID: 37909

Message Description: MESGID_VLAN_HB_DOWN_SUM

Message Meaning: VLAN heartbeat lost summary

Type: Event

Category: HA

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Log Message	string	4096

38010 - LOG_ID_FIPS_ENCRY_FAIL

Message ID: 38010

Message Description: LOG_ID_FIPS_ENCRY_FAIL

Message Meaning: FIPS CC encryption failed

Type: Event

Category: USER

Severity: Alert

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
authproto	The protocol that initiated the authentication	string	512
action	Action	string	65
status	Status	string	23
msg	Message	string	4096

38011 - LOG_ID_FIPS_DECRY_FAIL

Message ID: 38011

Message Description: LOG_ID_FIPS_DECRY_FAIL

Message Meaning: FIPS CC decryption failed

Type: Event

Category: USER

Severity: Alert

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
action	Action	string	65
status	Status	string	23
msg	Message	string	4096
ui	User Interface	string	64

38012 - LOG_ID_ENTROPY_TOKEN

Message ID: 38012

Message Description: LOG_ID_ENTROPY_TOKEN

Message Meaning: Seeding from entropy source

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
action	Action	string	65
msg	Message	string	4096

38031 - LOG_ID_FSSO_LOGON

Message ID: 38031

Message Description: LOG_ID_FSSO_LOGON

Message Meaning: FSSO logon successful

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256

Log Field Name	Description	Data Type	Length
action	Action	string	65
status	Status	string	23
msg	Message	string	4096
srcip	Source IP	ip	39
server	AD server FQDN or IP	string	64
reason	Reason	string	256

38032 - LOG_ID_FSSO_LOGOFF

Message ID: 38032

Message Description: LOG_ID_FSSO_LOGOFF

Message Meaning: FSSO logout successful

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
action	Action	string	65
status	Status	string	23
msg	Message	string	4096

Log Field Name	Description	Data Type	Length
srcip	Source IP	ip	39
server	AD server FQDN or IP	string	64
reason	Reason	string	256

38033 - LOG_ID_FSSO_SVR_STATUS

Message ID: 38033

Message Description: LOG_ID_FSSO_SVR_STATUS

Message Meaning: FSSO Active Directory server authentication status

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
action	Action	string	65
msg	Message	string	4096
server	AD server FQDN or IP	string	64

38400 - LOGID_EVENT_NOTIF_SEND_SUCC

Message ID: 38400

Message Description: LOGID_EVENT_NOTIF_SEND_SUCC

Message Meaning: Notification message sent

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
msg	Message Text	string	4096
count	Count	uint32	10
service	Name of Service	string	64
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
profile	Profile Name	string	64
duration	Duration	uint32	10
from	Sender Email Address for Notification	string	128
to	Recipient Email Addresses for Notification	string	512
msgproto	Message Protocol Number	string	16
nf_type	Notification Type	string	14
virus	Virus Name	string	128
profiletype	Profile Type	string	64
profilegroup	Profile Group Name	string	4

38401 - LOGID_EVENT_NOTIF_SEND_FAIL

Message ID: 38401

Message Description: LOGID_EVENT_NOTIF_SEND_FAIL

Message Meaning: Notification message send failed

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
msg	Message Text	string	4096
count	Count	uint32	10
service	Name of Service	string	64
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
profile	Profile Name	string	64
duration	Duration	uint32	10
from	Sender Email Address for Notification	string	128
to	Recipient Email Addresses for Notification	string	512
msgproto	Message Protocol Number	string	16
nf_type	Notification Type	string	14

Log Field Name	Description	Data Type	Length
virus	Virus Name	string	128
profiletype	Profile Type	string	64
profilegroup	Profile Group Name	string	4
sess_duration	Session Duration	uint32	10

38402 - LOGID_EVENT_NOTIF_DNS_FAIL

Message ID: 38402

Message Description: LOGID_EVENT_NOTIF_DNS_FAIL

Message Meaning: MMSC hostname unresolvable

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096
service	Name of Service	string	64
profile	Profile Name	string	64
hostname	Hostname	string	128
profiletype	Profile Type	string	64
profile_vd	Virtual Domain Name	string	64

38403 - LOGID_EVENT_NOTIF_INSUFFICIENT_RESOURCE

Message ID: 38403

Message Description: LOGID_EVENT_NOTIF_INSUFFICIENT_RESOURCE

Message Meaning: Insufficient system resource notification

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

38404 - LOGID_EVENT_NOTIF_HOSTNAME_ERROR

Message ID: 38404

Message Description: LOGID_EVENT_NOTIF_HOSTNAME_ERROR

Message Meaning: FortiGuard hostname unresolvable

Type: Event

Category: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096
hostname	Hostname	string	128

38405 - LOGID_NOTIF_CODE_SENDTO_SMS_PHONE

Message ID: 38405

Message Description: LOGID_NOTIF_CODE_SENDTO_SMS_PHONE

Message Meaning: Guest user account login information sent to phone

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	4096
user	User Name	string	256
action	Action	string	65
msg	Message Text	string	4096

38406 - LOGID_NOTIF_CODE_SENDTO_SMS_TO

Message ID: 38406

Message Description: LOGID_NOTIF_CODE_SENDTO_SMS_TO

Message Meaning: Guest user account login information sent as SMS

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
action	Action	string	65
msg	Message Text	string	4096

38407 - LOGID_NOTIF_CODE_SENDTO_EMAIL

Message ID: 38407

Message Description: LOGID_NOTIF_CODE_SENDTO_EMAIL

Message Meaning: Guest user account login information sent to email

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
action	Action	string	65
msg	Message Text	string	4096

38408 - LOGID_EVENT_OFTP_SSL_CONNECTED

Message ID: 38408

Message Description: LOGID_EVENT_OFTP_SSL_CONNECTED

Message Meaning: SSL connection established

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5

38409 - LOGID_EVENT_OFTP_SSL_DISCONNECTED

Message ID: 38409

Message Description: LOGID_EVENT_OFTP_SSL_DISCONNECTED

Message Meaning: SSL connection closed

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5

38410 - LOGID_EVENT_OFTP_SSL_FAILED

Message ID: 38410

Message Description: LOGID_EVENT_OFTP_SSL_FAILED

Message Meaning: SSL connection failed

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
status	Status	string	23

Log Field Name	Description	Data Type	Length
msg	Message Text	string	4096
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
reason	Reason	string	256

38411 - LOGID_EVENT_TWO_F_AUTH_CODE_SENDTO

Message ID: 38411

Message Description: LOGID_EVENT_TWO_F_AUTH_CODE_SENDTO

Message Meaning: Two-factor authentication code sent

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
action	Action	string	65
msg	Message Text	string	4096

38412 - LOGID_EVENT_TOKEN_CODE_SENDTO

Message ID: 38412

Message Description: LOGID_EVENT_TOKEN_CODE_SENDTO

Message Meaning: Token activation code sent

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
action	Action	string	65
msg	Message Text	string	4096

38656 - LOGID_EVENT_RAD_RPT_PROTO_ERROR

Message ID: 38656

Message Description: LOGID_EVENT_RAD_RPT_PROTO_ERROR

Message Meaning: RADIUS protocol error summary

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message	string	4096
count	Number of Packets	uint32	10
duration	Duration	uint32	10

38657 - LOGID_EVENT_RAD_RPT_PROF_NOT_FOUND

Message ID: 38657

Message Description: LOGID_EVENT_RAD_RPT_PROF_NOT_FOUND

Message Meaning: RADIUS profile not found summary

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	4096
msg	Message	string	4096
count	Number of Packets	uint32	10
duration	Duration	uint32	10

38658 - LOGID_EVENT_RAD_RPT_CTX_NOT_FOUND

Message ID: 38658

Message Description: LOGID_EVENT_RAD_RPT_CTX_NOT_FOUND

Message Meaning: RADIUS profile CTX not found summary

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message	string	4096
count	Number of Packets	uint32	10
duration	Duration	uint32	10

38659 - LOGID_EVENT_RAD_RPT_ACCT_STOP_MISSED

Message ID: 38659

Message Description: LOGID_EVENT_RAD_RPT_ACCT_STOP_MISSED

Message Meaning: RADIUS accounting stop message missing summary

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message	string	4096
count	Number of Packets	uint32	10
duration	Duration	uint32	10

38660 - LOGID_EVENT_RAD_RPT_ACCT_EVENT

Message ID: 38660

Message Description: LOGID_EVENT_RAD_RPT_ACCT_EVENT

Message Meaning: RADIUS accounting event summary

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message	string	4096
count	Number of Packets	uint32	10
duration	Duration	uint32	10

38661 - LOGID_EVENT_RAD_RPT_OTHER

Message ID: 38661

Message Description: LOGID_EVENT_RAD_RPT_OTHER

Message Meaning: RADIUS endpoint block event or other event summary

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	4096
msg	Message	string	4096
count	Number of Packets	uint32	10
duration	Duration	uint32	10

38662 - LOGID_EVENT_RAD_STAT_PROTO_ERROR

Message ID: 38662

Message Description: LOGID_EVENT_RAD_STAT_PROTO_ERROR

Message Meaning: RADIUS accounting protocol error

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message	string	4096
srcip	Source IP	ip	39
reason	Reason	string	256
carrier_ep	The FortiOS Carrier end-point identification	string	64
rsso_key	RADIUS SSO attribute value	string	64
acct_stat	Accounting state (RADIUS)	string	14

38663 - LOGID_EVENT_RAD_STAT_PROF_NOT_FOUND

Message ID: 38663

Message Description: LOGID_EVENT_RAD_STAT_PROF_NOT_FOUND

Message Meaning: RADIUS accounting profile not found

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message	string	4096
srcip	Source IP	ip	39
reason	Reason	string	256
carrier_ep	The FortiOS Carrier end-point identification	string	64
rsso_key	RADIUS SSO attribute value	string	64
acct_stat	Accounting state (RADIUS)	string	14

38665 - LOGID_EVENT_RAD_STAT_ACCT_STOP_MISSED

Message ID: 38665

Message Description: LOGID_EVENT_RAD_STAT_ACCT_STOP_MISSED

Message Meaning: RADIUS accounting stop message missing

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message	string	4096
srcip	Source IP	ip	39
reason	Reason	string	256
carrier_ep	The FortiOS Carrier end-point identification	string	64
rsso_key	RADIUS SSO attribute value	string	64
acct_stat	Accounting state (RADIUS)	string	14

38666 - LOGID_EVENT_RAD_STAT_ACCT_EVENT**Message ID:** 38666**Message Description:** LOGID_EVENT_RAD_STAT_ACCT_EVENT**Message Meaning:** RADIUS accounting event**Type:** Event**Category:** USER**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message	string	4096
srcip	Source IP	ip	39
carrier_ep	The FortiOS Carrier end-point identification	string	64
rsso_key	RADIUS SSO attribute value	string	64
acct_stat	Accounting state (RADIUS)	string	14

38667 - LOGID_EVENT_RAD_STAT_OTHER

Message ID: 38667

Message Description: LOGID_EVENT_RAD_STAT_OTHER

Message Meaning: RADIUS other accounting event

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message	string	4096
srcip	Source IP	ip	39
reason	Reason	string	256
count	Number of Packets	uint32	10
carrier_ep	The FortiOS Carrier end-point identification	string	64
rsso_key	RADIUS SSO attribute value	string	64
acct_stat	Accounting state (RADIUS)	string	14

38668 - LOGID_EVENT_RAD_STAT_EP_BLK

Message ID: 38668

Message Description: LOGID_EVENT_RAD_STAT_EP_BLK

Message Meaning: RADIUS endpoint block event

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096

Log Field Name	Description	Data Type	Length
msg	Message	string	4096
srcip	Source IP	ip	39
reason	Reason	string	256
carrier_ep	The FortiOS Carrier end-point identification	string	64
rsso_key	RADIUS SSO attribute value	string	64
acct_stat	Accounting state (RADIUS)	string	14

39424 - LOG_ID_EVENT_SSL_VPN_USER_TUNNEL_UP

Message ID: 39424

Message Description: LOG_ID_EVENT_SSL_VPN_USER_TUNNEL_UP

Message Meaning: SSL VPN tunnel up

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
remip	Remote IP	ip	39

Log Field Name	Description	Data Type	Length
user	User Name	string	256
group	User Group Name	string	64
msg	Message	string	4096
reason	Reason	string	256
dst_host		string	64

39425 - LOG_ID_EVENT_SSL_VPN_USER_TUNNEL_DOWN

Message ID: 39425

Message Description: LOG_ID_EVENT_SSL_VPN_USER_TUNNEL_DOWN

Message Meaning: SSL VPN tunnel down

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
remip	Remote IP	ip	39
user	User Name	string	256

Log Field Name	Description	Data Type	Length
group	User Group Name	string	64
msg	Message	string	4096
reason	Reason	string	256
duration	Duration	uint32	10
sentbyte	Bytes Sent	uint64	20
rcvdbyte	Received Bytes	uint64	20
dst_host		string	64

39426 - LOG_ID_EVENT_SSL_VPN_USER_SSL_LOGIN_FAIL

Message ID: 39426

Message Description: LOG_ID_EVENT_SSL_VPN_USER_SSL_LOGIN_FAIL

Message Meaning: SSL VPN login fail

Type: Event

Category: VPN

Severity: Alert

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64

Log Field Name	Description	Data Type	Length
remip	Remote IP	ip	39
user	User Name	string	256
group	User Group Name	string	64
msg	Message	string	4096
reason	Reason	string	256
dst_host		string	64

39936 - LOG_ID_EVENT_SSL_VPN_SESSION_WEB_TUNNEL_STATS

Message ID: 39936

Message Description: LOG_ID_EVENT_SSL_VPN_SESSION_WEB_TUNNEL_STATS

Message Meaning: SSL VPN statistics

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
remip	Remote IP	ip	39

Log Field Name	Description	Data Type	Length
user	User Name	string	256
group	User Group Name	string	64
msg	Message	string	4096
duration	Duration	uint32	10
sentbyte	Bytes Sent	uint64	20
rcvdbyte	Received Bytes	uint64	20
nextstat	Time interval in seconds for the next statistics	uint32	10
dst_host		string	64

39937 - LOG_ID_EVENT_SSL_VPN_SESSION_WEBAPP_DENY

Message ID: 39937

Message Description: LOG_ID_EVENT_SSL_VPN_SESSION_WEBAPP_DENY

Message Meaning: SSL VPN deny

Type: Event

Category: VPN

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
tunnelid	Tunnel ID	uint32	10

Log Field Name	Description	Data Type	Length
tunneltype	Tunnel Type	string	64
remip	Remote IP	ip	39
user	User Name	string	256
group	User Group Name	string	64
msg	Message	string	4096
reason	Reason	string	256
dst_host		string	64

39938 - LOG_ID_EVENT_SSL_VPN_SESSION_WEBAPP_PASS

Message ID: 39938

Message Description: LOG_ID_EVENT_SSL_VPN_SESSION_WEBAPP_PASS

Message Meaning: SSL VPN pass

Type: Event

Category: VPN

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64

Log Field Name	Description	Data Type	Length
remip	Remote IP	ip	39
user	User Name	string	256
group	User Group Name	string	64
msg	Message	string	4096
reason	Reason	string	256
dst_host		string	64

39939 - LOG_ID_EVENT_SSL_VPN_SESSION_WEBAPP_TIMEOUT

Message ID: 39939

Message Description: LOG_ID_EVENT_SSL_VPN_SESSION_WEBAPP_TIMEOUT

Message Meaning: SSL VPN timeout

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
remip	Remote IP	ip	39

Log Field Name	Description	Data Type	Length
user	User Name	string	256
group	User Group Name	string	64
msg	Message	string	4096
reason	Reason	string	256
dst_host		string	64

39940 - LOG_ID_EVENT_SSL_VPN_SESSION_WEBAPP_CLOSE

Message ID: 39940

Message Description: LOG_ID_EVENT_SSL_VPN_SESSION_WEBAPP_CLOSE

Message Meaning: SSL VPN close

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
remip	Remote IP	ip	39
user	User Name	string	256

Log Field Name	Description	Data Type	Length
group	User Group Name	string	64
msg	Message	string	4096
reason	Reason	string	256
dst_host		string	64

39941 - LOG_ID_EVENT_SSL_VPN_SESSION_SYS_BUSY

Message ID: 39941

Message Description: LOG_ID_EVENT_SSL_VPN_SESSION_SYS_BUSY

Message Meaning: SSL VPN system busy

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
remip	Remote IP	ip	39
user	User Name	string	256
group	User Group Name	string	64

Log Field Name	Description	Data Type	Length
msg	Message	string	4096
reason	Reason	string	256
dst_host		string	64

39942 - LOG_ID_EVENT_SSL_VPN_SESSION_CERT_OK

Message ID: 39942

Message Description: LOG_ID_EVENT_SSL_VPN_SESSION_CERT_OK

Message Meaning: SSL VPN certificate OK

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
remip	Remote IP	ip	39
user	User Name	string	256
group	User Group Name	string	64
msg	Message	string	4096

Log Field Name	Description	Data Type	Length
reason	Reason	string	256
dst_host		string	64

39943 - LOG_ID_EVENT_SSL_VPN_SESSION_NEW_CON

Message ID: 39943

Message Description: LOG_ID_EVENT_SSL_VPN_SESSION_NEW_CON

Message Meaning: SSL VPN new connection

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
remip	Remote IP	ip	39
user	User Name	string	256
group	User Group Name	string	64
msg	Message	string	4096
reason	Reason	string	256
dst_host		string	64

39944 - LOG_ID_EVENT_SSL_VPN_SESSION_ALERT

Message ID: 39944

Message Description: LOG_ID_EVENT_SSL_VPN_SESSION_ALERT

Message Meaning: SSL VPN alert

Type: Event

Category: VPN

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
remip	Remote IP	ip	39
user	User Name	string	256
group	User Group Name	string	64
msg	Message	string	4096
reason	Reason	string	256
dst_host		string	64
desc		string	128

39945 - LOG_ID_EVENT_SSL_VPN_SESSION_EXIT_FAIL

Message ID: 39945

Message Description: LOG_ID_EVENT_SSL_VPN_SESSION_EXIT_FAIL**Message Meaning:** SSL VPN exit fail**Type:** Event**Category:** VPN**Severity:** Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
remip	Remote IP	ip	39
user	User Name	string	256
group	User Group Name	string	64
msg	Message	string	4096
reason	Reason	string	256
dst_host		string	64

39946 - LOG_ID_EVENT_SSL_VPN_SESSION_EXIT_ERR

Message ID: 39946**Message Description:** LOG_ID_EVENT_SSL_VPN_SESSION_EXIT_ERR**Message Meaning:** SSL VPN exit error**Type:** Event**Category:** VPN

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
remip	Remote IP	ip	39
user	User Name	string	256
group	User Group Name	string	64
msg	Message	string	4096
reason	Reason	string	256
dst_host		string	64

39947 - LOG_ID_EVENT_SSL_VPN_SESSION_TUNNEL_UP

Message ID: 39947**Message Description:** LOG_ID_EVENT_SSL_VPN_SESSION_TUNNEL_UP**Message Meaning:** SSL VPN tunnel up**Type:** Event**Category:** VPN**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
remip	Remote IP	ip	39
user	User Name	string	256
group	User Group Name	string	64
msg	Message	string	4096
reason	Reason	string	256
dst_host		string	64

39948 - LOG_ID_EVENT_SSL_VPN_SESSION_TUNNEL_DOWN

Message ID: 39948

Message Description: LOG_ID_EVENT_SSL_VPN_SESSION_TUNNEL_DOWN

Message Meaning: SSL VPN tunnel down

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10

Log Field Name	Description	Data Type	Length
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
remip	Remote IP	ip	39
user	User Name	string	256
group	User Group Name	string	64
msg	Message	string	4096
reason	Reason	string	256
duration	Duration	uint32	10
sentbyte	Bytes Sent	uint64	20
rcvdbyte	Received Bytes	uint64	20
dst_host		string	64

39949 - LOG_ID_EVENT_SSL_VPN_SESSION_TUNNEL_STATS

Message ID: 39949

Message Description: LOG_ID_EVENT_SSL_VPN_SESSION_TUNNEL_STATS

Message Meaning: SSL VPN statistics

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
remip	Remote IP	ip	39
user	User Name	string	256
group	User Group Name	string	64
msg	Message	string	4096
duration	Duration	uint32	10
sentbyte	Bytes Sent	uint64	20
rcvdbyte	Received Bytes	uint64	20
nextstat	Time interval in seconds for the next statistics	uint32	10
dst_host		string	64

39950 - LOG_ID_EVENT_SSL_VPN_SESSION_TUNNEL_UNKNOWNTAG

Message ID: 39950

Message Description: LOG_ID_EVENT_SSL_VPN_SESSION_TUNNEL_UNKNOWNTAG

Message Meaning: SSL VPN unknown tag

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
remip	Remote IP	ip	39
user	User Name	string	256
group	User Group Name	string	64
msg	Message	string	4096
reason	Reason	string	256
dst_host		string	64

39951 - LOG_ID_EVENT_SSL_VPN_SESSION_TUNNEL_ERROR

Message ID: 39951

Message Description: LOG_ID_EVENT_SSL_VPN_SESSION_TUNNEL_ERROR

Message Meaning: SSL VPN tunnel error

Type: Event

Category: VPN

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10

Log Field Name	Description	Data Type	Length
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
remip	Remote IP	ip	39
user	User Name	string	256
group	User Group Name	string	64
msg	Message	string	4096
reason	Reason	string	256
dst_host		string	64

39952 - LOG_ID_EVENT_SSL_VPN_SESSION_ENTER_CONSERVE_MODE

Message ID: 39952

Message Description: LOG_ID_EVENT_SSL_VPN_SESSION_ENTER_CONSERVE_MODE

Message Meaning: SSL VPN enter conserve mode

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
remip	Remote IP	ip	39
user	User Name	string	256
group	User Group Name	string	64
msg	Message	string	4096
reason	Reason	string	256
dst_host		string	64

39953 - LOG_ID_EVENT_SSL_VPN_SESSION_LEAVE_CONSERVE_MODE

Message ID: 39953

Message Description: LOG_ID_EVENT_SSL_VPN_SESSION_LEAVE_CONSERVE_MODE

Message Meaning: SSL VPN leave conserve mode

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
remip	Remote IP	ip	39
user	User Name	string	256
group	User Group Name	string	64
msg	Message	string	4096
reason	Reason	string	256
dst_host		string	64

40001 - LOG_ID_PPTP_TUNNEL_UP

Message ID: 40001

Message Description: LOG_ID_PPTP_TUNNEL_UP

Message Meaning: PPTP tunnel up

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
remip	Remote IP	ip	39
tunnelip	Tunnel IP	ip	39
user	User Name	string	256
group	User Group Name	string	64
msg	Message	string	4096

40002 - LOG_ID_PPTP_TUNNEL_DOWN

Message ID: 40002

Message Description: LOG_ID_PPTP_TUNNEL_DOWN

Message Meaning: PPTP tunnel down

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
remip	Remote IP	ip	39
tunnelip	Tunnel IP	ip	39
user	User Name	string	256
group	User Group Name	string	64
msg	Message	string	4096

40003 - LOG_ID_PPTP_TUNNEL_STAT

Message ID: 40003

Message Description: LOG_ID_PPTP_TUNNEL_STAT

Message Meaning: PPTP tunnel status

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
remip	Remote IP	ip	39
tunnelip	Tunnel IP	ip	39
user	User Name	string	256
group	User Group Name	string	64
msg	Message	string	4096

40014 - LOG_ID_PPTP_REACH_MAX_CON

Message ID: 40014

Message Description: LOG_ID_PPTP_REACH_MAX_CON

Message Meaning: PPTP client connection limit reached

Type: Event

Category: VPN

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	4096
action	Action	string	65
msg	Message	string	4096
status	Status	string	23

40017 - LOG_ID_L2TPD_CLIENT_CON_FAIL

Message ID: 40017

Message Description: LOG_ID_L2TPD_CLIENT_CON_FAIL

Message Meaning: L2TP client connection failed

Type: Event

Category: VPN

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Message	string	4096
status	Status	string	23
reason	Reason	string	256

40019 - LOG_ID_L2TPD_CLIENT_DISCON

Message ID: 40019

Message Description: LOG_ID_L2TPD_CLIENT_DISCON**Message Meaning:** L2TP client disconnected**Type:** Event**Category:** VPN**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Message	string	4096
status	Status	string	23

40021 - LOG_ID_PPTP_NOT_CONIG

Message ID: 40021**Message Description:** LOG_ID_PPTP_NOT_CONIG**Message Meaning:** PPTP not configured in VDOM**Type:** Event**Category:** VPN**Severity:** Debug

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Message	string	4096
status	Status	string	23

40022 - LOG_ID_PPTP_NO_IP_AVAIL

Message ID: 40022

Message Description: LOG_ID_PPTP_NO_IP_AVAIL

Message Meaning: PPTP IP addresses unavailable

Type: Event

Category: VPN

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Message	string	4096
status	Status	string	23

40024 - LOG_ID_PPTP_OUT_MEM

Message ID: 40024

Message Description: LOG_ID_PPTP_OUT_MEM

Message Meaning: PPTP config list insufficient memory

Type: Event

Category: VPN

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Message	string	4096
status	Status	string	23

40034 - LOG_ID_PPTP_START

Message ID: 40034

Message Description: LOG_ID_PPTP_START**Message Meaning:** PPTP daemon started**Type:** Event**Category:** VPN**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Message	string	4096
status	Status	string	23

40035 - LOG_ID_PPTP_START_FAIL

Message ID: 40035**Message Description:** LOG_ID_PPTP_START_FAIL**Message Meaning:** PPTP daemon failed to start**Type:** Event**Category:** VPN**Severity:** Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Message	string	4096
status	Status	string	23
reason	Reason	string	256

40036 - LOG_ID_PPTP_EXIT

Message ID: 40036

Message Description: LOG_ID_PPTP_EXIT

Message Meaning: PPTP daemon exited

Type: Event

Category: VPN

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Message	string	4096
status	Status	string	23

40037 - LOG_ID_PPTPD_SVR_DISCON

Message ID: 40037

Message Description: LOG_ID_PPTPD_SVR_DISCON

Message Meaning: PPTP daemon disconnected

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Message	string	4096
status	Status	string	23
reason	Reason	string	256

40038 - LOG_ID_PPTPD_CLIENT_CON

Message ID: 40038

Message Description: LOG_ID_PPTPD_CLIENT_CON

Message Meaning: PPTP client connected

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Message	string	4096
status	Status	string	23

40039 - LOG_ID_PPTPD_CLIENT_DISCON

Message ID: 40039

Message Description: LOG_ID_PPTPD_CLIENT_DISCON

Message Meaning: PPTP client disconnected

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Message	string	4096
status	Status	string	23

40101 - LOG_ID_L2TP_TUNNEL_UP

Message ID: 40101

Message Description: LOG_ID_L2TP_TUNNEL_UP

Message Meaning: L2TP tunnel up

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
remip	Remote IP	ip	39
tunnelip	Tunnel IP	ip	39
user	User Name	string	256
group	User Group Name	string	64
msg	Message	string	4096

40102 - LOG_ID_L2TP_TUNNEL_DOWN

Message ID: 40102

Message Description: LOG_ID_L2TP_TUNNEL_DOWN

Message Meaning: L2TP tunnel down

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
remip	Remote IP	ip	39
tunnelip	Tunnel IP	ip	39
user	User Name	string	256
group	User Group Name	string	64
msg	Message	string	4096

40103 - LOG_ID_L2TP_TUNNEL_STAT

Message ID: 40103

Message Description: LOG_ID_L2TP_TUNNEL_STAT

Message Meaning: L2TP tunnel status

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096

Log Field Name	Description	Data Type	Length
action	Action	string	65
tunnelid	Tunnel ID	uint32	10
tunneltype	Tunnel Type	string	64
remip	Remote IP	ip	39
tunnelip	Tunnel IP	ip	39
user	User Name	string	256
group	User Group Name	string	64
msg	Message	string	4096

40114 - LOG_ID_L2TPD_START

Message ID: 40114

Message Description: LOG_ID_L2TPD_START

Message Meaning: L2TP daemon started

Type: Event

Category: VPN

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Message	string	4096
status	Status	string	23

40115 - LOG_ID_L2TPD_EXIT

Message ID: 40115

Message Description: LOG_ID_L2TPD_EXIT

Message Meaning: L2TP daemon exited

Type: Event

Category: VPN

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Message	string	4096
status	Status	string	23

40118 - LOG_ID_L2TPD_CLIENT_CON

Message ID: 40118

Message Description: LOG_ID_L2TPD_CLIENT_CON

Message Meaning: L2TP client connected

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Message	string	4096
status	Status	string	23

40704 - LOG_ID_EVENT_SYS_PERF

Message ID: 40704

Message Description: LOG_ID_EVENT_SYS_PERF

Message Meaning: System performance statistics

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
action	Action	string	65
msg	Message Text	string	4096
cpu	CPU Usage	uint8	3
mem	Memory Usage	uint8	3
totalsession	Total Number of Sessions	uint32	10
disk	Disk Usage	uint8	3
bandwidth	Bandwidth	string	42
setuprate	Session Setup Rate	uint64	20
disklograte	Disk Log Rate	uint64	20
fazlograte	FortiAnalyzer Logging Rate	uint64	20
freediskstorage		uint32	10
sysuptime		uint32	10



This log message is only sent to remote FortiAnalyzer and memory, but not to disk.

40705 - LOG_ID_EVENT_SYS_CPU_USAGE

Message ID: 40705

Message Description: LOG_ID_EVENT_SYS_CPU_USAGE

Message Meaning: CPU usage statistics

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10

Log Field Name	Description	Data Type	Length
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Message Text	string	4096
cpu	CPU Usage	uint8	3

40706 - LOG_ID_EVENT_SYS_BROKEN_SYMBOLIC_LINK

Message ID: 40706

Message Description: LOG_ID_EVENT_SYS_BROKEN_SYMBOLIC_LINK

Message Meaning: Delete broken symbolic link

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

40960 - LOGID_EVENT_WAD_WEBPROXY_FWD_SRV_ERROR

Message ID: 40960

Message Description: LOGID_EVENT_WAD_WEBPROXY_FWD_SRV_ERROR

Message Meaning: Web proxy forward server error

Type: Event

Category: WAD

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
fwserver_name		string	32
addr_type	Address Type	string	4
ip		ip	39
fqdn	Fully Qualified Domain Name	string	256
port	Port Number	uint16	5
msg	Log Message	string	4096

41000 - LOG_ID_UPD_FGT_SUCC

Message ID: 41000

Message Description: LOG_ID_UPD_FGT_SUCC

Message Meaning: FortiGate update succeeded

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
status	Status	string	23
msg	Message Text	string	4096

41001 - LOG_ID_UPD_FGT_FAIL

Message ID: 41001

Message Description: LOG_ID_UPD_FGT_FAIL

Message Meaning: FortiGate update failed

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10

Log Field Name	Description	Data Type	Length
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
status	Status	string	23
msg	Message Text	string	4096

41002 - LOG_ID_UPD_SRC_VIS

Message ID: 41002

Message Description: LOG_ID_UPD_SRC_VIS

Message Meaning: Source visibility signature package updated

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
tz		string	5
logdesc	Log Description	string	4096
status	Status	string	23
msg	Message Text	string	4096

41006 - LOG_ID_UPD_FSA_VIRDB

Message ID: 41006

Message Description: LOG_ID_UPD_FSA_VIRDB

Message Meaning: FortiSandbox AV database updated

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096
version	Version	string	64

41984 - LOG_ID_EVENT_VPN_CERT_LOAD

Message ID: 41984

Message Description: LOG_ID_EVENT_VPN_CERT_LOAD

Message Meaning: Certificate loaded

Type: Event**Category:** VPN**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
user	User Name	string	256
msg	Message	string	4096
status	Status	string	23
ui	User Interface	string	64
name	Name	string	128
cert-type	Certification type	string	6

41985 - LOG_ID_EVENT_VPN_CERT_REMOVAL

Message ID: 41985**Message Description:** LOG_ID_EVENT_VPN_CERT_REMOVAL**Message Meaning:** Certificate removed**Type:** Event**Category:** VPN**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
user	User Name	string	256
msg	Message	string	4096
status	Status	string	23
ui	User Interface	string	64
name	Name	string	128
cert-type	Certification type	string	6

41986 - LOG_ID_EVENT_VPN_CERT_REGEN

Message ID: 41986

Message Description: LOG_ID_EVENT_VPN_CERT_REGEN

Message Meaning: Certificate regenerated

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
user	User Name	string	256
msg	Message	string	4096
status	Status	string	23
ui	User Interface	string	64
name	Name	string	128
cert-type	Certification type	string	6

41987 - LOG_ID_EVENT_VPN_CERT_UPDATE

Message ID: 41987

Message Description: LOG_ID_EVENT_VPN_CERT_UPDATE

Message Meaning: Certificate updated

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Message	string	4096
status	Status	string	23
reason	Reason	string	256
name	Name	string	128
cert-type	Certification type	string	6
method	Method	string	64

41988 - LOG_ID_EVENT_SSL_VPN_SETTING_UPDATE

Message ID: 41988

Message Description: LOG_ID_EVENT_SSL_VPN_SETTING_UPDATE

Message Meaning: SSL setting changed

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
user	User Name	string	256
msg	Message	string	4096
ui	User Interface	string	64

41989 - LOG_ID_EVENT_VPN_CERT_ERR

Message ID: 41989

Message Description: LOG_ID_EVENT_VPN_CERT_ERR

Message Meaning: Certificate error

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Message	string	4096
status	Status	string	23
name	Name	string	128

Log Field Name	Description	Data Type	Length
cert-type	Certification type	string	6
method	Method	string	64

41990 - LOG_ID_EVENT_VPN_CERT_UPDATE_FAILED

Message ID: 41990

Message Description: LOG_ID_EVENT_VPN_CERT_UPDATE_FAILED

Message Meaning: Certificate update failed

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Message	string	4096
status	Status	string	23
reason	Reason	string	256
name	Name	string	128
cert-type	Certification type	string	6
method	Method	string	64

41991 - LOG_ID_EVENT_VPN_CERT_EXPORT

Message ID: 41991

Message Description: LOG_ID_EVENT_VPN_CERT_EXPORT

Message Meaning: Certificate exported

Type: Event

Category: VPN

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
user	User Name	string	256
msg	Message	string	4096
status	Status	string	23
ui	User Interface	string	64
name	Name	string	128
cert-type	Certification type	string	6

42201 - LOG_ID_NETX_VMX_ATTACH

Message ID: 42201

Message Description: LOG_ID_NETX_VMX_ATTACH

Message Meaning: VMX instance successfully attached

Type: Event

Category: SYSTEM**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

42202 - LOG_ID_NETX_VMX_DETACH

Message ID: 42202**Message Description:** LOG_ID_NETX_VMX_DETACH**Message Meaning:** VMX instance successfully detached**Type:** Event**Category:** SYSTEM**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

42203 - LOG_ID_NETX_VMX_DENIED

Message ID: 42203

Message Description: LOG_ID_NETX_VMX_DENIED

Message Meaning: VMX instance successfully denied

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

43008 - LOG_ID_EVENT_AUTH_SUCCESS

Message ID: 43008

Message Description: LOG_ID_EVENT_AUTH_SUCCESS

Message Meaning: Authentication success

Type: Event

Category: USER**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
authproto	The protocol that initiated the authentication	string	512
action	Action	string	65
status	Status	string	23
msg	Message	string	4096
srcip	Source IP	ip	39
reason	Reason	string	256
dstip	Destination IP	ip	39
policyid	Policy ID	uint32	10
interface		string	32
group	User Group Name	string	64

43009 - LOG_ID_EVENT_AUTH_FAILED

Message ID: 43009**Message Description:** LOG_ID_EVENT_AUTH_FAILED**Message Meaning:** Authentication failed**Type:** Event**Category:** USER**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
authproto	The protocol that initiated the authentication	string	512
action	Action	string	65
status	Status	string	23
msg	Message	string	4096
srcip	Source IP	ip	39
reason	Reason	string	256
dstip	Destination IP	ip	39
policyid	Policy ID	uint32	10
interface		string	32
group	User Group Name	string	64

43010 - LOG_ID_EVENT_AUTH_LOCKOUT

Message ID: 43010

Message Description: LOG_ID_EVENT_AUTH_LOCKOUT

Message Meaning: Authentication lockout

Type: Event

Category: USER

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
authproto	The protocol that initiated the authentication	string	512
action	Action	string	65
status	Status	string	23
msg	Message	string	4096
srcip	Source IP	ip	39
reason	Reason	string	256
dstip	Destination IP	ip	39
policyid	Policy ID	uint32	10
interface		string	32
group	User Group Name	string	64

43011 - LOG_ID_EVENT_AUTH_TIME_OUT

Message ID: 43011

Message Description: LOG_ID_EVENT_AUTH_TIME_OUT

Message Meaning: Authentication timed out

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
authproto	The protocol that initiated the authentication	string	512
action	Action	string	65
status	Status	string	23
msg	Message	string	4096
srcip	Source IP	ip	39
reason	Reason	string	256
dstip	Destination IP	ip	39
policyid	Policy ID	uint32	10
interface		string	32
group	User Group Name	string	64
authserver		string	32

43014 - LOG_ID_EVENT_AUTH_FSAE_LOGON

Message ID: 43014

Message Description: LOG_ID_EVENT_AUTH_FSAE_LOGON

Message Meaning: FSSO logon authentication status

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
action	Action	string	65
msg	Message	string	4096
srcip	Source IP	ip	39
server	AD server FQDN or IP	string	64

43015 - LOG_ID_EVENT_AUTH_FSAE_LOGOFF

Message ID: 43015

Message Description: LOG_ID_EVENT_AUTH_FSAE_LOGOFF

Message Meaning: FSSO log off authentication status

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
action	Action	string	65
msg	Message	string	4096
srcip	Source IP	ip	39
server	AD server FQDN or IP	string	64

43016 - LOG_ID_EVENT_AUTH_NTLM_AUTH_SUCCESS

Message ID: 43016

Message Description: LOG_ID_EVENT_AUTH_NTLM_AUTH_SUCCESS

Message Meaning: NTLM authentication successful

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	4096
user	User Name	string	256
authproto	The protocol that initiated the authentication	string	512
action	Action	string	65
status	Status	string	23
msg	Message	string	4096
srcip	Source IP	ip	39
reason	Reason	string	256
dstip	Destination IP	ip	39
policyid	Policy ID	uint32	10
group	User Group Name	string	64
adgroup	AD Group Name	string	128

43017 - LOG_ID_EVENT_AUTH_NTLM_AUTH_FAIL

Message ID: 43017

Message Description: LOG_ID_EVENT_AUTH_NTLM_AUTH_FAIL

Message Meaning: NTLM authentication failed

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
authproto	The protocol that initiated the authentication	string	512
action	Action	string	65
status	Status	string	23
msg	Message	string	4096
srcip	Source IP	ip	39
reason	Reason	string	256
dstip	Destination IP	ip	39
policyid	Policy ID	uint32	10
group	User Group Name	string	64
adgroup	AD Group Name	string	128

43018 - LOG_ID_EVENT_AUTH_FGOVRD_FAIL

Message ID: 43018

Message Description: LOG_ID_EVENT_AUTH_FGOVRD_FAIL

Message Meaning: FortiGuard override failed

Type: Event

Category: USER

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
status	Status	string	23
msg	Message	string	4096
srcip	Source IP	ip	39
reason	Reason	string	256
dstip	Destination IP	ip	39
initiator	Original login user name for Fortiguard override	string	64

43020 - LOG_ID_EVENT_AUTH_FGOVRD_SUCCESS

Message ID: 43020

Message Description: LOG_ID_EVENT_AUTH_FGOVRD_SUCCESS

Message Meaning: FortiGuard override successful

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
status	Status	string	23

Log Field Name	Description	Data Type	Length
msg	Message	string	4096
srcip	Source IP	ip	39
reason	Reason	string	256
dstip	Destination IP	ip	39
initiator	Original login user name for Fortiguard override	string	64
scope	FortiGuard Override Scope	string	16
expiry	FortiGuard override expiry timestamp	string	64
oldwprof	Old Web Filter Profile	string	64

43025 - LOG_ID_EVENT_AUTH_PROXY_SUCCESS

Message ID: 43025

Message Description: LOG_ID_EVENT_AUTH_PROXY_SUCCESS

Message Meaning: Explicit proxy authentication successful

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
authproto	The protocol that initiated the authentication	string	512

Log Field Name	Description	Data Type	Length
action	Action	string	65
status	Status	string	23
msg	Message	string	4096
srcip	Source IP	ip	39
reason	Reason	string	256
dstip	Destination IP	ip	39
group	User Group Name	string	64
authid		string	36

43026 - LOG_ID_EVENT_AUTH_PROXY_FAILED

Message ID: 43026

Message Description: LOG_ID_EVENT_AUTH_PROXY_FAILED

Message Meaning: Explicit proxy authentication failed

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
authproto	The protocol that initiated the authentication	string	512

Log Field Name	Description	Data Type	Length
action	Action	string	65
status	Status	string	23
msg	Message	string	4096
srcip	Source IP	ip	39
reason	Reason	string	256
dstip	Destination IP	ip	39
group	User Group Name	string	64
authid		string	36

43027 - LOG_ID_EVENT_AUTH_PROXY_TIME_OUT

Message ID: 43027

Message Description: LOG_ID_EVENT_AUTH_PROXY_TIME_OUT

Message Meaning: Explicit proxy authentication timed out

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
authproto	The protocol that initiated the authentication	string	512

Log Field Name	Description	Data Type	Length
action	Action	string	65
status	Status	string	23
msg	Message	string	4096
srcip	Source IP	ip	39
reason	Reason	string	256
dstip	Destination IP	ip	39
group	User Group Name	string	64

43028 - LOG_ID_EVENT_AUTH_PROXY_GROUP_INFO_FAILED

Message ID: 43028

Message Description: LOG_ID_EVENT_AUTH_PROXY_GROUP_INFO_FAILED

Message Meaning: Explicit proxy user group query failed

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
authproto	The protocol that initiated the authentication	string	512
action	Action	string	65

Log Field Name	Description	Data Type	Length
status	Status	string	23
msg	Message	string	4096
srcip	Source IP	ip	39
reason	Reason	string	256
dstip	Destination IP	ip	39
group	User Group Name	string	64
authid		string	36

43029 - LOG_ID_EVENT_AUTH_WARNING_SUCCESS

Message ID: 43029

Message Description: LOG_ID_EVENT_AUTH_WARNING_SUCCESS

Message Meaning: FortiGuard authentication override successful

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
status	Status	string	23
msg	Message	string	4096
srcip	Source IP	ip	39

Log Field Name	Description	Data Type	Length
reason	Reason	string	256
dstip	Destination IP	ip	39
initiator	Original login user name for Fortiguard override	string	64
scope	FortiGuard Override Scope	string	16
expiry	FortiGuard override expiry timestamp	string	64
oldwprof	Old Web Filter Profile	string	64
category		uint32	10

43030 - LOG_ID_EVENT_AUTH_WARNING_TBL_FULL

Message ID: 43030

Message Description: LOG_ID_EVENT_AUTH_WARNING_TBL_FULL

Message Meaning: FortiGuard authentication override failed

Type: Event

Category: USER

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
status	Status	string	23
msg	Message	string	4096
srcip	Source IP	ip	39

Log Field Name	Description	Data Type	Length
reason	Reason	string	256
dstip	Destination IP	ip	39
initiator	Original login user name for Fortiguard override	string	64

43032 - LOG_ID_EVENT_AUTH_PROXY_USER_LIMIT_REACHED

Message ID: 43032

Message Description: LOG_ID_EVENT_AUTH_PROXY_USER_LIMIT_REACHED

Message Meaning: Explicit proxy authentication user limit reached

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
authproto	The protocol that initiated the authentication	string	512
action	Action	string	65
status	Status	string	23
msg	Message	string	4096
srcip	Source IP	ip	39
reason	Reason	string	256

Log Field Name	Description	Data Type	Length
dstip	Destination IP	ip	39
group	User Group Name	string	64
authid		string	36

43033 - LOG_ID_EVENT_AUTH_PROXY_MULTIPLE_LOGIN

Message ID: 43033

Message Description: LOG_ID_EVENT_AUTH_PROXY_MULTIPLE_LOGIN

Message Meaning: Explicit proxy authentication user concurrent check failed

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
authproto	The protocol that initiated the authentication	string	512
action	Action	string	65
status	Status	string	23
msg	Message	string	4096
srcip	Source IP	ip	39
reason	Reason	string	256

Log Field Name	Description	Data Type	Length
dstip	Destination IP	ip	39
group	User Group Name	string	64
authid		string	36

43034 - LOG_ID_EVENT_AUTH_PROXY_NO_RESP

Message ID: 43034

Message Description: LOG_ID_EVENT_AUTH_PROXY_NO_RESP

Message Meaning: Explicit proxy authentication no response

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
status	Status	string	23
msg	Message	string	4096
srcip	Source IP	ip	39
dstip	Destination IP	ip	39
policyid	Policy ID	uint32	10
url		string	512
agent		string	64

43037 - LOG_ID_EVENT_AUTH_IPV4_FLUSH

Message ID: 43037

Message Description: LOG_ID_EVENT_AUTH_IPV4_FLUSH

Message Meaning: Authentication IPv4 logon flush

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
status	Status	string	23
msg	Message	string	4096

43038 - LOG_ID_EVENT_AUTH_IPV6_FLUSH

Message ID: 43038

Message Description: LOG_ID_EVENT_AUTH_IPV6_FLUSH

Message Meaning: Authentication IPv6 logon flush

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
status	Status	string	23
msg	Message	string	4096

43039 - LOG_ID_EVENT_AUTH_LOGON

Message ID: 43039

Message Description: LOG_ID_EVENT_AUTH_LOGON

Message Meaning: Authentication logon

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
action	Action	string	65
status	Status	string	23
msg	Message	string	4096
srcip	Source IP	ip	39
authserver		string	32

43040 - LOG_ID_EVENT_AUTH_LOGOUT

Message ID: 43040

Message Description: LOG_ID_EVENT_AUTH_LOGOUT

Message Meaning: Authentication logout

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096

Log Field Name	Description	Data Type	Length
user	User Name	string	256
action	Action	string	65
status	Status	string	23
msg	Message	string	4096
srcip	Source IP	ip	39
authserver		string	32

43041 - LOG_ID_EVENT_AUTH_DISCLAIMER_ACCEPT

Message ID: 43041

Message Description: LOG_ID_EVENT_AUTH_DISCLAIMER_ACCEPT

Message Meaning: Disclaimer accepted

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
authproto	The protocol that initiated the authentication	string	512
action	Action	string	65
status	Status	string	23

Log Field Name	Description	Data Type	Length
msg	Message	string	4096
srcip	Source IP	ip	39
reason	Reason	string	256
dstip	Destination IP	ip	39
policyid	Policy ID	uint32	10
interface		string	32
group	User Group Name	string	64

43042 - LOG_ID_EVENT_AUTH_DISCLAIMER_DECLINE

Message ID: 43042

Message Description: LOG_ID_EVENT_AUTH_DISCLAIMER_DECLINE

Message Meaning: Disclaimer declined

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
authproto	The protocol that initiated the authentication	string	512
action	Action	string	65

Log Field Name	Description	Data Type	Length
status	Status	string	23
msg	Message	string	4096
srcip	Source IP	ip	39
reason	Reason	string	256
dstip	Destination IP	ip	39
policyid	Policy ID	uint32	10
interface		string	32
group	User Group Name	string	64

43043 - LOG_ID_EVENT_AUTH_EMAIL_COLLECTING_SUCCESS

Message ID: 43043

Message Description: LOG_ID_EVENT_AUTH_EMAIL_COLLECTING_SUCCESS

Message Meaning: Email collecting succeeded

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
authproto	The protocol that initiated the authentication	string	512

Log Field Name	Description	Data Type	Length
action	Action	string	65
status	Status	string	23
msg	Message	string	4096
srcip	Source IP	ip	39
reason	Reason	string	256
dstip	Destination IP	ip	39
policyid	Policy ID	uint32	10
interface		string	32
group	User Group Name	string	64

43044 - LOG_ID_EVENT_AUTH_EMAIL_COLLECTING_FAIL

Message ID: 43044

Message Description: LOG_ID_EVENT_AUTH_EMAIL_COLLECTING_FAIL

Message Meaning: Email collecting failed

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256

Log Field Name	Description	Data Type	Length
authproto	The protocol that initiated the authentication	string	512
action	Action	string	65
status	Status	string	23
msg	Message	string	4096
srcip	Source IP	ip	39
reason	Reason	string	256
dstip	Destination IP	ip	39
policyid	Policy ID	uint32	10
interface		string	32
group	User Group Name	string	64

43045 - LOG_ID_EVENT_AUTH_8021X_SUCCESS

Message ID: 43045

Message Description: LOG_ID_EVENT_AUTH_8021X_SUCCESS

Message Meaning: 802.1x authentication succeeded

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096

Log Field Name	Description	Data Type	Length
user	User Name	string	256
action	Action	string	65
status	Status	string	23
msg	Message	string	4096
reason	Reason	string	256
interface		string	32
stamac		string	17

43046 - LOG_ID_EVENT_AUTH_8021X_FAIL

Message ID: 43046

Message Description: LOG_ID_EVENT_AUTH_8021X_FAIL

Message Meaning: 802.1x authentication failed

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
action	Action	string	65
status	Status	string	23

Log Field Name	Description	Data Type	Length
msg	Message	string	4096
reason	Reason	string	256
interface		string	32
stamac		string	17

43050 - LOG_ID_EVENT_AUTH_FSAE_CONNECT

Message ID: 43050

Message Description: LOG_ID_EVENT_AUTH_FSAE_CONNECT

Message Meaning: FSSO server connected

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Message	string	4096
server	AD server FQDN or IP	string	64

43051 - LOG_ID_EVENT_AUTH_FSAE_DISCONNECT

Message ID: 43051

Message Description: LOG_ID_EVENT_AUTH_FSAE_DISCONNECT

Message Meaning: FSSO server disconnected

Type: Event

Category: USER

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Message	string	4096
server	AD server FQDN or IP	string	64

43264 - LOGID_MMS_STATS

Message ID: 43264

Message Description: LOGID_MMS_STATS

Message Meaning: MMS statistics

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
duration	Duration	uint32	10
msgproto	Message Protocol Number	string	16
infected	Infected MMS	uint32	10
suspicious	Number of Suspicious MMSs	uint32	10
scanned	Number of Scanned MMSs	uint32	10
checksum	for MMS Statistics	uint32	10

43520 - LOG_ID_EVENT_WIRELESS_SYS

Message ID: 43520

Message Description: LOG_ID_EVENT_WIRELESS_SYS

Message Meaning: Wireless system activity

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096

43521 - LOG_ID_EVENT_WIRELESS_ROGUE

Message ID: 43521

Message Description: LOG_ID_EVENT_WIRELESS_ROGUE

Message Meaning: Rogue AP activity

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
bssid	Service Set ID	string	17

Log Field Name	Description	Data Type	Length
aptype	AP Type	uint8	3
rate		uint16	6
radioband	Radio Band	string	64
channel	Channel	uint8	3
manuf	Manufacturer name	string	20
security	Security	string	40
encryption	Encryption Method	string	12
signal	Signal	int8	4
noise		int8	4
live	time in seconds	uint32	10
age	time in seconds - time passed since last seen	uint32	10
onwire	A flag to indicate if the AP is onwire or not	string	3
detectionmethod	Detection Method	string	21
stamac	Station/Client MAC address	string	17
apscan	The name of the AP, which scanned and detected the rogue AP	string	36
sndetected	SN of the AP which detected the rogue AP	string	36
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
stacount	Number of stations/clients	uint32	10
snclosest	SN of the AP closest to the rogue AP	string	36
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
apstatus	Access Point Status	uint8	3

43522 - LOG_ID_EVENT_WIRELESS_WTP

Message ID: 43522

Message Description: LOG_ID_EVENT_WIRELESS_WTP

Message Meaning: Physical AP activity

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
sn	Serial Number	string	64
ap	Access Point	string	36
profile	Profile Name	string	64
ip		ip	39
meshmode	Mesh mode	string	19
snmeshparent	SN of the mesh parent	string	36
reason	Reason	string	256

43524 - LOG_ID_EVENT_WIRELESS_STA

Message ID: 43524

Message Description: LOG_ID_EVENT_WIRELESS_STA

Message Meaning: Wireless client activity

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10

Log Field Name	Description	Data Type	Length
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
radioband	Radio Band	string	64
channel	Channel	uint8	3
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3
user	User Name	string	256
group	User Group Name	string	64
srcip	Source IP	ip	39
mpsk		string	33

43525 - LOG_ID_EVENT_WIRELESS_ONWIRE

Message ID: 43525

Message Description: LOG_ID_EVENT_WIRELESS_ONWIRE

Message Meaning: Rogue AP on wire**Type:** Event**Category:** WIRELESS**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
bssid	Service Set ID	string	17
aptype	AP Type	uint8	3
rate		uint16	6
radioband	Radio Band	string	64
channel	Channel	uint8	3
manuf	Manufacturer name	string	20
security	Security	string	40
encryption	Encryption Method	string	12
signal	Signal	int8	4
noise		int8	4
live	time in seconds	uint32	10
age	time in seconds - time passed since last seen	uint32	10
onwire	A flag to indicate if the AP is onwire or not	string	3

Log Field Name	Description	Data Type	Length
detectionmethod	Detection Method	string	21
stamac	Station/Client MAC address	string	17
apscan	The name of the AP, which scanned and detected the rogue AP	string	36
sndetected	SN of the AP which detected the rogue AP	string	36
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
stacount	Number of stations/clients	uint32	10
snclosest	SN of the AP closest to the rogue AP	string	36
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
apstatus	Access Point Status	uint8	3

43526 - LOG_ID_EVENT_WIRELESS_WTPR

Message ID: 43526

Message Description: LOG_ID_EVENT_WIRELESS_WTPR

Message Meaning: Physical AP radio activity

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65

Log Field Name	Description	Data Type	Length
msg	Log Message	string	4096
radioband	Radio Band	string	64
sn	Serial Number	string	64
ap	Access Point	string	36
ip		ip	39
radioid	Radio ID	uint8	3
bandwidth	Bandwidth	string	42
configcountry	Config Country	string	4
opercountry	Operating Country	string	4
cftgtxpower	Config TX power	uint32	10
opertxpower	Operating TX power	uint32	10

43527 - LOG_ID_EVENT_WIRELESS_ROGUE_CFG

Message ID: 43527

Message Description: LOG_ID_EVENT_WIRELESS_ROGUE_CFG

Message Meaning: Rogue AP status configured

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
bssid	Service Set ID	string	17
apstatus	Access Point Status	uint8	3

43528 - LOG_ID_EVENT_WIRELESS_WTPR_ERROR

Message ID: 43528

Message Description: LOG_ID_EVENT_WIRELESS_WTPR_ERROR

Message Meaning: Physical AP radio error activity

Type: Event

Category: WIRELESS

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
radioband	Radio Band	string	64
sn	Serial Number	string	64

Log Field Name	Description	Data Type	Length
ap	Access Point	string	36
ip		ip	39
radioid	Radio ID	uint8	3
bandwidth	Bandwidth	string	42
configcountry	Config Country	string	4
opercountry	Operating Country	string	4
cfgtxpower	Config TX power	uint32	10
opertxpower	Operating TX power	uint32	10

43529 - LOG_ID_EVENT_WIRELESS_CLB

Message ID: 43529

Message Description: LOG_ID_EVENT_WIRELESS_CLB

Message Meaning: Wireless client load balancing

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096

Log Field Name	Description	Data Type	Length
ssid	Base Service Set ID	string	33
radioband	Radio Band	string	64
stamac	Station/Client MAC address	string	17
stacount	Number of stations/clients	uint32	10
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36

43530 - LOG_ID_EVENT_WIRELESS_WIDS_WL_BRIDGE

Message ID: 43530

Message Description: LOG_ID_EVENT_WIRELESS_WIDS_WL_BRIDGE

Message Meaning: Wireless bridge intrusion detected

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096

Log Field Name	Description	Data Type	Length
bssid	Service Set ID	string	17
channel	Channel	uint8	3
manuf	Manufacturer name	string	20
live	time in seconds	uint32	10
age	time in seconds - time passed since last seen	uint32	10
sndetected	SN of the AP which detected the rogue AP	string	36
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
threatype	WIDS threat type	string	64
rsssi	Received signal strength indicator	uint8	3
frametype	Frame Type	string	32
ds	direction with distribution system	string	8
seq	Sequence	string	16
encrypt	whether the packet is encrypted or not	uint8	3
tamac	the MAC address of Transmitter, if none, then Receiver	string	17

43531 - LOG_ID_EVENT_WIRELESS_WIDS_BR_DEAUTH

Message ID: 43531

Message Description: LOG_ID_EVENT_WIRELESS_WIDS_BR_DEAUTH

Message Meaning: Wireless broadcasting deauthentication detected

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
bssid	Service Set ID	string	17
channel	Channel	uint8	3
manuf	Manufacturer name	string	20
live	time in seconds	uint32	10
age	time in seconds - time passed since last seen	uint32	10
sndetected	SN of the AP which detected the rogue AP	string	36
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
threattype	WIDS threat type	string	64
rsi	Received signal strength indicator	uint8	3
frametype	Frame Type	string	32
ds	direction with distribution system	string	8
seq	Sequence	string	16
encrypt	whether the packet is encrypted or not	uint8	3
tamac	the MAC address of Transmitter, if none, then Receiver	string	17

43532 - LOG_ID_EVENT_WIRELESS_WIDS_NL_PBRESP

Message ID: 43532

Message Description: LOG_ID_EVENT_WIRELESS_WIDS_NL_PBRESP

Message Meaning: Wireless null SSID probe response detected

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10

Log Field Name	Description	Data Type	Length
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
bssid	Service Set ID	string	17
channel	Channel	uint8	3
manuf	Manufacturer name	string	20
live	time in seconds	uint32	10
age	time in seconds - time passed since last seen	uint32	10
sndetected	SN of the AP which detected the rogue AP	string	36
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
threattype	WIDS threat type	string	64
rsi	Received signal strength indicator	uint8	3
frametype	Frame Type	string	32
ds	direction with distribution system	string	8
seq	Sequence	string	16
encrypt	whether the packet is encrypted or not	uint8	3
tamac	the MAC address of Transmitter, if none, then Receiver	string	17

43533 - LOG_ID_EVENT_WIRELESS_WIDS_MAC_OUI

Message ID: 43533

Message Description: LOG_ID_EVENT_WIRELESS_WIDS_MAC_OUI

Message Meaning: Wireless invalid MAC OUI detected

Type: Event**Category:** WIRELESS**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
bssid	Service Set ID	string	17
channel	Channel	uint8	3
manuf	Manufacturer name	string	20
live	time in seconds	uint32	10
age	time in seconds - time passed since last seen	uint32	10
sndetected	SN of the AP which detected the rogue AP	string	36
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
threattype	WIDS threat type	string	64
rsssi	Received signal strength indicator	uint8	3
frametype	Frame Type	string	32
ds	direction with distribution system	string	8
seq	Sequence	string	16
encrypt	whether the packet is encrypted or not	uint8	3
tamac	the MAC address of Transmitter, if none, then Receiver	string	17
invalidmac	the MAC address with invalid OUI	string	17

43534 - LOG_ID_EVENT_WIRELESS_WIDS_LONG_DUR

Message ID: 43534

Message Description: LOG_ID_EVENT_WIRELESS_WIDS_LONG_DUR

Message Meaning: Wireless long duration attack detected

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
bssid	Service Set ID	string	17
channel	Channel	uint8	3
manuf	Manufacturer name	string	20
live	time in seconds	uint32	10
age	time in seconds - time passed since last seen	uint32	10
sndetected	SN of the AP which detected the rogue AP	string	36
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
threattype	WIDS threat type	string	64
rss	Received signal strength indicator	uint8	3
frametype	Frame Type	string	32

Log Field Name	Description	Data Type	Length
ds	direction with distribution system	string	8
seq	Sequence	string	16
encrypt	whether the packet is encrypted or not	uint8	3
tamac	the MAC address of Transmitter, if none, then Receiver	string	17
duration	Duration of the last threatening packed captured from TA	uint32	10

43535 - LOG_ID_EVENT_WIRELESS_WIDS_WEP_IV

Message ID: 43535

Message Description: LOG_ID_EVENT_WIRELESS_WIDS_WEP_IV

Message Meaning: Wireless Weak WEP IV detected

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
bssid	Service Set ID	string	17
channel	Channel	uint8	3
manuf	Manufacturer name	string	20

Log Field Name	Description	Data Type	Length
live	time in seconds	uint32	10
age	time in seconds - time passed since last seen	uint32	10
sndetected	SN of the AP which detected the rogue AP	string	36
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
threatype	WIDS threat type	string	64
rsssi	Received signal strength indicator	uint8	3
frametype	Frame Type	string	32
ds	direction with distribution system	string	8
seq	Sequence	string	16
encrypt	whether the packet is encrypted or not	uint8	3
tamac	the MAC address of Transmitter, if none, then Receiver	string	17
weakwepiv	Weak Wep Initiation Vector	string	8

43542 - LOG_ID_EVENT_WIRELESS_WIDS_EAPOL_FLOOD

Message ID: 43542

Message Description: LOG_ID_EVENT_WIRELESS_WIDS_EAPOL_FLOOD

Message Meaning: Wireless EAPOL packet flooding detected

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
manuf	Manufacturer name	string	20
live	time in seconds	uint32	10
sndetected	SN of the AP which detected the rogue AP	string	36
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
threattype	WIDS threat type	string	64
tamac	the MAC address of Transmitter, if none, then Receiver	string	17
eapoltype	EAPOL packet type	string	16
eapolcnt	EAPOL packet count	uint32	10

43544 - LOG_ID_EVENT_WIRELESS_WIDS_MGMT_FLOOD

Message ID: 43544

Message Description: LOG_ID_EVENT_WIRELESS_WIDS_MGMT_FLOOD

Message Meaning: Wireless management flooding detected

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
bssid	Service Set ID	string	17
channel	Channel	uint8	3
manuf	Manufacturer name	string	20
live	time in seconds	uint32	10
age	time in seconds - time passed since last seen	uint32	10
sndetected	SN of the AP which detected the rogue AP	string	36
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
threattype	WIDS threat type	string	64
rss	Received signal strength indicator	uint8	3
frametype	Frame Type	string	32
ds	direction with distribution system	string	8
tamac	the MAC address of Transmitter, if none, then Receiver	string	17
mgmtcnt	The number of unauthorized client flooding managemet frames	uint32	10

43546 - LOG_ID_EVENT_WIRELESS_WIDS_SPOOF_DEAUTH

Message ID: 43546

Message Description: LOG_ID_EVENT_WIRELESS_WIDS_SPOOF_DEAUTH

Message Meaning: Wireless spoofed deauthentication detected

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
bssid	Service Set ID	string	17
channel	Channel	uint8	3
manuf	Manufacturer name	string	20
live	time in seconds	uint32	10
age	time in seconds - time passed since last seen	uint32	10
sndetected	SN of the AP which detected the rogue AP	string	36
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
threattype	WIDS threat type	string	64
rsi	Received signal strength indicator	uint8	3
frametype	Frame Type	string	32
ds	direction with distribution system	string	8
seq	Sequence	string	16
encrypt	whether the packet is encrypted or not	uint8	3
tamac	the MAC address of Transmitter, if none, then Receiver	string	17

43548 - LOG_ID_EVENT_WIRELESS_WIDS_ASLEAP

Message ID: 43548

Message Description: LOG_ID_EVENT_WIRELESS_WIDS_ASLEAP

Message Meaning: Wireless Asleep attack detected

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
bssid	Service Set ID	string	17
channel	Channel	uint8	3
manuf	Manufacturer name	string	20
live	time in seconds	uint32	10
age	time in seconds - time passed since last seen	uint32	10
sndetected	SN of the AP which detected the rogue AP	string	36
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
threattype	WIDS threat type	string	64
rsssi	Received signal strength indicator	uint8	3
frametype	Frame Type	string	32
ds	direction with distribution system	string	8
seq	Sequence	string	16
encrypt	whether the packet is encrypted or not	uint8	3
tamac	the MAC address of Transmitter, if none, then Receiver	string	17

43550 - LOG_ID_EVENT_WIRELESS_STA_LOCATE

Message ID: 43550

Message Description: LOG_ID_EVENT_WIRELESS_STA_LOCATE

Message Meaning: Wireless station presence detection

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
radioband	Radio Band	string	64
signal	Signal	int8	4
noise		int8	4
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
radioid	Radio ID	uint8	3

43551 - LOG_ID_EVENT_WIRELESS_WTP_JOIN

Message ID: 43551

Message Description: LOG_ID_EVENT_WIRELESS_WTP_JOIN

Message Meaning: Physical AP join

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
sn	Serial Number	string	64
ap	Access Point	string	36
profile	Profile Name	string	64
ip		ip	39
meshmode	Mesh mode	string	19
snmeshparent	SN of the mesh parent	string	36
reason	Reason	string	256

43552 - LOG_ID_EVENT_WIRELESS_WTP_LEAVE

Message ID: 43552

Message Description: LOG_ID_EVENT_WIRELESS_WTP_LEAVE

Message Meaning: Physical AP leave

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10

Log Field Name	Description	Data Type	Length
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
sn	Serial Number	string	64
ap	Access Point	string	36
profile	Profile Name	string	64
ip		ip	39
meshmode	Mesh mode	string	19
snmeshparent	SN of the mesh parent	string	36
reason	Reason	string	256

43553 - LOG_ID_EVENT_WIRELESS_WTP_FAIL

Message ID: 43553

Message Description: LOG_ID_EVENT_WIRELESS_WTP_FAIL

Message Meaning: Physical AP fail

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
sn	Serial Number	string	64
ap	Access Point	string	36
profile	Profile Name	string	64
ip		ip	39
meshmode	Mesh mode	string	19
snmeshparent	SN of the mesh parent	string	36
reason	Reason	string	256

43554 - LOG_ID_EVENT_WIRELESS_WTP_UPDATE

Message ID: 43554

Message Description: LOG_ID_EVENT_WIRELESS_WTP_UPDATE

Message Meaning: Physical AP update

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
sn	Serial Number	string	64
ap	Access Point	string	36
profile	Profile Name	string	64
ip		ip	39
meshmode	Mesh mode	string	19
snmeshparent	SN of the mesh parent	string	36
reason	Reason	string	256

43555 - LOG_ID_EVENT_WIRELESS_WTP_RESET

Message ID: 43555

Message Description: LOG_ID_EVENT_WIRELESS_WTP_RESET

Message Meaning: Physical AP reset

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
sn	Serial Number	string	64
ap	Access Point	string	36
profile	Profile Name	string	64
ip		ip	39
meshmode	Mesh mode	string	19
snmeshparent	SN of the mesh parent	string	36
reason	Reason	string	256

43556 - LOG_ID_EVENT_WIRELESS_WTP_KICK

Message ID: 43556

Message Description: LOG_ID_EVENT_WIRELESS_WTP_KICK

Message Meaning: Physical AP kick

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
sn	Serial Number	string	64
ap	Access Point	string	36
profile	Profile Name	string	64
ip		ip	39
meshmode	Mesh mode	string	19
snmeshparent	SN of the mesh parent	string	36
reason	Reason	string	256

43557 - LOG_ID_EVENT_WIRELESS_WTP_ADD_FAILURE

Message ID: 43557

Message Description: LOG_ID_EVENT_WIRELESS_WTP_ADD_FAILURE

Message Meaning: Physical AP add failure

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
sn	Serial Number	string	64
ap	Access Point	string	36
profile	Profile Name	string	64
ip		ip	39
meshmode	Mesh mode	string	19
snmeshparent	SN of the mesh parent	string	36
reason	Reason	string	256

43558 - LOG_ID_EVENT_WIRELESS_WTP_CFG_ERR

Message ID: 43558

Message Description: LOG_ID_EVENT_WIRELESS_WTP_CFG_ERR

Message Meaning: Physical AP config error

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
sn	Serial Number	string	64
ap	Access Point	string	36
profile	Profile Name	string	64
ip		ip	39
meshmode	Mesh mode	string	19
snmeshparent	SN of the mesh parent	string	36
reason	Reason	string	256

43559 - LOG_ID_EVENT_WIRELESS_WTP_SN_MISMATCH

Message ID: 43559

Message Description: LOG_ID_EVENT_WIRELESS_WTP_SN_MISMATCH

Message Meaning: Physical AP SN mismatch

Type: Event

Category: WIRELESS

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
sn	Serial Number	string	64
ap	Access Point	string	36
profile	Profile Name	string	64
ip		ip	39
meshmode	Mesh mode	string	19
snmeshparent	SN of the mesh parent	string	36
reason	Reason	string	256

43560 - LOG_ID_EVENT_WIRELESS_SYS_AC_RESTARTED

Message ID: 43560

Message Description: LOG_ID_EVENT_WIRELESS_SYS_AC_RESTARTED

Message Meaning: Wireless system restarted

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096

43561 - LOG_ID_EVENT_WIRELESS_SYS_AC_HOSTAPD_UP

Message ID: 43561

Message Description: LOG_ID_EVENT_WIRELESS_SYS_AC_HOSTAPD_UP

Message Meaning: Wireless system hostapd up

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096

43562 - LOG_ID_EVENT_WIRELESS_SYS_AC_HOSTAPD_DOWN

Message ID: 43562

Message Description: LOG_ID_EVENT_WIRELESS_SYS_AC_HOSTAPD_DOWN

Message Meaning: Wireless system hostapd down

Type: Event**Category:** WIRELESS**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096

43563 - LOG_ID_EVENT_WIRELESS_ROGUE_DETECT

Message ID: 43563**Message Description:** LOG_ID_EVENT_WIRELESS_ROGUE_DETECT**Message Meaning:** Rogue AP detected**Type:** Event**Category:** WIRELESS**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
bssid	Service Set ID	string	17
aptype	AP Type	uint8	3
rate		uint16	6
radioband	Radio Band	string	64
channel	Channel	uint8	3
manuf	Manufacturer name	string	20
security	Security	string	40
encryption	Encryption Method	string	12
signal	Signal	int8	4
noise		int8	4
live	time in seconds	uint32	10
age	time in seconds - time passed since last seen	uint32	10
onwire	A flag to indicate if the AP is onwire or not	string	3
detectionmethod	Detection Method	string	21
stamac	Station/Client MAC address	string	17
apscan	The name of the AP, which scanned and detected the rogue AP	string	36
sndetected	SN of the AP which detected the rogue AP	string	36
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
stacount	Number of stations/clients	uint32	10
snclosest	SN of the AP closest to the rogue AP	string	36
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
apstatus	Access Point Status	uint8	3

43564 - LOG_ID_EVENT_WIRELESS_ROGUE_OFFAIR

Message ID: 43564

Message Description: LOG_ID_EVENT_WIRELESS_ROGUE_OFFAIR

Message Meaning: Rogue AP off air

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
bssid	Service Set ID	string	17
aptype	AP Type	uint8	3
rate		uint16	6
radioband	Radio Band	string	64
channel	Channel	uint8	3
manuf	Manufacturer name	string	20
security	Security	string	40
encryption	Encryption Method	string	12
signal	Signal	int8	4

Log Field Name	Description	Data Type	Length
noise		int8	4
live	time in seconds	uint32	10
age	time in seconds - time passed since last seen	uint32	10
onwire	A flag to indicate if the AP is onwire or not	string	3
detectionmethod	Detection Method	string	21
stamac	Station/Client MAC address	string	17
apscan	The name of the AP, which scanned and detected the rogue AP	string	36
sndetected	SN of the AP which detected the rogue AP	string	36
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
stacount	Number of stations/clients	uint32	10
snclosest	SN of the AP closest to the rogue AP	string	36
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
apstatus	Access Point Status	uint8	3

43565 - LOG_ID_EVENT_WIRELESS_ROGUE_ONAIR

Message ID: 43565

Message Description: LOG_ID_EVENT_WIRELESS_ROGUE_ONAIR

Message Meaning: Rogue AP on air

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
bssid	Service Set ID	string	17
aptype	AP Type	uint8	3
rate		uint16	6
radioband	Radio Band	string	64
channel	Channel	uint8	3
manuf	Manufacturer name	string	20
security	Security	string	40
encryption	Encryption Method	string	12
signal	Signal	int8	4
noise		int8	4
live	time in seconds	uint32	10
age	time in seconds - time passed since last seen	uint32	10
onwire	A flag to indicate if the AP is onwire or not	string	3
detectionmethod	Detection Method	string	21
stamac	Station/Client MAC address	string	17
apscan	The name of the AP, which scanned and detected the rogue AP	string	36
sndetected	SN of the AP which detected the rogue AP	string	36
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
stacount	Number of stations/clients	uint32	10
snclosest	SN of the AP closest to the rogue AP	string	36
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
apstatus	Access Point Status	uint8	3

43566 - LOG_ID_EVENT_WIRELESS_ROGUE_OFFWIRE

Message ID: 43566

Message Description: LOG_ID_EVENT_WIRELESS_ROGUE_OFFWIRE**Message Meaning:** Rogue AP off wire**Type:** Event**Category:** WIRELESS**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
bssid	Service Set ID	string	17
aptype	AP Type	uint8	3
rate		uint16	6
radioband	Radio Band	string	64
channel	Channel	uint8	3
manuf	Manufacturer name	string	20
security	Security	string	40
encryption	Encryption Method	string	12
signal	Signal	int8	4
noise		int8	4
live	time in seconds	uint32	10
age	time in seconds - time passed since last seen	uint32	10

Log Field Name	Description	Data Type	Length
onwire	A flag to indicate if the AP is onwire or not	string	3
detectionmethod	Detection Method	string	21
stamac	Station/Client MAC address	string	17
apscan	The name of the AP, which scanned and detected the rogue AP	string	36
sndetected	SN of the AP which detected the rogue AP	string	36
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
stacount	Number of stations/clients	uint32	10
snclosest	SN of the AP closest to the rogue AP	string	36
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
apstatus	Access Point Status	uint8	3

43567 - LOG_ID_EVENT_WIRELESS_FAKEAP_DETECT

Message ID: 43567

Message Description: LOG_ID_EVENT_WIRELESS_FAKEAP_DETECT

Message Meaning: Fake AP detected

Type: Event

Category: WIRELESS

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096

Log Field Name	Description	Data Type	Length
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
bssid	Service Set ID	string	17
aptype	AP Type	uint8	3
rate		uint16	6
radioband	Radio Band	string	64
channel	Channel	uint8	3
manuf	Manufacturer name	string	20
security	Security	string	40
encryption	Encryption Method	string	12
signal	Signal	int8	4
noise		int8	4
live	time in seconds	uint32	10
age	time in seconds - time passed since last seen	uint32	10
onwire	A flag to indicate if the AP is onwire or not	string	3
detectionmethod	Detection Method	string	21
stamac	Station/Client MAC address	string	17
apscan	The name of the AP, which scanned and detected the rogue AP	string	36
sndetected	SN of the AP which detected the rogue AP	string	36
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
stacount	Number of stations/clients	uint32	10
snclosest	SN of the AP closest to the rogue AP	string	36
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
apstatus	Access Point Status	uint8	3

43568 - LOG_ID_EVENT_WIRELESS_FAKEAP_ONAIR

Message ID: 43568

Message Description: LOG_ID_EVENT_WIRELESS_FAKEAP_ONAIR

Message Meaning: Fake AP on air

Type: Event

Category: WIRELESS**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
bssid	Service Set ID	string	17
aptype	AP Type	uint8	3
rate		uint16	6
radioband	Radio Band	string	64
channel	Channel	uint8	3
manuf	Manufacturer name	string	20
security	Security	string	40
encryption	Encryption Method	string	12
signal	Signal	int8	4
noise		int8	4
live	time in seconds	uint32	10
age	time in seconds - time passed since last seen	uint32	10
onwire	A flag to indicate if the AP is onwire or not	string	3
detectionmethod	Detection Method	string	21
stamac	Station/Client MAC address	string	17

Log Field Name	Description	Data Type	Length
apscan	The name of the AP, which scanned and detected the rogue AP	string	36
sndetected	SN of the AP which detected the rogue AP	string	36
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
stacount	Number of stations/clients	uint32	10
snclosest	SN of the AP closest to the rogue AP	string	36
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
apstatus	Access Point Status	uint8	3

43569 - LOG_ID_EVENT_WIRELESS_ROGUE_SUPPRESSED

Message ID: 43569

Message Description: LOG_ID_EVENT_WIRELESS_ROGUE_SUPPRESSED

Message Meaning: Rogue AP suppressed

Type: Event

Category: WIRELESS

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33

Log Field Name	Description	Data Type	Length
bssid	Service Set ID	string	17
aptype	AP Type	uint8	3
rate		uint16	6
radioband	Radio Band	string	64
channel	Channel	uint8	3
manuf	Manufacturer name	string	20
security	Security	string	40
encryption	Encryption Method	string	12
signal	Signal	int8	4
noise		int8	4
live	time in seconds	uint32	10
age	time in seconds - time passed since last seen	uint32	10
onwire	A flag to indicate if the AP is onwire or not	string	3
detectionmethod	Detection Method	string	21
stamac	Station/Client MAC address	string	17
apscan	The name of the AP, which scanned and detected the rogue AP	string	36
sndetected	SN of the AP which detected the rogue AP	string	36
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
stacount	Number of stations/clients	uint32	10
snclosest	SN of the AP closest to the rogue AP	string	36
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
apstatus	Access Point Status	uint8	3

43570 - LOG_ID_EVENT_WIRELESS_ROGUE_UNSUPPRESSED

Message ID: 43570

Message Description: LOG_ID_EVENT_WIRELESS_ROGUE_UNSUPPRESSED

Message Meaning: Rogue AP unsuppressed

Type: Event

Category: WIRELESS

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
bssid	Service Set ID	string	17
aptype	AP Type	uint8	3
rate		uint16	6
radioband	Radio Band	string	64
channel	Channel	uint8	3
manuf	Manufacturer name	string	20
security	Security	string	40
encryption	Encryption Method	string	12
signal	Signal	int8	4
noise		int8	4
live	time in seconds	uint32	10
age	time in seconds - time passed since last seen	uint32	10
onwire	A flag to indicate if the AP is onwire or not	string	3
detectionmethod	Detection Method	string	21
stamac	Station/Client MAC address	string	17
apscan	The name of the AP, which scanned and detected the rogue AP	string	36

Log Field Name	Description	Data Type	Length
sndetected	SN of the AP which detected the rogue AP	string	36
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
stacount	Number of stations/clients	uint32	10
snclosest	SN of the AP closest to the rogue AP	string	36
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
apstatus	Access Point Status	uint8	3

43571 - LOG_ID_EVENT_WIRELESS_ROGUE_DETECT_CHG

Message ID: 43571

Message Description: LOG_ID_EVENT_WIRELESS_ROGUE_DETECT_CHG

Message Meaning: Rogue AP change detected

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
bssid	Service Set ID	string	17

Log Field Name	Description	Data Type	Length
aptype	AP Type	uint8	3
rate		uint16	6
radioband	Radio Band	string	64
channel	Channel	uint8	3
manuf	Manufacturer name	string	20
security	Security	string	40
encryption	Encryption Method	string	12
signal	Signal	int8	4
noise		int8	4
live	time in seconds	uint32	10
age	time in seconds - time passed since last seen	uint32	10
onwire	A flag to indicate if the AP is onwire or not	string	3
detectionmethod	Detection Method	string	21
stamac	Station/Client MAC address	string	17
apscan	The name of the AP, which scanned and detected the rogue AP	string	36
sndetected	SN of the AP which detected the rogue AP	string	36
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
stacount	Number of stations/clients	uint32	10
snclosest	SN of the AP closest to the rogue AP	string	36
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
apstatus	Access Point Status	uint8	3

43572 - LOG_ID_EVENT_WIRELESS_STA ASSO

Message ID: 43572

Message Description: LOG_ID_EVENT_WIRELESS_STA ASSO

Message Meaning: Wireless client associated

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
radioband	Radio Band	string	64
channel	Channel	uint8	3
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3
user	User Name	string	256
group	User Group Name	string	64
srcip	Source IP	ip	39
mpsk		string	33

43573 - LOG_ID_EVENT_WIRELESS_STA_AUTH

Message ID: 43573

Message Description: LOG_ID_EVENT_WIRELESS_STA_AUTH**Message Meaning:** Wireless client authenticated**Type:** Event**Category:** WIRELESS**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
radioband	Radio Band	string	64
channel	Channel	uint8	3
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3
user	User Name	string	256
group	User Group Name	string	64

Log Field Name	Description	Data Type	Length
srcip	Source IP	ip	39
mpsk		string	33

43574 - LOG_ID_EVENT_WIRELESS_STA_DASS

Message ID: 43574

Message Description: LOG_ID_EVENT_WIRELESS_STA_DASS

Message Meaning: Wireless client disassociated

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
radioband	Radio Band	string	64
channel	Channel	uint8	3
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17

Log Field Name	Description	Data Type	Length
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3
user	User Name	string	256
group	User Group Name	string	64
srcip	Source IP	ip	39
mpsk		string	33

43575 - LOG_ID_EVENT_WIRELESS_STA_DAUT

Message ID: 43575

Message Description: LOG_ID_EVENT_WIRELESS_STA_DAUT

Message Meaning: Wireless client deauthenticated

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65

Log Field Name	Description	Data Type	Length
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
radioband	Radio Band	string	64
channel	Channel	uint8	3
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3
user	User Name	string	256
group	User Group Name	string	64
srcip	Source IP	ip	39
mpsk		string	33
remotewtptime		string	32

43576 - LOG_ID_EVENT_WIRELESS_STA_IDLE

Message ID: 43576

Message Description: LOG_ID_EVENT_WIRELESS_STA_IDLE

Message Meaning: Wireless client idle

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
radioband	Radio Band	string	64
channel	Channel	uint8	3
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3
user	User Name	string	256
group	User Group Name	string	64
srcip	Source IP	ip	39
mpsk		string	33

43577 - LOG_ID_EVENT_WIRELESS_STA_DENY

Message ID: 43577

Message Description: LOG_ID_EVENT_WIRELESS_STA_DENY

Message Meaning: Wireless client denied

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
radioband	Radio Band	string	64
channel	Channel	uint8	3
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3
user	User Name	string	256
group	User Group Name	string	64
srcip	Source IP	ip	39
mpsk		string	33
remotewtptime		string	32

43578 - LOG_ID_EVENT_WIRELESS_STA_KICK

Message ID: 43578

Message Description: LOG_ID_EVENT_WIRELESS_STA_KICK

Message Meaning: Wireless client kicked

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
radioband	Radio Band	string	64
channel	Channel	uint8	3
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36

Log Field Name	Description	Data Type	Length
radioid	Radio ID	uint8	3
user	User Name	string	256
group	User Group Name	string	64
srcip	Source IP	ip	39
mpsk		string	33

43579 - LOG_ID_EVENT_WIRELESS_STA_IP

Message ID: 43579

Message Description: LOG_ID_EVENT_WIRELESS_STA_IP

Message Meaning: Wireless client IP assigned

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
radioband	Radio Band	string	64
channel	Channel	uint8	3

Log Field Name	Description	Data Type	Length
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3
user	User Name	string	256
group	User Group Name	string	64
srcip	Source IP	ip	39
mpsk		string	33

43580 - LOG_ID_EVENT_WIRELESS_STA_LEAVE_WTP

Message ID: 43580

Message Description: LOG_ID_EVENT_WIRELESS_STA_LEAVE_WTP

Message Meaning: Wireless client left WTP

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
radioband	Radio Band	string	64
channel	Channel	uint8	3
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3
user	User Name	string	256
group	User Group Name	string	64
srcip	Source IP	ip	39
mpsk		string	33

43581 - LOG_ID_EVENT_WIRELESS_STA_WTP_DISCONN

Message ID: 43581

Message Description: LOG_ID_EVENT_WIRELESS_STA_WTP_DISCONN

Message Meaning: Wireless client WTP disconnected

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
radioband	Radio Band	string	64
channel	Channel	uint8	3
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3
user	User Name	string	256
group	User Group Name	string	64
srcip	Source IP	ip	39
mpsk		string	33

43582 - LOG_ID_EVENT_WIRELESS_ROGUE_CFG_UNCLASSIFIED

Message ID: 43582

Message Description: LOG_ID_EVENT_WIRELESS_ROGUE_CFG_UNCLASSIFIED

Message Meaning: Rogue AP status configured as unclassified

Type: Event**Category:** WIRELESS**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
bssid	Service Set ID	string	17
apstatus	Access Point Status	uint8	3

43583 - LOG_ID_EVENT_WIRELESS_ROGUE_CFG_ACCEPTED

Message ID: 43583**Message Description:** LOG_ID_EVENT_WIRELESS_ROGUE_CFG_ACCEPTED**Message Meaning:** Rogue AP status configured as accepted**Type:** Event**Category:** WIRELESS**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
bssid	Service Set ID	string	17
apstatus	Access Point Status	uint8	3

43584 - LOG_ID_EVENT_WIRELESS_ROGUE_CFG_ROGUE

Message ID: 43584

Message Description: LOG_ID_EVENT_WIRELESS_ROGUE_CFG_ROGUE

Message Meaning: Rogue AP status configured as rogue

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
bssid	Service Set ID	string	17
apstatus	Access Point Status	uint8	3

43585 - LOG_ID_EVENT_WIRELESS_ROGUE_CFG_SUPPRESSED

Message ID: 43585

Message Description: LOG_ID_EVENT_WIRELESS_ROGUE_CFG_SUPPRESSED

Message Meaning: Rogue AP status configured as suppressed

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65

Log Field Name	Description	Data Type	Length
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
bssid	Service Set ID	string	17
apstatus	Access Point Status	uint8	3

43586 - LOG_ID_EVENT_WIRELESS_WTPR_DARRP_CHAN

Message ID: 43586

Message Description: LOG_ID_EVENT_WIRELESS_WTPR_DARRP_CHAN

Message Meaning: Physical AP radio DARRP channel change

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
radioband	Radio Band	string	64
sn	Serial Number	string	64
ap	Access Point	string	36
ip		ip	39

Log Field Name	Description	Data Type	Length
radioid	Radio ID	uint8	3
bandwidth	Bandwidth	string	42
configcountry	Config Country	string	4
opercountry	Operating Country	string	4
cfgtxpower	Config TX power	uint32	10
opertxpower	Operating TX power	uint32	10

43587 - LOG_ID_EVENT_WIRELESS_WTPR_DARRP_START

Message ID: 43587

Message Description: LOG_ID_EVENT_WIRELESS_WTPR_DARRP_START

Message Meaning: Physical AP radio DARRP start

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
radioband	Radio Band	string	64
sn	Serial Number	string	64

Log Field Name	Description	Data Type	Length
ap	Access Point	string	36
ip		ip	39
radioid	Radio ID	uint8	3
bandwidth	Bandwidth	string	42
configcountry	Config Country	string	4
opercountry	Operating Country	string	4
cfgtxpower	Config TX power	uint32	10
opertxpower	Operating TX power	uint32	10

43588 - LOG_ID_EVENT_WIRELESS_WTPR_OPER_CHAN

Message ID: 43588

Message Description: LOG_ID_EVENT_WIRELESS_WTPR_OPER_CHAN

Message Meaning: Physical AP radio operation channel change

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096

Log Field Name	Description	Data Type	Length
radioband	Radio Band	string	64
sn	Serial Number	string	64
ap	Access Point	string	36
ip		ip	39
radioid	Radio ID	uint8	3
bandwidth	Bandwidth	string	42
configcountry	Config Country	string	4
opercountry	Operating Country	string	4
cfgtxpower	Config TX power	uint32	10
opertxpower	Operating TX power	uint32	10

43589 - LOG_ID_EVENT_WIRELESS_WTPR_RADAR

Message ID: 43589

Message Description: LOG_ID_EVENT_WIRELESS_WTPR_RADAR

Message Meaning: Physical AP radio radar detected

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096

Log Field Name	Description	Data Type	Length
action	Action	string	65
msg	Log Message	string	4096
radioband	Radio Band	string	64
sn	Serial Number	string	64
ap	Access Point	string	36
ip		ip	39
radioid	Radio ID	uint8	3
bandwidth	Bandwidth	string	42
configcountry	Config Country	string	4
opercountry	Operating Country	string	4
cfgtxpower	Config TX power	uint32	10
opertxpower	Operating TX power	uint32	10

43590 - LOG_ID_EVENT_WIRELESS_WTPR_NOL

Message ID: 43590

Message Description: LOG_ID_EVENT_WIRELESS_WTPR_NOL

Message Meaning: Physical AP radio channel removed from NOL

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
radioband	Radio Band	string	64
sn	Serial Number	string	64
ap	Access Point	string	36
ip		ip	39
radioid	Radio ID	uint8	3
bandwidth	Bandwidth	string	42
configcountry	Config Country	string	4
opercountry	Operating Country	string	4
cfgtxpower	Config TX power	uint32	10
opertxpower	Operating TX power	uint32	10

43591 - LOG_ID_EVENT_WIRELESS_WTPR_COUNTRY_CFG_SUCCESS

Message ID: 43591

Message Description: LOG_ID_EVENT_WIRELESS_WTPR_COUNTRY_CFG_SUCCESS

Message Meaning: Physical AP radio country config success

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
radioband	Radio Band	string	64
sn	Serial Number	string	64
ap	Access Point	string	36
ip		ip	39
radioid	Radio ID	uint8	3
bandwidth	Bandwidth	string	42
configcountry	Config Country	string	4
opercountry	Operating Country	string	4
cfgtxpower	Config TX power	uint32	10
opertxpower	Operating TX power	uint32	10

43592 - LOG_ID_EVENT_WIRELESS_WTPR_OPER_COUNTRY

Message ID: 43592

Message Description: LOG_ID_EVENT_WIRELESS_WTPR_OPER_COUNTRY

Message Meaning: Physical AP radio operation country

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
radioband	Radio Band	string	64
sn	Serial Number	string	64
ap	Access Point	string	36
ip		ip	39
radioid	Radio ID	uint8	3
bandwidth	Bandwidth	string	42
configcountry	Config Country	string	4
opercountry	Operating Country	string	4
cfgtxpower	Config TX power	uint32	10
opertxpower	Operating TX power	uint32	10

43593 - LOG_ID_EVENT_WIRELESS_WTPR_CFG_TXPOWER

Message ID: 43593

Message Description: LOG_ID_EVENT_WIRELESS_WTPR_CFG_TXPOWER

Message Meaning: Physical AP radio config TX power

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
radioband	Radio Band	string	64
sn	Serial Number	string	64
ap	Access Point	string	36
ip		ip	39
radioid	Radio ID	uint8	3
bandwidth	Bandwidth	string	42
configcountry	Config Country	string	4
opercountry	Operating Country	string	4
cfgtxpower	Config TX power	uint32	10
opertxpower	Operating TX power	uint32	10

43594 - LOG_ID_EVENT_WIRELESS_WTPR_OPER_TXPOWER

Message ID: 43594

Message Description: LOG_ID_EVENT_WIRELESS_WTPR_OPER_TXPOWER

Message Meaning: Physical AP radio operation TX power

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10

Log Field Name	Description	Data Type	Length
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
radioband	Radio Band	string	64
sn	Serial Number	string	64
ap	Access Point	string	36
ip		ip	39
radioid	Radio ID	uint8	3
bandwidth	Bandwidth	string	42
configcountry	Config Country	string	4
opercountry	Operating Country	string	4
cfgtxpower	Config TX power	uint32	10
opertxpower	Operating TX power	uint32	10

43595 - LOG_ID_EVENT_WIRELESS_CLB_DENY

Message ID: 43595

Message Description: LOG_ID_EVENT_WIRELESS_CLB_DENY

Message Meaning: Wireless client load balancing denied

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
radioband	Radio Band	string	64
stamac	Station/Client MAC address	string	17
stacount	Number of stations/clients	uint32	10
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36

43596 - LOG_ID_EVENT_WIRELESS_CLB_RETRY

Message ID: 43596

Message Description: LOG_ID_EVENT_WIRELESS_CLB_RETRY

Message Meaning: Wireless client load balancing retry

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
radioband	Radio Band	string	64
stamac	Station/Client MAC address	string	17
stacount	Number of stations/clients	uint32	10
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36

43597 - LOG_ID_EVENT_WIRELESS_WTP_ADD

Message ID: 43597

Message Description: LOG_ID_EVENT_WIRELESS_WTP_ADD

Message Meaning: Physical AP add

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
sn	Serial Number	string	64
ap	Access Point	string	36
profile	Profile Name	string	64
ip		ip	39
meshmode	Mesh mode	string	19
snmeshparent	SN of the mesh parent	string	36
reason	Reason	string	256

43598 - LOG_ID_EVENT_WIRELESS_WTP_ADD_XSS

Message ID: 43598

Message Description: LOG_ID_EVENT_WIRELESS_WTP_ADD_XSS

Message Meaning: Physical AP add XSS

Type: Event

Category: WIRELESS

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10

Log Field Name	Description	Data Type	Length
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
sn	Serial Number	string	64
ap	Access Point	string	36
profile	Profile Name	string	64
ip		ip	39
meshmode	Mesh mode	string	19
snmeshparent	SN of the mesh parent	string	36
reason	Reason	string	256

43599 - LOG_ID_EVENT_WIRELESS_WTP_DEL

Message ID: 43599

Message Description: LOG_ID_EVENT_WIRELESS_WTP_DEL

Message Meaning: Physical AP delete

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
sn	Serial Number	string	64
ap	Access Point	string	36
profile	Profile Name	string	64
ip		ip	39
meshmode	Mesh mode	string	19
snmeshparent	SN of the mesh parent	string	36
reason	Reason	string	256

43600 - LOG_ID_EVENT_WIRELESS_WTPR_DARRP_STOP

Message ID: 43600

Message Description: LOG_ID_EVENT_WIRELESS_WTPR_DARRP_STOP

Message Meaning: Physical AP radio DARRP stop

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
radioband	Radio Band	string	64
sn	Serial Number	string	64
ap	Access Point	string	36
ip		ip	39
radioid	Radio ID	uint8	3
bandwidth	Bandwidth	string	42
configcountry	Config Country	string	4
opercountry	Operating Country	string	4
cfgtxpower	Config TX power	uint32	10
opertxpower	Operating TX power	uint32	10

43601 - LOG_ID_EVENT_WIRELESS_STA_CAP_SIGNON

Message ID: 43601

Message Description: LOG_ID_EVENT_WIRELESS_STA_CAP_SIGNON

Message Meaning: Wireless station sign on

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10

Log Field Name	Description	Data Type	Length
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
radioband	Radio Band	string	64
channel	Channel	uint8	3
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3
user	User Name	string	256
group	User Group Name	string	64
srcip	Source IP	ip	39
mpsk		string	33

43602 - LOG_ID_EVENT_WIRELESS_STA_CAP_SIGNON_SUCCESS

Message ID: 43602

Message Description: LOG_ID_EVENT_WIRELESS_STA_CAP_SIGNON_SUCCESS

Message Meaning: Wireless station sign on success

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
radioband	Radio Band	string	64
channel	Channel	uint8	3
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3
user	User Name	string	256
group	User Group Name	string	64
srcip	Source IP	ip	39
mpsk		string	33

43603 - LOG_ID_EVENT_WIRELESS_STA_CAP_SIGNON_FAILURE

Message ID: 43603

Message Description: LOG_ID_EVENT_WIRELESS_STA_CAP_SIGNON_FAILURE

Message Meaning: Wireless station sign on failed

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
radioband	Radio Band	string	64
channel	Channel	uint8	3
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36

Log Field Name	Description	Data Type	Length
radioid	Radio ID	uint8	3
user	User Name	string	256
group	User Group Name	string	64
srcip	Source IP	ip	39
mpsk		string	33

43604 - LOG_ID_EVENT_WIRELESS_STA_CAP_EMAIL_REQUEST

Message ID: 43604

Message Description: LOG_ID_EVENT_WIRELESS_STA_CAP_EMAIL_REQUEST

Message Meaning: Captive-portal VAP e-mail collect request sent

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
radioband	Radio Band	string	64
channel	Channel	uint8	3

Log Field Name	Description	Data Type	Length
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3
user	User Name	string	256
group	User Group Name	string	64
srcip	Source IP	ip	39
mpsk		string	33

43605 - LOG_ID_EVENT_WIRELESS_STA_CAP_EMAIL_SUCCESS

Message ID: 43605

Message Description: LOG_ID_EVENT_WIRELESS_STA_CAP_EMAIL_SUCCESS

Message Meaning: Captive-portal VAP e-mail collect success

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
radioband	Radio Band	string	64
channel	Channel	uint8	3
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3
user	User Name	string	256
group	User Group Name	string	64
srcip	Source IP	ip	39
mpsk		string	33

43606 - LOG_ID_EVENT_WIRELESS_STA_CAP_EMAIL_FAILURE

Message ID: 43606

Message Description: LOG_ID_EVENT_WIRELESS_STA_CAP_EMAIL_FAILURE

Message Meaning: Captive-portal VAP e-mail collect failed

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
radioband	Radio Band	string	64
channel	Channel	uint8	3
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3
user	User Name	string	256
group	User Group Name	string	64
srcip	Source IP	ip	39
mpsk		string	33

43607 - LOG_ID_EVENT_WIRELESS_STA_CAP_DISCLAIMER_CHECK

Message ID: 43607

Message Description: LOG_ID_EVENT_WIRELESS_STA_CAP_DISCLAIMER_CHECK

Message Meaning: Captive-portal VAP disclaimer agreed

Type: Event**Category:** WIRELESS**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
radioband	Radio Band	string	64
channel	Channel	uint8	3
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3
user	User Name	string	256
group	User Group Name	string	64
srcip	Source IP	ip	39
mpsk		string	33

43608 - LOG_ID_EVENT_WIRELESS_STA_CAP_DISCLAIMER_DECLINE

Message ID: 43608

Message Description: LOG_ID_EVENT_WIRELESS_STA_CAP_DISCLAIMER_DECLINE

Message Meaning: Captive-portal VAP disclaimer declined

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
radioband	Radio Band	string	64
channel	Channel	uint8	3
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36

Log Field Name	Description	Data Type	Length
radioid	Radio ID	uint8	3
user	User Name	string	256
group	User Group Name	string	64
srcip	Source IP	ip	39
mpsk		string	33

43609 - LOG_ID_EVENT_WIRELESS_WTPR_DARRP_OPTIMIZATION_START

Message ID: 43609

Message Description: LOG_ID_EVENT_WIRELESS_WTPR_DARRP_OPTIMIZATION_START

Message Meaning: DARRP optimization start

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
radioband	Radio Band	string	64
sn	Serial Number	string	64
ap	Access Point	string	36

Log Field Name	Description	Data Type	Length
ip		ip	39
radioid	Radio ID	uint8	3
bandwidth	Bandwidth	string	42
configcountry	Config Country	string	4
opercountry	Operating Country	string	4
cfgtxpower	Config TX power	uint32	10
opertxpower	Operating TX power	uint32	10

43610 - LOG_ID_EVENT_WIRELESS_WTPR_DARRP_OPTIMIZATION_STOP

Message ID: 43610

Message Description: LOG_ID_EVENT_WIRELESS_WTPR_DARRP_OPTIMIZATION_STOP

Message Meaning: DARRP optimization stop

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
radioband	Radio Band	string	64

Log Field Name	Description	Data Type	Length
sn	Serial Number	string	64
ap	Access Point	string	36
ip		ip	39
radioid	Radio ID	uint8	3
bandwidth	Bandwidth	string	42
configcountry	Config Country	string	4
opercountry	Operating Country	string	4
cfgtxpower	Config TX power	uint32	10
opertxpower	Operating TX power	uint32	10

43611 - LOG_ID_EVENT_WIRELESS_SYS_AC_UP

Message ID: 43611

Message Description: LOG_ID_EVENT_WIRELESS_SYS_AC_UP

Message Meaning: Wireless controller start

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096

43612 - LOG_ID_EVENT_WIRELESS_SYS_AC_CFG_LOADED

Message ID: 43612

Message Description: LOG_ID_EVENT_WIRELESS_SYS_AC_CFG_LOADED

Message Meaning: Wireless controller configuration loaded

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096

43613 - LOG_ID_EVENT_WIRELESS_WTP_ERR

Message ID: 43613

Message Description: LOG_ID_EVENT_WIRELESS_WTP_ERR

Message Meaning: Physical AP error

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10

Log Field Name	Description	Data Type	Length
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
sn	Serial Number	string	64
ap	Access Point	string	36
profile	Profile Name	string	64
ip		ip	39
meshmode	Mesh mode	string	19
snmeshparent	SN of the mesh parent	string	36
reason	Reason	string	256

43614 - LOG_ID_EVENT_WIRELESS_DHCP_STAVATION

Message ID: 43614

Message Description: LOG_ID_EVENT_WIRELESS_DHCP_STAVATION

Message Meaning: DHCP Starvation detected

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
sn	Serial Number	string	64
ap	Access Point	string	36
vap		string	36
source_mac		string	17
client_addr		string	17
xid		uint32	10
vapmode		string	17

43615 - LOG_ID_EVENT_WIRELESS_SYS_AC_IPSEC_FAIL

Message ID: 43615

Message Description: LOG_ID_EVENT_WIRELESS_SYS_AC_IPSEC_FAIL

Message Meaning: Wireless controller IPsec setup failed

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096

43616 - LOG_ID_EVENT_WIRELESS_WTPR_NOL_ADD

Message ID: 43616

Message Description: LOG_ID_EVENT_WIRELESS_WTPR_NOL_ADD

Message Meaning: Physical AP radio NOL added

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
radioband	Radio Band	string	64
sn	Serial Number	string	64
ap	Access Point	string	36
ip		ip	39
radioid	Radio ID	uint8	3
bandwidth	Bandwidth	string	42
configcountry	Config Country	string	4
opercountry	Operating Country	string	4
cfgtxpower	Config TX power	uint32	10
opertxpower	Operating TX power	uint32	10

43618 - LOG_ID_EVENT_WIRELESS_WTP_IMAGE_RC_SUCCESS

Message ID: 43618

Message Description: LOG_ID_EVENT_WIRELESS_WTP_IMAGE_RC_SUCCESS

Message Meaning: Physical AP image receive success

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
sn	Serial Number	string	64
ap	Access Point	string	36
profile	Profile Name	string	64
ip		ip	39
meshmode	Mesh mode	string	19
snmeshparent	SN of the mesh parent	string	36
reason	Reason	string	256

43619 - LOG_ID_EVENT_WIRELESS_OFFENDINGAP_DETECT

Message ID: 43619

Message Description: LOG_ID_EVENT_WIRELESS_OFFENDINGAP_DETECT

Message Meaning: Offending AP detected

Type: Event

Category: WIRELESS

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
bssid	Service Set ID	string	17
aptype	AP Type	uint8	3
rate		uint16	6
radioband	Radio Band	string	64
channel	Channel	uint8	3
manuf	Manufacturer name	string	20
security	Security	string	40
encryption	Encryption Method	string	12
signal	Signal	int8	4
noise		int8	4
live	time in seconds	uint32	10
age	time in seconds - time passed since last seen	uint32	10
onwire	A flag to indicate if the AP is onwire or not	string	3
detectionmethod	Detection Method	string	21
stamac	Station/Client MAC address	string	17
apscan	The name of the AP, which scanned and detected the rogue AP	string	36
sndetected	SN of the AP which detected the rogue AP	string	36
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
stacount	Number of stations/clients	uint32	10
snclosest	SN of the AP closest to the rogue AP	string	36
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
apstatus	Access Point Status	uint8	3

43620 - LOG_ID_EVENT_WIRELESS_OFFENDINGAP_ONAIR

Message ID: 43620

Message Description: LOG_ID_EVENT_WIRELESS_OFFENDINGAP_ONAIR

Message Meaning: Offending AP on air

Type: Event

Category: WIRELESS

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
bssid	Service Set ID	string	17
aptype	AP Type	uint8	3
rate		uint16	6
radioband	Radio Band	string	64
channel	Channel	uint8	3
manuf	Manufacturer name	string	20
security	Security	string	40
encryption	Encryption Method	string	12
signal	Signal	int8	4
noise		int8	4
live	time in seconds	uint32	10
age	time in seconds - time passed since last seen	uint32	10
onwire	A flag to indicate if the AP is onwire or not	string	3

Log Field Name	Description	Data Type	Length
detectionmethod	Detection Method	string	21
stamac	Station/Client MAC address	string	17
apscan	The name of the AP, which scanned and detected the rogue AP	string	36
sndetected	SN of the AP which detected the rogue AP	string	36
radioiddetected	Radio ID on the AP which detected the rogue AP	uint8	3
stacount	Number of stations/clients	uint32	10
snclosest	SN of the AP closest to the rogue AP	string	36
radioidclosest	Radio ID on the AP closest the rogue AP	uint8	3
apstatus	Access Point Status	uint8	3

43621 - LOG_ID_EVENT_WIRELESS_WTP_DATA_CHAN_CHG

Message ID: 43621

Message Description: LOG_ID_EVENT_WIRELESS_WTP_DATA_CHAN_CHG

Message Meaning: Wireless wtp data channel changed

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65

Log Field Name	Description	Data Type	Length
msg	Log Message	string	4096
sn	Serial Number	string	64
ap	Access Point	string	36
profile	Profile Name	string	64
ip		ip	39
meshmode	Mesh mode	string	19
snmeshparent	SN of the mesh parent	string	36
reason	Reason	string	256

43622 - LOG_ID_EVENT_WIRELESS_WTP_VLAN_PROBE

Message ID: 43622

Message Description: LOG_ID_EVENT_WIRELESS_WTP_VLAN_PROBE

Message Meaning: WTP is probing vlan

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096

Log Field Name	Description	Data Type	Length
sn	Serial Number	string	64
ap	Access Point	string	36
profile	Profile Name	string	64
ip		ip	39
meshmode	Mesh mode	string	19
snmeshparent	SN of the mesh parent	string	36
reason	Reason	string	256

43623 - LOG_ID_EVENT_WIRELESS_WTP_VLAN_MISSING

Message ID: 43623

Message Description: LOG_ID_EVENT_WIRELESS_WTP_VLAN_MISSING

Message Meaning: VLAN not detected

Type: Event

Category: WIRELESS

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
sn	Serial Number	string	64

Log Field Name	Description	Data Type	Length
ap	Access Point	string	36
profile	Profile Name	string	64
ip		ip	39
meshmode	Mesh mode	string	19
snmeshparent	SN of the mesh parent	string	36
reason	Reason	string	256

43624 - LOG_ID_EVENT_WIRELESS_WTP_VLAN_DETECTED

Message ID: 43624

Message Description: LOG_ID_EVENT_WIRELESS_WTP_VLAN_DETECTED

Message Meaning: VLAN detected

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
sn	Serial Number	string	64
ap	Access Point	string	36

Log Field Name	Description	Data Type	Length
profile	Profile Name	string	64
ip		ip	39
meshmode	Mesh mode	string	19
snmeshparent	SN of the mesh parent	string	36
reason	Reason	string	256

43625 - LOG_ID_EVENT_WIRELESS_STA_CAP_CMCC_SUCCESS

Message ID: 43625

Message Description: LOG_ID_EVENT_WIRELESS_STA_CAP_CMCC_SUCCESS

Message Meaning: Wireless station CMCC sign on success

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
radioband	Radio Band	string	64
channel	Channel	uint8	3

Log Field Name	Description	Data Type	Length
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3
user	User Name	string	256
group	User Group Name	string	64
srcip	Source IP	ip	39
mpsk		string	33

43626 - LOG_ID_EVENT_WIRELESS_STA_CAP_CMCC_FAILURE

Message ID: 43626

Message Description: LOG_ID_EVENT_WIRELESS_STA_CAP_CMCC_FAILURE

Message Meaning: Wireless station CMCC sign on failed

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
radioband	Radio Band	string	64
channel	Channel	uint8	3
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3
user	User Name	string	256
group	User Group Name	string	64
srcip	Source IP	ip	39
mpsk		string	33

43627 - LOG_ID_EVENT_WIRELESS_STA_CAP_CMCC_TIMEOUT

Message ID: 43627

Message Description: LOG_ID_EVENT_WIRELESS_STA_CAP_CMCC_TIMEOUT

Message Meaning: Wireless station CMCC sign on timeout

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
radioband	Radio Band	string	64
channel	Channel	uint8	3
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3
user	User Name	string	256
group	User Group Name	string	64
srcip	Source IP	ip	39
mpsk		string	33

43628 - LOG_ID_EVENT_WIRELESS_STA_CAP_CMCC_MAC_AUTH_SUCCESS

Message ID: 43628

Message Description: LOG_ID_EVENT_WIRELESS_STA_CAP_CMCC_MAC_AUTH_SUCCESS

Message Meaning: Wireless station CMCC MAC auth success

Type: Event**Category:** WIRELESS**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
radioband	Radio Band	string	64
channel	Channel	uint8	3
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3
user	User Name	string	256
group	User Group Name	string	64
srcip	Source IP	ip	39
mpsk		string	33

43629 - LOG_ID_EVENT_WIRELESS_STA_RADIUS_AUTH_FAILURE

Message ID: 43629

Message Description: LOG_ID_EVENT_WIRELESS_STA_RADIUS_AUTH_FAILURE

Message Meaning: Wireless client RADIUS authentication failure

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
channel	Channel	uint8	3
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3

Log Field Name	Description	Data Type	Length
user	User Name	string	256
remotewtptime		string	32

43630 - LOG_ID_EVENT_WIRELESS_STA_RADIUS_AUTH_SUCCESS

Message ID: 43630

Message Description: LOG_ID_EVENT_WIRELESS_STA_RADIUS_AUTH_SUCCESS

Message Meaning: Wireless client RADIUS authentication success

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
channel	Channel	uint8	3
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64

Log Field Name	Description	Data Type	Length
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3
user	User Name	string	256
remotewtptime		string	32

43631 - LOG_ID_EVENT_WIRELESS_STA_RADIUS_AUTH_NO_RESP

Message ID: 43631

Message Description: LOG_ID_EVENT_WIRELESS_STA_RADIUS_AUTH_NO_RESP

Message Meaning: Wireless client RADIUS authentication server not responding

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
channel	Channel	uint8	3

Log Field Name	Description	Data Type	Length
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3
user	User Name	string	256
remotewtptime		string	32

43632 - LOG_ID_EVENT_WIRELESS_STA_RADIUS_MAC_AUTH_FAILURE

Message ID: 43632

Message Description: LOG_ID_EVENT_WIRELESS_STA_RADIUS_MAC_AUTH_FAILURE

Message Meaning: Wireless client RADIUS MAC authentication failure

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096

Log Field Name	Description	Data Type	Length
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
channel	Channel	uint8	3
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3
user	User Name	string	256
remotewtptime		string	32

43633 - LOG_ID_EVENT_WIRELESS_STA_RADIUS_MAC_AUTH_SUCCESS

Message ID: 43633

Message Description: LOG_ID_EVENT_WIRELESS_STA_RADIUS_MAC_AUTH_SUCCESS

Message Meaning: Wireless client RADIUS MAC authentication success

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
channel	Channel	uint8	3
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3
user	User Name	string	256
remotewtptime		string	32

43634 - LOG_ID_EVENT_WIRELESS_STA_RADIUS_MAC_AUTH_NO_RESP

Message ID: 43634

Message Description: LOG_ID_EVENT_WIRELESS_STA_RADIUS_MAC_AUTH_NO_RESP

Message Meaning: Wireless client RADIUS MAC authentication server not responding

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
channel	Channel	uint8	3
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3
user	User Name	string	256
remotewtptime		string	32

43635 - LOG_ID_EVENT_WIRELESS_STA_OKC_NO_MATCH

Message ID: 43635

Message Description: LOG_ID_EVENT_WIRELESS_STA_OKC_NO_MATCH

Message Meaning: Wireless client authenticates through OKC failed with no match

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
channel	Channel	uint8	3
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3
user	User Name	string	256
remotewtptime		string	32

43636 - LOG_ID_EVENT_WIRELESS_STA_OKC_LOCAL_MATCH

Message ID: 43636

Message Description: LOG_ID_EVENT_WIRELESS_STA_OKC_LOCAL_MATCH

Message Meaning: Wireless client authenticates through local OKC success

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
channel	Channel	uint8	3
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3
user	User Name	string	256
remotewtptime		string	32

43637 - LOG_ID_EVENT_WIRELESS_STA_OKC_INTER_AC_MATCH**Message ID:** 43637**Message Description:** LOG_ID_EVENT_WIRELESS_STA_OKC_INTER_AC_MATCH**Message Meaning:** Wireless client authenticates through inter AC OKC success

Type: Event**Category:** WIRELESS**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
channel	Channel	uint8	3
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3
user	User Name	string	256
remotewtptime		string	32

43638 - LOG_ID_EVENT_WIRELESS_STA_OKC_INTER_AP_MATCH

Message ID: 43638

Message Description: LOG_ID_EVENT_WIRELESS_STA_OKC_INTER_AP_MATCH

Message Meaning: Wireless client authenticates through inter AP OKC success

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
channel	Channel	uint8	3
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3
user	User Name	string	256
remotewtptime		string	32

43639 - LOG_ID_EVENT_WIRELESS_STA_FT_INVALID_ACTION_REQ**Message ID:** 43639**Message Description:** LOG_ID_EVENT_WIRELESS_STA_FT_INVALID_ACTION_REQ**Message Meaning:** Wireless client sent invalid FT action request**Type:** Event**Category:** WIRELESS**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
channel	Channel	uint8	3
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3

Log Field Name	Description	Data Type	Length
user	User Name	string	256
remotewtptime		string	32

43640 - LOG_ID_EVENT_WIRELESS_STA_FT_INVALID_AUTH_REQ

Message ID: 43640

Message Description: LOG_ID_EVENT_WIRELESS_STA_FT_INVALID_AUTH_REQ

Message Meaning: Wireless client sent invalid FT auth request

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
channel	Channel	uint8	3
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64

Log Field Name	Description	Data Type	Length
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3
user	User Name	string	256
remotewtptime		string	32

43641 - LOG_ID_EVENT_WIRELESS_STA_FT_INVALID_REASSOC_REQ

Message ID: 43641

Message Description: LOG_ID_EVENT_WIRELESS_STA_FT_INVALID_REASSOC_REQ

Message Meaning: Wireless client sent invalid FT reassociation request

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
channel	Channel	uint8	3

Log Field Name	Description	Data Type	Length
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3
user	User Name	string	256
remotewtptime		string	32

43642 - LOG_ID_EVENT_WIRELESS_STA_FT_ACTION_REQ

Message ID: 43642

Message Description: LOG_ID_EVENT_WIRELESS_STA_FT_ACTION_REQ

Message Meaning: Wireless client sent FT action request

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096

Log Field Name	Description	Data Type	Length
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
channel	Channel	uint8	3
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3
user	User Name	string	256
remotewtptime		string	32

43643 - LOG_ID_EVENT_WIRELESS_STA_FT_ACTION_RESP

Message ID: 43643

Message Description: LOG_ID_EVENT_WIRELESS_STA_FT_ACTION_RESP

Message Meaning: FT action response was sent to wireless client

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
channel	Channel	uint8	3
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3
user	User Name	string	256
remotewtptime		string	32

43644 - LOG_ID_EVENT_WIRELESS_STA_FT_AUTH_REQ

Message ID: 43644

Message Description: LOG_ID_EVENT_WIRELESS_STA_FT_AUTH_REQ

Message Meaning: Wireless client sent FT auth request

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
channel	Channel	uint8	3
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3
user	User Name	string	256
remotewtptime		string	32

43645 - LOG_ID_EVENT_WIRELESS_STA_FT_AUTH_RESP

Message ID: 43645

Message Description: LOG_ID_EVENT_WIRELESS_STA_FT_AUTH_RESP

Message Meaning: FT auth response was sent to wireless client

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
channel	Channel	uint8	3
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3
user	User Name	string	256
remotewtptime		string	32

43646 - LOG_ID_EVENT_WIRELESS_STA_FT_REASSOC_REQ

Message ID: 43646

Message Description: LOG_ID_EVENT_WIRELESS_STA_FT_REASSOC_REQ

Message Meaning: Wireless client sent FT reassociation request

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
channel	Channel	uint8	3
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3
user	User Name	string	256
remotewtptime		string	32

43647 - LOG_ID_EVENT_WIRELESS_STA_FT_REASSOC_RESP**Message ID:** 43647**Message Description:** LOG_ID_EVENT_WIRELESS_STA_FT_REASSOC_RESP**Message Meaning:** FT reassociation response was sent to wireless client

Type: Event**Category:** WIRELESS**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
channel	Channel	uint8	3
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3
user	User Name	string	256
remotewtptime		string	32

43648 - LOG_ID_EVENT_WIRELESS_STA_WPA_MSG_INVALID_SECOND_MSG

Message ID: 43648

Message Description: LOG_ID_EVENT_WIRELESS_STA_WPA_MSG_INVALID_SECOND_MSG**Message Meaning:** Wireless client 4 way handshake failed with invalid 2/4 message**Type:** Event**Category:** WIRELESS**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
channel	Channel	uint8	3
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3
user	User Name	string	256
remotewtptime		string	32

43649 - LOG_ID_EVENT_WIRELESS_STA_WPA_MSG_INVALID_FOURTH_MSG

Message ID: 43649

Message Description: LOG_ID_EVENT_WIRELESS_STA_WPA_MSG_INVALID_FOURTH_MSG

Message Meaning: Wireless client 4 way handshake failed with invalid 4/4 message

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
channel	Channel	uint8	3
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3

Log Field Name	Description	Data Type	Length
user	User Name	string	256
remotewtptime		string	32

43650 - LOG_ID_EVENT_WIRELESS_STA_WPA_MSG_FIRST_MSG

Message ID: 43650

Message Description: LOG_ID_EVENT_WIRELESS_STA_WPA_MSG_FIRST_MSG

Message Meaning: AP sent 1/4 message of 4 way handshake to wireless client

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
channel	Channel	uint8	3
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64

Log Field Name	Description	Data Type	Length
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3
user	User Name	string	256
remotewtptime		string	32

43651 - LOG_ID_EVENT_WIRELESS_STA_WPA_MSG_SECOND_MSG

Message ID: 43651

Message Description: LOG_ID_EVENT_WIRELESS_STA_WPA_MSG_SECOND_MSG

Message Meaning: Wireless client sent 2/4 message of 4 way handshake

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
channel	Channel	uint8	3

Log Field Name	Description	Data Type	Length
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3
user	User Name	string	256
remotewtptime		string	32

43652 - LOG_ID_EVENT_WIRELESS_STA_WPA_MSG_THIRD_MSG

Message ID: 43652

Message Description: LOG_ID_EVENT_WIRELESS_STA_WPA_MSG_THIRD_MSG

Message Meaning: AP sent 3/4 message of 4 way handshake to wireless client

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096

Log Field Name	Description	Data Type	Length
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
channel	Channel	uint8	3
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3
user	User Name	string	256
remotewtptime		string	32

43653 - LOG_ID_EVENT_WIRELESS_STA_WPA_MSG_FOURTH_MSG

Message ID: 43653

Message Description: LOG_ID_EVENT_WIRELESS_STA_WPA_MSG_FOURTH_MSG

Message Meaning: Wireless client sent 4/4 message of 4 way handshake

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
channel	Channel	uint8	3
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3
user	User Name	string	256
remotewtptime		string	32

43654 - LOG_ID_EVENT_WIRELESS_STA_WPA_MSG_FIRST_GROUP_MSG

Message ID: 43654

Message Description: LOG_ID_EVENT_WIRELESS_STA_WPA_MSG_FIRST_GROUP_MSG

Message Meaning: AP sent 1/2 message of group key handshake to wireless client

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
channel	Channel	uint8	3
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3
user	User Name	string	256
remotewtptime		string	32

43655 - LOG_ID_EVENT_WIRELESS_STA_WPA_MSG_SECOND_GROUP_MSG

Message ID: 43655

Message Description: LOG_ID_EVENT_WIRELESS_STA_WPA_MSG_SECOND_GROUP_MSG

Message Meaning: Wireless client sent 2/2 message of group key handshake

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
channel	Channel	uint8	3
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3
user	User Name	string	256
remotewtptime		string	32

43656 - LOG_ID_EVENT_WIRELESS_STA_WPA_MSG_MAX_STA_CNT

Message ID: 43656

Message Description: LOG_ID_EVENT_WIRELESS_STA_WPA_MSG_MAX_STA_CNT

Message Meaning: Max sta count limit for the PSK was reached

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
channel	Channel	uint8	3
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3
user	User Name	string	256
remotewtptime		string	32

43657 - LOG_ID_EVENT_WIRELESS_STA_ASSOC_FAIL**Message ID:** 43657**Message Description:** LOG_ID_EVENT_WIRELESS_STA_ASSOC_FAIL**Message Meaning:** Wireless station association failed

Type: Event**Category:** WIRELESS**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
channel	Channel	uint8	3
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3
user	User Name	string	256
remotewtptime		string	32

43658 - LOG_ID_EVENT_WIRELESS_STA_DHCP_NO_RESP

Message ID: 43658

Message Description: LOG_ID_EVENT_WIRELESS_STA_DHCP_NO_RESP**Message Meaning:** Wireless station DHCP process failed with no server response**Type:** Event**Category:** WIRELESS**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
remotewtptime		string	32

43659 - LOG_ID_EVENT_WIRELESS_STA_DHCP_DIFF_OFFER

Message ID: 43659**Message Description:** LOG_ID_EVENT_WIRELESS_STA_DHCP_DIFF_OFFER**Message Meaning:** Another DHCP server sent DHCP offer to wireless station

Type: Event**Category:** WIRELESS**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
remotewtptime		string	32

43660 - LOG_ID_EVENT_WIRELESS_STA_DHCP_NO_ACK

Message ID: 43660**Message Description:** LOG_ID_EVENT_WIRELESS_STA_DHCP_NO_ACK**Message Meaning:** No DHCP ACK from server**Type:** Event**Category:** WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
remotewtptime		string	32

43661 - LOG_ID_EVENT_WIRELESS_STA_DHCP_NAK**Message ID:** 43661**Message Description:** LOG_ID_EVENT_WIRELESS_STA_DHCP_NAK**Message Meaning:** DHCP server sent DHCP NAK**Type:** Event**Category:** WIRELESS**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
remotewtptime		string	32

43662 - LOG_ID_EVENT_WIRELESS_STA_DHCP_DUP_IP

Message ID: 43662

Message Description: LOG_ID_EVENT_WIRELESS_STA_DHCP_DUP_IP

Message Meaning: IP offered has been used by another wireless station

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
remotewtptime		string	32

43663 - LOG_ID_EVENT_WIRELESS_STA_DHCP_DISCOVER

Message ID: 43663

Message Description: LOG_ID_EVENT_WIRELESS_STA_DHCP_DISCOVER

Message Meaning: Wireless station sent DHCP DISCOVER

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
remotewtptime		string	32

43664 - LOG_ID_EVENT_WIRELESS_STA_DHCP_OFFER

Message ID: 43664

Message Description: LOG_ID_EVENT_WIRELESS_STA_DHCP_OFFER

Message Meaning: DHCP server sent DHCP OFFER

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
remotewtptime		string	32

43665 - LOG_ID_EVENT_WIRELESS_STA_DHCP_DECLINE

Message ID: 43665

Message Description: LOG_ID_EVENT_WIRELESS_STA_DHCP_DECLINE

Message Meaning: Wireless station sent DHCP DECLINE

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
remotewtptime		string	32

43666 - LOG_ID_EVENT_WIRELESS_STA_DHCP_REQUEST

Message ID: 43666

Message Description: LOG_ID_EVENT_WIRELESS_STA_DHCP_REQUEST

Message Meaning: Wireless station sent DHCP REQUEST

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
remotewtptime		string	32

43667 - LOG_ID_EVENT_WIRELESS_STA_DHCP_ACK

Message ID: 43667

Message Description: LOG_ID_EVENT_WIRELESS_STA_DHCP_ACK

Message Meaning: DHCP server sent DHCP ACK

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
remotewtptime		string	32

43668 - LOG_ID_EVENT_WIRELESS_STA_DHCP_RELEASE

Message ID: 43668

Message Description: LOG_ID_EVENT_WIRELESS_STA_DHCP_RELEASE

Message Meaning: Wireless station sent DHCP RELEASE

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
remotewtptime		string	32

43669 - LOG_ID_EVENT_WIRELESS_STA_DHCP_INFORM

Message ID: 43669

Message Description: LOG_ID_EVENT_WIRELESS_STA_DHCP_INFORM

Message Meaning: Wireless station sent DHCP INFORM

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
remotewtptime		string	32

43670 - LOG_ID_EVENT_WIRELESS_STA_DHCP_SELF_ASSIGNED

Message ID: 43670

Message Description: LOG_ID_EVENT_WIRELESS_STA_DHCP_SELF_ASSIGNED

Message Meaning: Wireless station is using self-assigned IP

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
remotewtptime		string	32

43671 - LOG_ID_EVENT_WIRELESS_STA_DNS_NO_RESP

Message ID: 43671

Message Description: LOG_ID_EVENT_WIRELESS_STA_DNS_NO_RESP

Message Meaning: Wireless station DNS process failed with no server response

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
remotewtptime		string	32

43672 - LOG_ID_EVENT_WIRELESS_STA_DNS_SERVER_FAILURE

Message ID: 43672

Message Description: LOG_ID_EVENT_WIRELESS_STA_DNS_SERVER_FAILURE

Message Meaning: Wireless station DNS process failed due to server failure

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
remotewtptime		string	32

43673 - LOG_ID_EVENT_WIRELESS_STA_DNS_NO_DOMAIN

Message ID: 43673

Message Description: LOG_ID_EVENT_WIRELESS_STA_DNS_NO_DOMAIN

Message Meaning: Wireless station DNS process failed due to non-existing domain

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
remotewtptime		string	32

43674 - LOG_ID_EVENT_WIRELESS_STA_WPA_KRACK_FT_REASSOC

Message ID: 43674

Message Description: LOG_ID_EVENT_WIRELESS_STA_WPA_KRACK_FT_REASSOC

Message Meaning: Wireless station WPA key reinstallation attack on FT reassociation

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
channel	Channel	uint8	3
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3
user	User Name	string	256
remotewtptime		string	32

43675 - LOG_ID_EVENT_WIRELESS_STA_AUTH_REQ

Message ID: 43675

Message Description: LOG_ID_EVENT_WIRELESS_STA_AUTH_REQ

Message Meaning: Authentication request from wireless station

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
channel	Channel	uint8	3
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3
user	User Name	string	256
remotewtptime		string	32

43676 - LOG_ID_EVENT_WIRELESS_STA_AUTH_RESP**Message ID:** 43676**Message Description:** LOG_ID_EVENT_WIRELESS_STA_AUTH_RESP**Message Meaning:** Authentication response to wireless station

Type: Event**Category:** WIRELESS**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
channel	Channel	uint8	3
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3
user	User Name	string	256
remotewtptime		string	32

43677 - LOG_ID_EVENT_WIRELESS_STA_ASSOC_REQ

Message ID: 43677

Message Description: LOG_ID_EVENT_WIRELESS_STA_ASSOC_REQ**Message Meaning:** Association request from wireless station**Type:** Event**Category:** WIRELESS**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
channel	Channel	uint8	3
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3
user	User Name	string	256
remotewtptime		string	32

43678 - LOG_ID_EVENT_WIRELESS_STA_REASSOC_REQ

Message ID: 43678

Message Description: LOG_ID_EVENT_WIRELESS_STA_REASSOC_REQ

Message Meaning: Reassociation request from wireless station

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
channel	Channel	uint8	3
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3

Log Field Name	Description	Data Type	Length
user	User Name	string	256
remotewtptime		string	32

43679 - LOG_ID_EVENT_WIRELESS_STA_ASSOC_RESP

Message ID: 43679

Message Description: LOG_ID_EVENT_WIRELESS_STA_ASSOC_RESP

Message Meaning: Association response to wireless station

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
channel	Channel	uint8	3
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64

Log Field Name	Description	Data Type	Length
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3
user	User Name	string	256
remotewtptime		string	32

43680 - LOG_ID_EVENT_WIRELESS_STA_REASSOC_RESP

Message ID: 43680

Message Description: LOG_ID_EVENT_WIRELESS_STA_REASSOC_RESP

Message Meaning: Reassociation response to wireless station

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
channel	Channel	uint8	3

Log Field Name	Description	Data Type	Length
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3
user	User Name	string	256
remotewtptime		string	32

43681 - LOG_ID_EVENT_WIRELESS_STA_PROBE_REQ

Message ID: 43681

Message Description: LOG_ID_EVENT_WIRELESS_STA_PROBE_REQ

Message Meaning: Probe request from wireless station

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096

Log Field Name	Description	Data Type	Length
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
channel	Channel	uint8	3
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3
user	User Name	string	256
remotewtptime		string	32

43682 - LOG_ID_EVENT_WIRELESS_STA_PROBE_RESP

Message ID: 43682

Message Description: LOG_ID_EVENT_WIRELESS_STA_PROBE_RESP

Message Meaning: Probe response to wireless station

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
channel	Channel	uint8	3
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3
user	User Name	string	256
remotewtptime		string	32

43683 - LOG_ID_EVENT_WIRELESS_BLE_DEV_LOCATE

Message ID: 43683

Message Description: LOG_ID_EVENT_WIRELESS_BLE_DEV_LOCATE

Message Meaning: Wireless ble dev detection

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
signal	Signal	int8	4
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36

43684 - LOG_ID_EVENT_WIRELESS_ADDRGRP_DUPLICATE_MAC

Message ID: 43684

Message Description: LOG_ID_EVENT_WIRELESS_ADDRGRP_DUPLICATE_MAC

Message Meaning: Wireless addrgrp duplicate mac

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
addrgrp		string	36

43685 - LOG_ID_EVENT_WIRELESS_ADDRGRP_ADDR_APPLY

Message ID: 43685

Message Description: LOG_ID_EVENT_WIRELESS_ADDRGRP_ADDR_APPLY

Message Meaning: Wireless addrgrp address apply

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
addrgrp		string	36

43686 - LOG_ID_EVENT_WIRELESS_STA_WPA_MSG_INVALID_SCHEDULE

Message ID: 43686

Message Description: LOG_ID_EVENT_WIRELESS_STA_WPA_MSG_INVALID_SCHEDULE

Message Meaning: PSK is out of any valid schedules

Type: Event

Category: WIRELESS

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
channel	Channel	uint8	3
security	Security	string	40
encryption	Encryption Method	string	12
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
reason	Reason	string	256
vap		string	36
radioid	Radio ID	uint8	3

Log Field Name	Description	Data Type	Length
user	User Name	string	256
remotewtptime		string	32

43687 - LOG_ID_EVENT_WIRELESS_STA_WL_BRIDGE_TRAFFIC_STATS

Message ID: 43687

Message Description: LOG_ID_EVENT_WIRELESS_STA_WL_BRIDGE_TRAFFIC_STATS

Message Meaning: Traffic stats for station with bridge wlan

Type: Event

Category: WIRELESS

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Log Message	string	4096
ssid	Base Service Set ID	string	33
stamac	Station/Client MAC address	string	17
sn	Serial Number	string	64
ap	Access Point	string	36
vap		string	36
user	User Name	string	256

Log Field Name	Description	Data Type	Length
srcip	Source IP	ip	39
sentbyte		uint64	20
rcvdbyte		uint64	20
nextstat		uint32	10

43776 - LOG_ID_EVENT_NAC_QUARANTINE

Message ID: 43776

Message Description: LOG_ID_EVENT_NAC_QUARANTINE

Message Meaning: NAC quarantine

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
action	Action	string	65
msg	Message Text	string	4096
service	Name of Service	string	64
proto	Protocol Number	uint8	3
srcip	Source IP	ip	39

Log Field Name	Description	Data Type	Length
srcport	Source Port	uint16	5
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
duration	Duration	uint32	10
src_int	Source Interface	string	64
dst_int	Destination Interface	string	64
banned_src	NAC quarantine Banned Source IP	string	16
admin		string	64
group	User group Name	string	64
policyid	Policy ID	uint32	10
banned_rule	NAC quarantine Banned Rule Name	string	80
sensor	NAC Sensor Name	string	36

43777 - LOG_ID_EVENT_NAC_ANOMALY_QUARANTINE

Message ID: 43777

Message Description: LOG_ID_EVENT_NAC_ANOMALY_QUARANTINE

Message Meaning: NAC anomaly quarantine

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
action	Action	string	65
msg	Message Text	string	4096
service	Name of Service	string	64
proto	Protocol Number	uint8	3
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
duration	Duration	uint32	10
src_int	Source Interface	string	64
dst_int	Destination Interface	string	64
banned_src	NAC quarantine Banned Source IP	string	16
admin		string	64
group	User group Name	string	64
policyid	Policy ID	uint32	10
banned_rule	NAC quarantine Banned Rule Name	string	80
sensor	NAC Sensor Name	string	36

43800 - LOG_ID_EVENT_ELBC_BLADE_JOIN

Message ID: 43800

Message Description: LOG_ID_EVENT_ELBC_BLADE_JOIN

Message Meaning: Blade ready to process traffic

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10

Log Field Name	Description	Data Type	Length
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Message Text	string	4096
informationsource	Information Source	string	4096
slot	Slot Number	uint8	3
chassisid	Chassis ID	uint8	3

43801 - LOG_ID_EVENT_ELBC_BLADE_LEAVE

Message ID: 43801

Message Description: LOG_ID_EVENT_ELBC_BLADE_LEAVE

Message Meaning: Blade not ready to process traffic

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Message Text	string	4096
informationsource	Information Source	string	4096
slot	Slot Number	uint8	3
chassisid	Chassis ID	uint8	3

43802 - LOG_ID_EVENT_ELBC_MASTER_BLADE_FOUND

Message ID: 43802

Message Description: LOG_ID_EVENT_ELBC_MASTER_BLADE_FOUND

Message Meaning: Master blade found

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096

Log Field Name	Description	Data Type	Length
action	Action	string	65
msg	Message Text	string	4096
informationsource	Information Source	string	4096
slot	Slot Number	uint8	3
chassisid	Chassis ID	uint8	3

43803 - LOG_ID_EVENT_ELBC_MASTER_BLADE_LOST

Message ID: 43803

Message Description: LOG_ID_EVENT_ELBC_MASTER_BLADE_LOST

Message Meaning: Master blade lost

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Message Text	string	4096
informationsource	Information Source	string	4096
slot	Slot Number	uint8	3
chassisid	Chassis ID	uint8	3

43804 - LOG_ID_EVENT_ELBC_MASTER_BLADE_CHANGE

Message ID: 43804

Message Description: LOG_ID_EVENT_ELBC_MASTER_BLADE_CHANGE

Message Meaning: Master blade changed

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Message Text	string	4096
informationsource	Information Source	string	4096
oldslot	Original Slot Number	uint8	3
oldchassisid	Original Chassis Number	uint8	3
newslot	New Slot Number	uint8	3
newchassisid	New Chassis ID	uint8	3

43805 - LOG_ID_EVENT_ELBC_ACTIVE_CHANNEL_FOUND

Message ID: 43805

Message Description: LOG_ID_EVENT_ELBC_ACTIVE_CHANNEL_FOUND

Message Meaning: ELBC channel active

Type: Event

Category: SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Message Text	string	4096
informationsource	Information Source	string	4096
slot	Slot Number	uint8	3
chassisid	Chassis ID	uint8	3
newchannel	New Channel Number	uint8	3

43806 - LOG_ID_EVENT_ELBC_ACTIVE_CHANNEL_LOST

Message ID: 43806**Message Description:** LOG_ID_EVENT_ELBC_ACTIVE_CHANNEL_LOST**Message Meaning:** ELBC channel inactive**Type:** Event**Category:** SYSTEM**Severity:** Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Message Text	string	4096
informationsource	Information Source	string	4096
slot	Slot Number	uint8	3
chassisid	Chassis ID	uint8	3
oldchannel	Original Channel Number	uint8	3

43807 - LOG_ID_EVENT_ELBC_ACTIVE_CHANNEL_CHANGE

Message ID: 43807

Message Description: LOG_ID_EVENT_ELBC_ACTIVE_CHANNEL_CHANGE

Message Meaning: ELBC channel failover

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Message Text	string	4096
informationsource	Information Source	string	4096
slot	Slot Number	uint8	3
chassisid	Chassis ID	uint8	3
newchannel	New Channel Number	uint8	3
oldchannel	Original Channel Number	uint8	3

43808 - LOG_ID_EVENT_ELBC_CHASSIS_ACTIVE

Message ID: 43808

Message Description: LOG_ID_EVENT_ELBC_CHASSIS_ACTIVE

Message Meaning: ELBC chassis active

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	4096
action	Action	string	65
msg	Message Text	string	4096
informationsource	Information Source	string	4096
chassisid	Chassis ID	uint8	3

43809 - LOG_ID_EVENT_ELBC_CHASSIS_INACTIVE

Message ID: 43809

Message Description: LOG_ID_EVENT_ELBC_CHASSIS_INACTIVE

Message Meaning: ELBC chassis inactive

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
msg	Message Text	string	4096
informationsource	Information Source	string	4096
chassisid	Chassis ID	uint8	3

44544 - LOGID_EVENT_CONFIG_PATH

Message ID: 44544

Message Description: LOGID_EVENT_CONFIG_PATH

Message Meaning: Path configured

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096
cfgtid	config transaction id	uint32	10
cfgpath	configuration path	string	128

44545 - LOGID_EVENT_CONFIG_OBJ

Message ID: 44545

Message Description: LOGID_EVENT_CONFIG_OBJ

Message Meaning: Object configured

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096
cfgtid	config transaction id	uint32	10
cfgpath	configuration path	string	128
cfgobj	configuration object	string	256

44546 - LOGID_EVENT_CONFIG_ATTR

Message ID: 44546**Message Description:** LOGID_EVENT_CONFIG_ATTR**Message Meaning:** Attribute configured**Type:** Event**Category:** SYSTEM**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096
cfgtid	config transaction id	uint32	10
cfgpath	configuration path	string	128
cfgattr	configuration attribute	string	4096

44547 - LOGID_EVENT_CONFIG_OBJATTR

Message ID: 44547

Message Description: LOGID_EVENT_CONFIG_OBJATTR

Message Meaning: Object attribute configured

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096
cfgtid	config transaction id	uint32	10
cfgpath	configuration path	string	128
cfgattr	configuration attribute	string	4096
cfgobj	configuration object	string	256

44548 - LOGID_EVENT_CONFIG_EXEC

Message ID: 44548

Message Description: LOGID_EVENT_CONFIG_EXEC

Message Meaning: Action performed

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

44549 - LOGID_EVENT_CONFIG_OBJATTR_MTNER

Message ID: 44549

Message Description: LOGID_EVENT_CONFIG_OBJATTR_MTNER

Message Meaning: Object attribute configured by maintainer

Type: Event

Category: SYSTEM

Severity: Alert

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64

Log Field Name	Description	Data Type	Length
action	Action	string	65
msg	Message Text	string	4096
cfgtid	config transaction id	uint32	10
cfgpath	configuration path	string	128
cfgattr	configuration attribute	string	4096
cfgobj	configuration object	string	256

44550 - LOGID_EVENT_CONFIG_OBJ_MTNER

Message ID: 44550

Message Description: LOGID_EVENT_CONFIG_OBJ_MTNER

Message Meaning: Object configured by maintainer

Type: Event

Category: SYSTEM

Severity: Alert

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096

Log Field Name	Description	Data Type	Length
cfgtid	config transaction id	uint32	10
cfgpath	configuration path	string	128
cfgobj	configuration object	string	256

44551 - LOGID_EVENT_CONFIG_ATTR_MTNER

Message ID: 44551

Message Description: LOGID_EVENT_CONFIG_ATTR_MTNER

Message Meaning: Attribute configured by maintainer

Type: Event

Category: SYSTEM

Severity: Alert

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096
cfgtid	config transaction id	uint32	10
cfgpath	configuration path	string	128
cfgattr	configuration attribute	string	4096

44552 - LOGID_EVENT_CONFIG_PATH_MTNER

Message ID: 44552

Message Description: LOGID_EVENT_CONFIG_PATH_MTNER

Message Meaning: Path configured by maintainer

Type: Event

Category: SYSTEM

Severity: Alert

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ui	User Interface	string	64
action	Action	string	65
msg	Message Text	string	4096
cfgtid	config transaction id	uint32	10
cfgpath	configuration path	string	128

44553 - LOGID_EVENT_CONFIG_FIXEDPORT_DIS

Message ID: 44553

Message Description: LOGID_EVENT_CONFIG_FIXEDPORT_DIS

Message Meaning: Policy attribute fixed port changed during upgrade

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096
sn	Serial Number	string	64
policyid	Policy ID	uint32	10

44554 - LOGID_EVENT_CONFIG_POL_CHANGED

Message ID: 44554**Message Description:** LOGID_EVENT_CONFIG_POL_CHANGED**Message Meaning:** Learning mode policy is converted to accept policy during upgrade.**Type:** Event**Category:** SYSTEM**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096
sn	Serial Number	string	64
policyid	Policy ID	uint32	10

44555 - LOGID_EVENT_CMDB_DEADLOCK_DETECTED

Message ID: 44555

Message Description: LOGID_EVENT_CMDB_DEADLOCK_DETECTED

Message Meaning: CMDB lock deadlock is detected.

Type: Event

Category: SYSTEM

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

45057 - LOG_ID_FCC_ADD

Message ID: 45057

Message Description: LOG_ID_FCC_ADD

Message Meaning: FortiClient connection added

Type: Event

Category: ENDPOINT

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	EndPoint Action	string	65
status	Status	string	23
license_limit	Maximum Number of FortiClients for the License	string	32
used_for_type	Connection for the type	uint32	10
connection_type	FortiClient Connection Type	string	6
count	Count of EndPoint Connections	uint32	10
user	User Name	string	256
ip	Source IP	ip	39
name	Display Name of the Connection	string	128
fctuid		string	32
msg	Log Message	string	4096

45058 - LOG_ID_FCC_CLOSE

Message ID: 45058

Message Description: LOG_ID_FCC_CLOSE

Message Meaning: FortiClient connection closed

Type: Event

Category: ENDPOINT

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096

45061 - LOG_ID_FCC_CLOSE_BY_TYPE

Message ID: 45061

Message Description: LOG_ID_FCC_CLOSE_BY_TYPE

Message Meaning: FortiClient connection closed by type

Type: Event

Category: ENDPOINT

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
subtype	Log subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	EndPoint Action	string	65
status	Status	string	23
license_limit	Maximum Number of FortiClients for the License	string	32
used_for_type	Connection for the type	uint32	10
connection_type	FortiClient Connection Type	string	6
count	Count of EndPoint Connections	uint32	10
user	User Name	string	256
ip	Source IP	ip	39
name	Display Name of the Connection	string	128
fctuid		string	32
msg	Log Message	string	4096

45071 - LOG_ID_FCC_VULN_SCAN

Message ID: 45071

Message Description: LOG_ID_FCC_VULN_SCAN

Message Meaning: FortiClient Vulnerability Scan

Type: Event

Category: ENDPOINT

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
fctuid		string	32
msg	Log Message	string	4096
scantime		uint64	20
srcip		ip	39
srcname		string	64
srcmac		string	17
devtype		string	32
vulnid		uint32	10
vulnname		string	128
vulncat	Vulnerability Category	string	32
severity		string	10
cveid	CVE ID	string	720
vendorurl		string	256

45109 - LOG_ID_EC_FTCL_LOGOFF

Message ID: 45109

Message Description: LOG_ID_EC_FTCL_LOGOFF

Message Meaning: FortiClient logged off

Type: Event

Category: ENDPOINT

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ip	Source IP	ip	39
fctuid		string	32
msg	Log Message	string	4096
hostname	Endpoint Hostname	string	128
interface	Interface	string	32

45114 - LOG_ID_EC_REG_QUARANTINE

Message ID: 45114

Message Description: LOG_ID_EC_REG_QUARANTINE

Message Meaning: FortiClient endpoint quarantined

Type: Event

Category: ENDPOINT

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
subtype	Log subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ip	Source IP	ip	39
fctuid		string	32
msg	Log Message	string	4096
hostname	Endpoint Hostname	string	128
fctemssn		string	16

45115 - LOG_ID_EC_REG_UNQUARANTINE

Message ID: 45115

Message Description: LOG_ID_EC_REG_UNQUARANTINE

Message Meaning: FortiClient endpoint quarantine removed

Type: Event

Category: ENDPOINT

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
ip	Source IP	ip	39
fctuid		string	32
msg	Log Message	string	4096
hostname	Endpoint Hostname	string	128
fctemssn		string	16

45119 - LOG_ID_EC_FTCL_DISCONN

Message ID: 45119

Message Description: LOG_ID_EC_FTCL_DISCONN

Message Meaning: FortiClient disconnected

Type: Event

Category: ENDPOINT

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256

Log Field Name	Description	Data Type	Length
ip	Source IP	ip	39
fctuid		string	32
msg	Log Message	string	4096
hostname	Endpoint Hostname	string	128
interface	Interface	string	32

46000 - LOG_ID_VIP_REAL_SVR_ENA

Message ID: 46000

Message Description: LOG_ID_VIP_REAL_SVR_ENA

Message Meaning: VIP real server enabled

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096
server	Server IP Address	string	64
port	Port Number	uint16	5
vip	Virtual IP	string	64

46001 - LOG_ID_VIP_REAL_SVR_DISA

Message ID: 46001

Message Description: LOG_ID_VIP_REAL_SVR_DISA

Message Meaning: VIP real server disabled

Type: Event

Category: SYSTEM

Severity: Alert

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096
server	Server IP Address	string	64
port	Port Number	uint16	5
vip	Virtual IP	string	64

46002 - LOG_ID_VIP_REAL_SVR_UP

Message ID: 46002

Message Description: LOG_ID_VIP_REAL_SVR_UP

Message Meaning: VIP real server up

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096
server	Server IP Address	string	64
port	Port Number	uint16	5
vip	Virtual IP	string	64

46003 - LOG_ID_VIP_REAL_SVR_DOWN**Message ID:** 46003**Message Description:** LOG_ID_VIP_REAL_SVR_DOWN**Message Meaning:** VIP real server down**Type:** Event**Category:** SYSTEM**Severity:** Alert

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096
server	Server IP Address	string	64
port	Port Number	uint16	5
vip	Virtual IP	string	64

46004 - LOG_ID_VIP_REAL_SVR_ENT_HOLDDOWN

Message ID: 46004

Message Description: LOG_ID_VIP_REAL_SVR_ENT_HOLDDOWN

Message Meaning: VIP real server entered hold-down

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096
server	Server IP Address	string	64
port	Port Number	uint16	5
vip	Virtual IP	string	64

46005 - LOG_ID_VIP_REAL_SVR_FAIL_HOLDDOWN

Message ID: 46005

Message Description: LOG_ID_VIP_REAL_SVR_FAIL_HOLDDOWN

Message Meaning: VIP real server health check failed during hold-down

Type: Event

Category: SYSTEM

Severity: Alert

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096

Log Field Name	Description	Data Type	Length
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096
server	Server IP Address	string	64
port	Port Number	uint16	5
vip	Virtual IP	string	64

46006 - LOG_ID_VIP_REAL_SVR_FAIL

Message ID: 46006

Message Description: LOG_ID_VIP_REAL_SVR_FAIL

Message Meaning: VIP real server health check failed

Type: Event

Category: SYSTEM

Severity: Debug

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
action	Action	string	65
status	Status	string	23
msg	Message Text	string	4096
server	Server IP Address	string	64

Log Field Name	Description	Data Type	Length
port	Port Number	uint16	5
vip	Virtual IP	string	64
monitor-name	Health Monitor Type	string	35
monitor-type	Health Monitor Name	string	32

46400 - LOG_ID_EVENT_EXT_SYS

Message ID: 46400

Message Description: LOG_ID_EVENT_EXT_SYS

Message Meaning: FortiExtender system activity

Type: Event

Category: FORTIEXTENDER

Severity: Notice

Log Field Name	Description	Data Type	Length
date		string	10
time		string	8
logid		string	10
type		string	16
subtype		string	20
level		string	11
devid		string	16
vd		string	32
eventtime		uint64	20
tz		string	5
logdesc		string	4096
msg		string	4096

46401 - LOG_ID_EVENT_EXT_LOCAL

Message ID: 46401

Message Description: LOG_ID_EVENT_EXT_LOCAL

Message Meaning: FortiExtender controller activity

Type: Event

Category: FORTIEXTENDER**Severity:** Notice

Log Field Name	Description	Data Type	Length
date		string	10
time		string	8
logid		string	10
type		string	16
subtype		string	20
level		string	11
devid		string	16
vd		string	32
eventtime		uint64	20
tz		string	5
logdesc		string	4096

46402 - LOG_ID_EVENT_EXT_LOCAL_ERROR

Message ID: 46402**Message Description:** LOG_ID_EVENT_EXT_LOCAL_ERROR**Message Meaning:** FortiExtender controller activity error**Type:** Event**Category:** FORTIEXTENDER**Severity:** Error

Log Field Name	Description	Data Type	Length
date		string	10
time		string	8
logid		string	10
type		string	16
subtype		string	20
level		string	11
devid		string	16
vd		string	32
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
tz		string	5
logdesc		string	4096

46403 - LOG_ID_EVENT_EXT_REMOTE_EMERG

Message ID: 46403

Message Description: LOG_ID_EVENT_EXT_REMOTE_EMERG

Message Meaning: Remote FortiExtender emergency activity

Type: Event

Category: FORTIEXTENDER

Severity: Emergency

Log Field Name	Description	Data Type	Length
date		string	10
time		string	8
logid		string	10
type		string	16
subtype		string	20
level		string	11
devid		string	16
vd		string	32
eventtime		uint64	20
tz		string	5
logdesc		string	4096
msg		string	4096
sn		string	64
ip		ip	39

46404 - LOG_ID_EVENT_EXT_REMOTE_ALERT

Message ID: 46404

Message Description: LOG_ID_EVENT_EXT_REMOTE_ALERT

Message Meaning: Remote FortiExtender alert activity

Type: Event

Category: FORTIEXTENDER**Severity:** Alert

Log Field Name	Description	Data Type	Length
date		string	10
time		string	8
logid		string	10
type		string	16
subtype		string	20
level		string	11
devid		string	16
vd		string	32
eventtime		uint64	20
tz		string	5
logdesc		string	4096
msg		string	4096
sn		string	64
ip		ip	39

46405 - LOG_ID_EVENT_EXT_REMOTE_CRITICAL

Message ID: 46405**Message Description:** LOG_ID_EVENT_EXT_REMOTE_CRITICAL**Message Meaning:** Remote FortiExtender critical activity**Type:** Event**Category:** FORTIEXTENDER**Severity:** Critical

Log Field Name	Description	Data Type	Length
date		string	10
time		string	8
logid		string	10
type		string	16
subtype		string	20
level		string	11

Log Field Name	Description	Data Type	Length
devid		string	16
vd		string	32
eventtime		uint64	20
tz		string	5
logdesc		string	4096
msg		string	4096
sn		string	64
ip		ip	39

46406 - LOG_ID_EVENT_EXT_REMOTE_ERROR

Message ID: 46406

Message Description: LOG_ID_EVENT_EXT_REMOTE_ERROR

Message Meaning: Remote FortiExtender error activity

Type: Event

Category: FORTIEXTENDER

Severity: Error

Log Field Name	Description	Data Type	Length
date		string	10
time		string	8
logid		string	10
type		string	16
subtype		string	20
level		string	11
devid		string	16
vd		string	32
eventtime		uint64	20
tz		string	5
logdesc		string	4096
msg		string	4096
sn		string	64
ip		ip	39

46407 - LOG_ID_EVENT_EXT_REMOTE_WARNING

Message ID: 46407

Message Description: LOG_ID_EVENT_EXT_REMOTE_WARNING

Message Meaning: Remote FortiExtender warning activity

Type: Event

Category: FORTIEXTENDER

Severity: Warning

Log Field Name	Description	Data Type	Length
date		string	10
time		string	8
logid		string	10
type		string	16
subtype		string	20
level		string	11
devid		string	16
vd		string	32
eventtime		uint64	20
tz		string	5
logdesc		string	4096
msg		string	4096
sn		string	64
ip		ip	39

46408 - LOG_ID_EVENT_EXT_REMOTE_NOTIF

Message ID: 46408

Message Description: LOG_ID_EVENT_EXT_REMOTE_NOTIF

Message Meaning: Remote FortiExtender notify activity

Type: Event

Category: FORTIEXTENDER

Severity: Notice

Log Field Name	Description	Data Type	Length
date		string	10
time		string	8
logid		string	10
type		string	16
subtype		string	20
level		string	11
devid		string	16
vd		string	32
eventtime		uint64	20
tz		string	5
logdesc		string	4096
msg		string	4096
sn		string	64
ip		ip	39

46409 - LOG_ID_EVENT_EXT_REMOTE_INFO

Message ID: 46409

Message Description: LOG_ID_EVENT_EXT_REMOTE_INFO

Message Meaning: Remote FortiExtender info activity

Type: Event

Category: FORTIEXTENDER

Severity: Information

Log Field Name	Description	Data Type	Length
date		string	10
time		string	8
logid		string	10
type		string	16
subtype		string	20
level		string	11
devid		string	16

Log Field Name	Description	Data Type	Length
vd		string	32
eventtime		uint64	20
tz		string	5
logdesc		string	4096
msg		string	4096
sn		string	64
ip		ip	39

46410 - LOG_ID_EVENT_EXT_REMOTE_DEBUG

Message ID: 46410

Message Description: LOG_ID_EVENT_EXT_REMOTE_DEBUG

Message Meaning: Remote FortiExtender debug activity

Type: Event

Category: FORTIEXTENDER

Severity: Debug

Log Field Name	Description	Data Type	Length
date		string	10
time		string	8
logid		string	10
type		string	16
subtype		string	20
level		string	11
devid		string	16
vd		string	32
eventtime		uint64	20
tz		string	5
logdesc		string	4096
msg		string	4096
sn		string	64
ip		ip	39

46501 - LOG_ID_INTERNAL_LTE_MODEM_DETECTION

Message ID: 46501

Message Description: LOG_ID_INTERNAL_LTE_MODEM_DETECTION

Message Meaning: LTE modem detection

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

46502 - LOG_ID_INTERNAL_LTE_MODEM_GPSD

Message ID: 46502

Message Description: LOG_ID_INTERNAL_LTE_MODEM_GPSD

Message Meaning: LTE modem GPS daemon started or stopped

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

46503 - LOG_ID_INTERNAL_LTE_MODEM_GPS_LOC_ACQUISITION

Message ID: 46503

Message Description: LOG_ID_INTERNAL_LTE_MODEM_GPS_LOC_ACQUISITION

Message Meaning: LTE modem GPS location acquisition

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

46504 - LOG_ID_INTERNAL_LTE_MODEM_BILLD

Message ID: 46504

Message Description: LOG_ID_INTERNAL_LTE_MODEM_BILLD

Message Meaning: LTE modem billing daemon started or stopped

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

46505 - LOG_ID_INTERNAL_LTE_MODEM_BILLING_PURGED

Message ID: 46505

Message Description: LOG_ID_INTERNAL_LTE_MODEM_BILLING_PURGED

Message Meaning: LTE billing data purged

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

46506 - LOG_ID_INTERNAL_LTE_MODEM_BILLING_DAILY_LOG

Message ID: 46506

Message Description: LOG_ID_INTERNAL_LTE_MODEM_BILLING_DAILY_LOG

Message Meaning: LTE billing daily usage information

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

46507 - LOG_ID_INTERNAL_LTE_MODEM_FW_UPGRADE

Message ID: 46507

Message Description: LOG_ID_INTERNAL_LTE_MODEM_FW_UPGRADE

Message Meaning: LTE modem firmware upgrade event

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

46508 - LOG_ID_INTERNAL_LTE_MODEM_QDL_DETECTION

Message ID: 46508

Message Description: LOG_ID_INTERNAL_LTE_MODEM_QDL_DETECTION

Message Meaning: LTE modem QDL device detection event

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

46509 - LOG_ID_INTERNAL_LTE_MODEM_REBOOT

Message ID: 46509

Message Description: LOG_ID_INTERNAL_LTE_MODEM_REBOOT

Message Meaning: LTE modem reboot event

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

46510 - LOG_ID_INTERNAL_LTE_MODEM_OP_MODE

Message ID: 46510

Message Description: LOG_ID_INTERNAL_LTE_MODEM_OP_MODE

Message Meaning: LTE modem operation mode

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

46511 - LOG_ID_INTERNAL_LTE_MODEM_POWER_ON_OFF

Message ID: 46511

Message Description: LOG_ID_INTERNAL_LTE_MODEM_POWER_ON_OFF

Message Meaning: LTE modem powered on or powered off

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

46512 - LOG_ID_INTERNAL_LTE_MODEM_SIM_STATE

Message ID: 46512

Message Description: LOG_ID_INTERNAL_LTE_MODEM_SIM_STATE

Message Meaning: LTE modem sim card state event

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

46513 - LOG_ID_INTERNAL_LTE_MODEM_LINK_CONNECTION

Message ID: 46513

Message Description: LOG_ID_INTERNAL_LTE_MODEM_LINK_CONNECTION

Message Meaning: LTE modem data link connection event

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

46514 - LOG_ID_INTERNAL_LTE_MODEM_MANUAL_HANOVER

Message ID: 46514

Message Description: LOG_ID_INTERNAL_LTE_MODEM_MANUAL_HANOVER

Message Meaning: LTE modem manual handover event

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

46515 - LOG_ID_INTERNAL_LTE_MODEM_IP_ADDR

Message ID: 46515

Message Description: LOG_ID_INTERNAL_LTE_MODEM_IP_ADDR

Message Meaning: LTE modem ip address event

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

46516 - LOG_ID_INTERNAL_LTE_MODEM_BEARER_TECH_CHANGE

Message ID: 46516

Message Description: LOG_ID_INTERNAL_LTE_MODEM_BEARER_TECH_CHANGE

Message Meaning: LTE modem bearer event

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

46517 - LOG_ID_INTERNAL_LTE_MODEM_HARDWARE_ERROR

Message ID: 46517

Message Description: LOG_ID_INTERNAL_LTE_MODEM_HARDWARE_ERROR

Message Meaning: LTE modem hardware error event

Type: Event

Category: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

46600 - LOG_ID_EVENT_AUTOMATION_TRIGGERED

Message ID: 46600

Message Description: LOG_ID_EVENT_AUTOMATION_TRIGGERED

Message Meaning: Automation stitch triggered

Type: Event

Category: SYSTEM

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096

Log Field Name	Description	Data Type	Length
action	Action	string	65
msg	Message Text	string	4096
from	Sender Email Address for Notification	string	128
stitch		string	36
trigger		string	36

46900 - LOG_ID_POE_STATUS_REPORT

Message ID: 46900

Message Description: LOG_ID_POE_STATUS_REPORT

Message Meaning: PoE device status reported

Type: Event

Category: SYSTEM

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

47000 - LOG_ID_MALWARE_LIST_TRUNCATED_ENTER

Message ID: 47000

Message Description: LOG_ID_MALWARE_LIST_TRUNCATED_ENTER

Message Meaning: External malware list is truncated

Type: Event**Category:** SYSTEM**Severity:** Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

47001 - LOG_ID_MALWARE_LIST_TRUNCATED_EXIT

Message ID: 47001**Message Description:** LOG_ID_MALWARE_LIST_TRUNCATED_EXIT**Message Meaning:** External malware list is no longer truncated**Type:** Event**Category:** SYSTEM**Severity:** Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

47203 - LOG_ID_ENTER_BYPASS

Message ID: 47203

Message Description: LOG_ID_ENTER_BYPASS

Message Meaning: Bypass ports pair entered bypass mode

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

47204 - LOG_ID_EXIT_BYPASS

Message ID: 47204

Message Description: LOG_ID_EXIT_BYPASS

Message Meaning: Bypass ports pair exited bypass mode

Type: Event

Category: SYSTEM

Severity: Warning

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

48000 - LOG_ID_WAD_SSL_RCV_HS

Message ID: 48000

Message Description: LOG_ID_WAD_SSL_RCV_HS

Message Meaning: SSL handshake received

Type: Event

Category: WAD

Severity: Debug

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Log Message	string	4096
session_id	Session ID	uint32	10
policyid	Policy ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
action	Action	string	65
handshake	Handshake	string	32

48001 - LOG_ID_WAD_SSL_RCV_WRG_HS

Message ID: 48001

Message Description: LOG_ID_WAD_SSL_RCV_WRG_HS

Message Meaning: SSL handshake message incorrect

Type: Event

Category: WAD

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Log Message	string	4096
session_id	Session ID	uint32	10
policyid	Policy ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
action	Action	string	65

48002 - LOG_ID_WAD_SSL_SENT_HS

Message ID: 48002

Message Description: LOG_ID_WAD_SSL_SENT_HS

Message Meaning: SSL handshake sent

Type: Event

Category: WAD

Severity: Debug

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Log Message	string	4096
session_id	Session ID	uint32	10
policyid	Policy ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
action	Action	string	65
handshake	Handshake	string	32

48003 - LOG_ID_WAD_SSL_WRG_HS_LEN

Message ID: 48003

Message Description: LOG_ID_WAD_SSL_WRG_HS_LEN

Message Meaning: SSL handshake length invalid

Type: Event

Category: WAD

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
tz		string	5
logdesc	Log Description	string	4096
msg	Log Message	string	4096
session_id	Session ID	uint32	10
policyid	Policy ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
action	Action	string	65
handshake	Handshake	string	32

48004 - LOG_ID_WAD_SSL_RCV_CCS

Message ID: 48004

Message Description: LOG_ID_WAD_SSL_RCV_CCS

Message Meaning: SSL ChangeCipherSpec received

Type: Event

Category: WAD

Severity: Debug

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	4096
msg	Log Message	string	4096
session_id	Session ID	uint32	10
policyid	Policy ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
action	Action	string	65

48005 - LOG_ID_WAD_SSL_RSA_DH_FAIL

Message ID: 48005

Message Description: LOG_ID_WAD_SSL_RSA_DH_FAIL

Message Meaning: RSA verification of Diffie-Hellman parameters failed

Type: Event

Category: WAD

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Log Message	string	4096

Log Field Name	Description	Data Type	Length
session_id	Session ID	uint32	10
policyid	Policy ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
action	Action	string	65

48006 - LOG_ID_WAD_SSL_SENT_CCS

Message ID: 48006

Message Description: LOG_ID_WAD_SSL_SENT_CCS

Message Meaning: SSL ChangeCipherSpec sent

Type: Event

Category: WAD

Severity: Debug

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Log Message	string	4096
session_id	Session ID	uint32	10
policyid	Policy ID	uint32	10

Log Field Name	Description	Data Type	Length
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
action	Action	string	65

48007 - LOG_ID_WAD_SSL_BAD_HASH

Message ID: 48007

Message Description: LOG_ID_WAD_SSL_BAD_HASH

Message Meaning: SSL Finished hash mismatch

Type: Event

Category: WAD

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Log Message	string	4096
session_id	Session ID	uint32	10
policyid	Policy ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5

Log Field Name	Description	Data Type	Length
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
action	Action	string	65
ssllocal		string	76
sslremote		string	76

48009 - LOG_ID_WAD_SSL_DECRY_FAIL

Message ID: 48009

Message Description: LOG_ID_WAD_SSL_DECRY_FAIL

Message Meaning: SSL decryption failed

Type: Event

Category: WAD

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Log Message	string	4096
session_id	Session ID	uint32	10
policyid	Policy ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5

Log Field Name	Description	Data Type	Length
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
action	Action	string	65
reason	Reason	string	256

48011 - LOG_ID_WAD_SSL_LESS_MINOR

Message ID: 48011

Message Description: LOG_ID_WAD_SSL_LESS_MINOR

Message Meaning: SSL minor version less than configured minimum value

Type: Event

Category: WAD

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Log Message	string	4096
session_id	Session ID	uint32	10
policyid	Policy ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
dstip	Destination IP	ip	39

Log Field Name	Description	Data Type	Length
dstport	Destination Port	uint16	5
action	Action	string	65

48013 - LOG_ID_WAD_SSL_NOT_SUPPORT_CS

Message ID: 48013

Message Description: LOG_ID_WAD_SSL_NOT_SUPPORT_CS

Message Meaning: SSL Cipher Suites not supported

Type: Event

Category: WAD

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Log Message	string	4096
session_id	Session ID	uint32	10
policyid	Policy ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
action	Action	string	65

48016 - LOG_ID_WAD_SSL_HS_FIN

Message ID: 48016

Message Description: LOG_ID_WAD_SSL_HS_FIN

Message Meaning: SSL handshake completed

Type: Event

Category: WAD

Severity: Debug

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Log Message	string	4096
session_id	Session ID	uint32	10
policyid	Policy ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
action	Action	string	65

48017 - LOG_ID_WAD_SSL_HS_TOO_LONG

Message ID: 48017

Message Description: LOG_ID_WAD_SSL_HS_TOO_LONG

Message Meaning: SSL handshake too long

Type: Event**Category:** WAD**Severity:** Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Log Message	string	4096
session_id	Session ID	uint32	10
policyid	Policy ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
action	Action	string	65
handshake	Handshake	string	32

48019 - LOG_ID_WAD_SSL_SENT_ALERT

Message ID: 48019**Message Description:** LOG_ID_WAD_SSL_SENT_ALERT**Message Meaning:** SSL alert sent**Type:** Event**Category:** WAD**Severity:** Debug

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Log Message	string	4096
session_id	Session ID	uint32	10
policyid	Policy ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
action	Action	string	65
alert	Alert	string	256
desc	Description	string	128

48023 - LOG_ID_WAD_SSL_RCV_ALERT

Message ID: 48023

Message Description: LOG_ID_WAD_SSL_RCV_ALERT

Message Meaning: SSL alert received

Type: Event

Category: WAD

Severity: Debug

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Log Message	string	4096
session_id	Session ID	uint32	10
policyid	Policy ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
action	Action	string	65
alert	Alert	string	256
desc	Description	string	128

48027 - LOG_ID_WAD_SSL_INVALID_CONT_TYPE

Message ID: 48027

Message Description: LOG_ID_WAD_SSL_INVALID_CONT_TYPE

Message Meaning: SSL Content Type invalid

Type: Event

Category: WAD

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Log Message	string	4096
session_id	Session ID	uint32	10
policyid	Policy ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
action	Action	string	65

48029 - LOG_ID_WAD_SSL_BAD_CCS_LEN

Message ID: 48029

Message Description: LOG_ID_WAD_SSL_BAD_CCS_LEN

Message Meaning: SSL ChangeCipherSpec length invalid

Type: Event

Category: WAD

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Log Message	string	4096
session_id	Session ID	uint32	10
policyid	Policy ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
action	Action	string	65

48031 - LOG_ID_WAD_SSL_BAD_DH

Message ID: 48031

Message Description: LOG_ID_WAD_SSL_BAD_DH

Message Meaning: SSL Diffie-Hellman value invalid

Type: Event

Category: WAD

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Log Message	string	4096
session_id	Session ID	uint32	10
policyid	Policy ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
action	Action	string	65

48032 - LOG_ID_WAD_SSL_PUB_KEY_TOO_BIG

Message ID: 48032

Message Description: LOG_ID_WAD_SSL_PUB_KEY_TOO_BIG

Message Meaning: Certificate's public key too long

Type: Event

Category: WAD

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Log Message	string	4096
session_id	Session ID	uint32	10
policyid	Policy ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
action	Action	string	65

48034 - LOG_ID_WAD_SSL_SERVER_KEY_HASH_ALGORITHM_MISMATCH

Message ID: 48034

Message Description: LOG_ID_WAD_SSL_SERVER_KEY_HASH_ALGORITHM_MISMATCH

Message Meaning: Server Key Exchange hash algorithm mismatch

Type: Event

Category: WAD

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Log Message	string	4096
session_id	Session ID	uint32	10
policyid	Policy ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
action	Action	string	65
received		uint8	3

48035 - LOG_ID_WAD_SSL_SERVER_KEY_SIGNATURE_ALGORITHM_MISMATCH

Message ID: 48035

Message Description: LOG_ID_WAD_SSL_SERVER_KEY_SIGNATURE_ALGORITHM_MISMATCH

Message Meaning: Server Key Exchange signature algorithm mismatch

Type: Event

Category: WAD

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
tz		string	5
logdesc	Log Description	string	4096
msg	Log Message	string	4096
session_id	Session ID	uint32	10
policyid	Policy ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
action	Action	string	65
expectedsignature		uint8	3
receivedsignature		uint8	3

48038 - LOG_ID_WAD_SSL_RCV_FATAL_ALERT

Message ID: 48038

Message Description: LOG_ID_WAD_SSL_RCV_FATAL_ALERT

Message Meaning: SSL Fatal Alert received

Type: Event

Category: WAD

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
tz		string	5
logdesc	Log Description	string	4096
msg	Log Message	string	4096
session_id	Session ID	uint32	10
policyid	Policy ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
action	Action	string	65
alert	Alert	string	256
desc	Description	string	128

48039 - LOG_ID_WAD_SSL_SENT_FATAL_ALERT

Message ID: 48039

Message Description: LOG_ID_WAD_SSL_SENT_FATAL_ALERT

Message Meaning: SSL fatal alert sent

Type: Event

Category: WAD

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
tz		string	5
logdesc	Log Description	string	4096
msg	Log Message	string	4096
session_id	Session ID	uint32	10
policyid	Policy ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
action	Action	string	65
alert	Alert	string	256
desc	Description	string	128

48101 - LOG_ID_WAD_AUTH_FAIL_PSK

Message ID: 48101

Message Description: LOG_ID_WAD_AUTH_FAIL_PSK

Message Meaning: WAN Optimization peer PSK authentication failed

Type: Event

Category: WAD

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
tz		string	5
logdesc	Log Description	string	4096
msg	Log Message	string	4096
policyid	Policy ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
serial	Serial Number	uint32	10
authgrp	Authorization Group	string	36
host	Host Name	string	256

48102 - LOG_ID_WAD_AUTH_FAIL_OTH

Message ID: 48102

Message Description: LOG_ID_WAD_AUTH_FAIL_OTH

Message Meaning: WAN Optimization peer authentication failed

Type: Event

Category: WAD

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5

Log Field Name	Description	Data Type	Length
logdesc	Log Description	string	4096
msg	Log Message	string	4096
policyid	Policy ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
serial	Serial Number	uint32	10
authgrp	Authorization Group	string	36
peer		string	36

48300 - LOG_ID_WRG_SVR_FGT_CONF

Message ID: 48300

Message Description: LOG_ID_WRG_SVR_FGT_CONF

Message Meaning: Server side WAN Optimization FortiGate configured incorrectly

Type: Event

Category: WAD

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096

Log Field Name	Description	Data Type	Length
msg	Log Message	string	4096
session_id	Session ID	uint32	10
policyid	Policy ID	uint32	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5

48301 - LOG_ID_UNEXP_APP_TYPE

Message ID: 48301

Message Description: LOG_ID_UNEXP_APP_TYPE

Message Meaning: Unexpected application type for WAN Optimization

Type: Event

Category: WAD

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Log Message	string	4096
session_id	Session ID	uint32	10
policyid	Policy ID	uint32	10

Log Field Name	Description	Data Type	Length
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
app-type	Address Type	string	64

51000 - LOG_ID_NB_TBL_CHG

Message ID: 51000

Message Description: LOG_ID_NB_TBL_CHG

Message Meaning: Neighbor table changed

Type: Event

Category: ROUTER

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message	string	4096
action	Action	string	65
service	Name of Service	string	64
mac	Mac Address	string	17
src_int	Source Interface	string	64
srcip		ip	39

52000 - LOG_ID_EVENT_SECURITY_AUDIT_FABRIC_SUMMARY

Message ID: 52000

Message Description: LOG_ID_EVENT_SECURITY_AUDIT_FABRIC_SUMMARY

Message Meaning: Security Rating summary

Type: Event

Category: SECURITY-RATING

Severity: Notice

Log Field Name	Description	Data Type	Length
date		string	10
time		string	8
logid		string	10
type		string	16
subtype		string	20
level		string	11
devid		string	16
vd		string	32
eventtime		uint64	20
tz		string	5
logdesc		string	4096
auditid		uint64	20
audittime		uint64	20
auditscore		string	20
criticalcount		int32	10
highcount		int32	10
mediumcount		int32	10
lowcount		int32	10
passedcount		int32	10

52001 - LOG_ID_EVENT_SECURITY_AUDIT_FABRIC_CHANGE

Message ID: 52001

Message Description: LOG_ID_EVENT_SECURITY_AUDIT_FABRIC_CHANGE

Message Meaning: Security Rating result change

Type: Event**Category:** SECURITY-RATING**Severity:** Notice

Log Field Name	Description	Data Type	Length
date		string	10
time		string	8
logid		string	10
type		string	16
subtype		string	20
level		string	11
devid		string	16
vd		string	32
eventtime		uint64	20
tz		string	5
logdesc		string	4096
auditid		uint64	20
audittime		uint64	20
auditscore		string	20
criticalcount		int32	10
highcount		int32	10
mediumcount		int32	10
lowcount		int32	10
passedcount		int32	10

53000 - LOG_ID_SDNC_CONNECTED

Message ID: 53000**Message Description:** LOG_ID_SDNC_CONNECTED**Message Meaning:** Connected to SDN server**Type:** Event**Category:** SYSTEM**Severity:** Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
action	Action	string	65
msg	Message Text	string	4096

53001 - LOG_ID_SDNC_DISCONNECTED

Message ID: 53001

Message Description: LOG_ID_SDNC_DISCONNECTED

Message Meaning: Disconnected from SDN server

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16

Log Field Name	Description	Data Type	Length
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
user	User Name	string	256
action	Action	string	65
msg	Message Text	string	4096

53002 - LOG_ID_SDNC_SUBSCRIBE

Message ID: 53002

Message Description: LOG_ID_SDNC_SUBSCRIBE

Message Meaning: Dynamic SDN address channel opened

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

53003 - LOG_ID_SDNC_UNSUBSCRIBE

Message ID: 53003

Message Description: LOG_ID_SDNC_UNSUBSCRIBE

Message Meaning: Dynamic SDN address channel closed

Type: Event

Category: SYSTEM

Severity: Information

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message Text	string	4096

53100 - LOG_ID_VPN_OCVPN_REGISTERED

Message ID: 53100

Message Description: LOG_ID_VPN_OCVPN_REGISTERED

Message Meaning: Overlay Controller VPN registered

Type: Event

Category: VPN

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message	string	4096
status	Status	string	23

53101 - LOG_ID_VPN_OCVPN_UNREGISTERED

Message ID: 53101

Message Description: LOG_ID_VPN_OCVPN_UNREGISTERED

Message Meaning: Overlay Controller VPN unregistered

Type: Event

Category: VPN

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message	string	4096
status	Status	string	23

53102 - LOG_ID_VPN_OCVPN_COMM_ESTABLISHED

Message ID: 53102

Message Description: LOG_ID_VPN_OCVPN_COMM_ESTABLISHED

Message Meaning: Overlay Controller VPN server communication established

Type: Event

Category: VPN

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message	string	4096
status	Status	string	23

53103 - LOG_ID_VPN_OCVPN_COMM_ERROR

Message ID: 53103

Message Description: LOG_ID_VPN_OCVPN_COMM_ERROR

Message Meaning: Overlay Controller VPN server communication error

Type: Event

Category: VPN

Severity: Error

Log Field Name	Description	Data Type	Length
date	Date	string	10

Log Field Name	Description	Data Type	Length
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message	string	4096
status	Status	string	23

53104 - LOG_ID_VPN_OCVPN_DNS_ERROR

Message ID: 53104

Message Description: LOG_ID_VPN_OCVPN_DNS_ERROR

Message Meaning: Overlay Controller VPN DNS error

Type: Event

Category: VPN

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
tz		string	5
logdesc	Log Description	string	4096
msg	Message	string	4096
status	Status	string	23

53105 - LOG_ID_VPN_OCVPN_ROUTE_ERROR

Message ID: 53105

Message Description: LOG_ID_VPN_OCVPN_ROUTE_ERROR

Message Meaning: Overlay Controller VPN routing error

Type: Event

Category: VPN

Severity: Notice

Log Field Name	Description	Data Type	Length
date	Date	string	10
time	Time	string	8
logid	Log ID	string	10
type	Log Type	string	16
subtype	Log Subtype	string	20
level	Log Level	string	11
devid	Device ID	string	16
vd	Virtual Domain Name	string	32
eventtime		uint64	20
tz		string	5
logdesc	Log Description	string	4096
msg	Message	string	4096
status	Status	string	23

53200 - LOG_ID_CONNECTOR_OBJECT_ADD

Message ID: 53200

Message Description: LOG_ID_CONNECTOR_OBJECT_ADD

Message Meaning: IP address added

Type: Event

Category: CONNECTOR

Severity: Information

Log Field Name	Description	Data Type	Length
date		string	10
time		string	8
logid		string	10
type		string	16
subtype		string	20
level		string	11
devid		string	16
vd		string	32
eventtime		uint64	20
tz		string	5
logdesc		string	4096
cfgobj		string	256
action		string	65
addr		string	80
cldobjid		string	128
netid		string	128
msg		string	4096

53201 - LOG_ID_CONNECTOR_OBJECT_REMOVE

Message ID: 53201

Message Description: LOG_ID_CONNECTOR_OBJECT_REMOVE

Message Meaning: IP address removed

Type: Event

Category: CONNECTOR

Severity: Information

Log Field Name	Description	Data Type	Length
date		string	10

Log Field Name	Description	Data Type	Length
time		string	8
logid		string	10
type		string	16
subtype		string	20
level		string	11
devid		string	16
vd		string	32
eventtime		uint64	20
tz		string	5
logdesc		string	4096
cfgobj		string	256
action		string	65
addr		string	80
cldobjid		string	128
netid		string	128
msg		string	4096

FILE-FILTER

64000 - LOG_ID_FILE_FILTER_BLOCK

Message ID: 64000

Message Description: LOG_ID_FILE_FILTER_BLOCK

Message Meaning: File was blocked by file filter

Type: FILE-FILTER

Category: FILE-FILTER

Severity: Warning

Log Field Name	Description	Data Type	Length
action		string	20
agent		string	64
authserver		string	32

Log Field Name	Description	Data Type	Length
date		string	10
devid		string	16
direction		string	8
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
filename		string	256
filesize		uint64	10
filetype		string	23
filtername		string	32
forwardedfor		string	128
from		string	128
group		string	64
hostname		string	256
level		string	11
logid		string	10
matchfilename		string	256
matchfiletype		string	23
msg		string	512
policyid		uint32	10
profile		string	64
proto		uint8	3
rawdata		string	20480
recipient		string	512
sender		string	128
service		string	36

Log Field Name	Description	Data Type	Length
sessionid		uint32	10
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subject		string	256
subservice		string	16
subtype		string	20
time		string	8
to		string	512
trueclntip		ip	39
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url		string	512
user		string	256
vd		string	32
vrf		uint8	3

64001 - LOG_ID_FILE_FILTER_LOG

Message ID: 64001

Message Description: LOG_ID_FILE_FILTER_LOG

Message Meaning: File was detected by file filter

Type: FILE-FILTER

Category: FILE-FILTER

Severity: Notice

Log Field Name	Description	Data Type	Length
action		string	20

Log Field Name	Description	Data Type	Length
agent		string	64
authserver		string	32
date		string	10
devid		string	16
direction		string	8
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
filename		string	256
filesize		uint64	10
filetype		string	23
filtername		string	32
forwardedfor		string	128
from		string	128
group		string	64
hostname		string	256
level		string	11
logid		string	10
matchfilename		string	256
matchfiletype		string	23
msg		string	512
policyid		uint32	10
profile		string	64
proto		uint8	3
rawdata		string	20480
recipient		string	512

Log Field Name	Description	Data Type	Length
sender		string	128
service		string	36
sessionid		uint32	10
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subject		string	256
subservice		string	16
subtype		string	20
time		string	8
to		string	512
trueclntip		ip	39
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url		string	512
user		string	256
vd		string	32
vrf		uint8	3

GTP

41216 - LOGID_GTP_FORWARD

Message ID: 41216

Message Description: LOGID_GTP_FORWARD

Message Meaning: GTP forward

Type: GTP

Category: GTP-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
c-gsn	Control Plane GSN	ip	39
date	Date	string	10
deny_cause	Deny Cause	string	25
devid		string	16
dstport	Destination Port	uint16	5
dtlexp	Detailed Explanation	string	64
end-usr-address	End user IP Address	ip	39
endusraddress6		ip	39
eventtime		uint64	20
from	From	ip	128
headerteid	Tunnel Endpoint ID Header	uint32	10
ietype	Malformed GTP IE number	uint8	3
imei-sv		string	32
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
linked-nsapi	Linked Netscape Server Application Programming Interface	uint8	3
logid	Log ID	string	10
msg-type	Message Type	uint8	3
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
nsapi	Netscape Server Application Programming Interface	uint8	3
profile	Profile Name	string	64
rai		string	32
rat-type	Radio Access Technology type	string	7
selection	APN selection, which is one IE in gtp packet	string	14
seqnum	GTP packet sequence number	uint32	10
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
to	To	ip	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
tz		string	5
u-gsn	User Plane GSN	ip	39
uli		string	32
ulimcc		uint16	3
ulimnc		uint16	3
vd	Virtual Domain Name	string	32
version	Version	uint32	64

41217 - LOGID_GTP_DENY

Message ID: 41217

Message Description: LOGID_GTP_DENY

Message Meaning: GTP deny

Type: GTP

Category: GTP-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
c-gsn	Control Plane GSN	ip	39
date	Date	string	10
deny_cause	Deny Cause	string	25
devid		string	16
dstport	Destination Port	uint16	5
dtlexp	Detailed Explanation	string	64
end-usr-address	End user IP Address	ip	39
endusraddress6		ip	39
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
from	From	ip	128
headerteid	Tunnel Endpoint ID Header	uint32	10
ietype	Malformed GTP IE number	uint8	3
imei-sv		string	32
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
linked-nsapi	Linked Netscape Server Application Programming Interface	uint8	3
logid	Log ID	string	10
msg-type	Message Type	uint8	3
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
nsapi	Netscape Server Application Programming Interface	uint8	3
profile	Profile Name	string	64
rai		string	32
rat-type	Radio Access Technology type	string	7
selection	APN selection, which is one IE in gtp packet	string	14
seqnum	GTP packet sequence number	uint32	10
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	ip	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
tz		string	5
u-gsn	User Plane GSN	ip	39
uli		string	32
ulimcc		uint16	3
ulimnc		uint16	3
vd	Virtual Domain Name	string	32
version	Version	uint32	64

41218 - LOGID_GTP_RATE_LIMIT

Message ID: 41218

Message Description: LOGID_GTP_RATE_LIMIT

Message Meaning: GTP rate limit

Type: GTP

Category: GTP-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
c-gsn	Control Plane GSN	ip	39
date	Date	string	10
deny_cause	Deny Cause	string	25
devid		string	16
dstport	Destination Port	uint16	5
dtlexp	Detailed Explanation	string	64
end-usr-address	End user IP Address	ip	39
endusraddress6		ip	39
eventtime		uint64	20
from	From	ip	128
headerteid	Tunnel Endpoint ID Header	uint32	10
ietype	Malformed GTP IE number	uint8	3
imei-sv		string	32
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
linked-nsapi	Linked Netscape Server Application Programming Interface	uint8	3
logid	Log ID	string	10
msg-type	Message Type	uint8	3
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
nsapi	Netscape Server Application Programming Interface	uint8	3
profile	Profile Name	string	64
rai		string	32

Log Field Name	Description	Data Type	Length
rat-type	Radio Access Technology type	string	7
selection	APN selection, which is one IE in gtp packet	string	14
seqnum	GTP packet sequence number	uint32	10
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	ip	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
tz		string	5
u-gsn	User Plane GSN	ip	39
uli		string	32
ulimcc		uint16	3
ulimnc		uint16	3
vd	Virtual Domain Name	string	32
version	Version	uint32	64

41219 - LOGID_GTP_STATE_INVALID

Message ID: 41219

Message Description: LOGID_GTP_STATE_INVALID

Message Meaning: GTP state invalid

Type: GTP

Category: GTP-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
c-gsn	Control Plane GSN	ip	39
date	Date	string	10
deny_cause	Deny Cause	string	25

Log Field Name	Description	Data Type	Length
devid		string	16
dstport	Destination Port	uint16	5
dtlexp	Detailed Explanation	string	64
end-usr-address	End user IP Address	ip	39
endusraddress6		ip	39
eventtime		uint64	20
from	From	ip	128
headerteid	Tunnel Endpoint ID Header	uint32	10
ietype	Malformed GTP IE number	uint8	3
imei-sv		string	32
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
linked-nsapi	Linked Netscape Server Application Programming Interface	uint8	3
logid	Log ID	string	10
msg-type	Message Type	uint8	3
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
nsapi	Netscape Server Application Programming Interface	uint8	3
profile	Profile Name	string	64
rai		string	32
rat-type	Radio Access Technology type	string	7
selection	APN selection, which is one IE in gtp packet	string	14
seqnum	GTP packet sequence number	uint32	10
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	ip	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
tz		string	5

Log Field Name	Description	Data Type	Length
u-gsn	User Plane GSN	ip	39
uli		string	32
ulimcc		uint16	3
ulimnc		uint16	3
vd	Virtual Domain Name	string	32
version	Version	uint32	64

41220 - LOGID_GTP_TUNNEL_LIMIT

Message ID: 41220

Message Description: LOGID_GTP_TUNNEL_LIMIT

Message Meaning: Tunnel limit GTP message. These messages occur only when the maximum number of GTP tunnels is reached. No new tunnels are created when the maximum number is reached

Type: GTP

Category: GTP-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
c-gsn	Control Plane GSN	ip	39
date	Date	string	10
deny_cause	Deny Cause	string	25
devid		string	16
dstport	Destination Port	uint16	5
dtlexp	Detailed Explanation	string	64
end-usr-address	End user IP Address	ip	39
endusraddress6		ip	39
eventtime		uint64	20
from	From	ip	128
headerteid	Tunnel Endpoint ID Header	uint32	10
ietype	Malformed GTP IE number	uint8	3
imei-sv		string	32
imsi	International mobile subscriber ID	string	16

Log Field Name	Description	Data Type	Length
level	Log Level	string	11
linked-nsapi	Linked Netscape Server Application Programming Interface	uint8	3
logid	Log ID	string	10
msg-type	Message Type	uint8	3
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
nsapi	Netscape Server Application Programming Interface	uint8	3
profile	Profile Name	string	64
rai		string	32
rat-type	Radio Access Technology type	string	7
selection	APN selection, which is one IE in gtp packet	string	14
seqnum	GTP packet sequence number	uint32	10
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	ip	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
tz		string	5
u-gsn	User Plane GSN	ip	39
uli		string	32
ulimcc		uint16	3
ulimnc		uint16	3
vd	Virtual Domain Name	string	32
version	Version	uint32	64

41221 - LOGID_GTP_TRAFFIC_COUNT

Message ID: 41221

Message Description: LOGID_GTP_TRAFFIC_COUNT

Message Meaning: Statistic summary information when the GTP tunnel is being torn down

Type: GTP

Category: GTP-ALL**Severity:** Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
date	Date	string	10
devid		string	16
end-usr-address	End user IP Address	ip	39
endusraddress6		ip	39
eventtime		uint64	20
imei-sv		string	32
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
linked-nsapi	Linked Netscape Server Application Programming Interface	uint8	3
logid	Log ID	string	10
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
nsapi	Netscape Server Application Programming Interface	uint8	3
profile	Profile Name	string	64
rai		string	32
rat-type	Radio Access Technology type	string	7
selection	APN selection, which is one IE in gtp packet	string	14
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
tz		string	5
uli		string	32
ulimcc		uint16	3
ulimnc		uint16	3
vd	Virtual Domain Name	string	32
version	Version	uint32	64
c-bytes	Control Plane Data Bytes	uint64	20

Log Field Name	Description	Data Type	Length
c-ggsn	Control Plane GGSN IP Address	ip	39
c-ggsn-teid	Control Plane GGSN Tunnel Endpoint Identifier	uint32	10
c-pkts	Control Plane Packets	uint64	20
c-sgsn	Control Plane SGSN IP Address	ip	39
c-sgsn-teid	Control Plane SGSN Tunnel Endpoint Identifier	uint32	10
duration	tunnel duration	uint32	10
u-bytes	User Plane Data Bytes	uint64	20
u-ggsn	user plane ggsn IP address	ip	39
u-ggsn-teid	user plane ggsn teid	uint32	10
u-pkts	User Plane Packets	uint64	20
u-sgsn	user plane sgsn IP address	ip	39
u-sgsn-teid	user plane sgsn tunnel endpoint identifier	uint32	10

41222 - LOGID_GTP_USER_DATA

Message ID: 41222

Message Description: LOGID_GTP_USER_DATA

Message Meaning: GTP user data

Type: GTP

Category: GTP-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
date	Date	string	10
devid		string	16
end-usr-address	End user IP Address	ip	39
endusraddress6		ip	39
eventtime		uint64	20
from	From	ip	128
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11

Log Field Name	Description	Data Type	Length
logid	Log ID	string	10
profile	Profile Name	string	64
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	ip	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32
version	Version	uint32	64
user_data	user traffic content inside gtp-u tunnel	string	256

41223 - LOGID_GTPV2_FORWARD

Message ID: 41223

Message Description: LOGID_GTPV2_FORWARD

Message Meaning: GTPv2 forward message

Type: GTP

Category: GTP-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
date	Date	string	10
deny_cause	Deny Cause	string	25
devid		string	16
dstport	Destination Port	uint16	5
dtlexp	Detailed Explanation	string	64
end-usr-address	End user IP Address	ip	39
endusraddress6		ip	39
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
from	From	ip	128
headerteid	Tunnel Endpoint ID Header	uint32	10
ietype	Malformed GTP IE number	uint8	3
imei-sv		string	32
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
logid	Log ID	string	10
msg-type	Message Type	uint8	3
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
profile	Profile Name	string	64
rat-type	Radio Access Technology type	string	7
selection	APN selection, which is one IE in gtp packet	string	14
seqnum	GTP packet sequence number	uint32	10
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	ip	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
tz		string	5
uli		string	32
ulimcc		uint16	3
ulimnc		uint16	3
vd	Virtual Domain Name	string	32
version	Version	uint32	64
cpaddr	Control Plane Address (either downlink or uplink)	ip	39
cpteid	Control Plane teid (either downlink or uplink)	uint32	10
snetwork	Source Network, it's a IE type in GTPv2 packet	string	64

41224 - LOGID_GTPV2_DENY

Message ID: 41224

Message Description: LOGID_GTPV2_DENY

Message Meaning: GTPv2 deny message

Type: GTP

Category: GTP-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
date	Date	string	10
deny_cause	Deny Cause	string	25
devid		string	16
dstport	Destination Port	uint16	5
dtlexp	Detailed Explanation	string	64
end-usr-address	End user IP Address	ip	39
endusraddress6		ip	39
eventtime		uint64	20
from	From	ip	128
headerteid	Tunnel Endpoint ID Header	uint32	10
ietype	Malformed GTP IE number	uint8	3
imei-sv		string	32
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
logid	Log ID	string	10
msg-type	Message Type	uint8	3
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
profile	Profile Name	string	64
rat-type	Radio Access Technology type	string	7
selection	APN selection, which is one IE in gtp packet	string	14
seqnum	GTP packet sequence number	uint32	10
srcport	Source Port	uint16	5

Log Field Name	Description	Data Type	Length
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	ip	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
tz		string	5
uli		string	32
ulimcc		uint16	3
ulimnc		uint16	3
vd	Virtual Domain Name	string	32
version	Version	uint32	64
cpaddr	Control Plane Address (either downlink or uplink)	ip	39
cpteid	Control Plane teid (either downlink or uplink)	uint32	10
snetwork	Source Network, it's a IE type in GTPv2 packet	string	64

41225 - LOGID_GTPV2_RATE_LIMIT

Message ID: 41225

Message Description: LOGID_GTPV2_RATE_LIMIT

Message Meaning: GTPv2 rate limit message

Type: GTP

Category: GTP-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
date	Date	string	10
deny_cause	Deny Cause	string	25
devid		string	16
dstport	Destination Port	uint16	5
dtlexp	Detailed Explanation	string	64

Log Field Name	Description	Data Type	Length
end-usr-address	End user IP Address	ip	39
endusraddress6		ip	39
eventtime		uint64	20
from	From	ip	128
headerteid	Tunnel Endpoint ID Header	uint32	10
ietype	Malformed GTP IE number	uint8	3
imei-sv		string	32
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
logid	Log ID	string	10
msg-type	Message Type	uint8	3
msisdn	Mobile Subscriber Integrated Services Digital Network- Number (telephone # to a SIM card)	string	16
profile	Profile Name	string	64
rat-type	Radio Access Technology type	string	7
selection	APN selection, which is one IE in gtp packet	string	14
seqnum	GTP packet sequence number	uint32	10
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	ip	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
tz		string	5
uli		string	32
ulimcc		uint16	3
ulimnc		uint16	3
vd	Virtual Domain Name	string	32
version	Version	uint32	64
cpaddr	Control Plane Address (either downlink or uplink)	ip	39

Log Field Name	Description	Data Type	Length
cpteid	Control Plane teid (either downlink or uplink)	uint32	10
snetwork	Source Network, it's a IE type in GTPv2 packet	string	64

41226 - LOGID_GTPV2_STATE_INVALID

Message ID: 41226

Message Description: LOGID_GTPV2_STATE_INVALID

Message Meaning: GTPv2 state invalid message

Type: GTP

Category: GTP-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
date	Date	string	10
deny_cause	Deny Cause	string	25
devid		string	16
dstport	Destination Port	uint16	5
dtlexp	Detailed Explanation	string	64
end-usr-address	End user IP Address	ip	39
endusraddress6		ip	39
eventtime		uint64	20
from	From	ip	128
headerteid	Tunnel Endpoint ID Header	uint32	10
ietype	Malformed GTP IE number	uint8	3
imei-sv		string	32
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
logid	Log ID	string	10
msg-type	Message Type	uint8	3
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
profile	Profile Name	string	64

Log Field Name	Description	Data Type	Length
rat-type	Radio Access Technology type	string	7
selection	APN selection, which is one IE in gtp packet	string	14
seqnum	GTP packet sequence number	uint32	10
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	ip	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
tz		string	5
uli		string	32
ulimcc		uint16	3
ulimnc		uint16	3
vd	Virtual Domain Name	string	32
version	Version	uint32	64
cpaddr	Control Plane Address (either downlink or uplink)	ip	39
cpteid	Control Plane teid (either downlink or uplink)	uint32	10
snetwork	Source Network, it's a IE type in GTPv2 packet	string	64

41227 - LOGID_GTPV2_TUNNEL_LIMIT

Message ID: 41227

Message Description: LOGID_GTPV2_TUNNEL_LIMIT

Message Meaning: Tunnel limit GTP (version 2) message

Type: GTP

Category: GTP-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
date	Date	string	10

Log Field Name	Description	Data Type	Length
deny_cause	Deny Cause	string	25
devid		string	16
dstport	Destination Port	uint16	5
dtlexp	Detailed Explanation	string	64
end-usr-address	End user IP Address	ip	39
endusraddress6		ip	39
eventtime		uint64	20
from	From	ip	128
headerteid	Tunnel Endpoint ID Header	uint32	10
ietype	Malformed GTP IE number	uint8	3
imei-sv		string	32
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
logid	Log ID	string	10
msg-type	Message Type	uint8	3
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
profile	Profile Name	string	64
rat-type	Radio Access Technology type	string	7
selection	APN selection, which is one IE in gtp packet	string	14
seqnum	GTP packet sequence number	uint32	10
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	ip	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
tz		string	5
uli		string	32
ulimcc		uint16	3

Log Field Name	Description	Data Type	Length
ulimnc		uint16	3
vd	Virtual Domain Name	string	32
version	Version	uint32	64
cpaddr	Control Plane Address (either downlink or uplink)	ip	39
cpteid	Control Plane teid (either downlink or uplink)	uint32	10
snetwork	Source Network, it's a IE type in GTPv2 packet	string	64

41228 - LOGID_GTPV2_TRAFFIC_COUNT

Message ID: 41228

Message Description: LOGID_GTPV2_TRAFFIC_COUNT

Message Meaning: Statistic summary information when the GTPv2 tunnel is being torn down

Type: GTP

Category: GTP-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
date	Date	string	10
devid		string	16
end-usr-address	End user IP Address	ip	39
endusraddress6		ip	39
eventtime		uint64	20
imei-sv		string	32
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
logid	Log ID	string	10
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
profile	Profile Name	string	64
rat-type	Radio Access Technology type	string	7
selection	APN selection, which is one IE in gtp packet	string	14
status	Status	string	23

Log Field Name	Description	Data Type	Length
subtype	Log Subtype	string	20
time	Time	string	8
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
tz		string	5
uli		string	32
ulimcc		uint16	3
ulimnc		uint16	3
vd	Virtual Domain Name	string	32
version	Version	uint32	64
c-bytes	Control Plane Data Bytes	uint64	20
c-pkts	Control Plane Packets	uint64	20
duration	tunnel duration	uint32	10
u-bytes	User Plane Data Bytes	uint64	20
u-pkts	User Plane Packets	uint64	20
snetwork	Source Network, it's a IE type in GTPv2 packet	string	64
cpdladdr	Control Plane Downlink IP Address	ip	39
cpdlisraddr	Control Plane ISR Downlink IP Address	ip	39
cpdlisrteid	control plane ISR downlink tunnel endpoint identifier	uint32	10
cpdlteid	control plane downlink tunnel endpoint identifier	uint32	10
cpuladdr	control plane uplink IP address	ip	39
cpulteid	control plane uplink teid	uint32	10

41229 - LOGID_GTPU_FORWARD

Message ID: 41229

Message Description: LOGID_GTPU_FORWARD

Message Meaning: GTPU forward message

Type: GTP

Category: GTP-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
date	Date	string	10
deny_cause	Deny Cause	string	25
devid		string	16
dstport	Destination Port	uint16	5
eventtime		uint64	20
from	From	ip	128
headerteid	Tunnel Endpoint ID Header	uint32	10
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
logid	Log ID	string	10
msg-type	Message Type	uint8	3
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
profile	Profile Name	string	64
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	ip	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32
version	Version	uint32	64

41230 - LOGID_GTPU_DENY

Message ID: 41230

Message Description: LOGID_GTPU_DENY

Message Meaning: GTPU deny message

Type: GTP

Category: GTP-ALL

Severity: Information

Log Field Name	Description	Data Type	Length
apn	Access Point Name	string	128
date	Date	string	10
deny_cause	Deny Cause	string	25
devid		string	16
dstport	Destination Port	uint16	5
eventtime		uint64	20
from	From	ip	128
headerteid	Tunnel Endpoint ID Header	uint32	10
imsi	International mobile subscriber ID	string	16
level	Log Level	string	11
logid	Log ID	string	10
msg-type	Message Type	uint8	3
msisdn	Mobile Subscriber Integrated Services Digital Network-Number (telephone # to a SIM card)	string	16
profile	Profile Name	string	64
srcport	Source Port	uint16	5
status	Status	string	23
subtype	Log Subtype	string	20
time	Time	string	8
to	To	ip	512
tunnel-idx	tunnel serial number, internally assigned	uint32	10
type	Log Type	string	16
tz		string	5
vd	Virtual Domain Name	string	32
version	Version	uint32	64

IPS

16384 - LOGID_ATTCK_SIGNATURE_TCP_UDP

Message ID: 16384

Message Description: LOGID_ATTCK_SIGNATURE_TCP_UDP

Message Meaning: Attack detected by UCP/TCP signature

Type: IPS

Category: SIGNATURE

Severity: Alert

Log Field Name	Description	Data Type	Length
action	Security action performed by IPS	string	16
attack	Attack Name	string	256
attackcontext	the trigger patterns and the packetdata with base64 encoding	string	2040
attackcontextid	attack context id / total	string	10
attackid	Attack ID	uint32	10
authserver		string	32
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction		string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	IPS Event Type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname		string	256
incidentserialno	Incident serial number	uint32	10
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message for the attack	string	518

Log Field Name	Description	Data Type	Length
policyid	Policy ID	uint32	10
profile	Profile name for IPS	string	64
proto	Protocol number	uint8	3
rawdata		string	20480
rawdataid		string	10
ref	URL of the FortiGuard IPS database entry for the attack.	string	4096
service	Service name	string	80
sessionid	Session ID	uint32	10
severity	Severity of the attack	string	8
srccountry		string	64
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url		string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

16385 - LOGID_ATTCK_SIGNATURE_ICMP

Message ID: 16385

Message Description: LOGID_ATTCK_SIGNATURE_ICMP

Message Meaning: Attack detected by ICMP signature

Type: IPS**Category:** SIGNATURE**Severity:** Alert

Log Field Name	Description	Data Type	Length
action	Security action performed by IPS	string	16
attack	Attack Name	string	256
attackcontext	the trigger patterns and the packetdata with base64 encoding	string	2040
attackcontextid	attack context id / total	string	10
attackid	Attack ID	uint32	10
authserver		string	32
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction		string	8
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
eventtime		uint64	20
eventtype	IPS Event Type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
incidentserialno	Incident serial number	uint32	10
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message for the attack	string	518
policyid	Policy ID	uint32	10
profile	Profile name for IPS	string	64
proto	Protocol number	uint8	3
rawdata		string	20480

Log Field Name	Description	Data Type	Length
rawdataid		string	10
ref	URL of the FortiGuard IPS database entry for the attack.	string	4096
service	Service name	string	80
sessionid	Session ID	uint32	10
severity	Severity of the attack	string	8
srccountry		string	64
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3
icmpcode	Destination Port of the ICMP message	string	6
icmpid	Source port of the ICMP message	string	8
icmptype	The type of ICMP message	string	6

16386 - LOGID_ATTCK_SIGNATURE_OTHERS

Message ID: 16386

Message Description: LOGID_ATTCK_SIGNATURE_OTHERS

Message Meaning: Attack detected by other signature

Type: IPS

Category: SIGNATURE

Severity: Alert

Log Field Name	Description	Data Type	Length
action	Security action performed by IPS	string	16
attack	Attack Name	string	256
attackcontext	the trigger patterns and the packetdata with base64 encoding	string	2040
attackcontextid	attack context id / total	string	10
attackid	Attack ID	uint32	10
authserver		string	32
craction		uint32	10
crlevel	Client Reputation Level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
dstintf	Destination Interface	string	64
dstintfrole		string	10
dstip	Destination IP	ip	39
eventtime		uint64	20
eventtype	IPS Event Type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
incidentserialno	Incident serial number	uint32	10
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message for the attack	string	518
policyid	Policy ID	uint32	10
profile	Profile name for IPS	string	64
proto	Protocol number	uint8	3
rawdata		string	20480
rawdataid		string	10
ref	URL of the FortiGuard IPS database entry for the attack.	string	4096
service	Service name	string	80

Log Field Name	Description	Data Type	Length
sessionid	Session ID	uint32	10
severity	Severity of the attack	string	8
srccountry		string	64
srcdomain		string	255
srcintf	Source Interface	string	64
srcintfrole		string	10
srcip	Source IP	ip	39
subtype	Log Subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

16399 - LOGID_ATTACK_MALICIOUS_URL

Message ID: 16399

Message Description: LOGID_ATTACK_MALICIOUS_URL

Message Meaning: Attack detected by a malicious URL

Type: IPS

Category: MALICIOUS-URL

Severity: Alert

Log Field Name	Description	Data Type	Length
action		string	16
attack		string	256
attackcontext		string	2040
attackcontextid		string	10

Log Field Name	Description	Data Type	Length
authserver		string	32
craction		uint32	10
crlevel		string	10
crscore		uint32	10
date		string	10
devid		string	16
direction		string	8
dstintf		string	64
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
forwardedfor		string	128
hostname		string	256
level		string	11
logid		string	10
msg		string	518
policyid		uint32	10
profile		string	64
proto		uint8	3
rawdata		string	20480
rawdataid		string	10
service		string	80
sessionid		uint32	10
severity		string	8
srccountry		string	64
srcdomain		string	255
srcintf		string	64

Log Field Name	Description	Data Type	Length
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
trueclntip		ip	39
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url		string	512
user		string	256
vd		string	32
vrf		uint8	3

16400 - LOGID_ATTACK_BOTNET_WARNING

Message ID: 16400

Message Description: LOGID_ATTACK_BOTNET_WARNING

Message Meaning: Botnet C&C Communication (warning)

Type: IPS

Category: BOTNET

Severity: Warning

Log Field Name	Description	Data Type	Length
action		string	16
attack		string	256
attackcontext		string	2040
attackcontextid		string	10
attackid		uint32	10
authserver		string	32
crackon		uint32	10

Log Field Name	Description	Data Type	Length
crlevel		string	10
crscore		uint32	10
date		string	10
devid		string	16
direction		string	8
dstintf		string	64
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
forwardedfor		string	128
group		string	64
level		string	11
logid		string	10
msg		string	518
policyid		uint32	10
profile		string	64
proto		uint8	3
rawdata		string	20480
rawdataid		string	10
ref		string	4096
service		string	80
sessionid		uint32	10
severity		string	8
srccountry		string	64
srcdomain		string	255
srcintf		string	64
srcintfrole		string	10

Log Field Name	Description	Data Type	Length
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
trueclntip		ip	39
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32
vrf		uint8	3

16401 - LOGID_ATTACK_BOTNET_NOTIF

Message ID: 16401

Message Description: LOGID_ATTACK_BOTNET_NOTIF

Message Meaning: Botnet C&C Communication (notice)

Type: IPS

Category: BOTNET

Severity: Notice

Log Field Name	Description	Data Type	Length
action		string	16
attack		string	256
attackcontext		string	2040
attackcontextid		string	10
attackid		uint32	10
authserver		string	32
craction		uint32	10
crlevel		string	10
crscore		uint32	10

Log Field Name	Description	Data Type	Length
date		string	10
devid		string	16
direction		string	8
dstintf		string	64
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
forwardedfor		string	128
group		string	64
level		string	11
logid		string	10
msg		string	518
policyid		uint32	10
profile		string	64
proto		uint8	3
rawdata		string	20480
rawdataid		string	10
ref		string	4096
service		string	80
sessionid		uint32	10
severity		string	8
srccountry		string	64
srcdomain		string	255
srcintf		string	64
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5

Log Field Name	Description	Data Type	Length
subtype		string	20
time		string	8
trueclntip		ip	39
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32
vrf		uint8	3

SSH

61000 - LOG_ID_SSH_COMMAND_BLOCK

Message ID: 61000

Message Description: LOG_ID_SSH_COMMAND_BLOCK

Message Meaning: SSH shell command is blocked

Type: SSH

Category: SSH-COMMAND

Severity: Warning

Log Field Name	Description	Data Type	Length
action		string	17
channeltype		string	15
command		string	256
date		string	10
devid		string	16
direction		string	4096
dstintf		string	32
dstintfrole		string	10
dstip		ip	39

Log Field Name	Description	Data Type	Length
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
group		string	64
level		string	11
logid		string	10
login		string	128
policyid		uint32	10
profile		string	64
proto		uint8	3
sessionid		uint32	10
severity		string	8
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32

61001 - LOG_ID_SSH_COMMAND_BLOCK_ALERT

Message ID: 61001

Message Description: LOG_ID_SSH_COMMAND_BLOCK_ALERT

Message Meaning: SSH shell command is blocked

Type: SSH**Category:** SSH-COMMAND**Severity:** Alert

Log Field Name	Description	Data Type	Length
action		string	17
channeltype		string	15
command		string	256
date		string	10
devid		string	16
direction		string	4096
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
group		string	64
level		string	11
logid		string	10
login		string	128
policyid		uint32	10
profile		string	64
proto		uint8	3
sessionid		uint32	10
severity		string	8
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20

Log Field Name	Description	Data Type	Length
time		string	8
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32

61002 - LOG_ID_SSH_COMMAND_PASS

Message ID: 61002

Message Description: LOG_ID_SSH_COMMAND_PASS

Message Meaning: SSH shell command is detected

Type: SSH

Category: SSH-COMMAND

Severity: Notice

Log Field Name	Description	Data Type	Length
action		string	17
channeltype		string	15
command		string	256
date		string	10
devid		string	16
direction		string	4096
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
group		string	64

Log Field Name	Description	Data Type	Length
level		string	11
logid		string	10
login		string	128
policyid		uint32	10
profile		string	64
proto		uint8	3
sessionid		uint32	10
severity		string	8
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32

61003 - LOG_ID_SSH_COMMAND_PASS_ALERT

Message ID: 61003

Message Description: LOG_ID_SSH_COMMAND_PASS_ALERT

Message Meaning: SSH shell command is detected

Type: SSH

Category: SSH-COMMAND

Severity: Alert

Log Field Name	Description	Data Type	Length
action		string	17
channeltype		string	15
command		string	256
date		string	10
devid		string	16
direction		string	4096
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
group		string	64
level		string	11
logid		string	10
login		string	128
policyid		uint32	10
profile		string	64
proto		uint8	3
sessionid		uint32	10
severity		string	8
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
type		string	16

Log Field Name	Description	Data Type	Length
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32

61010 - LOG_ID_SSH_CHANNEL_BLOCK

Message ID: 61010

Message Description: LOG_ID_SSH_CHANNEL_BLOCK

Message Meaning: SSH channel is blocked

Type: SSH

Category: SSH-CHANNEL

Severity: Warning

Log Field Name	Description	Data Type	Length
action		string	17
channeltype		string	15
command		string	256
date		string	10
devid		string	16
direction		string	4096
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
group		string	64
level		string	11
logid		string	10

Log Field Name	Description	Data Type	Length
login		string	128
policyid		uint32	10
profile		string	64
proto		uint8	3
sessionid		uint32	10
severity		string	8
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32

61011 - LOG_ID_SSH_CHANNEL_PASS

Message ID: 61011

Message Description: LOG_ID_SSH_CHANNEL_PASS

Message Meaning: SSH channel is detected

Type: SSH

Category: SSH-CHANNEL

Severity: Notice

Log Field Name	Description	Data Type	Length
action		string	17
channeletype		string	15

Log Field Name	Description	Data Type	Length
command		string	256
date		string	10
devid		string	16
direction		string	4096
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
group		string	64
level		string	11
logid		string	10
login		string	128
policyid		uint32	10
profile		string	64
proto		uint8	3
sessionid		uint32	10
severity		string	8
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
type		string	16
tz		string	5
unauthuser		string	66

Log Field Name	Description	Data Type	Length
unauthusersource		string	66
user		string	256
vd		string	32

SSL

62000 - LOG_ID_SSL_CERT_BLACKLISTED

Message ID: 62000

Message Description: LOG_ID_SSL_CERT_BLACKLISTED

Message Meaning: Certificate blacklisted

Type: SSL

Category: SSL-ANOMALIES

Severity: Warning

Log Field Name	Description	Data Type	Length
action		string	17
cat		uint8	3
catdesc		string	64
certhash		string	40
date		string	10
devid		string	16
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
group		string	64
hostname		string	256
level		string	11

Log Field Name	Description	Data Type	Length
logid		string	10
msg		string	4096
policyid		uint32	10
profile		string	64
proto		uint8	3
reason		string	64
service		string	5
sessionid		uint32	10
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32

62001 - LOG_ID_SSL_CERT_PASS

Message ID: 62001

Message Description: LOG_ID_SSL_CERT_PASS

Message Meaning: Server certificate passed

Type: SSL

Category: SSL-ANOMALIES

Severity: Notice

Log Field Name	Description	Data Type	Length
action		string	17
cat		uint8	3
catdesc		string	64
certhash		string	40
date		string	10
devid		string	16
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
group		string	64
hostname		string	256
level		string	11
logid		string	10
msg		string	4096
policyid		uint32	10
profile		string	64
proto		uint8	3
reason		string	64
service		string	5
sessionid		uint32	10
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20

Log Field Name	Description	Data Type	Length
time		string	8
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32

62002 - LOG_ID_SSL_CERT_BLOCK

Message ID: 62002

Message Description: LOG_ID_SSL_CERT_BLOCK

Message Meaning: Server certificate blocked

Type: SSL

Category: SSL-ANOMALIES

Severity: Warning

Log Field Name	Description	Data Type	Length
action		string	17
cat		uint8	3
catdesc		string	64
certhash		string	40
date		string	10
devid		string	16
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
group		string	64

Log Field Name	Description	Data Type	Length
hostname		string	256
level		string	11
logid		string	10
msg		string	4096
policyid		uint32	10
profile		string	64
proto		uint8	3
reason		string	64
service		string	5
sessionid		uint32	10
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32

62003 - LOG_ID_SSL_EXEMPT

Message ID: 62003

Message Description: LOG_ID_SSL_EXEMPT

Message Meaning: SSL connection exempted

Type: SSL

Category: SSL-ANOMALIES

Severity: Notice

Log Field Name	Description	Data Type	Length
action		string	17
cat		uint8	3
catdesc		string	64
certhash		string	40
date		string	10
devid		string	16
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
group		string	64
hostname		string	256
level		string	11
logid		string	10
msg		string	4096
policyid		uint32	10
profile		string	64
proto		uint8	3
reason		string	64
service		string	5
sessionid		uint32	10
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20

Log Field Name	Description	Data Type	Length
time		string	8
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32

62050 - LOG_ID_SSL_HS_CERT_REQ_EXEMPT

Message ID: 62050

Message Description: LOG_ID_SSL_HS_CERT_REQ_EXEMPT

Message Meaning: Certificate request exempted

Type: SSL

Category: SSL-ANOMALIES

Severity: Notice

Log Field Name	Description	Data Type	Length
action		string	17
cat		uint8	3
catdesc		string	64
certhash		string	40
date		string	10
devid		string	16
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
group		string	64

Log Field Name	Description	Data Type	Length
hostname		string	256
level		string	11
logid		string	10
msg		string	4096
policyid		uint32	10
profile		string	64
proto		uint8	3
reason		string	64
service		string	5
sessionid		uint32	10
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32

62051 - LOG_ID_SSL_HS_CERT_REQ_BLOCK

Message ID: 62051

Message Description: LOG_ID_SSL_HS_CERT_REQ_BLOCK

Message Meaning: Certificate request blocked

Type: SSL

Category: SSL-ANOMALIES

Severity: Warning

Log Field Name	Description	Data Type	Length
action		string	17
cat		uint8	3
catdesc		string	64
certhash		string	40
date		string	10
devid		string	16
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
group		string	64
hostname		string	256
level		string	11
logid		string	10
msg		string	4096
policyid		uint32	10
profile		string	64
proto		uint8	3
reason		string	64
service		string	5
sessionid		uint32	10
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20

Log Field Name	Description	Data Type	Length
time		string	8
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32

62052 - LOG_ID_SSL_HS_UNSUPPROTED_EXEMPT

Message ID: 62052

Message Description: LOG_ID_SSL_HS_UNSUPPROTED_EXEMPT

Message Meaning: Connection is bypassed due to unsupported SSL traffic

Type: SSL

Category: SSL-ANOMALIES

Severity: Notice

Log Field Name	Description	Data Type	Length
action		string	17
cat		uint8	3
catdesc		string	64
certhash		string	40
date		string	10
devid		string	16
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
group		string	64

Log Field Name	Description	Data Type	Length
hostname		string	256
level		string	11
logid		string	10
msg		string	4096
policyid		uint32	10
profile		string	64
proto		uint8	3
reason		string	64
service		string	5
sessionid		uint32	10
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32

62053 - LOG_ID_SSL_HS_UNSUPPORTED_BLOCK

Message ID: 62053

Message Description: LOG_ID_SSL_HS_UNSUPPORTED_BLOCK

Message Meaning: Connection is blocked due to unsupported SSL traffic

Type: SSL

Category: SSL-ANOMALIES

Severity: Warning

Log Field Name	Description	Data Type	Length
action		string	17
cat		uint8	3
catdesc		string	64
certhash		string	40
date		string	10
devid		string	16
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
group		string	64
hostname		string	256
level		string	11
logid		string	10
msg		string	4096
policyid		uint32	10
profile		string	64
proto		uint8	3
reason		string	64
service		string	5
sessionid		uint32	10
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20

Log Field Name	Description	Data Type	Length
time		string	8
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32

62200 - LOG_ID_SSL_EXEMPT_ADDR

Message ID: 62200

Message Description: LOG_ID_SSL_EXEMPT_ADDR

Message Meaning: SSL connection is exempted based on address

Type: SSL

Category: SSL-EXEMPT

Severity: Notice

Log Field Name	Description	Data Type	Length
action		string	17
cat		uint8	3
catdesc		string	64
certhash		string	40
date		string	10
devid		string	16
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
group		string	64

Log Field Name	Description	Data Type	Length
hostname		string	256
level		string	11
logid		string	10
msg		string	4096
policyid		uint32	10
profile		string	64
proto		uint8	3
reason		string	64
service		string	5
sessionid		uint32	10
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32

62202 - LOG_ID_SSL_EXEMPT_FTGD_CAT

Message ID: 62202

Message Description: LOG_ID_SSL_EXEMPT_FTGD_CAT

Message Meaning: SSL connection is exempted based on FortiGuard category rating

Type: SSL

Category: SSL-EXEMPT

Severity: Notice

Log Field Name	Description	Data Type	Length
action		string	17
cat		uint8	3
catdesc		string	64
certhash		string	40
date		string	10
devid		string	16
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
fctuid		string	32
group		string	64
hostname		string	256
level		string	11
logid		string	10
msg		string	4096
policyid		uint32	10
profile		string	64
proto		uint8	3
reason		string	64
service		string	5
sessionid		uint32	10
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20

Log Field Name	Description	Data Type	Length
time		string	8
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
user		string	256
vd		string	32

Traffic

2 - LOG_ID_TRAFFIC_ALLOW

Message ID: 2

Message Description: LOG_ID_TRAFFIC_ALLOW

Message Meaning: Allowed traffic

Type: Traffic

Category: FORWARD

Severity: Notice

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
agent		string	64
ap		string	36
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16

Log Field Name	Description	Data Type	Length
apsn		string	36
authserver		string	32
centralnatid	Central NAT ID	uint32	10
channel		uint32	10
comment		string	1024
craction	Action performed by Client Reputation	uint32	10
crlevel		string	10
crscore	Client Reputation score	uint32	10
date	Date	string	10
devid	Device serial number	string	16
devtype	Device type	string	66
dstauthserver		string	32
dstcountry	Country name for the destination IP	string	64
dstdevtype		string	66
dstfamily		string	66
dstgroup		string	64
dsthwvendor		string	66
dsthwversion		string	66
dstinetsvc		string	64
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstport	Destination Port	uint16	5
dstserver		uint8	3
dstssid	Destination SSID	string	33
dstswversion		string	66
dstunauthuser		string	66

Log Field Name	Description	Data Type	Length
dstunauthusersource		string	66
dstuser		string	256
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
identifier		uint16	5
lanin	LAN incoming traffic in bytes	uint64	20
lanout	LAN outgoing traffic in bytes	uint64	20
level	Log Level	string	11
logid	Log ID	string	10
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
policyid	Firewall Policy ID	uint32	10
policyname		string	36
policytype		string	24
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
radioband		string	64
rcvdbyte	Received Bytes	uint64	20
rcvddelta		uint64	20
rcvdpkt	Received Packets	uint32	10
sentbyte	Sent Bytes	uint64	20
senddelta		uint64	20
sentpkt	Sent Packets	uint32	10
service	Name of service	string	80
sessionid	Session ID	uint32	10

Log Field Name	Description	Data Type	Length
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
shapingpolicyid		uint32	10
srccountry	Country name for Source IP	string	64
srcdomain		string	255
srcfamily		string	66
srchwvendor		string	66
srchwversion		string	66
srcinetsvc		string	64
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcserver		uint8	3
srcssid	Source SSID	string	33
srcswversion		string	66
srcuuid	UUID of the Source IP Address	string	37
sslaction		string	26
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39

Log Field Name	Description	Data Type	Length
transport	NAT Source Port	uint16	5
type	Log type	string	16
tz		string	5
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
url		string	512
user	User name	string	256
utmaction	Security action performed by UTM	string	32
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14
vrf		uint8	3
vwlid		uint32	10
vwlname		string	36
vwlquality		string	320
vwlservice		string	64
wvpvlanid		uint32	10
wanin	WAN incoming traffic in bytes	uint64	20
wanoptapptype	WAN Optimization Application type	string	9
wanout	WAN outgoing traffic in bytes	uint64	20

3 - LOG_ID_TRAFFIC_DENY

Message ID: 3

Message Description: LOG_ID_TRAFFIC_DENY

Message Meaning: Traffic violation

Type: Traffic

Category: FORWARD

Severity: Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
agent		string	64
ap		string	36
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
apsn		string	36
authserver		string	32
centralnatid	Central NAT ID	uint32	10
channel		uint32	10
comment		string	1024
craction	Action performed by Client Reputation	uint32	10
crlevel		string	10
crscore	Client Reputation score	uint32	10
date	Date	string	10
devid	Device serial number	string	16
devtype	Device type	string	66
dstauthserver		string	32
dstcountry	Country name for the destination IP	string	64
dstdevtype		string	66
dstfamily		string	66
dstgroup		string	64
dsthwvendor		string	66
dsthwversion		string	66
dstinetsvc		string	64

Log Field Name	Description	Data Type	Length
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstport	Destination Port	uint16	5
dstserver		uint8	3
dstssid	Destination SSID	string	33
dstswversion		string	66
dstunauthuser		string	66
dstunauthusersource		string	66
dstuser		string	256
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
identifier		uint16	5
lanin	LAN incoming traffic in bytes	uint64	20
lanout	LAN outgoing traffic in bytes	uint64	20
level	Log Level	string	11
logid	Log ID	string	10
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
policyid	Firewall Policy ID	uint32	10
policyname		string	36
policytype		string	24

Log Field Name	Description	Data Type	Length
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
radioband		string	64
rcvdbyte	Received Bytes	uint64	20
rcvddelta		uint64	20
rcvdpkt	Received Packets	uint32	10
sentbyte	Sent Bytes	uint64	20
sentdelta		uint64	20
sentpkt	Sent Packets	uint32	10
service	Name of service	string	80
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
shapingpolicyid		uint32	10
srccountry	Country name for Source IP	string	64
srcdomain		string	255
srcfamily		string	66
srchwvendor		string	66
srchwversion		string	66
srcinetsvc		string	64
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5

Log Field Name	Description	Data Type	Length
srcserver		uint8	3
srcssid	Source SSID	string	33
srcswversion		string	66
srcuuid	UUID of the Source IP Address	string	37
sslaction		string	26
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
tz		string	5
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
url		string	512
user	User name	string	256
utmaction	Security action performed by UTM	string	32
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14
vrf		uint8	3
vwlid		uint32	10
vwlname		string	36
vwlquality		string	320
vwlservice		string	64
vwplanid		uint32	10
wanin	WAN incoming traffic in bytes	uint64	20
wanoptapptype	WAN Optimization Application type	string	9
wanout	WAN outgoing traffic in bytes	uint64	20

4 - LOG_ID_TRAFFIC_OTHER_START

Message ID: 4

Message Description: LOG_ID_TRAFFIC_OTHER_START

Message Meaning: Traffic other session start

Type: Traffic

Category: FORWARD

Severity: Notice

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
agent		string	64
ap		string	36
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
apsn		string	36
authserver		string	32
centralnatid	Central NAT ID	uint32	10
channel		uint32	10
comment		string	1024
craction	Action performed by Client Reputation	uint32	10
crlevel		string	10
crscore	Client Reputation score	uint32	10
date	Date	string	10
devid	Device serial number	string	16
devtype	Device type	string	66
dstauthserver		string	32

Log Field Name	Description	Data Type	Length
dstcountry	Country name for the destination IP	string	64
dstdevtype		string	66
dstfamily		string	66
dstgroup		string	64
dsthwvendor		string	66
dsthwversion		string	66
dstinetsvc		string	64
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstport	Destination Port	uint16	5
dstserver		uint8	3
dstssid	Destination SSID	string	33
dstswversion		string	66
dstunauthuser		string	66
dstunauthusersource		string	66
dstuser		string	256
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
identifier		uint16	5
lanin	LAN incoming traffic in bytes	uint64	20
lanout	LAN outgoing traffic in bytes	uint64	20
level	Log Level	string	11
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
policyid	Firewall Policy ID	uint32	10
policyname		string	36
policytype		string	24
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
radioband		string	64
rcvdbyte	Received Bytes	uint64	20
rcvddelta		uint64	20
rcvdpkt	Received Packets	uint32	10
sentbyte	Sent Bytes	uint64	20
sentedelta		uint64	20
sentpkt	Sent Packets	uint32	10
service	Name of service	string	80
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
shapingpolicyid		uint32	10
srccountry	Country name for Source IP	string	64
srcdomain		string	255
srcfamily		string	66
srchwvvendor		string	66
srchwversion		string	66

Log Field Name	Description	Data Type	Length
srcinetsvc		string	64
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcserver		uint8	3
srcssid	Source SSID	string	33
srcswversion		string	66
srcuuid	UUID of the Source IP Address	string	37
sslaction		string	26
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
tz		string	5
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
url		string	512
user	User name	string	256
utmaction	Security action performed by UTM	string	32
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14
vrf		uint8	3

Log Field Name	Description	Data Type	Length
vwlid		uint32	10
vwlname		string	36
vwlquality		string	320
vwlservice		string	64
vwpvlanid		uint32	10
wanin	WAN incoming traffic in bytes	uint64	20
wanoptapptype	WAN Optimization Application type	string	9
wanout	WAN outgoing traffic in bytes	uint64	20

5 - LOG_ID_TRAFFIC_OTHER_ICMP_ALLOW

Message ID: 5

Message Description: LOG_ID_TRAFFIC_OTHER_ICMP_ALLOW

Message Meaning: Traffic allowed ICMP

Type: Traffic

Category: FORWARD

Severity: Notice

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
agent		string	64
ap		string	36
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
apsn		string	36
authserver		string	32

Log Field Name	Description	Data Type	Length
centralnatid	Central NAT ID	uint32	10
channel		uint32	10
comment		string	1024
craction	Action performed by Client Reputation	uint32	10
crlevel		string	10
crscore	Client Reputation score	uint32	10
date	Date	string	10
devid	Device serial number	string	16
devtype	Device type	string	66
dstauthserver		string	32
dstcountry	Country name for the destination IP	string	64
dstdevtype		string	66
dstfamily		string	66
dstgroup		string	64
dsthwvendor		string	66
dsthwversion		string	66
dstinetsvc		string	64
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstport	Destination Port	uint16	5
dstserver		uint8	3
dstssid	Destination SSID	string	33
dstswversion		string	66
dstunauthuser		string	66
dstunauthusersource		string	66
dstuser		string	256

Log Field Name	Description	Data Type	Length
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
identifier		uint16	5
lanin	LAN incoming traffic in bytes	uint64	20
lanout	LAN outgoing traffic in bytes	uint64	20
level	Log Level	string	11
logid	Log ID	string	10
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
policyid	Firewall Policy ID	uint32	10
polycyname		string	36
policytype		string	24
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
radioband		string	64
rcvdbyte	Received Bytes	uint64	20
rcvdelta		uint64	20
rcvdpkt	Received Packets	uint32	10
sentbyte	Sent Bytes	uint64	20
sentdelta		uint64	20
sentpkt	Sent Packets	uint32	10
service	Name of service	string	80
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10

Log Field Name	Description	Data Type	Length
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrecvname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
shapingpolicyid		uint32	10
srccountry	Country name for Source IP	string	64
srcdomain		string	255
srcfamily		string	66
srchwvvendor		string	66
srchwversion		string	66
srcinetsvc		string	64
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcserver		uint8	3
srcssid	Source SSID	string	33
srcswversion		string	66
srcuuid	UUID of the Source IP Address	string	37
sslaction		string	26
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16

Log Field Name	Description	Data Type	Length
tz		string	5
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
url		string	512
user	User name	string	256
utmaction	Security action performed by UTM	string	32
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14
vrf		uint8	3
vwlid		uint32	10
vwlname		string	36
vwlquality		string	320
vwlservice		string	64
vwpvlanid		uint32	10
wanin	WAN incoming traffic in bytes	uint64	20
wanoptapptype	WAN Optimization Application type	string	9
wanout	WAN outgoing traffic in bytes	uint64	20

6 - LOG_ID_TRAFFIC_OTHER_ICMP_DENY

Message ID: 6

Message Description: LOG_ID_TRAFFIC_OTHER_ICMP_DENY

Message Meaning: Traffic denied ICMP

Type: Traffic

Category: FORWARD

Severity: Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16

Log Field Name	Description	Data Type	Length
agent		string	64
ap		string	36
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
apsn		string	36
authserver		string	32
centralnatid	Central NAT ID	uint32	10
channel		uint32	10
comment		string	1024
craction	Action performed by Client Reputation	uint32	10
crlevel		string	10
crscore	Client Reputation score	uint32	10
date	Date	string	10
devid	Device serial number	string	16
devtype	Device type	string	66
dstauthserver		string	32
dstcountry	Country name for the destination IP	string	64
dstdevtype		string	66
dstfamily		string	66
dstgroup		string	64
dsthwvendor		string	66
dsthwversion		string	66
dstinetsvc		string	64
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39

Log Field Name	Description	Data Type	Length
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstport	Destination Port	uint16	5
dstserver		uint8	3
dstssid	Destination SSID	string	33
dstswversion		string	66
dstunauthuser		string	66
dstunauthusersource		string	66
dstuser		string	256
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
identifier		uint16	5
lanin	LAN incoming traffic in bytes	uint64	20
lanout	LAN outgoing traffic in bytes	uint64	20
level	Log Level	string	11
logid	Log ID	string	10
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
policyid	Firewall Policy ID	uint32	10
policyname		string	36
policytype		string	24
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
radioband		string	64

Log Field Name	Description	Data Type	Length
rcvdbyte	Received Bytes	uint64	20
rcvddelta		uint64	20
rcvdpkt	Received Packets	uint32	10
sentbyte	Sent Bytes	uint64	20
sentdelta		uint64	20
sentpkt	Sent Packets	uint32	10
service	Name of service	string	80
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
shapingpolicyid		uint32	10
srccountry	Country name for Source IP	string	64
srcdomain		string	255
srcfamily		string	66
srchwvendor		string	66
srchwversion		string	66
srcinetsvc		string	64
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcserver		uint8	3
srcssid	Source SSID	string	33
srcswversion		string	66

Log Field Name	Description	Data Type	Length
srcuuid	UUID of the Source IP Address	string	37
sslaction		string	26
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
tz		string	5
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
url		string	512
user	User name	string	256
utmaction	Security action performed by UTM	string	32
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14
vrf		uint8	3
vwlid		uint32	10
vwlname		string	36
vwlquality		string	320
vwlservice		string	64
vwvlanid		uint32	10
wanin	WAN incoming traffic in bytes	uint64	20
wanoptapptype	WAN Optimization Application type	string	9
wanout	WAN outgoing traffic in bytes	uint64	20

7 - LOG_ID_TRAFFIC_OTHER_INVALID

Message ID: 7

Message Description: LOG_ID_TRAFFIC_OTHER_INVALID

Message Meaning: Traffic other invalid

Type: Traffic

Category: FORWARD

Severity: Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
agent		string	64
ap		string	36
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
apsn		string	36
authserver		string	32
centralnatid	Central NAT ID	uint32	10
channel		uint32	10
comment		string	1024
craction	Action performed by Client Reputation	uint32	10
crlevel		string	10
crscore	Client Reputation score	uint32	10
date	Date	string	10
devid	Device serial number	string	16
devtype	Device type	string	66
dstauthserver		string	32
dstcountry	Country name for the destination IP	string	64
dstdevtype		string	66

Log Field Name	Description	Data Type	Length
dstfamily		string	66
dstgroup		string	64
dsthwvendor		string	66
dsthwversion		string	66
dstinetsvc		string	64
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstport	Destination Port	uint16	5
dstserver		uint8	3
dstssid	Destination SSID	string	33
dstswversion		string	66
dstunauthuser		string	66
dstunauthusersource		string	66
dstuser		string	256
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
identifier		uint16	5
lanin	LAN incoming traffic in bytes	uint64	20
lanout	LAN outgoing traffic in bytes	uint64	20
level	Log Level	string	11
logid	Log ID	string	10
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17

Log Field Name	Description	Data Type	Length
msg	Log message	string	64
osname	Name of the device's OS	string	66
policyid	Firewall Policy ID	uint32	10
policyname		string	36
policytype		string	24
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
radioband		string	64
rcvdbyte	Received Bytes	uint64	20
rcvddelta		uint64	20
rcvdpkt	Received Packets	uint32	10
sentbyte	Sent Bytes	uint64	20
sentedelta		uint64	20
sentpkt	Sent Packets	uint32	10
service	Name of service	string	80
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
shapingpolicyid		uint32	10
srccountry	Country name for Source IP	string	64
srcdomain		string	255
srcfamily		string	66
srchwvendor		string	66
srchwversion		string	66
srcinetsvc		string	64
srcintf	Source interface name	string	32

Log Field Name	Description	Data Type	Length
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcserver		uint8	3
srcssid	Source SSID	string	33
srcswversion		string	66
srcuuid	UUID of the Source IP Address	string	37
sslaction		string	26
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
tz		string	5
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
url		string	512
user	User name	string	256
utmaction	Security action performed by UTM	string	32
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14
vrf		uint8	3
vwlid		uint32	10
vwlname		string	36

Log Field Name	Description	Data Type	Length
vwquality		string	320
vwlservice		string	64
vwvlanid		uint32	10
wanin	WAN incoming traffic in bytes	uint64	20
wanoptapptype	WAN Optimization Application type	string	9
wanout	WAN outgoing traffic in bytes	uint64	20

8 - LOG_ID_TRAFFIC_WANOPT

Message ID: 8

Message Description: LOG_ID_TRAFFIC_WANOPT

Message Meaning: WAN optimization traffic

Type: Traffic

Category: FORWARD

Severity: Notice

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
agent		string	64
ap		string	36
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
apsn		string	36
authserver		string	32
centralnatid	Central NAT ID	uint32	10
channel		uint32	10

Log Field Name	Description	Data Type	Length
comment		string	1024
craction	Action performed by Client Reputation	uint32	10
crlevel		string	10
crscore	Client Reputation score	uint32	10
date	Date	string	10
devid	Device serial number	string	16
devtype	Device type	string	66
dstauthserver		string	32
dstcountry	Country name for the destination IP	string	64
dstdevtype		string	66
dstfamily		string	66
dstgroup		string	64
dsthwvendor		string	66
dsthwversion		string	66
dstinetsvc		string	64
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstport	Destination Port	uint16	5
dstserver		uint8	3
dstssid	Destination SSID	string	33
dstswversion		string	66
dstunauthuser		string	66
dstunauthusersource		string	66
dstuser		string	256
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
identifier		uint16	5
lanin	LAN incoming traffic in bytes	uint64	20
lanout	LAN outgoing traffic in bytes	uint64	20
level	Log Level	string	11
logid	Log ID	string	10
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
policyid	Firewall Policy ID	uint32	10
policyname		string	36
policytype		string	24
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
radioband		string	64
rcvdbyte	Received Bytes	uint64	20
rcvddelta		uint64	20
rcvdpkt	Received Packets	uint32	10
sentbyte	Sent Bytes	uint64	20
senddelta		uint64	20
sentpkt	Sent Packets	uint32	10
service	Name of service	string	80
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36

Log Field Name	Description	Data Type	Length
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
shapingpolicyid		uint32	10
srccountry	Country name for Source IP	string	64
srcdomain		string	255
srcfamily		string	66
srchwvendor		string	66
srchwversion		string	66
srcinetsvc		string	64
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcserver		uint8	3
srcssid	Source SSID	string	33
srcswversion		string	66
srcuuid	UUID of the Source IP Address	string	37
sslaction		string	26
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
tz		string	5
unauthuser	Unauthenticated user name	string	66

Log Field Name	Description	Data Type	Length
unauthusersource	The method used to detect unauthenticated user name	string	66
url		string	512
user	User name	string	256
utmaction	Security action performed by UTM	string	32
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14
vrf		uint8	3
vwlid		uint32	10
vwlname		string	36
vwlquality		string	320
vwlservice		string	64
vwvlanid		uint32	10
wanin	WAN incoming traffic in bytes	uint64	20
wanoptapptype	WAN Optimization Application type	string	9
wanout	WAN outgoing traffic in bytes	uint64	20
countapp	Number of App Ctrl logs associated with the session	uint32	10
countav	Number of AV logs associated with the session	uint32	10
countcifs		uint32	10
countdlp	Number of the DLP logs associated with the session	uint32	10
countdns		uint32	10
countemail	Number of the email logs associated with the session	uint32	10
countff		uint32	10
countips	Number of the IPS logs associated with the session	uint32	10
countssh		uint32	10
countssl		uint32	10
countwaf		uint32	10
countweb	Number of the Web Filter logs associated with the session	uint32	10

9 - LOG_ID_TRAFFIC_WEBCACHE

Message ID: 9

Message Description: LOG_ID_TRAFFIC_WEBCACHE**Message Meaning:** Web cache traffic**Type:** Traffic**Category:** FORWARD**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
agent		string	64
ap		string	36
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
apsn		string	36
authserver		string	32
centralnatid	Central NAT ID	uint32	10
channel		uint32	10
comment		string	1024
craction	Action performed by Client Reputation	uint32	10
crlevel		string	10
crscore	Client Reputation score	uint32	10
date	Date	string	10
devid	Device serial number	string	16
devtype	Device type	string	66
dstauthserver		string	32
dstcountry	Country name for the destination IP	string	64
dstdevtype		string	66

Log Field Name	Description	Data Type	Length
dstfamily		string	66
dstgroup		string	64
dsthwvendor		string	66
dsthwversion		string	66
dstinetsvc		string	64
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstport	Destination Port	uint16	5
dstserver		uint8	3
dstssid	Destination SSID	string	33
dstswversion		string	66
dstunauthuser		string	66
dstunauthusersource		string	66
dstuser		string	256
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
identifier		uint16	5
lanin	LAN incoming traffic in bytes	uint64	20
lanout	LAN outgoing traffic in bytes	uint64	20
level	Log Level	string	11
logid	Log ID	string	10
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17

Log Field Name	Description	Data Type	Length
msg	Log message	string	64
osname	Name of the device's OS	string	66
policyid	Firewall Policy ID	uint32	10
polycyname		string	36
policytype		string	24
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
radioband		string	64
rcvdbyte	Received Bytes	uint64	20
rcvddelta		uint64	20
rcvdpkt	Received Packets	uint32	10
sentbyte	Sent Bytes	uint64	20
sentdelta		uint64	20
sentpkt	Sent Packets	uint32	10
service	Name of service	string	80
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
shapingpolicyid		uint32	10
srccountry	Country name for Source IP	string	64
srcdomain		string	255
srcfamily		string	66
srchwvendor		string	66
srchwversion		string	66
srcinetsvc		string	64
srcintf	Source interface name	string	32

Log Field Name	Description	Data Type	Length
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcserver		uint8	3
srcssid	Source SSID	string	33
srcswversion		string	66
srcuuid	UUID of the Source IP Address	string	37
sslaction		string	26
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
tz		string	5
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
url		string	512
user	User name	string	256
utmaction	Security action performed by UTM	string	32
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14
vrf		uint8	3
vwlid		uint32	10
vwlname		string	36

Log Field Name	Description	Data Type	Length
vwlquality		string	320
vwlservice		string	64
vwpvlanid		uint32	10
wanin	WAN incoming traffic in bytes	uint64	20
wanoptapptype	WAN Optimization Application type	string	9
wanout	WAN outgoing traffic in bytes	uint64	20
countapp	Number of App Ctrl logs associated with the session	uint32	10
countav	Number of AV logs associated with the session	uint32	10
countcifs		uint32	10
countdlp	Number of the DLP logs associated with the session	uint32	10
countdns		uint32	10
countemail	Number of the email logs associated with the session	uint32	10
countff		uint32	10
countips	Number of the IPS logs associated with the session	uint32	10
countssh		uint32	10
countssl		uint32	10
countwaf		uint32	10
countweb	Number of the Web Filter logs associated with the session	uint32	10

10 - LOG_ID_TRAFFIC_EXPLICIT_PROXY

Message ID: 10

Message Description: LOG_ID_TRAFFIC_EXPLICIT_PROXY

Message Meaning: Explicit proxy traffic

Type: Traffic

Category: FORWARD

Severity: Notice

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16

Log Field Name	Description	Data Type	Length
agent		string	64
ap		string	36
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
apsn		string	36
authserver		string	32
centralnatid	Central NAT ID	uint32	10
channel		uint32	10
comment		string	1024
craction	Action performed by Client Reputation	uint32	10
crlevel		string	10
crscore	Client Reputation score	uint32	10
date	Date	string	10
devid	Device serial number	string	16
devtype	Device type	string	66
dstauthserver		string	32
dstcountry	Country name for the destination IP	string	64
dstdevtype		string	66
dstfamily		string	66
dstgroup		string	64
dsthwvendor		string	66
dsthwversion		string	66
dstinetsvc		string	64
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39

Log Field Name	Description	Data Type	Length
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstport	Destination Port	uint16	5
dstserver		uint8	3
dstssid	Destination SSID	string	33
dstswversion		string	66
dstunauthuser		string	66
dstunauthusersource		string	66
dstuser		string	256
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
identifier		uint16	5
lanin	LAN incoming traffic in bytes	uint64	20
lanout	LAN outgoing traffic in bytes	uint64	20
level	Log Level	string	11
logid	Log ID	string	10
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
policyid	Firewall Policy ID	uint32	10
policyname		string	36
policytype		string	24
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
radioband		string	64

Log Field Name	Description	Data Type	Length
rcvdbyte	Received Bytes	uint64	20
rcvddelta		uint64	20
rcvdpkt	Received Packets	uint32	10
sentbyte	Sent Bytes	uint64	20
sentdelta		uint64	20
sentpkt	Sent Packets	uint32	10
service	Name of service	string	80
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
shapingpolicyid		uint32	10
srccountry	Country name for Source IP	string	64
srcdomain		string	255
srcfamily		string	66
srchwvendor		string	66
srchwversion		string	66
srcinetsvc		string	64
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcserver		uint8	3
srcssid	Source SSID	string	33
srcswversion		string	66

Log Field Name	Description	Data Type	Length
srcuuid	UUID of the Source IP Address	string	37
sslaction		string	26
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
tz		string	5
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
url		string	512
user	User name	string	256
utmaction	Security action performed by UTM	string	32
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14
vrf		uint8	3
vwlid		uint32	10
vwlname		string	36
vwlquality		string	320
vwlservice		string	64
vwplanid		uint32	10
wanin	WAN incoming traffic in bytes	uint64	20
wanoptapptype	WAN Optimization Application type	string	9
wanout	WAN outgoing traffic in bytes	uint64	20
countapp	Number of App Ctrl logs associated with the session	uint32	10
countav	Number of AV logs associated with the session	uint32	10

Log Field Name	Description	Data Type	Length
countcifs		uint32	10
countdnp	Number of the DLP logs associated with the session	uint32	10
countdns		uint32	10
countemail	Number of the email logs associated with the session	uint32	10
countff		uint32	10
countips	Number of the IPS logs associated with the session	uint32	10
countssh		uint32	10
countssl		uint32	10
countwaf		uint32	10
countweb	Number of the Web Filter logs associated with the session	uint32	10

11 - LOG_ID_TRAFFIC_FAIL_CONN

Message ID: 11

Message Description: LOG_ID_TRAFFIC_FAIL_CONN

Message Meaning: Failed connection attempts

Type: Traffic

Category: FORWARD

Severity: Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
agent		string	64
ap		string	36
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16

Log Field Name	Description	Data Type	Length
apsn		string	36
authserver		string	32
centralnatid	Central NAT ID	uint32	10
channel		uint32	10
comment		string	1024
craction	Action performed by Client Reputation	uint32	10
crlevel		string	10
crscore	Client Reputation score	uint32	10
date	Date	string	10
devid	Device serial number	string	16
devtype	Device type	string	66
dstauthserver		string	32
dstcountry	Country name for the destination IP	string	64
dstdevtype		string	66
dstfamily		string	66
dstgroup		string	64
dsthwvendor		string	66
dsthwversion		string	66
dstinetsvc		string	64
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstport	Destination Port	uint16	5
dstserver		uint8	3
dstssid	Destination SSID	string	33
dstswversion		string	66
dstunauthuser		string	66

Log Field Name	Description	Data Type	Length
dstunauthusersource		string	66
dstuser		string	256
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
identifier		uint16	5
lanin	LAN incoming traffic in bytes	uint64	20
lanout	LAN outgoing traffic in bytes	uint64	20
level	Log Level	string	11
logid	Log ID	string	10
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
policyid	Firewall Policy ID	uint32	10
policyname		string	36
policytype		string	24
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
radioband		string	64
rcvdbyte	Received Bytes	uint64	20
rcvddelta		uint64	20
rcvdpkt	Received Packets	uint32	10
sentbyte	Sent Bytes	uint64	20
senddelta		uint64	20
sentpkt	Sent Packets	uint32	10
service	Name of service	string	80
sessionid	Session ID	uint32	10

Log Field Name	Description	Data Type	Length
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
shapingpolicyid		uint32	10
srccountry	Country name for Source IP	string	64
srcdomain		string	255
srcfamily		string	66
srchwvendor		string	66
srchwversion		string	66
srcinetsvc		string	64
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcserver		uint8	3
srcssid	Source SSID	string	33
srcswversion		string	66
srcuuid	UUID of the Source IP Address	string	37
sslaction		string	26
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39

Log Field Name	Description	Data Type	Length
transport	NAT Source Port	uint16	5
type	Log type	string	16
tz		string	5
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
url		string	512
user	User name	string	256
utmaction	Security action performed by UTM	string	32
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14
vrf		uint8	3
vwlid		uint32	10
vwlname		string	36
vwlquality		string	320
vwlservice		string	64
wvpvlanid		uint32	10
wanin	WAN incoming traffic in bytes	uint64	20
wanoptapptype	WAN Optimization Application type	string	9
wanout	WAN outgoing traffic in bytes	uint64	20

12 - LOG_ID_TRAFFIC_MULTICAST

Message ID: 12

Message Description: LOG_ID_TRAFFIC_MULTICAST

Message Meaning: Multicast traffic

Type: Traffic

Category: MULTICAST

Severity: Notice

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
agent		string	64
ap		string	36
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
apsn		string	36
authserver		string	32
centralnatid		uint32	10
channel		uint32	10
comment		string	1024
craction		uint32	10
crlevel		string	10
crscore		uint32	10
date	Date	string	10
devid	Device serial number	string	16
devtype	Device type	string	66
dstauthserver		string	32
dstcountry		string	64
dstdevtype		string	66
dstfamily		string	66
dstgroup		string	64
dsthwvendor		string	66
dsthwversion		string	66
dstinetsvc		string	64

Log Field Name	Description	Data Type	Length
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstport	Destination Port	uint16	5
dstserver		uint8	3
dstssid	Destination SSID	string	33
dstswversion		string	66
dstunauthuser		string	66
dstunauthusersource		string	66
dstuser		string	256
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
identifier		uint16	5
lanin		uint64	20
lanout		uint64	20
level	Log Level	string	11
logid	Log ID	string	10
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
policyid	Firewall Policy ID	uint32	10
policyname		string	36
policytype		string	24

Log Field Name	Description	Data Type	Length
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
radioband		string	64
rcvdbyte	Received Bytes	uint64	20
rcvddelta		uint64	20
rcvdpkt	Received Packets	uint32	10
sentbyte	Sent Bytes	uint64	20
sentsdelta		uint64	20
sentpkt	Sent Packets	uint32	10
service	Name of service	string	80
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
shapingpolicyid		uint32	10
srccountry		string	64
srcdomain		string	255
srcfamily		string	66
srchwvvendor		string	66
srchwversion		string	66
srcinetsvc		string	64
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5

Log Field Name	Description	Data Type	Length
srcserver		uint8	3
srcssid	Source SSID	string	33
srcswversion		string	66
srcuuid	UUID of the Source IP Address	string	37
sslaction		string	26
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
transport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
tz		string	5
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
url		string	512
user	User name	string	256
utmaction		string	32
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14
vrf		uint8	3
vwlid		uint32	10
vwlname		string	36
vwlquality		string	320
vwlservice		string	64
vwplanid		uint32	10
wanin		uint64	20
wanoptapptype		string	9
wanout		uint64	20

13 - LOG_ID_TRAFFIC_END_FORWARD

Message ID: 13

Message Description: LOG_ID_TRAFFIC_END_FORWARD

Message Meaning: Forward traffic

Type: Traffic

Category: FORWARD

Severity: Notice

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
agent		string	64
ap		string	36
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
apsn		string	36
authserver		string	32
centralnatid	Central NAT ID	uint32	10
channel		uint32	10
comment		string	1024
craction	Action performed by Client Reputation	uint32	10
crlevel		string	10
crscore	Client Reputation score	uint32	10
date	Date	string	10
devid	Device serial number	string	16
devtype	Device type	string	66
dstauthserver		string	32

Log Field Name	Description	Data Type	Length
dstcountry	Country name for the destination IP	string	64
dstdevtype		string	66
dstfamily		string	66
dstgroup		string	64
dsthwvendor		string	66
dsthwversion		string	66
dstinetsvc		string	64
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstport	Destination Port	uint16	5
dstserver		uint8	3
dstssid	Destination SSID	string	33
dstswversion		string	66
dstunauthuser		string	66
dstunauthusersource		string	66
dstuser		string	256
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
identifier		uint16	5
lanin	LAN incoming traffic in bytes	uint64	20
lanout	LAN outgoing traffic in bytes	uint64	20
level	Log Level	string	11
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
policyid	Firewall Policy ID	uint32	10
policyname		string	36
policytype		string	24
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
radioband		string	64
rcvdbyte	Received Bytes	uint64	20
rcvddelta		uint64	20
rcvdpkt	Received Packets	uint32	10
sentbyte	Sent Bytes	uint64	20
senddelta		uint64	20
sentpkt	Sent Packets	uint32	10
service	Name of service	string	80
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
shapingpolicyid		uint32	10
srccountry	Country name for Source IP	string	64
srcdomain		string	255
srcfamily		string	66
srchwvvendor		string	66
srchwversion		string	66

Log Field Name	Description	Data Type	Length
srcinetsvc		string	64
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcserver		uint8	3
srcssid	Source SSID	string	33
srcswversion		string	66
srcuuid	UUID of the Source IP Address	string	37
sslaction		string	26
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
tz		string	5
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
url		string	512
user	User name	string	256
utmaction	Security action performed by UTM	string	32
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14
vrf		uint8	3

Log Field Name	Description	Data Type	Length
vwlid		uint32	10
vwlname		string	36
vwlquality		string	320
vwlservice		string	64
vwpvlanid		uint32	10
wanin	WAN incoming traffic in bytes	uint64	20
wanoptapptype	WAN Optimization Application type	string	9
wanout	WAN outgoing traffic in bytes	uint64	20
countapp	Number of App Ctrl logs associated with the session	uint32	10
countav	Number of AV logs associated with the session	uint32	10
countcifs		uint32	10
countdlp	Number of the DLP logs associated with the session	uint32	10
countdns		uint32	10
countemail	Number of the email logs associated with the session	uint32	10
countff		uint32	10
countips	Number of the IPS logs associated with the session	uint32	10
countssh		uint32	10
countssl		uint32	10
countwaf		uint32	10
countweb	Number of the Web Filter logs associated with the session	uint32	10

14 - LOG_ID_TRAFFIC_END_LOCAL

Message ID: 14

Message Description: LOG_ID_TRAFFIC_END_LOCAL

Message Meaning: Local traffic

Type: Traffic

Category: LOCAL

Severity: Notice

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
agent		string	64
ap		string	36
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
apsn		string	36
authserver		string	32
centralnatid	Central NAT ID	uint32	10
channel		uint32	10
comment		string	1024
craction		uint32	10
crlevel		string	10
crscore		uint32	10
date	Date	string	10
devid	Device serial number	string	16
devtype	Device type	string	66
dstauthserver		string	32
dstcountry		string	64
dstdevtype		string	66
dstfamily		string	66
dstgroup		string	64
dsthwvendor		string	66
dsthwversion		string	66
dstinetsvc		string	64

Log Field Name	Description	Data Type	Length
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstport	Destination Port	uint16	5
dstserver		uint8	3
dstssid	Destination SSID	string	33
dstswversion		string	66
dstunauthuser		string	66
dstunauthusersource		string	66
dstuser		string	256
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
identifier		uint16	5
lanin		uint64	20
lanout		uint64	20
level	Log Level	string	11
logid	Log ID	string	10
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
policyid	Firewall Policy ID	uint32	10
policyname		string	36
policytype		string	24

Log Field Name	Description	Data Type	Length
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
radioband		string	64
rcvdbyte	Received Bytes	uint64	20
rcvddelta		uint64	20
rcvdpkt	Received Packets	uint32	10
sentbyte	Sent Bytes	uint64	20
sentsdelta		uint64	20
sentpkt	Sent Packets	uint32	10
service	Name of service	string	80
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
shapingpolicyid		uint32	10
srccountry		string	64
srcdomain		string	255
srcfamily		string	66
srchwvendor		string	66
srchwversion		string	66
srcinetsvc		string	64
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5

Log Field Name	Description	Data Type	Length
srcserver		uint8	3
srcssid	Source SSID	string	33
srcswversion		string	66
srcuuid	UUID of the Source IP Address	string	37
sslaction		string	26
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
transport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
tz		string	5
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
url		string	512
user	User name	string	256
utmaction		string	32
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14
vrf		uint8	3
vwlid		uint32	10
vwlname		string	36
vwlquality		string	320
vwlservice		string	64
vwplanid		uint32	10
wanin		uint64	20
wanoptapptype		string	9
wanout		uint64	20

15 - LOG_ID_TRAFFIC_START_FORWARD

Message ID: 15

Message Description: LOG_ID_TRAFFIC_START_FORWARD

Message Meaning: Forward traffic session start

Type: Traffic

Category: FORWARD

Severity: Notice

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
agent		string	64
ap		string	36
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
apsn		string	36
authserver		string	32
centralnatid	Central NAT ID	uint32	10
channel		uint32	10
comment		string	1024
craction	Action performed by Client Reputation	uint32	10
crlevel		string	10
crscore	Client Reputation score	uint32	10
date	Date	string	10
devid	Device serial number	string	16
devtype	Device type	string	66
dstauthserver		string	32

Log Field Name	Description	Data Type	Length
dstcountry	Country name for the destination IP	string	64
dstdevtype		string	66
dstfamily		string	66
dstgroup		string	64
dsthwvendor		string	66
dsthwversion		string	66
dstinetsvc		string	64
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstport	Destination Port	uint16	5
dstserver		uint8	3
dstssid	Destination SSID	string	33
dstswversion		string	66
dstunauthuser		string	66
dstunauthusersource		string	66
dstuser		string	256
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
identifier		uint16	5
lanin	LAN incoming traffic in bytes	uint64	20
lanout	LAN outgoing traffic in bytes	uint64	20
level	Log Level	string	11
logid	Log ID	string	10

Log Field Name	Description	Data Type	Length
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
policyid	Firewall Policy ID	uint32	10
policyname		string	36
policytype		string	24
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
radioband		string	64
rcvdbyte	Received Bytes	uint64	20
rcvddelta		uint64	20
rcvdpkt	Received Packets	uint32	10
sentbyte	Sent Bytes	uint64	20
senddelta		uint64	20
sentpkt	Sent Packets	uint32	10
service	Name of service	string	80
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
shapingpolicyid		uint32	10
srccountry	Country name for Source IP	string	64
srcdomain		string	255
srcfamily		string	66
srchwvvendor		string	66
srchwversion		string	66

Log Field Name	Description	Data Type	Length
srcinetsvc		string	64
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcserver		uint8	3
srcssid	Source SSID	string	33
srcswversion		string	66
srcuuid	UUID of the Source IP Address	string	37
sslaction		string	26
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
tz		string	5
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
url		string	512
user	User name	string	256
utmaction	Security action performed by UTM	string	32
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14
vrf		uint8	3

Log Field Name	Description	Data Type	Length
vwlid		uint32	10
vwlname		string	36
vwlquality		string	320
vwlservice		string	64
vwpvlanid		uint32	10
wanin	WAN incoming traffic in bytes	uint64	20
wanoptapptype	WAN Optimization Application type	string	9
wanout	WAN outgoing traffic in bytes	uint64	20

16 - LOG_ID_TRAFFIC_START_LOCAL

Message ID: 16

Message Description: LOG_ID_TRAFFIC_START_LOCAL

Message Meaning: Local traffic session start

Type: Traffic

Category: LOCAL

Severity: Notice

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
agent		string	64
ap		string	36
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
apsn		string	36
authserver		string	32

Log Field Name	Description	Data Type	Length
centralnatid	Central NAT ID	uint32	10
channel		uint32	10
comment		string	1024
craction		uint32	10
crlevel		string	10
crscore		uint32	10
date	Date	string	10
devid	Device serial number	string	16
devtype	Device type	string	66
dstauthserver		string	32
dstcountry		string	64
dstdevtype		string	66
dstfamily		string	66
dstgroup		string	64
dsthwvendor		string	66
dsthwversion		string	66
dstinetsvc		string	64
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstport	Destination Port	uint16	5
dstserver		uint8	3
dstssid	Destination SSID	string	33
dstswversion		string	66
dstunauthuser		string	66
dstunauthusersource		string	66
dstuser		string	256

Log Field Name	Description	Data Type	Length
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
identifier		uint16	5
lanin		uint64	20
lanout		uint64	20
level	Log Level	string	11
logid	Log ID	string	10
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
policyid	Firewall Policy ID	uint32	10
polycyname		string	36
policytype		string	24
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
radioband		string	64
rcvdbyte	Received Bytes	uint64	20
rcvdelta		uint64	20
rcvdpkt	Received Packets	uint32	10
sentbyte	Sent Bytes	uint64	20
sentdelta		uint64	20
sentpkt	Sent Packets	uint32	10
service	Name of service	string	80
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10

Log Field Name	Description	Data Type	Length
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrecvname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
shapingpolicyid		uint32	10
srccountry		string	64
srcdomain		string	255
srcfamily		string	66
srchwvvendor		string	66
srchwversion		string	66
srcinetsvc		string	64
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcserver		uint8	3
srcssid	Source SSID	string	33
srcswversion		string	66
srcuuid	UUID of the Source IP Address	string	37
sslaction		string	26
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16

Log Field Name	Description	Data Type	Length
tz		string	5
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
url		string	512
user	User name	string	256
utmaction		string	32
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14
vrf		uint8	3
vwlid		uint32	10
vwlname		string	36
vwlquality		string	320
vwlservice		string	64
vwplanid		uint32	10
wanin		uint64	20
wanoptapptype		string	9
wanout		uint64	20

17 - LOG_ID_TRAFFIC_SNIFFER

Message ID: 17

Message Description: LOG_ID_TRAFFIC_SNIFFER

Message Meaning: Sniffer traffic

Type: Traffic

Category: SNIFFER

Severity: Notice

Log Field Name	Description	Data Type	Length
action		string	16
agent		string	64
ap		string	36

Log Field Name	Description	Data Type	Length
app		string	96
appact		string	16
appcat		string	64
appid		uint32	10
applist		string	64
apprisk		string	16
apsn		string	36
authserver		string	32
centralnatid		uint32	10
channel		uint32	10
comment		string	1024
countapp		uint32	10
countav		uint32	10
countcifs		uint32	10
countdlp		uint32	10
countdns		uint32	10
countemail		uint32	10
countff		uint32	10
countips		uint32	10
countssh		uint32	10
countssl		uint32	10
countwaf		uint32	10
countweb		uint32	10
craction		uint32	10
crlevel		string	10
crscore		uint32	10
date		string	10
devid		string	16
devtype		string	66
dstauthserver		string	32

Log Field Name	Description	Data Type	Length
dstcountry		string	64
dstdevtype		string	66
dstfamily		string	66
dstgroup		string	64
dsthwvendor		string	66
dsthwversion		string	66
dstinetsvc		string	64
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstmac		string	17
dstname		string	66
dstosname		string	66
dstport		uint16	5
dstserver		uint8	3
dstssid		string	33
dstswversion		string	66
dstunauthuser		string	66
dstunauthusersource		string	66
dstuser		string	256
dstuuid		string	37
duration		uint32	10
eventtime		uint64	20
fctuid		string	32
group		string	64
identifier		uint16	5
lanin		uint64	20
lanout		uint64	20
level		string	11
logid		string	10

Log Field Name	Description	Data Type	Length
masterdstmac		string	17
mastersrcmac		string	17
msg		string	64
osname		string	66
policyid		uint32	10
policyname		string	36
policytype		string	24
poluuid		string	37
proto		uint8	3
radioband		string	64
rcvdbyte		uint64	20
rcvddelta		uint64	20
rcvdpkt		uint32	10
sentbyte		uint64	20
sentedelta		uint64	20
sentpkt		uint32	10
service		string	80
sessionid		uint32	10
shaperdroprcvdbyte		uint32	10
shaperdropsentbyte		uint32	10
shaperperipdropbyte		uint32	10
shaperperipname		string	36
shaperrcvdname		string	36
shapersentname		string	36
shapingpolicyid		uint32	10
srccountry		string	64
srcdomain		string	255
srcfamily		string	66
srchwvendor		string	66
srchwversion		string	66

Log Field Name	Description	Data Type	Length
srcinetsvc		string	64
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcmac		string	17
srcname		string	66
srcport		uint16	5
srcserver		uint8	3
srcssid		string	33
srcswversion		string	66
srcuuid		string	37
sslaction		string	26
subtype		string	20
time		string	8
trandisp		string	16
tranip		ip	39
tranport		uint16	5
transip		ip	39
transport		uint16	5
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url		string	512
user		string	256
utmaction		string	32
vd		string	32
vpn		string	32
vpntype		string	14
vrf		uint8	3

Log Field Name	Description	Data Type	Length
vwlid		uint32	10
vwlname		string	36
vwlquality		string	320
vwlservice		string	64
vwvlanid		uint32	10
wanin		uint64	20
wanoptapptype		string	9
wanout		uint64	20

19 - LOG_ID_TRAFFIC_BROADCAST

Message ID: 19

Message Description: LOG_ID_TRAFFIC_BROADCAST

Message Meaning: Broadcast traffic

Type: Traffic

Category: MULTICAST

Severity: Notice

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
agent		string	64
ap		string	36
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
apsn		string	36
authserver		string	32

Log Field Name	Description	Data Type	Length
centralnatid		uint32	10
channel		uint32	10
comment		string	1024
craction		uint32	10
crlevel		string	10
crscore		uint32	10
date	Date	string	10
devid	Device serial number	string	16
devtype	Device type	string	66
dstauthserver		string	32
dstcountry		string	64
dstdevtype		string	66
dstfamily		string	66
dstgroup		string	64
dsthwvendor		string	66
dsthwversion		string	66
dstinetsvc		string	64
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstport	Destination Port	uint16	5
dstserver		uint8	3
dstssid	Destination SSID	string	33
dstswversion		string	66
dstunauthuser		string	66
dstunauthusersource		string	66
dstuser		string	256

Log Field Name	Description	Data Type	Length
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
identifier		uint16	5
lanin		uint64	20
lanout		uint64	20
level	Log Level	string	11
logid	Log ID	string	10
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
policyid	Firewall Policy ID	uint32	10
policyname		string	36
policytype		string	24
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
radioband		string	64
rcvdbyte	Received Bytes	uint64	20
rcvdelta		uint64	20
rcvpkt	Received Packets	uint32	10
sentbyte	Sent Bytes	uint64	20
sentdelta		uint64	20
sentpkt	Sent Packets	uint32	10
service	Name of service	string	80
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10

Log Field Name	Description	Data Type	Length
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrecvname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
shapingpolicyid		uint32	10
srccountry		string	64
srcdomain		string	255
srcfamily		string	66
srchwvvendor		string	66
srchwversion		string	66
srcinetsvc		string	64
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcserver		uint8	3
srcssid	Source SSID	string	33
srcswversion		string	66
srcuuid	UUID of the Source IP Address	string	37
sslaction		string	26
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16

Log Field Name	Description	Data Type	Length
tz		string	5
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
url		string	512
user	User name	string	256
utmaction		string	32
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14
vrf		uint8	3
vwlid		uint32	10
vwlname		string	36
vwlquality		string	320
vwlservice		string	64
vwpvlanid		uint32	10
wanin		uint64	20
wanoptapptype		string	9
wanout		uint64	20

20 - LOG_ID_TRAFFIC_STAT

Message ID: 20

Message Description: LOG_ID_TRAFFIC_STAT

Message Meaning: Forward traffic statistics

Type: Traffic

Category: FORWARD

Severity: Notice

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16

Log Field Name	Description	Data Type	Length
agent		string	64
ap		string	36
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
apsn		string	36
authserver		string	32
centralnatid	Central NAT ID	uint32	10
channel		uint32	10
comment		string	1024
craction	Action performed by Client Reputation	uint32	10
crlevel		string	10
crscore	Client Reputation score	uint32	10
date	Date	string	10
devid	Device serial number	string	16
devtype	Device type	string	66
dstauthserver		string	32
dstcountry	Country name for the destination IP	string	64
dstdevtype		string	66
dstfamily		string	66
dstgroup		string	64
dsthwvendor		string	66
dsthwversion		string	66
dstinetsvc		string	64
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39

Log Field Name	Description	Data Type	Length
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstport	Destination Port	uint16	5
dstserver		uint8	3
dstssid	Destination SSID	string	33
dstswversion		string	66
dstunauthuser		string	66
dstunauthusersource		string	66
dstuser		string	256
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64
identifier		uint16	5
lanin	LAN incoming traffic in bytes	uint64	20
lanout	LAN outgoing traffic in bytes	uint64	20
level	Log Level	string	11
logid	Log ID	string	10
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
policyid	Firewall Policy ID	uint32	10
policyname		string	36
policytype		string	24
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
radioband		string	64

Log Field Name	Description	Data Type	Length
rcvdbyte	Received Bytes	uint64	20
rcvddelta		uint64	20
rcvdpkt	Received Packets	uint32	10
sentbyte	Sent Bytes	uint64	20
sentdelta		uint64	20
sentpkt	Sent Packets	uint32	10
service	Name of service	string	80
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrcvdname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
shapingpolicyid		uint32	10
srccountry	Country name for Source IP	string	64
srcdomain		string	255
srcfamily		string	66
srchwvendor		string	66
srchwversion		string	66
srcinetsvc		string	64
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcserver		uint8	3
srcssid	Source SSID	string	33
srcswversion		string	66

Log Field Name	Description	Data Type	Length
srcuuid	UUID of the Source IP Address	string	37
sslaction		string	26
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
tz		string	5
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
url		string	512
user	User name	string	256
utmaction	Security action performed by UTM	string	32
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14
vrf		uint8	3
vwlid		uint32	10
vwlname		string	36
vwlquality		string	320
vwlservice		string	64
vwvlanid		uint32	10
wanin	WAN incoming traffic in bytes	uint64	20
wanoptapptype	WAN Optimization Application type	string	9
wanout	WAN outgoing traffic in bytes	uint64	20

21 - LOG_ID_TRAFFIC_SNIFFER_STAT

Message ID: 21

Message Description: LOG_ID_TRAFFIC_SNIFFER_STAT**Message Meaning:** Sniffer traffic statistics**Type:** Traffic**Category:** SNIFFER**Severity:** Notice

Log Field Name	Description	Data Type	Length
action		string	16
agent		string	64
ap		string	36
app		string	96
appact		string	16
appcat		string	64
appid		uint32	10
applist		string	64
apprisk		string	16
apsn		string	36
authserver		string	32
centralnatid		uint32	10
channel		uint32	10
comment		string	1024
craction		uint32	10
crlevel		string	10
crscore		uint32	10
date		string	10
devid		string	16
devtype		string	66
dstauthserver		string	32
dstcountry		string	64
dstdevtype		string	66
dstfamily		string	66
dstgroup		string	64
dsthwvendor		string	66

Log Field Name	Description	Data Type	Length
dsthwversion		string	66
dstinetsvc		string	64
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstmac		string	17
dstname		string	66
dstosname		string	66
dstport		uint16	5
dstserver		uint8	3
dstssid		string	33
dstswversion		string	66
dstunauthuser		string	66
dstunauthusersource		string	66
dstuser		string	256
dstuuid		string	37
duration		uint32	10
eventtime		uint64	20
fctuid		string	32
group		string	64
identifier		uint16	5
lanin		uint64	20
lanout		uint64	20
level		string	11
logid		string	10
masterdstmac		string	17
mastersrcmac		string	17
msg		string	64
osname		string	66
policyid		uint32	10

Log Field Name	Description	Data Type	Length
polycyname		string	36
policytype		string	24
poluuid		string	37
proto		uint8	3
radioband		string	64
rcvdbyte		uint64	20
rcvddelta		uint64	20
rcvdpkt		uint32	10
sentbyte		uint64	20
sentedelta		uint64	20
sentpkt		uint32	10
service		string	80
sessionid		uint32	10
shaperdroprcvdbyte		uint32	10
shaperdropsentbyte		uint32	10
shaperperipdropbyte		uint32	10
shaperperipname		string	36
shaperrcvdname		string	36
shapersentname		string	36
shapingpolicyid		uint32	10
srccountry		string	64
srcdomain		string	255
srcfamily		string	66
srchwvendor		string	66
srchwversion		string	66
srcinetsvc		string	64
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcmac		string	17

Log Field Name	Description	Data Type	Length
srcname		string	66
srcport		uint16	5
srcserver		uint8	3
srcssid		string	33
srcswversion		string	66
srcuuid		string	37
sslaction		string	26
subtype		string	20
time		string	8
trandisp		string	16
tranip		ip	39
tranport		uint16	5
transip		ip	39
transport		uint16	5
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url		string	512
user		string	256
utmaction		string	32
vd		string	32
vpn		string	32
vpntype		string	14
vrf		uint8	3
vwlid		uint32	10
vwlname		string	36
vwlquality		string	320
vwlservice		string	64
vwpvlanid		uint32	10

Log Field Name	Description	Data Type	Length
wanin		uint64	20
wanoptapptype		string	9
wanout		uint64	20

22 - LOG_ID_TRAFFIC_UTM_CORRELATION

Message ID: 22

Message Description: LOG_ID_TRAFFIC_UTM_CORRELATION

Message Meaning: Forward traffic for UTM correlation

Type: Traffic

Category: FORWARD

Severity: Notice

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	16
agent		string	64
ap		string	36
app	Application name	string	96
appact	The security action from app control	string	16
appcat	Application category	string	64
appid	Application ID	uint32	10
applist	Application Control profile (name)	string	64
apprisk	Application Risk Level	string	16
apsn		string	36
authserver		string	32
centralnatid	Central NAT ID	uint32	10
channel		uint32	10
comment		string	1024
craction	Action performed by Client Reputation	uint32	10
crlevel		string	10

Log Field Name	Description	Data Type	Length
crscore	Client Reputation score	uint32	10
date	Date	string	10
devid	Device serial number	string	16
devtype	Device type	string	66
dstauthserver		string	32
dstcountry	Country name for the destination IP	string	64
dstdevtype		string	66
dstfamily		string	66
dstgroup		string	64
dsthwvendor		string	66
dsthwversion		string	66
dstinetsvc		string	64
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstmac		string	17
dstname	The destination name.	string	66
dstosname		string	66
dstport	Destination Port	uint16	5
dstserver		uint8	3
dstssid	Destination SSID	string	33
dstswversion		string	66
dstunauthuser		string	66
dstunauthusersource		string	66
dstuser		string	256
dstuuid	UUID of the Destination IP address	string	37
duration	Duration of the session	uint32	10
eventtime		uint64	20
fctuid		string	32
group	User group name	string	64

Log Field Name	Description	Data Type	Length
identifier		uint16	5
lanin	LAN incoming traffic in bytes	uint64	20
lanout	LAN outgoing traffic in bytes	uint64	20
level	Log Level	string	11
logid	Log ID	string	10
masterdstmac		string	17
mastersrcmac	The master MAC address for a host that has multiple network interfaces	string	17
msg	Log message	string	64
osname	Name of the device's OS	string	66
policyid	Firewall Policy ID	uint32	10
policyname		string	36
policytype		string	24
poluuid	UUID of the Firewall Policy	string	37
proto	protocol number	uint8	3
radioband		string	64
rcvdbyte	Received Bytes	uint64	20
rcvddelta		uint64	20
rcvdpkt	Received Packets	uint32	10
sentbyte	Sent Bytes	uint64	20
sentedelta		uint64	20
sentpkt	Sent Packets	uint32	10
service	Name of service	string	80
sessionid	Session ID	uint32	10
shaperdroprcvdbyte	Received bytes dropped by shaper	uint32	10
shaperdropsentbyte	Sent bytes dropped by shaper	uint32	10
shaperperipdropbyte	Dropped bytes per IP by shaper	uint32	10
shaperperipname	Traffic shaper name (per IP)	string	36
shaperrecvname	Traffic shaper name for received traffic	string	36
shapersentname	Traffic shaper name for sent traffic	string	36
shapingpolicyid		uint32	10

Log Field Name	Description	Data Type	Length
srccountry	Country name for Source IP	string	64
srcdomain		string	255
srcfamily		string	66
srchwvvendor		string	66
srchwversion		string	66
srcinetsvc		string	64
srcintf	Source interface name	string	32
srcintfrole		string	10
srcip	Source IP address	ip	39
srcmac	MAC address associated with the Source IP	string	17
srcname	Source name	string	66
srcport	Source port number	uint16	5
srcserver		uint8	3
srcssid	Source SSID	string	33
srcswversion		string	66
srcuuid	UUID of the Source IP Address	string	37
sslaction		string	26
subtype	Subtype of the traffic	string	20
time	Time	string	8
trandisp	NAT translation type	string	16
tranip	NAT destination IP	ip	39
tranport	NAT Destination Port	uint16	5
transip	NAT Source IP	ip	39
transport	NAT Source Port	uint16	5
type	Log type	string	16
tz		string	5
unauthuser	Unauthenticated user name	string	66
unauthusersource	The method used to detect unauthenticated user name	string	66
url		string	512
user	User name	string	256

Log Field Name	Description	Data Type	Length
utmaction	Security action performed by UTM	string	32
vd	Virtual domain name	string	32
vpn	The name of the VPN tunnel	string	32
vpntype	The type of the VPN tunnel	string	14
vrf		uint8	3
vwlid		uint32	10
vwlname		string	36
vwlquality		string	320
vwlservice		string	64
vwvlanid		uint32	10
wanin	WAN incoming traffic in bytes	uint64	20
wanoptapptype	WAN Optimization Application type	string	9
wanout	WAN outgoing traffic in bytes	uint64	20
countapp	Number of App Ctrl logs associated with the session	uint32	10
countav	Number of AV logs associated with the session	uint32	10
countcifs		uint32	10
countdlp	Number of the DLP logs associated with the session	uint32	10
countdns		uint32	10
countemail	Number of the email logs associated with the session	uint32	10
countff		uint32	10
countips	Number of the IPS logs associated with the session	uint32	10
countssh		uint32	10
countssl		uint32	10
countwaf		uint32	10
countweb	Number of the Web Filter logs associated with the session	uint32	10

VoIP

44032 - LOGID_EVENT_VOIP_SIP

Message ID: 44032

Message Description: LOGID_EVENT_VOIP_SIP

Message Meaning: VoIP SIP**Type:** VoIP**Category:** VOIP**Severity:** Information

Log Field Name	Description	Data Type	Length
date		string	10
time		string	8
logid		string	10
type		string	16
subtype		string	20
level		string	11
devid		string	16
vd		string	32
eventtime		uint64	20
tz		string	5
session_id		uint32	10
epoch		uint32	10
event_id		uint32	10
srcip		ip	39
src_port		uint16	5
dstip		ip	39
dst_port		uint16	5
proto		uint8	3
src_int		string	16
dst_int		string	16
policy_id		uint32	10
profile		string	64
voip_proto		string	4
kind		string	10
action		string	15
status		string	23
duration		uint32	10

Log Field Name	Description	Data Type	Length
dir		string	16
call_id		string	64
from		string	128
to		string	512

44033 - LOGID_EVENT_VOIP_SIP_BLOCK

Message ID: 44033

Message Description: LOGID_EVENT_VOIP_SIP_BLOCK

Message Meaning: VoIP SIP blocked

Type: VoIP

Category: VOIP

Severity: Notice

Log Field Name	Description	Data Type	Length
date		string	10
time		string	8
logid		string	10
type		string	16
subtype		string	20
level		string	11
devid		string	16
vd		string	32
eventtime		uint64	20
tz		string	5
session_id		uint32	10
epoch		uint32	10
event_id		uint32	10
srcip		ip	39
src_port		uint16	5
dstip		ip	39
dst_port		uint16	5

Log Field Name	Description	Data Type	Length
proto		uint8	3
src_int		string	16
dst_int		string	16
policy_id		uint32	10
profile		string	64
voip_proto		string	4
kind		string	10
action		string	15
status		string	23
duration		uint32	10
dir		string	16
call_id		string	64
from		string	128
to		string	512
reason		string	128
message_type		string	16
request_name		string	64
count		uint32	10

44034 - LOGID_EVENT_VOIP_SIP_FUZZING

Message ID: 44034

Message Description: LOGID_EVENT_VOIP_SIP_FUZZING

Message Meaning: VoIP SIP fuzzing

Type: VoIP

Category: VOIP

Severity: Information

Log Field Name	Description	Data Type	Length
date		string	10
time		string	8
logid		string	10

Log Field Name	Description	Data Type	Length
type		string	16
subtype		string	20
level		string	11
devid		string	16
vd		string	32
eventtime		uint64	20
tz		string	5
session_id		uint32	10
epoch		uint32	10
event_id		uint32	10
srcip		ip	39
src_port		uint16	5
dstip		ip	39
dst_port		uint16	5
proto		uint8	3
src_int		string	16
dst_int		string	16
policy_id		uint32	10
profile		string	64
voip_proto		string	4
kind		string	10
action		string	15
duration		uint32	10
dir		string	16
call_id		string	64
message_type		string	16
request_name		string	64
malform_desc		string	47
malform_data		uint32	10
line		string	128
column		uint32	10

44035 - LOGID_EVENT_VOIP_SCCP_REGISTER

Message ID: 44035

Message Description: LOGID_EVENT_VOIP_SCCP_REGISTER

Message Meaning: VoIP SCCP registered

Type: VoIP

Category: VOIP

Severity: Information

Log Field Name	Description	Data Type	Length
date		string	10
time		string	8
logid		string	10
type		string	16
subtype		string	20
level		string	11
devid		string	16
vd		string	32
eventtime		uint64	20
tz		string	5
session_id		uint32	10
epoch		uint32	10
event_id		uint32	10
srcip		ip	39
src_port		uint16	5
dstip		ip	39
dst_port		uint16	5
proto		uint8	3
src_int		string	16
policy_id		uint32	10
profile		string	64
voip_proto		string	4
kind		string	10

Log Field Name	Description	Data Type	Length
action		string	15
status		string	23
locip		ip	39
phone		string	64

44036 - LOGID_EVENT_VOIP_SCCP_UNREGISTER

Message ID: 44036

Message Description: LOGID_EVENT_VOIP_SCCP_UNREGISTER

Message Meaning: VoIP SCCP unregistered

Type: VoIP

Category: VOIP

Severity: Information

Log Field Name	Description	Data Type	Length
date		string	10
time		string	8
logid		string	10
type		string	16
subtype		string	20
level		string	11
devid		string	16
vd		string	32
eventtime		uint64	20
tz		string	5
session_id		uint32	10
epoch		uint32	10
event_id		uint32	10
srcip		ip	39
src_port		uint16	5
dstip		ip	39
dst_port		uint16	5

Log Field Name	Description	Data Type	Length
proto		uint8	3
src_int		string	16
policy_id		uint32	10
profile		string	64
voip_proto		string	4
kind		string	10
action		string	15
status		string	23
reason		string	128
locip		ip	39
phone		string	64

44037 - LOGID_EVENT_VOIP_SCCP_CALL_BLOCK

Message ID: 44037

Message Description: LOGID_EVENT_VOIP_SCCP_CALL_BLOCK

Message Meaning: VoIP SCCP call blocked

Type: VoIP

Category: VOIP

Severity: Information

Log Field Name	Description	Data Type	Length
date		string	10
time		string	8
logid		string	10
type		string	16
subtype		string	20
level		string	11
devid		string	16
vd		string	32
eventtime		uint64	20
tz		string	5

Log Field Name	Description	Data Type	Length
session_id		uint32	10
epoch		uint32	10
event_id		uint32	10
srcip		ip	39
src_port		uint16	5
dstip		ip	39
dst_port		uint16	5
proto		uint8	3
src_int		string	16
policy_id		uint32	10
profile		string	64
voip_proto		string	4
kind		string	10
action		string	15
status		string	23
reason		string	128
locip		ip	39
phone		string	64

44038 - LOGID_EVENT_VOIP_SCCP_CALL_INFO

Message ID: 44038

Message Description: LOGID_EVENT_VOIP_SCCP_CALL_INFO

Message Meaning: VoIP SCCP call information

Type: VoIP

Category: VOIP

Severity: Information

Log Field Name	Description	Data Type	Length
date		string	10
time		string	8
logid		string	10

Log Field Name	Description	Data Type	Length
type		string	16
subtype		string	20
level		string	11
devid		string	16
vd		string	32
eventtime		uint64	20
tz		string	5
session_id		uint32	10
epoch		uint32	10
event_id		uint32	10
srcip		ip	39
src_port		uint16	5
dstip		ip	39
dst_port		uint16	5
proto		uint8	3
src_int		string	16
dst_int		string	16
policy_id		uint32	10
profile		string	64
voip_proto		string	4
kind		string	10
action		string	15
status		string	23
duration		uint32	10
locip		ip	39
phone		string	64
locport		uint16	5
remip		ip	39
remport		uint16	5

WAF

30248 - LOGID_WAF_SIGNATURE_BLOCK

Message ID: 30248

Message Description: LOGID_WAF_SIGNATURE_BLOCK

Message Meaning: Web application firewall blocked application by signature

Type: WAF

Category: WAF-SIGNATURE

Severity: Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
agent	Agent	string	64
authserver		string	32
constraint		string	4096
date	Date	string	10
devid		string	16
direction	Direction	string	4096
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventid	Event ID	uint32	10
eventtime		uint64	20
eventtype	Event Type	string	32
fctuid		string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
method		string	4096

Log Field Name	Description	Data Type	Length
msg	Log Message	string	4096
name		string	64
policyid	Policy ID	uint32	10
profile	Full profile name	string	64
proto	Protocol	uint8	3
rawdata		string	20480
service	Service name	string	5
sessionid	Session ID	uint32	10
severity	Severity	string	6
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	URL	string	512
user	User Name	string	256
vd	Virtual Domain Name	string	32

30249 - LOGID_WAF_SIGNATURE_PASS

Message ID: 30249

Message Description: LOGID_WAF_SIGNATURE_PASS

Message Meaning: Web application firewall passed application by signature

Type: WAF

Category: WAF-SIGNATURE

Severity: Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
agent	Agent	string	64
authserver		string	32
constraint		string	4096
date	Date	string	10
devid		string	16
direction	Direction	string	4096
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventid	Event ID	uint32	10
eventtime		uint64	20
eventtype	Event Type	string	32
fctuid		string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
method		string	4096
msg	Log Message	string	4096
name		string	64
policyid	Policy ID	uint32	10
profile	Full profile name	string	64
proto	Protocol	uint8	3
rawdata		string	20480
service	Service name	string	5
sessionid	Session ID	uint32	10
severity	Severity	string	6

Log Field Name	Description	Data Type	Length
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	URL	string	512
user	User Name	string	256
vd	Virtual Domain Name	string	32

30250 - LOGID_WAF_SIGNATURE_ERASE

Message ID: 30250

Message Description: LOGID_WAF_SIGNATURE_ERASE

Message Meaning: Web application firewall erased application by signature

Type: WAF

Category: WAF-SIGNATURE

Severity: Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
agent	Agent	string	64
authserver		string	32
constraint		string	4096
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid		string	16
direction	Direction	string	4096
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventid	Event ID	uint32	10
eventtime		uint64	20
eventtype	Event Type	string	32
fctuid		string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
method		string	4096
msg	Log Message	string	4096
name		string	64
policyid	Policy ID	uint32	10
profile	Full profile name	string	64
proto	Protocol	uint8	3
rawdata		string	20480
service	Service name	string	5
sessionid	Session ID	uint32	10
severity	Severity	string	6
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	URL	string	512
user	User Name	string	256
vd	Virtual Domain Name	string	32

30251 - LOGID_WAF_CUSTOM_SIGNATURE_BLOCK

Message ID: 30251

Message Description: LOGID_WAF_CUSTOM_SIGNATURE_BLOCK

Message Meaning: Web application firewall blocked application by custom signature

Type: WAF

Category: WAF-CUSTOM-SIGNATURE

Severity: Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
agent	Agent	string	64
authserver		string	32
constraint		string	4096
date	Date	string	10
devid		string	16
direction	Direction	string	4096
dstintf	Destination Interface	string	32
dstintfrold		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventid		uint32	10

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
eventtype	Event Type	string	32
fctuid		string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
method		string	4096
msg		string	4096
name	Method or custom signature name	string	64
policyid	Policy ID	uint32	10
profile	Full profile name	string	64
proto	Protocol	uint8	3
rawdata		string	20480
service	Service name	string	5
sessionid	Session ID	uint32	10
severity	Severity	string	6
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	URL	string	512
user	User Name	string	256
vd	Virtual Domain Name	string	32

30252 - LOGID_WAF_CUSTOM_SIGNATURE_PASS

Message ID: 30252

Message Description: LOGID_WAF_CUSTOM_SIGNATURE_PASS

Message Meaning: Web application firewall allowed application by custom signature

Type: WAF

Category: WAF-CUSTOM-SIGNATURE

Severity: Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
agent	Agent	string	64
authserver		string	32
constraint		string	4096
date	Date	string	10
devid		string	16
direction	Direction	string	4096
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventid		uint32	10
eventtime		uint64	20
eventtype	Event Type	string	32
fctuid		string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
method		string	4096
msg		string	4096
name	Method or custom signature name	string	64

Log Field Name	Description	Data Type	Length
policyid	Policy ID	uint32	10
profile	Full profile name	string	64
proto	Protocol	uint8	3
rawdata		string	20480
service	Service name	string	5
sessionid	Session ID	uint32	10
severity	Severity	string	6
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	URL	string	512
user	User Name	string	256
vd	Virtual Domain Name	string	32

30253 - LOGID_WAF_METHOD_BLOCK

Message ID: 30253

Message Description: LOGID_WAF_METHOD_BLOCK

Message Meaning: Web application firewall blocked application by HTTP method

Type: WAF

Category: WAF-HTTP-METHOD

Severity: Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
agent		string	64
authserver		string	32
constraint		string	4096
date	Date	string	10
devid		string	16
direction	Direction	string	4096
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventid	Event ID	uint32	10
eventtime		uint64	20
eventtype	Event Type	string	32
fctuid		string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
method	Http Method	string	4096
msg		string	4096
name		string	64
policyid	Policy ID	uint32	10
profile	Full profile name	string	64
proto	Protocol	uint8	3
rawdata		string	20480
service	Service name	string	5
sessionid	Session ID	uint32	10
severity	Severity	string	6

Log Field Name	Description	Data Type	Length
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	URL	string	512
user	User Name	string	256
vd	Virtual Domain Name	string	32

30255 - LOGID_WAF_ADDRESS_LIST_BLOCK

Message ID: 30255

Message Description: LOGID_WAF_ADDRESS_LIST_BLOCK

Message Meaning: Web application firewall blocked application by address list

Type: WAF

Category: WAF-ADDRESS-LIST

Severity: Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
agent	Agent	string	64
authserver		string	32
constraint		string	4096
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid		string	16
direction	Direction	string	4096
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventid		uint32	10
eventtime		uint64	20
eventtype	Event Type	string	32
fctuid		string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
method		string	4096
msg		string	4096
name		string	64
policyid	Policy ID	uint32	10
profile	Full profile name	string	64
proto	Protocol	uint8	3
rawdata		string	20480
service	Service name	string	5
sessionid	Session ID	uint32	10
severity	Severity	string	6
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	URL	string	512
user	User Name	string	256
vd	Virtual Domain Name	string	32

30257 - LOGID_WAF_CONSTRAINTS_BLOCK

Message ID: 30257

Message Description: LOGID_WAF_CONSTRAINTS_BLOCK

Message Meaning: Web application firewall blocked application by HTTP constraints

Type: WAF

Category: WAF-HTTP-CONSTRAINT

Severity: Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
agent	Agent	string	64
authserver		string	32
constraint	WAF http protocol restrictions	string	4096
date	Date	string	10
devid		string	16
direction	Direction	string	4096
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventid		uint32	10

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
eventtype	Event Type	string	32
fctuid		string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
method		string	4096
msg		string	4096
name		string	64
policyid	Policy ID	uint32	10
profile	Full profile name	string	64
proto	Protocol	uint8	3
rawdata		string	20480
service	Service name	string	5
sessionid	Session ID	uint32	10
severity	Severity	string	6
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	URL	string	512
user	User Name	string	256
vd	Virtual Domain Name	string	32

30258 - LOGID_WAF_CONSTRAINTS_PASS

Message ID: 30258

Message Description: LOGID_WAF_CONSTRAINTS_PASS

Message Meaning: Web application firewall allowed application by HTTP constraints

Type: WAF

Category: WAF-HTTP-CONSTRAINT

Severity: Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
agent	Agent	string	64
authserver		string	32
constraint	WAF http protocol restrictions	string	4096
date	Date	string	10
devid		string	16
direction	Direction	string	4096
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventid		uint32	10
eventtime		uint64	20
eventtype	Event Type	string	32
fctuid		string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
method		string	4096
msg		string	4096
name		string	64

Log Field Name	Description	Data Type	Length
policyid	Policy ID	uint32	10
profile	Full profile name	string	64
proto	Protocol	uint8	3
rawdata		string	20480
service	Service name	string	5
sessionid	Session ID	uint32	10
severity	Severity	string	6
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	URL	string	512
user	User Name	string	256
vd	Virtual Domain Name	string	32

30259 - LOGID_WAF_URL_ACCESS_PERMIT

Message ID: 30259

Message Description: LOGID_WAF_URL_ACCESS_PERMIT

Message Meaning: Web application firewall allowed application by URL access permit

Type: WAF

Category: WAF-URL-ACCESS

Severity: Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
agent	Agent	string	64
authserver		string	32
constraint		string	4096
date	Date	string	10
devid		string	16
direction	Direction	string	4096
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventid	Event ID	uint32	10
eventtime		uint64	20
eventtype	Event Type	string	32
fctuid		string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
method		string	4096
msg		string	4096
name		string	64
policyid	Policy ID	uint32	10
profile	Full profile name	string	64
proto	Protocol	uint8	3
rawdata		string	20480
service	Service name	string	5
sessionid	Session ID	uint32	10
severity	Severity	string	6

Log Field Name	Description	Data Type	Length
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	URL	string	512
user	User Name	string	256
vd	Virtual Domain Name	string	32

30260 - LOGID_WAF_URL_ACCESS_BYPASS

Message ID: 30260

Message Description: LOGID_WAF_URL_ACCESS_BYPASS

Message Meaning: Web application firewall allowed application by URL access bypass

Type: WAF

Category: WAF-URL-ACCESS

Severity: Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
agent	Agent	string	64
authserver		string	32
constraint		string	4096
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid		string	16
direction	Direction	string	4096
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventid	Event ID	uint32	10
eventtime		uint64	20
eventtype	Event Type	string	32
fctuid		string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
method		string	4096
msg		string	4096
name		string	64
policyid	Policy ID	uint32	10
profile	Full profile name	string	64
proto	Protocol	uint8	3
rawdata		string	20480
service	Service name	string	5
sessionid	Session ID	uint32	10
severity	Severity	string	6
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8

Log Field Name	Description	Data Type	Length
type	Log Type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	URL	string	512
user	User Name	string	256
vd	Virtual Domain Name	string	32

30261 - LOGID_WAF_URL_ACCESS_BLOCK

Message ID: 30261

Message Description: LOGID_WAF_URL_ACCESS_BLOCK

Message Meaning: Web application firewall blocked application by URL access

Type: WAF

Category: WAF-URL-ACCESS

Severity: Warning

Log Field Name	Description	Data Type	Length
action	status of the session. Uses following definition: - Deny = blocked by firewall policy. - Start = session start log (special option to enable logging at start of a session). This means firewall allowed. - All Others = allowed by Firewall Policy and the status indicates how it was closed.	string	17
agent	Agent	string	64
authserver		string	32
constraint		string	4096
date	Date	string	10
devid		string	16
direction	Direction	string	4096
dstintf	Destination Interface	string	32
dstintfrold		string	10
dstip	Destination IP Address	ip	39
dstport	Destination Port	uint16	5
eventid	Event ID	uint32	10

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
eventtype	Event Type	string	32
fctuid		string	32
group	User Group Name	string	64
level	Log Level	string	11
logid	Log ID	string	10
method		string	4096
msg		string	4096
name		string	64
policyid	Policy ID	uint32	10
profile	Full profile name	string	64
proto	Protocol	uint8	3
rawdata		string	20480
service	Service name	string	5
sessionid	Session ID	uint32	10
severity	Severity	string	6
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP Address	ip	39
srcport	Source Port	uint16	5
subtype	Log Subtype	string	20
time	Time	string	8
type	Log Type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	URL	string	512
user	User Name	string	256
vd	Virtual Domain Name	string	32

Web

12288 - LOG_ID_WEB_CONTENT_BANWORD

Message ID: 12288

Message Description: LOG_ID_WEB_CONTENT_BANWORD

Message Meaning: Web content banned word found

Type: Web

Category: CONTENT

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
authserver		string	32
banword	Banned word	string	128
contenttype	Content Type from HTTP header	string	64
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
from	MMS-only - From/To headers from the email	string	128
group	User group name	string	64

Log Field Name	Description	Data Type	Length
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
keyword	Keyword used for search	string	512
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
to	MMS-only - From/To headers from the email	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512

Log Field Name	Description	Data Type	Length
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

12289 - LOG_ID_WEB_CONTENT_MMS_BANWORD

Message ID: 12289

Message Description: LOG_ID_WEB_CONTENT_MMS_BANWORD

Message Meaning: Web content MMS banned word found

Type: Web

Category: CONTENT

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
authserver		string	32
banword	Banned word	string	128
contenttype	Content Type from HTTP header	string	64
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrold		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32

Log Field Name	Description	Data Type	Length
forwardedfor		string	128
from	MMS-only - From/To headers from the email	string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
keyword	Keyword used for search	string	512
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
to	MMS-only - From/To headers from the email	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5

Log Field Name	Description	Data Type	Length
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

12290 - LOG_ID_WEB_CONTENT_EXEMPTWORD

Message ID: 12290

Message Description: LOG_ID_WEB_CONTENT_EXEMPTWORD

Message Meaning: Web content exempt word found

Type: Web

Category: CONTENT

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
authserver		string	32
banword	Banned word	string	128
contenttype	Content Type from HTTP header	string	64
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
from	MMS-only - From/To headers from the email	string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
keyword	Keyword used for search	string	512
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
to	MMS-only - From/To headers from the email	string	512

Log Field Name	Description	Data Type	Length
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

12291 - LOG_ID_WEB_CONTENT_MMS_EXEMPTWORD

Message ID: 12291

Message Description: LOG_ID_WEB_CONTENT_MMS_EXEMPTWORD

Message Meaning: Web content MMS exempt word found

Type: Web

Category: CONTENT

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
authserver		string	32
banword	Banned word	string	128
contenttype	Content Type from HTTP header	string	64
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32

Log Field Name	Description	Data Type	Length
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
from	MMS-only - From/To headers from the email	string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
keyword	Keyword used for search	string	512
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5

Log Field Name	Description	Data Type	Length
subtype	Log subtype	string	20
time	Time	string	8
to	MMS-only - From/To headers from the email	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

12292 - LOG_ID_WEB_CONTENT_KEYWORD

Message ID: 12292

Message Description: LOG_ID_WEB_CONTENT_KEYWORD

Message Meaning: Message contained a key word in the profile list

Type: Web

Category: CONTENT

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
authserver		string	32
banword	Banned word	string	128
contenttype	Content Type from HTTP header	string	64
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
from	MMS-only - From/To headers from the email	string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
keyword	Keyword used for search	string	512
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32

Log Field Name	Description	Data Type	Length
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
to	MMS-only - From/To headers from the email	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

12293 - LOG_ID_WEB_CONTENT_SEARCH

Message ID: 12293

Message Description: LOG_ID_WEB_CONTENT_SEARCH

Message Meaning: Search phrase detected

Type: Web

Category: CONTENT

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
authserver		string	32
banword	Banned word	string	128
contenttype	Content Type from HTTP header	string	64
crackon		uint32	10

Log Field Name	Description	Data Type	Length
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
from	MMS-only - From/To headers from the email	string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
keyword	Keyword used for search	string	512
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36

Log Field Name	Description	Data Type	Length
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
to	MMS-only - From/To headers from the email	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

12305 - LOG_ID_WEB_CONTENT_MMS_BANWORD_NOTIF

Message ID: 12305

Message Description: LOG_ID_WEB_CONTENT_MMS_BANWORD_NOTIF

Message Meaning: Web content MMS banned word

Type: Web

Category: CONTENT

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
authserver		string	32

Log Field Name	Description	Data Type	Length
banword	Banned word	string	128
contenttype	Content Type from HTTP header	string	64
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
from	MMS-only - From/To headers from the email	string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
keyword	Keyword used for search	string	512
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512

Log Field Name	Description	Data Type	Length
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
to	MMS-only - From/To headers from the email	string	512
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

12544 - LOG_ID_URL_FILTER_BLOCK

Message ID: 12544

Message Description: LOG_ID_URL_FILTER_BLOCK

Message Meaning: URL address was blocked because it was found in the URL filter list

Type: Web

Category: URLFILTER

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
authserver		string	32
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20

Log Field Name	Description	Data Type	Length
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
urlfilteridx	URL filter ID	uint32	10
urlfilterlist	URL filter list	string	64
urlsource		string	64
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

12545 - LOG_ID_URL_FILTER_EXEMPT

Message ID: 12545

Message Description: LOG_ID_URL_FILTER_EXEMPT

Message Meaning: URL address was exempted because it was found in the URL filter list

Type: Web

Category: URLFILTER

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
authserver		string	32
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20

Log Field Name	Description	Data Type	Length
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
urlfilteridx	URL filter ID	uint32	10
urlfilterlist	URL filter list	string	64
urlsource		string	64
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

12546 - LOG_ID_URL_FILTER_ALLOW

Message ID: 12546

Message Description: LOG_ID_URL_FILTER_ALLOW

Message Meaning: URL address was allowed because it was found in the URL filter list

Type: Web

Category: URLFILTER

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
authserver		string	32
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20

Log Field Name	Description	Data Type	Length
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
urlfilteridx	URL filter ID	uint32	10
urlfilterlist	URL filter list	string	64
urlsource		string	64
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

12547 - LOG_ID_URL_FILTER_INVALID_HOSTNAME_HTTP_BLK

Message ID: 12547

Message Description: LOG_ID_URL_FILTER_INVALID_HOSTNAME_HTTP_BLK

Message Meaning: The request contained an invalid domain name

Type: Web

Category: URLFILTER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
authserver		string	32
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10

Log Field Name	Description	Data Type	Length
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

12548 - LOG_ID_URL_FILTER_INVALID_HOSTNAME_HTTPS_BLK

Message ID: 12548

Message Description: LOG_ID_URL_FILTER_INVALID_HOSTNAME_HTTPS_BLK

Message Meaning: HTTP certificate request contained an invalid domain name

Type: Web

Category: URLFILTER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
authserver		string	32
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5

Log Field Name	Description	Data Type	Length
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

12549 - LOG_ID_URL_FILTER_INVALID_HOSTNAME_HTTP_PASS

Message ID: 12549

Message Description: LOG_ID_URL_FILTER_INVALID_HOSTNAME_HTTP_PASS

Message Meaning: HTTP request contained an invalid name so the session has been filtered by IP only

Type: Web

Category: URLFILTER

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
authserver		string	32
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10

Log Field Name	Description	Data Type	Length
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5

Log Field Name	Description	Data Type	Length
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

12550 - LOG_ID_URL_FILTER_INVALID_HOSTNAME_HTTPS_PASS

Message ID: 12550

Message Description: LOG_ID_URL_FILTER_INVALID_HOSTNAME_HTTPS_PASS

Message Meaning: HTTPS request contained an invalid name so the session has been filtered by IP only

Type: Web

Category: URLFILTER

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
authserver		string	32
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32

Log Field Name	Description	Data Type	Length
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

12551 - LOG_ID_URL_FILTER_INVALID_HOSTNAME_SNI_BLK

Message ID: 12551

Message Description: LOG_ID_URL_FILTER_INVALID_HOSTNAME_SNI_BLK

Message Meaning: Insufficient resources

Type: Web

Category: URLFILTER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
authserver		string	32
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64

Log Field Name	Description	Data Type	Length
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

12552 - LOG_ID_URL_FILTER_INVALID_HOSTNAME_SNI_PASS

Message ID: 12552

Message Description: LOG_ID_URL_FILTER_INVALID_HOSTNAME_SNI_PASS

Message Meaning: Getting the host name failed

Type: Web

Category: URLFILTER

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
authserver		string	32
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10

Log Field Name	Description	Data Type	Length
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

12553 - LOG_ID_URL_FILTER_INVALID_CERT

Message ID: 12553

Message Description: LOG_ID_URL_FILTER_INVALID_CERT

Message Meaning: Server certificate validation failed

Type: Web

Category: URLFILTER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
authserver		string	32
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5

Log Field Name	Description	Data Type	Length
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

12554 - LOG_ID_URL_FILTER_INVALID_SESSION

Message ID: 12554

Message Description: LOG_ID_URL_FILTER_INVALID_SESSION

Message Meaning: SSL session blocked because its identification number was unknown

Type: Web

Category: URLFILTER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
authserver		string	32
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10

Log Field Name	Description	Data Type	Length
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5

Log Field Name	Description	Data Type	Length
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

12555 - LOG_ID_URL_FILTER_SRV_CERT_ERR_BLK

Message ID: 12555

Message Description: LOG_ID_URL_FILTER_SRV_CERT_ERR_BLK

Message Meaning: SSL session blocked

Type: Web

Category: URLFILTER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
authserver		string	32
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32

Log Field Name	Description	Data Type	Length
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

12556 - LOG_ID_URL_FILTER_SRV_CERT_ERR_PASS

Message ID: 12556

Message Description: LOG_ID_URL_FILTER_SRV_CERT_ERR_PASS

Message Meaning: SSL session ignored

Type: Web

Category: URLFILTER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
authserver		string	32
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64

Log Field Name	Description	Data Type	Length
rawdata		string	20480
rcvbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

12557 - LOG_ID_URL_FILTER_FAMS_NOT_ACTIVE

Message ID: 12557

Message Description: LOG_ID_URL_FILTER_FAMS_NOT_ACTIVE

Message Meaning: The FortiGuard Analysis and Management Service is not active. You must enable this service

Type: Web

Category: URLFILTER

Severity: Critical

Log Field Name	Description	Data Type	Length
date	Date	string	10
devid		string	16
eventtime		uint64	20
eventtype	Web Filter event type	string	32
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
tz		string	5
vd	Virtual domain name	string	32

12558 - LOG_ID_URL_FILTER_RATING_ERR

Message ID: 12558

Message Description: LOG_ID_URL_FILTER_RATING_ERR

Message Meaning: Rating error occurred

Type: Web

Category: URLFILTER

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
eventtype	Web Filter event type	string	32
fctuid		string	32
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
srcdomain		string	255
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
error	URL rating error message	string	256
urltype	URL filter type	string	8

12559 - LOG_ID_URL_FILTER_PASS

Message ID: 12559

Message Description: LOG_ID_URL_FILTER_PASS

Message Meaning: URL passed because it was in the URL filter list

Type: Web

Category: URLFILTER

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11

Log Field Name	Description	Data Type	Length
authserver		string	32
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rawdata		string	20480
rcvbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36

Log Field Name	Description	Data Type	Length
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
urlfilteridx	URL filter ID	uint32	10
urlfilterlist	URL filter list	string	64
urlsource		string	64
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

12560 - LOG_ID_URL_WISP_BLOCK

Message ID: 12560

Message Description: LOG_ID_URL_WISP_BLOCK

Message Meaning: URL blocked by Websense service

Type: Web

Category: URLFILTER

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11

Log Field Name	Description	Data Type	Length
authserver		string	32
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255

Log Field Name	Description	Data Type	Length
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

12561 - LOG_ID_URL_WISP_REDIR

Message ID: 12561

Message Description: LOG_ID_URL_WISP_REDIR

Message Meaning: URL blocked with redirect message by Websense service

Type: Web

Category: URLFILTER

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
authserver		string	32
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

12562 - LOG_ID_URL_WISP_ALLOW

Message ID: 12562

Message Description: LOG_ID_URL_WISP_ALLOW

Message Meaning: URL allowed by Websense service

Type: Web

Category: URLFILTER

Severity: Information

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
authserver		string	32
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39

Log Field Name	Description	Data Type	Length
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66

Log Field Name	Description	Data Type	Length
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

12688 - LOG_ID_WEB_SSL_EXEMPT

Message ID: 12688

Message Description: LOG_ID_WEB_SSL_EXEMPT

Message Meaning: URL address was exempted because it was found in the ssl-exempt

Type: Web

Category: SSL-EXEMPT

Severity: Information

Log Field Name	Description	Data Type	Length
action		string	11
authserver		string	32
cat		uint8	3
catdesc		string	64
craction		uint32	10
crlevel		string	10
crscore		uint32	10
date		string	10
devid		string	16
direction		string	8
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32

Log Field Name	Description	Data Type	Length
fctuid		string	32
forwardedfor		string	128
group		string	64
hostname		string	256
initiator		string	64
level		string	11
logid		string	10
method		string	6
msg		string	512
policyid		uint32	10
profile		string	64
proto		uint8	3
quotamax		uint64	20
quotatype		string	16
quotaused		uint64	20
rawdata		string	20480
rcvdbyte		uint64	20
referralurl		string	512
reqtype		string	8
sentbyte		uint64	20
service		string	36
sessionid		uint32	10
srcdomain		string	255
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
trueclntip		ip	39

Log Field Name	Description	Data Type	Length
type		string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url		string	512
urlsource		string	64
user		string	256
vd		string	32
vrf		uint8	3

12800 - LOG_ID_WEB_FTGD_ERR

Message ID: 12800

Message Description: LOG_ID_WEB_FTGD_ERR

Message Meaning: Rating error occurred (error)

Type: Web

Category: FTGD_ERR

Severity: Error

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
authserver		string	32
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5

Log Field Name	Description	Data Type	Length
error	URL rating error message	string	256
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16

Log Field Name	Description	Data Type	Length
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

12801 - LOG_ID_WEB_FTGD_WARNING

Message ID: 12801

Message Description: LOG_ID_WEB_FTGD_WARNING

Message Meaning: Rating error occurred (warning)

Type: Web

Category: FTGD_ERR

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
authserver		string	32
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
error	URL rating error message	string	256
eventtime		uint64	20

Log Field Name	Description	Data Type	Length
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66

Log Field Name	Description	Data Type	Length
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

12802 - LOG_ID_WEB_FTGD_QUOTA

Message ID: 12802

Message Description: LOG_ID_WEB_FTGD_QUOTA

Message Meaning: Daily FortiGuard quota status

Type: Web

Category: FTGD_QUOTA

Severity: Information

Log Field Name	Description	Data Type	Length
catdesc	Web category description	string	64
date	Date	string	10
devid		string	16
eventtime		uint64	20
eventtype	Web Filter event type	string	32
level	Log Level	string	11
logid	Log ID	string	10
profile	Web Filter profile name	string	64
quotaexceeded	Quota has been exceeded	string	3
quotamax	Maximum quota allowed - in seconds if time-based - in bytes if traffic-based	uint64	20
quotatype	Quota type	string	16
quotaused	Quota used - in seconds if time-based - in bytes if traffic-based).	uint64	20
subtype	Log subtype	string	20
time	Time	string	8
type	Log type	string	16

Log Field Name	Description	Data Type	Length
tz		string	5
user	User name	string	256
vd	Virtual domain name	string	32

13056 - LOG_ID_WEB_FTGD_CAT_BLK

Message ID: 13056

Message Description: LOG_ID_WEB_FTGD_CAT_BLK

Message Meaning: URL belongs to an blocked category within the firewall policy

Type: Web

Category: FTGD_BLK

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
authserver		string	32
cat	Web category ID	uint8	3
catdesc	Web category description	string	64
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128

Log Field Name	Description	Data Type	Length
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
method	Rating override method by URL domain name or IP address.	string	6
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
quotamax		uint64	20
quotatype		string	16
quotaused		uint64	20
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5

Log Field Name	Description	Data Type	Length
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
urlsource		string	64
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

13057 - LOG_ID_WEB_FTGD_CAT_WARN

Message ID: 13057

Message Description: LOG_ID_WEB_FTGD_CAT_WARN

Message Meaning: URL belongs to a category with warnings enabled

Type: Web

Category: FTGD_BLK

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
authserver		string	32
cat	Web category ID	uint8	3
catdesc	Web category description	string	64
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
method	Rating override method by URL domain name or IP address.	string	6
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
quotamax		uint64	20
quotatype		string	16
quotaused		uint64	20
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20

Log Field Name	Description	Data Type	Length
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
urlsource		string	64
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

13312 - LOG_ID_WEB_FTGD_CAT_ALLOW

Message ID: 13312

Message Description: LOG_ID_WEB_FTGD_CAT_ALLOW

Message Meaning: URL belongs to an allowed category within the firewall policy

Type: Web

Category: FTGD_ALLOW

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
authserver		string	32
cat	Web category ID	uint8	3
catdesc	Web category description	string	64
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8

Log Field Name	Description	Data Type	Length
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
method	Rating override method by URL domain name or IP address.	string	6
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
quotamax		uint64	20
quotatype		string	16
quotaused		uint64	20
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32

Log Field Name	Description	Data Type	Length
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
urlsource		string	64
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

13315 - LOG_ID_WEB_FTGD_QUOTA_COUNTING

Message ID: 13315

Message Description: LOG_ID_WEB_FTGD_QUOTA_COUNTING

Message Meaning: FortiGuard web filter category quota counting log message

Type: Web

Category: FTGD_QUOTA_COUNTING

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
authserver		string	32
cat	Web category ID	uint8	3
catdesc	Web category description	string	64
craction		uint32	10
crlevel	Client Reputation level	string	10

Log Field Name	Description	Data Type	Length
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
method	Rating override method by URL domain name or IP address.	string	6
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
quotamax	Maximum quota allowed - in seconds if time-based - in bytes if traffic-based	uint64	20
quotatype	Quota type	string	16
quotaused	Quota used - in seconds if time-based - in bytes if traffic-based).	uint64	20
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8

Log Field Name	Description	Data Type	Length
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
urlsource		string	64
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

13316 - LOG_ID_WEB_FTGD_QUOTA_EXPIRED

Message ID: 13316

Message Description: LOG_ID_WEB_FTGD_QUOTA_EXPIRED

Message Meaning: FortiGuard web filter category quota expired log message

Type: Web

Category: URLFILTER

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11

Log Field Name	Description	Data Type	Length
authserver		string	32
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rawdata		string	20480
rcvbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36

Log Field Name	Description	Data Type	Length
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
urlsource		string	64
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3
cat	Web category ID	uint8	3
catdesc	Web category description	string	64
method	Rating override method by URL domain name or IP address.	string	6
quotamax	Maximum quota allowed - in seconds if time-based - in bytes if traffic-based	uint64	20
quotatype	Quota type	string	16
quotaused	Quota used - in seconds if time-based - in bytes if traffic-based).	uint64	20

13317 - LOG_ID_WEB_URL

Message ID: 13317

Message Description: LOG_ID_WEB_URL

Message Meaning: URL has been visited

Type: Web

Category: URLFILTER**Severity:** Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
authserver		string	32
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8

Log Field Name	Description	Data Type	Length
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
urlsource		string	64
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3
cat	Web category ID	uint8	3
catdesc	Web category description	string	64
method	Rating override method by URL domain name or IP address.	string	6
quotamax	Maximum quota allowed - in seconds if time-based - in bytes if traffic-based	uint64	20
quotatype	Quota type	string	16
quotaused	Quota used - in seconds if time-based - in bytes if traffic-based).	uint64	20

13568 - LOG_ID_WEB_SCRIPTFILTER_ACTIVEX

Message ID: 13568

Message Description: LOG_ID_WEB_SCRIPTFILTER_ACTIVEX

Message Meaning: ActiveX script removed

Type: Web

Category: ACTIVEXFILTER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
authserver		string	32
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
filtertype		string	10
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rawdata		string	20480

Log Field Name	Description	Data Type	Length
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

13573 - LOG_ID_WEB_SCRIPTFILTER_COOKIE

Message ID: 13573

Message Description: LOG_ID_WEB_SCRIPTFILTER_COOKIE

Message Meaning: Cookie removed

Type: Web

Category: COOKIEFILTER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
authserver		string	32
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
filtertype	The script filter type	string	10
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8

Log Field Name	Description	Data Type	Length
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

13584 - LOG_ID_WEB_SCRIPTFILTER_APPLET

Message ID: 13584

Message Description: LOG_ID_WEB_SCRIPTFILTER_APPLET

Message Meaning: Java applet removed

Type: Web

Category: APPLETFILTER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
authserver		string	32

Log Field Name	Description	Data Type	Length
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
filtertype		string	10
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36

Log Field Name	Description	Data Type	Length
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

13600 - LOG_ID_WEB_SCRIPTFILTER_OTHER

Message ID: 13600

Message Description: LOG_ID_WEB_SCRIPTFILTER_OTHER

Message Meaning: Script entity removed

Type: Web

Category: SCRIPTFILTER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
authserver		string	32
craction		uint32	10
crlevel	Client Reputation level	string	10

Log Field Name	Description	Data Type	Length
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
filtertype	The script filter type	string	10
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255

Log Field Name	Description	Data Type	Length
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

13601 - LOG_ID_WEB_WF_COOKIE

Message ID: 13601

Message Description: LOG_ID_WEB_WF_COOKIE

Message Meaning: Cookie removed entirely

Type: Web

Category: COOKIEFILTER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
authserver		string	32
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10

Log Field Name	Description	Data Type	Length
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
filtertype	The script filter type	string	10
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10

Log Field Name	Description	Data Type	Length
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

13602 - LOG_ID_WEB_WF_REFERER

Message ID: 13602

Message Description: LOG_ID_WEB_WF_REFERER

Message Meaning: Referrer removed from request

Type: Web

Category: COOKIEFILTER

Severity: Notice

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
authserver		string	32
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8

Log Field Name	Description	Data Type	Length
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
filtertype	The script filter type	string	10
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5

Log Field Name	Description	Data Type	Length
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

13603 - LOG_ID_WEB_WF_COMMAND_BLOCK

Message ID: 13603

Message Description: LOG_ID_WEB_WF_COMMAND_BLOCK

Message Meaning: Command blocked

Type: Web

Category: WEBFILTER_COMMAND_BLOCK

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
authserver		string	32
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction		string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10

Log Field Name	Description	Data Type	Length
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
rawdata		string	20480
rcvdbyte		uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte		uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
trueclntip		ip	39
type	Log type	string	16
tz		string	5

Log Field Name	Description	Data Type	Length
unauthuser		string	66
unauthusersource		string	66
url		string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

13616 - LOG_ID_CONTENT_TYPE_BLOCK

Message ID: 13616

Message Description: LOG_ID_CONTENT_TYPE_BLOCK

Message Meaning: Blocked by HTTP header content type

Type: Web

Category: CONTENT

Severity: Warning

Log Field Name	Description	Data Type	Length
action	Security action performed by WF	string	11
agent	User agent - eg. agent="Mozilla/5.0"	string	64
authserver		string	32
banword	Banned word	string	128
contenttype	Content Type from HTTP header	string	64
craction		uint32	10
crlevel	Client Reputation level	string	10
crscore	Client Reputation Score	uint32	10
date	Date	string	10
devid		string	16
direction	Direction of the web traffic	string	8
dstintf	Destination Interface	string	32
dstintfrole		string	10
dstip	Destination IP	ip	39
dstport	Destination Port	uint16	5

Log Field Name	Description	Data Type	Length
eventtime		uint64	20
eventtype	Web Filter event type	string	32
fctuid		string	32
forwardedfor		string	128
from	MMS-only - From/To headers from the email	string	128
group	User group name	string	64
hostname	The host name of a URL	string	256
initiator	The initiator user for override	string	64
keyword	Keyword used for search	string	512
level	Log Level	string	11
logid	Log ID	string	10
msg	Log message	string	512
policyid	Policy ID	uint32	10
profile	Web Filter profile name	string	64
proto	Protocol number	uint8	3
rawdata		string	20480
rcvdbyte	Received Bytes	uint64	20
referralurl		string	512
reqtype	Request type	string	8
sentbyte	Sent Bytes	uint64	20
service	Service name	string	36
sessionid	Session ID	uint32	10
srcdomain		string	255
srcintf	Source Interface	string	32
srcintfrole		string	10
srcip	Source IP	ip	39
srcport	Source Port	uint16	5
subtype	Log subtype	string	20
time	Time	string	8
to	MMS-only - From/To headers from the email	string	512

Log Field Name	Description	Data Type	Length
trueclntip		ip	39
type	Log type	string	16
tz		string	5
unauthuser		string	66
unauthusersource		string	66
url	The URL address	string	512
user	User name	string	256
vd	Virtual domain name	string	32
vrf		uint8	3

13632 - LOGID_HTTP_HDR_CHG_REQ

Message ID: 13632

Message Description: LOGID_HTTP_HDR_CHG_REQ

Message Meaning: Depends on info in msg field

Type: Web

Category: HTTP_HEADER_CHANGE

Severity: Information

Log Field Name	Description	Data Type	Length
agent		string	64
authserver		string	32
chgheaders		string	20480
date		string	10
devid		string	16
dstintf		string	32
dstintfrold		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
group		string	64

Log Field Name	Description	Data Type	Length
level		string	11
logid		string	10
policyid		uint32	10
profile		string	64
proto		uint8	3
service		string	36
sessionid		uint32	10
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
transid		uint32	10
type		string	16
tz		string	5
url		string	512
user		string	256
vd		string	32

13633 - LOGID_HTTP_HDR_CHG_RESP

Message ID: 13633

Message Description: LOGID_HTTP_HDR_CHG_RESP

Message Meaning: Depends on info in msg field

Type: Web

Category: HTTP_HEADER_CHANGE

Severity: Information

Log Field Name	Description	Data Type	Length
agent		string	64
authserver		string	32

Log Field Name	Description	Data Type	Length
chgheaders		string	20480
date		string	10
devid		string	16
dstintf		string	32
dstintfrole		string	10
dstip		ip	39
dstport		uint16	5
eventtime		uint64	20
eventtype		string	32
group		string	64
level		string	11
logid		string	10
policyid		uint32	10
profile		string	64
proto		uint8	3
service		string	36
sessionid		uint32	10
srcintf		string	32
srcintfrole		string	10
srcip		ip	39
srcport		uint16	5
subtype		string	20
time		string	8
transid		uint32	10
type		string	16
tz		string	5
url		string	512
user		string	256
vd		string	32



FORTINET®



Copyright© 2023 Fortinet, Inc. All rights reserved. Fortinet®, FortiGate®, FortiCare® and FortiGuard®, and certain other marks are registered trademarks of Fortinet, Inc., in the U.S. and other jurisdictions, and other Fortinet names herein may also be registered and/or common law trademarks of Fortinet. All other product or company names may be trademarks of their respective owners. Performance and other metrics contained herein were attained in internal lab tests under ideal conditions, and actual performance and other results may vary. Network variables, different network environments and other conditions may affect performance results. Nothing herein represents any binding commitment by Fortinet, and Fortinet disclaims all warranties, whether express or implied, except to the extent Fortinet enters a binding written contract, signed by Fortinet's General Counsel, with a purchaser that expressly warrants that the identified product will perform according to certain expressly-identified performance metrics and, in such event, only the specific performance metrics expressly identified in such binding written contract shall be binding on Fortinet. For absolute clarity, any such warranty will be limited to performance in the same ideal conditions as in Fortinet's internal lab tests. In no event does Fortinet make any commitment related to future deliverables, features or development, and circumstances may change such that any forward-looking statements herein are not accurate. Fortinet disclaims in full any covenants, representations, and guarantees pursuant hereto, whether express or implied. Fortinet reserves the right to change, modify, transfer, or otherwise revise this publication without notice, and the most current version of the publication shall be applicable.